SAFETY DATA SHEET



1. Identification

Product identifier Solder-Safe 95/5 Lead-Free Solder

Other means of identification

SDS number WC006
Recommended use Solder.
Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer/Supplier Worthington Industries Incorporated

Address 200 Old Wilson Bridge Road

Columbus, OH 43085

United States

Email: cylinders@worthingtonindustries.com

Telephone Number: 866-928-2657

CHEMTREC - 24 HOURS:

Within US and Canada 800-424-9300

Outside US and Canada +1 703-741-5970 (collect calls accepted)

2. Hazard(s) identification

Physical hazards Not classified.
Health hazards Not classified.
Environmental hazards Not classified.

Label elements

Hazard symbol None.
Signal word None.
Hazard statement None.

Precautionary statement

Prevention Observe good industrial hygiene practices.

Response Wash thoroughly after handling.

Storage Store away from incompatible materials.

Disposal Dispose of waste and residues in accordance with local authority requirements.

Other hazards Molten material will produce thermal burns.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
TIN, ELEMENTAL	7440-31-5	90 - 98
ANTIMONY, ELEMENTAL	7440-36-0	2 - 10

Composition commentsAll concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in

percent by volume.

4. First-aid measures

Inhalation In case of inhalation of dust or fumes: Immediately remove from further exposure. Get immediate

medical assistance. For those providing assistance, avoid exposure to yourself or others. Use adequate respiratory protection. Give supplemental oxygen, if available. If breathing has stopped,

assist ventilation with a mechanical device or use mouth-to-mouth resuscitation.

Solder-Safe 95/5 Lead-Free Solder SDS Canada

Skin contact Contact with dust: Remove contaminated clothes and rinse skin thoroughly with water for at least

15 minutes. If skin rash or an allergic skin reaction develops, get medical attention.

Contact with dust: Rinse immediately with plenty of water for at least 15 minutes. Remove any Eye contact

contact lenses. Get medical attention if irritation develops or persists.

Rinse mouth thoroughly if dust is ingested. Get medical attention if symptoms occur. Ingestion

Most important symptoms/effects, acute and

delayed

Elevated temperatures or mechanical action may form dust and fumes which may be irritating to the eye, mucous membranes and respiratory tract. Contact with molten material may cause thermal burns.

Indication of immediate medical attention and special treatment needed

Treat symptomatically. Exposure may aggravate pre-existing respiratory disorders. Symptoms may be delayed.

General information Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Specific hazards arising from the chemical

Special protective equipment and precautions for firefighters

Fire fighting equipment/instructions Extinguish with foam, carbon dioxide or dry powder. Do not use water or halogenated extinguishing media.

Fire or high temperatures create: Metal oxides.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Move containers from fire area if you can do it without risk.

General fire hazards Solid metal is not flammable; however, finely divided metallic dust or powder may form an

explosive mixture with air.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Avoid inhalation of dust from the spilled material. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Wear protective clothing as described in Section 8 of this SDS.

Methods and materials for containment and cleaning up

Massive, solid metal: Pick up and arrange disposal without creating dust.

Dust: Collect dust or particulates using a vacuum cleaner with a HEPA filter. Use approved industrial vacuum cleaner for removal. Avoid generation and spreading of dust. Recover and recycle, if practical. Keep out of water supplies and sewers.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not contaminate water.

7. Handling and storage

Precautions for safe handling

Wear appropriate personal protective equipment (See Section 8). Keep formation of airborne dusts to a minimum. Provide appropriate exhaust ventilation at places where dust is formed. Avoid inhalation of dust and fumes. Avoid contact with eyes, skin, and clothing. Do not eat, drink or smoke when using the product. Wash thoroughly after handling.

Any surface that comes in contact with molten metal must be preheated or specially coated and rust free. Inadvertent contaminants to product such as moisture, ice, snow, grease, or oil can cause an explosion when charged to a molten metal bath or metal furnace (preheating metal will remove moisture from product).

Conditions for safe storage, including any incompatibilities Store in tightly closed original container in a dry, cool and well-ventilated place. Keep away from food, drink and animal feedingstuffs. Keep out of reach of children. Store away from incompatible materials (See Section 10).

8. Exposure controls/personal protection

Occupational exposure limits

US. ACGIH Threshold Limit Values

Components	Туре	Value	
ANTIMONY, ELEMENTAL	TWA	0.5 mg/m3	
(CAS 7440-36-0)			
TIN, ELEMENTAL (CAS	TWA	2 mg/m3	
7440-31-5)			

Solder-Safe 95/5 Lead-Free Solder SDS Canada

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	Туре	Value	
ANTIMONY, ELEMENTAL	TWA	0.5 mg/m3	
(CAS 7440-36-0)			
TIN, ELEMENTAL (CAS	TWA	2 mg/m3	
7440-31-5)			

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Туре	Value	
ANTIMONY, ELEMENTAL	TWA	0.5 mg/m3	
(CAS 7440-36-0)			
TIN, ELEMENTAL (CAS	TWA	2 mg/m3	
7440-31-5)			

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Components	Туре	Value	
ANTIMONY, ELEMENTAL (CAS 7440-36-0)	TWA	0.5 mg/m3	
TIN, ELEMENTAL (CAS	TWA	2 mg/m3	
7440-31-5)			

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

Components	Туре	Value
ANTIMONY, ELEMENTAL	TWA	0.5 mg/m3
(CAS 7440-36-0)		
TIN, ELEMENTAL (CAS	TWA	2 mg/m3
7440-31-5)		

Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment)

Components	Туре	Value	
ANTIMONY, ELEMENTAL (CAS 7440-36-0)	TWA	0.5 mg/m3	
TIN, ELEMENTÁL (CAS 7440-31-5)	TWA	2 mg/m3	

Biological limit valuesNo biological exposure limits noted for the ingredient(s).

Exposure guidelines No exposure standards allocated.

Appropriate engineering

controls

Provide adequate ventilation. Observe Occupational Exposure Limits and minimize the risk of inhalation of dust. Keep melting/soldering temperatures as low as possible to minimize the generation of fume. Shower, hand and eye washing facilities near the workplace are

recommended.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Wear a face shield when working with molten

material.

Skin protection

Hand protectionOtherWear protective gloves (i.e. latex, nitrile, neoprene).Chemical resistant clothing is recommended.

OEL. In a confined space a supplied respirator may be required. Selection and use of respiratory protective equipment should be in accordance with OSHA General Industry Standard 29 CFR 1910.134; or in Canada with CSA Standard Z94.4. Use a NIOSH/MSHA approved respirator if

there is a risk of exposure to dust/fume at levels exceeding the exposure limits.

Thermal hazards

Heat resistant/insulated gloves and clothing are recommended when working with molten material. Always observe good personal hygiene measures, such as washing after handling the material

General hygiene considerations

and before eating, drinking, and/or smoking. Routinely wash work clothing and protective

equipment to remove contaminants.

9. Physical and chemical properties

Appearance Silver to silver-gray metallic metal.

Physical state Solid.

Solder-Safe 95/5 Lead-Free Solder SDS Canada

Form Wire.

Color Silver to gray.
Odor Odorless.

Odor threshold

PH

Not applicable.

Not applicable.

Melting point/freezing point 232 °F (111.11 °C) (Tin)
Initial boiling point and boiling 2516 °F (1380 °C) (Antimony)

range

4100 °F (2260 °C) (Tin)

Flash point Not applicable.

Evaporation rate Not applicable.

Flammability (solid, gas) Non flammable. Fine particles may form explosive mixtures with air.

Upper/lower flammability or explosive limits

Flammability limit - lower

Not applicable.

(%)

Flammability limit - upper

Not applicable.

(%)

Explosive limit - lower (%) Not applicable.

Explosive limit - upper (%) Not applicable.

Vapor pressure Not applicable.

Vapor density Not applicable.

Relative density 5.77 - 5.84 (H20=1)

Solubility(ies)

Solubility (water) Insoluble in water.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperatureNot applicable.Decomposition temperatureNot available.ViscosityNot available.

Other information

Explosive properties Not explosive. **Oxidizing properties** Not oxidizing.

10. Stability and reactivity

Reactivity The product is non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoidContact with incompatible materials. Avoid molten metal contact with water.

Incompatible materials Chlorine. Turpentine. Strong acids. Strong bases. Nascent hydrogen. Reducing agents. Fluorine.

Bromine.

Hazardous decomposition

Toxic metal oxides are emitted when heated above the melting point.

products

Under reducing condition, such as any strong acid or base plus an active metal, or in the presence

of nascent hydrogen, highly toxic stibine gas (TLV = 0.10 ppm) may be evolved.

11. Toxicological information

Information on likely routes of exposure

Inhalation Elevated temperatures or mechanical action may form dust and fumes which may be irritating to

the mucous membranes and respiratory tract. Lung damage and possible pulmonary edema can result from dust exposure. Inhalation of fumes may cause a flu-like illness called metal fume

fever.

Skin contact Dust may irritate skin. Contact with molten material may cause thermal burns.

Elevated temperatures or mechanical action may form dust and fumes which may be irritating to

the eye.

Solder-Safe 95/5 Lead-Free Solder

908010 Version #: 01 Revision date: - Issue date: 17-July-2016

4 / 7

Ingestion of dusts generated during working operations may cause nausea and vomiting. Ingestion

Symptoms related to the physical, chemical and toxicological characteristics Elevated temperatures or mechanical action may form dust and fumes which may be irritating to the eye, mucous membranes and respiratory tract. Contact with molten material may cause

thermal burns.

Information on toxicological effects

May cause eye, skin and respiratory tract irritation. Exposure to antimony and its compounds can **Acute toxicity**

cause gastrointestinal pain, cough, loss of appetite, itching, skin eruptions, and irritation of skin,

eyes, nose and throat.

Dust may irritate skin. Skin corrosion/irritation

Serious eye damage/eye irritation

Elevated temperatures or mechanical action may form dust and fumes which may be irritating to

the eye.

Respiratory or skin sensitization

Canada - Alberta OELs: Irritant

ANTIMONY, ELEMENTAL (CAS 7440-36-0) Irritant

Respiratory sensitization No sensitizing effects known. Skin sensitization No sensitizing effects known.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

This product is not expected to cause reproductive or developmental effects. Reproductive toxicity

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not relevant, due to the form of the product.

Chronic effects Prolonged and repeated overexposure to dust and fumes can lead to benign pneumoconiosis

(stannosis). Exposure to antimony and its compounds can cause headache, sleeplessness, dizziness, metallic taste, ulcers, weight loss, nausea, vomiting, diarrhea, impairment of sense of

smell, and pain or tightness in chest.

Further information No other specific acute or chronic health impact noted.

12. Ecological information

Alloys in massive forms present a limited hazard for the environment. The product contains a **Ecotoxicity**

substance which is harmful to aquatic organisms and which may cause long-term adverse effects

in the aquatic environment.

The product is not biodegradable. Persistence and degradability

Bioaccumulative potential No data available.

Mobility in soil Alloys in massive forms are not mobile in the environment.

None expected. Other adverse effects

13. Disposal considerations

Dispose in accordance with all applicable regulations. **Disposal instructions**

Dispose of in accordance with local regulations. Local disposal regulations

Hazardous waste code Not regulated.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Scrapped material should be sent for refining to recover precious metal content. Solid metal and alloys in the form of particles may be reactive. Its hazardous characteristics, including fire and explosion, should be determined prior to disposal.

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

TDG

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

Solder-Safe 95/5 Lead-Free Solder 5/7

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and

Not applicable.

the IBC Code

15. Regulatory information

Canadian regulations

This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

International regulations

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

16. Other information

Issue date 17-July-2016

Revision date - Version # 01

Further information The classification for health and environmental hazards is derived by a combination of calculation

methods and test data, if available.

Solder-Safe 95/5 Lead-Free Solder SDS Canada

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

References EPA: AQUIRE database

NLM: Hazardous Substances Data Base

US. IARC Monographs on Occupational Exposures to Chemical Agents

HSDB® - Hazardous Substances Data Bank

IARC Monographs. Overall Evaluation of Carcinogenicity National Toxicology Program (NTP) Report on Carcinogens

ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices

Disclaimer

All information in this Safety Data Sheet is believed to be accurate and reliable. However, no guarantee or warranty of any kind is made with regard to the accuracy of information or the suitability of the recommendations contained herein. It is the user's responsibility to assess the safety and toxicity of this product under their own conditions of use and to comply with all

applicable laws and regulations.

Solder-Safe 95/5 Lead-Free Solder

908010 Version #: 01 Revision date: - Issue date: 17-July-2016

7 / 7