

SAFETY DATA SHEET.

Issuing date 28-Sep-2017

Revision Date 29-Jun-2019

Version 1.01

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product name 4630-0 SILICONE LUBE

Recommended use of the chemical and restrictions on use

Product code F01765

Product Type Combustible liquid
Synonyms None

Supplier's details

Recommended Use Lubricant for forklifts used in food, beverage, and pharmaceutical processing areas.

Uses advised against No information available

Manufactured For:
Imperial Supplies LLC
789 Armed Forces Drive
P.O. Box 11008
Green Bay, WI 53407-1008
1-800-558-2808

Manufacturer
American Jetway Corporation
34136 Myrtle Street
Wayne, MI 48184-0126
Phone:(734) 721-5930

Emergency telephone number
Chemical Emergency Phone Number

CHEMTREC: 1-800-262-8200 ID 1195 (UNITED STATES)

2. HAZARDS IDENTIFICATION

Classification

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Specific target organ toxicity (single exposure)	Category 3
Aspiration toxicity	Category 1
Flammable Liquids	Category 4

GHS Label elements, including precautionary statements

Emergency Overview

DANGER

Hazard Statements

Causes skin irritation.
Causes serious eye irritation.
May cause respiratory irritation. May cause drowsiness or dizziness.
May be fatal if swallowed and enters airways.
Combustible liquid



Appearance Clear

Physical state Liquid

Odor Solvent

Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling.
Wear protective gloves, eye protection, face protection.
Avoid breathing fumes, gas, mist, vapors, spray.
Use only outdoors or in a well-ventilated area.
Keep away from heat, sparks, open flames, hot surfaces - No smoking.

Precautionary Statements - Response

Specific treatment (see first aid on this label).
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice, attention
IF ON SKIN: Wash with plenty of soap and water.
If skin irritation occurs: Get medical advice, attention.
Take off contaminated clothing and wash it before reuse.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
Call a POISON CENTER or doctor, physician if you feel unwell.
IF SWALLOWED: Immediately call a POISON CENTER, doctor, physician.
Do NOT induce vomiting.
In case of fire: Use CO2, dry chemical, or foam to extinguish.

Precautionary Statements - Storage

Store locked up.
Store in a well-ventilated place. Keep container tightly closed.
Keep cool.

Precautionary Statements - Disposal

Dispose of contents, container to an approved waste disposal plant.

Hazards not otherwise classified (HNOC)

None

Other information

0% of the mixture consists of ingredient(s) of unknown toxicity.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %*
HYDROTREATED LIGHT DISTILLATES	64742-47-8	50-60
HEPTANE	64742-49-0	30-40
ACETONE	67-64-1	10-20

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES**First aid measures for different exposure routes**

General advice	Avoid contact with eyes, skin, and clothing. Avoid breathing vapors, mist, or gas.
Eye contact	Immediately flush with plenty of water for at least 15 minutes. After initial flushing, remove any contact lenses and continue flushing. If eye irritation persists, consult a doctor.
Skin contact	If on skin (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower. If skin irritation persists, call a physician. Remove and wash contaminated clothing before re-use.
Inhalation	Move to fresh air. If not breathing, give artificial respiration. If breathing has stopped, contact emergency medical services immediately.
Ingestion	Call a physician or Poison Control Center immediately. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Risk of product entering the lungs on vomiting after ingestion.
Protection of First-aiders	Remove all sources of ignition.

Most important symptoms/effects, acute and delayed

Main Symptoms	Causes skin and serious eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways.
----------------------	--

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician	Treat symptomatically.
---------------------------	------------------------

5. FIRE-FIGHTING MEASURES**Suitable Extinguishing Media**

Water fog.Dry chemical. Foam.Carbon dioxide (CO2). Cool containers/tanks with water spray.

Unsuitable Extinguishing Media Do not use a solid water stream as it may scatter and spread fire. Keep away from sources of ignition - No smoking.

Specific hazards arising from the chemical

Combustible material. Keep product and empty container away from heat and sources of ignition. Keep containers and surrounding areas cool with water spray.

Hazardous Combustion Products

Carbon oxides , Hydrocarbons, Fumes. Chlorine gas. Halogenated compounds.

Explosion Data

Sensitivity to Mechanical Impact none.

Sensitivity to Static Discharge Yes. none.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use shielding to protect fire-fighters from bursting containers.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions

Use with adequate ventilation to keep the exposure levels below the OELS. Follow safe handling advice and personal protective equipment recommendations.

Environmental precautions

Environmental precautions

Vapors can accumulate in low areas. Report spills as required by local and federal regulations. Do not allow material to contaminate ground water system. Do not flush into surface water or sanitary sewer system. Should not be released into the environment.

Methods and materials for containment and cleaning up

Methods for Containment

Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from entering drains.

Methods for cleaning up

Soak up with inert absorbent material. Contain liquid and collect with an inter, non-combustible material. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly . After cleaning, flush away traces with water. Prevent product from entering drains. Take precautionary measures against static discharges.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling

Avoid breathing vapors or mists. Avoid contact with skin, eyes and clothing. Keep away from open flames, hot surfaces and sources of ignition. Handle in accordance with good industrial hygiene and safety practice. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded.

Conditions for safe storage, including any incompatibilities

Technical measures/Storage conditions

Keep container tightly closed in a dry and well-ventilated place. Keep away from open flames, hot surfaces, and sources of ignition. Keep in properly labeled containers. Keep out of the reach of children. Store locked up. Keep cool.

Incompatible products

Strong acids, alkalis, oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
HYDROTREATED LIGHT DISTILLATES	TWA: 200 PPM 8 hours	-	-

64742-47-8			
HEPTANE 64742-49-0	TLV: 400 ppm STEL: 500 ppm	TWA: 500 ppm	-
ACETONE 67-64-1	STEL: 500 ppm TWA: 250 ppm	TWA: 1000 ppm TWA: 2400 mg/m ³ (vacated) TWA: 750 ppm (vacated) TWA: 1800 mg/m ³ (vacated) STEL: 2400 mg/m ³ The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors. (vacated) STEL: 1000 ppm	IDLH: 2500 ppm TWA: 250 ppm TWA: 590 mg/m ³

ACGIH: (American Conference of Governmental Industrial Hygienists)

OSHA: (Occupational Safety & Health Administration)

NIOSH IDLH: Immediately Dangerous to Life or Health

Other Exposure Guidelines

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Exposure controls

Engineering Measures

Ventilation systems. Use adequate ventilation to keep the exposure levels below the occupational exposure limits.

Individual protection measures, such as personal protective equipment

Eye/Face Protection

Tightly fitting safety goggles.

Skin and body protection

Chemical resistant apron. Protective gloves.

Respiratory protection

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

Hygiene measures

Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and chemical properties

Physical state	Liquid	Odor	Solvent
Appearance	Clear	Odor Threshold	
Color	Colorless		
Property	Values	Remarks • Methods	
pH	No information available		
Melting/freezing point	No information available		
Boiling point/boiling range			
Flash Point	> 93 °C / > 199 °F	(based on components)	
Evaporation rate	No information available		
Flammability (solid, gas)	No information available		
Flammability Limits in Air			
upper flammability limit			
lower flammability limit			
Vapor pressure			
Vapor density			
Specific Gravity	0.779		
Water solubility	No information available		
Partition coefficient: n-octanol/water			
Autoignition temperature	No information available		
Decomposition temperature			

Viscosity No information available
Explosive properties

Other information

VOC Content(%) 31.7

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to Avoid

Extremes of temperature and direct sunlight.

Incompatible Materials

Strong acids, alkalis, oxidizing agents.

Hazardous Decomposition Products

Carbon oxides , Hydrocarbons, Fumes.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation May cause respiratory irritation, May cause drowsiness or dizziness.
Eye contact Causes serious eye irritation.
Skin contact Causes skin irritation.
Ingestion May be fatal if swallowed and enters airways.

Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
HYDROTREATED LIGHT DISTILLATES 64742-47-8	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat) 4 h
HEPTANE 64742-49-0	> 5000 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	= 73680 ppm (Rat) 4 h
ACETONE 67-64-1	= 5800 mg/kg (Rat)	> 15700 mg/kg (Rabbit)	= 50100 mg/m ³ (Rat) 8 h

Information on toxicological effects

Symptoms Causes skin and serious eye irritation. May cause drowsiness or dizziness. May cause respiratory irritation. May be fatal if swallowed and enters airways.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Irritating to skin.
Eye damage/irritation Irritating to eyes.
Sensitization Not a known sensitizer.
Germ cell mutagenicity Not a germ cell mutagen.

Carcinogenicity	There are no known carcinogenic chemicals in this product.
Reproductive toxicity	This product does not contain any known or suspected reproductive hazards.
Specific target organ systemic toxicity (single exposure)	May cause respiratory irritation. May cause drowsiness and dizziness.
Specific target organ systemic toxicity (repeated exposure)	No known effect based on information supplied.
Chronic toxicity	Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Chronic hydrocarbon abuse has been associated with irregular heart rhythms and potential cardiac arrest.
Target Organ Effects	Skin, Eyes, Respiratory System, and Central Nervous System.
Neurological effects	Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.
Aspiration hazard	May be fatal if swallowed and enters airways. May be fatal if swallowed and enters airways.

Numerical measures of toxicity - Product Information

Unknown Acute Toxicity 0% of the mixture consists of ingredient(s) of unknown toxicity.

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral)	2874 mg/kg
ATEmix (dermal)	15150 mg/kg
ATEmix (inhalation-gas)	198334 mg/l
ATEmix (inhalation-dust/mist)	35.8 mg/l
ATEmix (inhalation-vapor)	5.4 mg/l

12. ECOLOGICAL INFORMATION**Ecotoxicity**

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to microorganisms	Toxicity to daphnia and other aquatic invertebrates
HYDROTREATED LIGHT DISTILLATES 64742-47-8	-	45 mg/L LC50 Pimephales promelas 96h flow-through 2.2 mg/L LC50 Lepomis macrochirus 96h static 2.4 mg/L LC50 Oncorhynchus mykiss 96h static	-	-
ACETONE 67-64-1	-	4.74 - 6.33 mL/L LC50 Oncorhynchus mykiss 96h 6210 - 8120 mg/L LC50 Pimephales promelas 96h static 8300 mg/L LC50 Lepomis macrochirus 96h	-	10294 - 17704 mg/L EC50 Daphnia magna 48h Static 12600 - 12700 mg/L EC50 Daphnia magna 48h

Persistence and degradability**Bioaccumulation**

Chemical Name	log Pow
ACETONE 67-64-1	-0.24

Other adverse effects No information available

13. DISPOSAL CONSIDERATIONS**Waste treatment**

Waste Disposal Methods This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261). Dispose of in accordance with federal, state, and local regulations. Dispose of in

accordance with federal, state, and local regulations.

Contaminated packaging

Do not re-use empty containers.

14. TRANSPORT INFORMATION

DOT Ground

CONSUMER COMMODITY ORM-D
or QUANTITY

IATA

UN1268, PETROLEUM DISTILLATES, N.O.S., 3, PGII, LTD. QTY

IMDG

UN1268, PETROLEUM DISTILLATES, N.O.S., 3, PGII, LTD. QTY.

15. REGULATORY INFORMATION

International Inventories

Chemical Name	TSCA	DSL/NDSL	EINECS/ELI NCS	ENCS	IECSC	KECL	PICCS	AICS
HYDROTREATED LIGHT DISTILLATES	X	X	X	Not listed	X	X	X	X
HEPTANE	X	X	X	Not listed	X	X	X	X
ACETONE	X	X	X	X	X	X	X	X

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

CHINA - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

U.S. Federal Regulations**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Star Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA

This material, as supplied, does contain substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
ACETONE 67-64-1	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

U.S. State Regulations**California Proposition 65**

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
ACETONE 67-64-1	X	X	X

EPA Pesticide Registration Number Not applicable

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all the information required by the CPR.

16. OTHER INFORMATION

NFPA	Health Hazard 2	Flammability 2	Instability 0	Physical and chemical hazards -
HMIS	Health Hazard 2*	Flammability 2	Physical Hazard 0	Personal protection B
<i>Chronic Hazard Star Legend</i>		<i>Repeated or prolonged exposure may cause central nervous system damage</i>		<i>Chronic Health Star Hazard</i>

Prepared By American Jetway Corporation
34136 Myrtle Street
Wayne, MI 48184-0126

Issuing date 28-Sep-2017
Revision Date 29-Jun-2019

Revision Note
(M)SDS sections updated: 2, 6

Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet