



TURTLE WAX, INC.
2250 W. Pinehurst Blvd., STE 150
Addison, IL 60101

SAFETY DATA SHEET

1. Product and Company Identification

1.1 Product Identifier

Product Name: Turtle Wax Premium Scratch Repair Kit – Clarifying Compound
Product Code (SKU): T234KT-RC (50194), T234KTC-RC (50195)

1.2 Relevant Identified Uses Of The Substance

Product Use: Automotive Rubbing and Polishing Compound

1.3 Details of the Supplier of the SDS

Company Name: Turtle Wax, Inc.
Street Address: 2250 W. Pinehurst Blvd., Suite 150
City, State, Zip Code: Addison, IL 60101

1.4 Emergency Telephone Numbers

Phone Number: 1(630)455-3700
Fax Number: 1(630)455-3868
Transportation: 1(800)424-9300 (CHEMTREC)
Medical Assistance: Call your local Poison Control Center

2. Hazard Identification:

2.1 Classification of the Substance or Mixture

Hazard Classification: Not Classified

2.2 Label Elements

Pictogram: Not Required

Signal Word: None

Hazard Statement: None

Precautionary Statement: None

2.3 Other Hazards

Description of additional HNOC: None

3. Information on Ingredients:

3.1 Substance Not Applicable

3.2 Mixture

<u>Component</u>	<u>CAS Number</u>	<u>Concentration (wt%)</u>
Water	7732-18-5	>65%
Petroleum Distillates Hydrotreated Light	64742-47-8	7 – 13%
Glycerin	56-81-5	1 – 3%
White Mineral Oil	8042-47-5	1 – 3%

4. **First Aid Measures:**

4.1 Description of First Aid Measures

Inhalation: Remove to fresh air and promote deep breathing. Get medical attention if effects persist.

Skin: In case of skin contact, wash thoroughly with soap and water. If irritation persists, get medical attention.

Eyes: In case of eye contact, immediately flush eyes with plenty of water. Remove contact lenses if worn. If irritation persists, get medical attention

Ingestion: If swallowed, do not induce vomiting. Never give anything by mouth to an unconscious person. Give water to drink if conscious. Get medical attention if effects persist.

4.2 Most important symptoms and effects – acute and chronic

Inhalation: May cause respiratory tract irritation.

Skin: May cause skin irritation. May cause drying, cracking, or mild dermatitis.

Eyes: May cause temporary eye irritation.

Ingestion: May cause stomach distress, nausea, and vomiting.

4.3 Indication of any immediate medical attention and special treatment

Symptoms may not appear immediately. Seek medical attention if effects persist and you feel unwell.

5. **Fire Fighting Measures:**

5.1 Extinguishing media

Water spray, carbon dioxide, dry chemical, and alcohol foam

5.2 Special hazards arising from the substance or mixture

CO₂, CO, and hydrocarbons

5.3 Advice for Fire Fighters

Keep up wind of fire. Wear full firefighting turn out gear (full bunker gear) and respiratory protection (SCBA). See Section 8 for personal protection.

6. **Accidental Release Measures:**

6.1 Personal precautions, protective equipment, and emergency procedures

Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

6.2 Methods and materials for containment and clean up

For containment: Contain and absorb spill with inert material. Place in suitable container for disposal. Spilled material may be slippery.

For clean up: Take up material and place in a suitable container. Provide adequate ventilation. Spilled material may be slippery.

7. Handling and Storage

7.1 Precautions for safe handling

Avoid contact with skin and eyes. Do not swallow. Do not eat, drink or smoke while handling. Wash hands with soap and water after handling. Launder all clothing and foot wear before re-use.

7.2 Conditions for safe storage including incompatibilities

Keep out of reach of children. Keep container tightly closed. Store in a well ventilated place. Do not store above 49°C (120°F).

7.3 Specific end uses

Shelf Life: Shelf life is considered to be 7 – 10 years when properly stored and kept closed.

8. Exposure Control/Personal Protection:

8.1 Control parameters

<u>Exposure Limits</u> <u>8 hr TWA:</u>	<u>(OSHA PEL)</u>	<u>(ACGIH TWA)</u>
Petroleum Distillates Hydrotreated Light	100 ppm	200 ppm
Nepheline Syenite	15 mg/m ³ (total dust) 5 mg/m ³ (Respirable fraction)	15 mg/m ³ (total dust)
White Mineral Oil	not applicable	not applicable
Glycerin	15 mg/m ³ (Total Particulate) 5 mg/m ³ (Mist Respirable Fraction)	not applicable

8.2 Exposure controls

Use adequate ventilation to keep exposure below recommended limits. Ensure that eye wash station and safety shower are close to work station.

Hand Protection Equipment: Wear chemical resistant gloves and clothing to prevent skin contact.

Eye Protection Equipment: Wear safety glasses or splash goggles to prevent eye contact.

Skin and Body Protection: Wear suitable protective clothing.

Respiration/Ventilation Protection Requirements: Provide good ventilation.

Ingestion Protection Requirements: Do not eat, drink or smoke while handling. Wash hands with soap and water after handling. Launder all clothing and foot wear before re-use.

9. Physical And Chemical Properties:

9.1 Information of basic chemical and physical properties

Physical Form:	Viscous Liquid
Color:	White Opaque

Odor:	typical
Odor Threshold:	not available
pH:	8.0
Melting Point/Freeze Point:	0°C (32°F) – Based on Water
Initial Boiling Point:	100°C (212°F) – Based on Water
Flash Point (Seta Closed Cup):	>93°C (200°F)
Flammability Limits:	Explosive Limits: Upper: not available Lower: not available
Evaporation Rate:	not available
Flammability Solid/Gas:	not applicable
Vapor Pressure:	not available
Vapor Density:	not available
Specific Gravity:	1.069
Solubility in Water:	Dispersible
Auto Ignition Temperature:	not available
Partition coefficient (n/octonol/water):	not available
Viscosity:	400 cP

9.2 Other information

%NVM by Weight:	20.0%
%VOC Content (California):	0.0%

10. Stability and Reactivity:

10.1 Reactivity

Does not react under normal conditions

10.2 Chemical stability

Stable

10.3 Possibility of hazardous reactions

Does not react under normal conditions

10.4 Conditions to avoid

Heat and incompatible materials

10.5 Incompatible materials

Strong oxidizers such as bleach and peroxides

10.6 Hazardous decomposition products

CO₂, CO and hydrocarbons

11. Toxicological Information:

11.1 Information on Toxicological effects

Turtle Wax Premium Scratch Repair Kit – Clarifying Compound

LD50 – Oral Rat	>2000 mg/Kg
LD50 – Dermal Rat	>2000 mg/Kg
LC50 – Inhalation Rat	>20 mg/L (4 hr)

Petroleum Distillate Hydrotreated Light (64742-47-8)

LD50 – Oral Rat	>5000 mg/Kg
LD50 – Dermal Rat	>2000 mg/Kg
LC50 – Inhalation Rat	5.2 mg/L (4 hr)

Glycerin

LD50 – Oral Rat 12600 mg/Kg

LD50 – Dermal Rat >10 g/Kg

Skin corrosion/irritation	Based on available data, classification data are not met
Serious eye damage/irritation	Based on available data, classification data are not met
Respiratory or skin sensitization	Based on available data, classification data are not met
Germ cell mutagenicity	Based on available data, classification data are not met
Carcinogenicity	Based on available data, classification data are not met
Reproductive toxicity	Based on available data, classification data are not met
Specific target organs – single exposure	Based on available data, classification data are not met
Specific target organs – repeated exposure	Based on available data, classification data are not met
Aspiration hazard	Based on available data, classification data are not met
Symptoms/injuries after inhalation	May cause respiratory tract irritation
Symptoms/injuries after skin contact	May cause skin irritation. May cause drying, cracking, or mild dermatitis.
Symptoms/injuries after eye contact	May cause temporary eye irritation.
Symptoms/injuries after ingestion	May cause stomach distress, nausea, and vomiting.

12. Ecological Information:

12.1 Toxicity

Not recommended for release into aquatic systems without treatment

12.2 Persistence and degradability

Not established

12.3 Bioaccumulative potential

Not established

12.4 Mobility in soil

Not established

12.5 Other adverse effects

None known

13. Disposal Considerations:

13.1 Waste treatment methods

RCRA Hazardous Waste:

Not regulated as a hazardous waste

Waste Disposal Method:

Dispose of in accordance with local, state and federal regulations

Waste Disposal Vessel:

Plastic or metal drums.

14. Transportation Information:

14.1 UN number

None - not regulated as a hazardous material

14.2 UN Proper shipping name

None

14.3 Transport Hazard class

Not applicable

14.4 Packaging group

Not applicable

14.5 Marine Pollutant

No

14.6 Transportation in Bulk

Not applicable

14.7 Special precautions

None

15. Regulatory Information:**15.1 US Federal Regulations**

TSCA Status: All ingredients are commercially available and listed by the manufacturer under TSCA.

15.2 Foreign Regulations

Canadian Status: All materials contained in this product are listed on the Canadian Domestic Substance List (DSL). Consult Turtle Wax, Inc. regarding status of ingredients.

European Union: All materials contained in this product are listed on EINECS.

AICS: All materials are registered for AICS (Australia)

15.3 State Regulations**State Regulatory Information:**

The following chemicals are specifically listed by individual states; other product specific health and safety data in other sections of the SDS may also be applicable for state requirements. For details on your regulatory requirements, contact the appropriate agency in your state.

California Prop 65:**CAS Number****Concentration****State Code**

None

15.4 HMIS & NFPA Classifications

HMIS Classification:	Health	1
	Flammability	1
	Reactivity	0
NFPA Classification:	Health	1

Flammability	1
Reactivity	0

16. Other Information:

Reason For Issue	Address Update
Prepared By	James Heidel
Preparer's Title	Technical Director, R&D
SDS Administrator	Jean Mayszak - Technical Compliance Manager, R&D
Approval Date	February 2, 2017
Supersedes Date	March 2, 2015
Revision Number	A – 4

This information is, to the best of Turtle Wax, Inc.'s knowledge and belief, accurate and reliable. However, no representation, warranty, or guarantee is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy oneself as to the suitability and completeness of such information for their own particular use.



TURTLE WAX, INC.
2250 W. Pinehurst Blvd., STE 150
Addison, IL 60101

SAFETY DATA SHEET

1. Product and Company Identification

1.1 Product Identifier

Product Name: Turtle Wax Premium Scratch Repair Kit - Clear Coat Pen
Product Code (SKU): T-234KT-CP (50194), T234KTC-CP (50195)

1.2 Relevant Identified Uses Of The Substance

Product Use: Automotive Paint - Clear

1.3 Details of the Supplier of the SDS

Company Name: Manufactured for Turtle Wax Inc. by: Genicolor
Street Address: 437 rue des Monteregiennes
City, State, Zip Code: Quebec, Qc, Canada G1C 7J7

1.4 Emergency Telephone Numbers

Phone Number: 1(887)661-4848
Fax Number: 1(887)661-4878
Transportation: 1(800)424-9300 (CHEMTREC)
Medical Assistance: Call your local Poison Control Center

2. Hazard Identification:

2.1 Classification of the Substance or Mixture

Hazard Classification: Flammable Liquid 1
Serious Eye Irritation 2A
Skin Sensitization 1
Aspiration Hazard 1
Acute Toxicity 4

2.2 Label Elements



Pictogram:

Signal Word:

Danger

Hazard Statement:

Extremely flammable liquid and vapor. Causes serious eye irritation. May cause an allergic skin reaction. May be fatal if swallowed and enters airways. Vapors and mist may be harmful. Inhaled product may cause dizziness, headache, or nausea.

Precautionary Statement:

Keep away from heat, sparks, hot surfaces, and open flames. No smoking. Keep container tightly closed. Ground container and receiving equipment. Use explosion proof ventilation, lighting, and tools. Protect against static charge. Avoid breathing fumes, vapors, and spray. Wash hands thoroughly after handling. Wear protective gloves,

goggles, and clothing. If on skin or hair, remove immediately. Remove all clothing and laundry before re-use. If irritation occurs, get medical attention. If in eyes, rinse thoroughly with water for 15 minutes. Remove contact lenses if easy to do. If eye irritation persists, get medical attention. If swallowed, call a poison control center or a physician immediately. Do not induce vomiting. Store in a cool, well ventilated place. Dispose of in accordance with local, state, and federal regulations.

2.3 Other Hazards

Description of additional HNOC: None

3. Information on Ingredients:

3.1 Substance not applicable

3.2 Mixture

<u>Component</u>	<u>CAS Number</u>	<u>Concentration (wt%)</u>
Cellulose Acetate Butyrate	9004-36-8	1-5%
Glycol Dibenzoate Ester	27138-31-4	3-7%
N-Butyl Alcohol	71-36-3	3-7%
Acetone	67-64-1	15-40%
Methyl Ethyl Ketone	78-93-3	1-5%
Methyl Isoamyl Ketone	110-12-3	3-7%
Toluene	108-88-3	7-13%
Isopropyl Alcohol	67-63-0	10-30%
Propylene Glycol Monomethyl Ether Acetate	108-65-6	10-30%
Heptane	142-82-5	15-40%
Ethylbenzene	100-41-1	0.1-1.0%
Xylene	1330-20-7	0.5-1.5%
Acrylic Polymer	25852-37-3	7-13%

4. First Aid Measures:

4.1 Description of First Aid Measures

Inhalation: Remove to fresh air and promote deep breathing. Get medical attention if effects persist.

Skin: In case of skin contact, wash thoroughly with soap and water. Remove contaminated clothing and laundry before re-use. If irritation or allergic reaction occurs, get medical attention.

Eyes: In case of eye contact, immediately flush eyes with plenty of water. Remove contact lenses if worn. If irritation persists, get medical attention

Ingestion: If swallowed, do not induce vomiting. Never give anything by mouth to an unconscious person. Call a poison control center or physician immediately.

4.2 Most important symptoms and effects – acute and chronic

Inhalation: Vapor may be harmful. May cause respiratory tract irritation. May cause dizziness, headache, and nausea.

Skin: May cause skin irritation and sensitization. Contact may cause redness, drying, de-fatting, and cracking of the skin. Contact may cause sensitization by skin contact.

Eyes: Cause serious eye irritation. Symptoms may include discomfort, excess blinking, and tearing, with redness and conjunctiva.

Ingestion: May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea, and vomiting. Contact a physician if product is ingested.

4.3 Indication of any immediate medical attention and special treatment

Symptoms may not appear immediately. Seek medical attention if effects persist and you feel unwell.

5. Fire Fighting Measures:

5.1 Extinguishing media

Carbon dioxide, dry chemical, and alcohol foam

5.2 Special hazards arising from the substance or mixture

CO₂, CO, and hydrocarbons

5.3 Advice for Fire Fighters

Keep up wind of fire. Wear full firefighting turn out gear (full bunker gear) and respiratory protection (SCBA). See Section 8 for personal protection.

6. Accidental Release Measures:

6.1 Personal precautions, protective equipment, and emergency procedures

Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

6.2 Methods and materials for containment and clean up

For containment: Contain and absorb spill with inert material. Place in suitable container for disposal. Spilled material may be slippery. Do not allow to enter sewer or run-off.

For clean up: Take up material and place in a suitable container. Provide adequate ventilation. Spilled material may be slippery.

7. Handling and Storage

7.1 Precautions for safe handling

Avoid contact with skin and eyes. Do not swallow. Do not eat, drink or smoke while handling. Wash hands with soap and water after handling. Launder all clothing and foot wear before re-use. Use only non-sparking tools. Keep away from sparks, open flames, and hot surfaces.

7.2 Conditions for safe storage including incompatibilities

Keep out of reach of children. Keep container tightly closed. Store in a well ventilated place. Do not store above 49°C (120°F).

7.3 Specific end uses

Shelf Life: Shelf life is considered to be 7 – 10 years when properly stored and kept closed.

8. Exposure Control/Personal Protection:

8.1 Control parameters

<u>Exposure Limits</u>	<u>8 hr TWA:</u>	<u>(OSHA PEL)</u>	<u>(ACGIH TWA)</u>
N-Butyl Alcohol		100 ppm	20 ppm
Acetone		1000 ppm	500 ppm
Methyl Ethyl Ketone		200 ppm	200 ppm
Methyl Isoamyl Ketone		none	20 ppm
Toluene		300 ppm	20 ppm
Heptane		500 ppm	500 ppm
Ethylbenzene		100 ppm	20 ppm
Xylene		100 ppm	100 ppm
Acrylic Polymer			

8.2 Exposure controls

Use adequate ventilation to keep exposure below recommended limits. Ensure that eye wash station and safety shower are close to work station. Use only spark resistant tools, and equipment.

Hand Protection Equipment: Wear chemical resistant gloves and clothing to prevent skin contact.

Eye Protection Equipment: Wear safety glasses or splash goggles to prevent eye contact.

Skin and Body Protection: Wear suitable protective clothing.

Respiration/Ventilation Protection Requirements: Provide good ventilation.

Ingestion Protection Requirements: Do not eat, drink or smoke while handling. Wash hands with soap and water after handling. Launder all clothing and foot wear before re-use.

9. Physical And Chemical Properties:

9.1 Information of basic chemical and physical properties

Physical Form:	thin liquid		
Color:	clear – water white		
Odor:	typical aromatic solvent		
Odor Threshold:	not available		
pH:	not applicable (solvent based paint)		
Melting Point/Freeze Point:	-134°C (209°F)		
Initial Boiling Point:	82°C (180°F)		
Flash Point (Seta Closed Cup):	<-7°C (<19°F)		
Flammability Limits:	Explosive Limits:	Upper: 12.8%	Lower: 1.0%
Evaporation Rate:	slower than ether		
Flammability Solid/Gas:	not applicable		
Vapor Pressure:	247 hPa @ 20°C (68°F)		
Vapor Density:	2.0		
Specific Gravity:	0.850		
Solubility in Water:	insoluble		
Auto Ignition Temperature:	246°C (480°F)		
Partition coefficient (n/octanol/water):	not available		

Viscosity: 1200 cP

9. 2 Other information

%NVM by Weight: 15.0%

%VOC Content (California): 27.0%

10. Stability and Reactivity:

10.1 Reactivity

Does not react under normal conditions

10.2 Chemical stability

Stable

10.3 Possibility of hazardous reactions

Does not react under normal conditions

10.4 Conditions to avoid

Heat and incompatible materials

10.5 Incompatible materials

Strong oxidizers such as bleach and peroxides

10.6 Hazardous decomposition products

CO₂, CO and hydrocarbons

11. Toxicological Information:

11.1 Information on Toxicological effects

Cellulose Acetate Butyrate – (9004-36-8)

LD50 – Oral Rat 6400 mg/Kg

LD50 – Guinea Pig 1000 mg/Kg

Glycol Dibenzoate Ester (27138-31-4)

LD50 – Oral Rat 5313 mg/Kg

LD50 – Dermal Rabbit 2000 mg/Kg

LC50 – Inhalation Rat 2000 mg/L (4hr)

N-Butyl Alcohol (71-36-3)

LD50 – Oral Rat 790 mg/Kg

LD50 – Dermal Rabbit 3400 mg/Kg

LC50 – Inhalation Rat 8000 ppm (4hr)

Acetone – (67-64-1)

LD50 – Oral Rat 5800 mg/Kg

LD50 – Dermal Rabbit 20,000 mg/Kg

LC50 – Inhalation Rat 50 g/m³(8hr)

Methyl Ethyl Ketone (78-93-3)

LD50 – Oral Rat 5000 mg/Kg

LD50 – Dermal Rabbit 5000 mg/Kg

LC50 – Inhalation Rat 5000 mg/L (4hr)

Methyl Isoamyl Ketone (110-12-3)

LD50 – Oral Rat	5700 mg/Kg
LD50 – Guinea Pig	16,280 mg/Kg
LC50 – Inhalation Rat	3800 mg/L (4hr)

Toluene – (108-88-3)

LD50 – Oral Rat	3000 mg/Kg
LD50 – Dermal Rabbit	4000 mg/Kg
LC50 – Inhalation Rat	5000 mg/L (4hr)

Isopropyl Alcohol (67-63-0)

LD50 – Oral Rat	2000 mg/Kg
LD50 – Dermal Rabbit	2000 mg/Kg
LC50 – Inhalation Rat	>72.6 mg/L (4hr)

Propylene Glycol Monomethyl Ether Acetate (108-65-6)

LD50 – Oral Rat	9000 mg/Kg
LD50 – Dermal Rabbit	5000 mg/Kg
LC50 – Inhalation Rat	4345 mg/L (4hr)

Heptane – (142-82-5)

LD50 – Oral Rat	5000 mg/Kg
LD50 – Dermal Rabbit	2000 mg/Kg
LC50 – Inhalation Rat	103,000 mg/L (4hr)

Ethyl Benzene (100-41-4)

LD50 – Oral Rat	3500 mg/Kg
LD50 – Dermal Rabbit	18,000 mg/Kg
LC50 – Inhalation Rat	4000 mg/L (4hr)

Xylene (1330-20-7)

LD50 – Oral Rat	4300 mg/Kg
LD50 – Dermal Rabbit	1700 mg/Kg
LC50 – Inhalation Rat	5000 mg/L (4hr)

Skin corrosion/irritation	Based on available data, classification data are not met
Serious eye damage/irritation	Causes serious eye irritation
Respiratory or skin sensitization	May cause an allergic skin reaction
Germ cell mutagenicity	Based on available data, classification data are not met
Carcinogenicity	Based on available data, classification data are not met

Isopropyl alcohol (67-63-0)	IARC Group 3	10-30%
Ethyl Benzene (100-41-4)	IARC Group 2B	0.1 – 1.0%
Toluene (108-88-3)	IARC Group 3	7-13%

Reproductive toxicity	Based on available data, classification data are not met
Specific target organs – single exposure	Based on available data, classification data are not met

Specific target organs – repeated exposure	Based on available data, classification data are not met
--	--

Aspiration hazard	May be fatal if swallowed and enters airways
Symptoms/injuries after inhalation	May cause respiratory tract irritation, dizziness, headache, and nausea.

Symptoms/injuries after skin contact	May cause skin irritation. Contact may cause redness, drying, de-fatting, and cracking of the skin. Contact may cause sensitization by skin contact for susceptible people.
Symptoms/injuries after eye contact	Cause serious eye irritation. Symptoms may include discomfort, excess blinking, and tearing, with redness and conjunctiva.
Symptoms/injuries after ingestion	May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea, and vomiting.

12. Ecological Information:

12.1 Toxicity

Not recommended for release into aquatic systems without treatment

12.2 Persistence and degradability

Not established

12.3 Bioaccumulative potential

Not established

12.4 Mobility in soil

Not established

12.5 Other adverse effects

None known

13. Disposal Considerations:

13.1 Waste treatment methods

RCRA Hazardous Waste:

Waste Disposal Method:

Waste Disposal Vessel:

Regulated as a RCRA Hazardous waste – D001 ignitable
Dispose of in accordance with local, state and federal regulations
Metal drums or containers, only.

14. Transportation Information:

14.1 UN number

1263

14.2 UN Proper shipping name

Flammable liquid N.O.S. (Paint)

14.3 Transport Hazard class

3

14.4 Packaging group

II

14.5 Marine Pollutant

No

14.6 Transportation in Bulk

Not applicable

14.7 Special precautions

Qualifies as Limited Quantity

15. Regulatory Information:

15.1 US Federal Regulations

TSCA Status: All ingredients are commercially available and listed by the manufacturer under TSCA.

15.2 Foreign Regulations

Canadian Status: All materials contained in this product are listed on the Canadian Domestic Substance List (DSL). Consult Turtle Wax, Inc. regarding status of ingredients.

European Union: All materials contained in this product are listed on EINECS.

AICS: All materials are registered for AICS (Australia)

WHMIS: B2/D2A, D2B – Flammable & Toxic. Vapor Harmful.



15.3 State Regulations

State Regulatory Information:

The following chemicals are specifically listed by individual states; other product specific health and safety data in other sections of the SDS may also be applicable for state requirements. For details on your regulatory requirements, contact the appropriate agency in your state.

California Prop 65:

<u>CAS Number</u>	<u>Concentration</u>	<u>State Code</u>
Ethyl Benzene (100-41-4)	0.1 – 1.0%	Cancer
Toluene (108-88-3)	7 - 13%	Developmental

15.4 HMIS & NFPA Classifications

HMIS Classification:	Health	2
	Flammability	3
	Reactivity	0
NFPA Classification:	Health	2
	Flammability	3
	Reactivity	0

16. Other Information:

Reason For Issue Address Update

Prepared By	James Heidel
Preparer's Title	Technical Director, R&D
SDS Administrator	Jean Mayszak – Technical Compliance Manager, R&D
Approval Date	February 2, 2017
Supersedes Date	March 2, 2015
Revision Number	A – 4

This information is, to the best of Turtle Wax, Inc.'s knowledge and belief, accurate and reliable. However, no representation, warranty, or guarantee is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy oneself as to the suitability and completeness of such information for their own particular use.