

Safety Data Sheet according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012. Date of issue: 01/04/2016

Revision date: 12/02/2016 Version: 1.0

SECTION 1: Identification of the sub	ostance/mixture and of the company/undertaking
1.1. Product identifier	
Product name	: SET Small Engine Tune-up
Product code	: 16-SET
1.2. Relevant identified uses of the subs	stance or mixture and uses advised against
Use of the substance/mixture	: Carburetor Air Intake Cleaner
1.3. Details of the supplier of the safety	data sheet
The Blaster Corporation 8500 Sweet Valley Drive Valley View, Ohio 44125 - USA T (216) 901-5800 - F (216)901-5801 www.blastercorp.com	
1.4. Emergency telephone number	
Emergency number	: ChemTel 800-255-3924
SECTION 2: Hazardsidentification	
2.1. Classification of the substance or m	ixture
GHS-US classification	
Flammable Aerosol 2 Gases Under Pressure - DissolvedGas Acute Toxicity 4 (Inhalation) Skin Sensitization 1 Aspiration Hazard 1	
2.2. Label elements	
	ed in accordance with the US Consumer Product Safety Commission regulations which take precedence the actual container label will not include the label elements below. The labeling below applies to : : (HS02) (HS04) (HS04) (HS07) (HS08) (HS08)
Signal word (GHS-US)	: Danger
Hazard statements (GHS-US)	: Flammable aerosol. Contains gas under pressure; may explode if heated. Harmful if inhaled. May cause an allergic skin reaction. May be fatal if swallowed and entersairways.
Precautionary statements (GHS-US)	 Keep away from heat/sparks/open flames/hot surfacesNo smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves. Ifswallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin: Wash with plenty of water. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. Cla a poison center/doctor if you feel unwell. Store locked up. Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 50 °C/122 °F. Dispose of contents and container in accordance with all local, regional, national and international regulations.
2.3. Other hazards	
No additional information available	
2.4. Unknown acute toxicity (GHS-US)	of unknown aquite toxicity
3 percent of the mixture consists of ingredient(s)	
SECTION 3: Composition/information	on oningredients
Not applicable	
Not applicable	

12/02/2016



Safety Data Sheet according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

3.2. Mixture			
Name	Product identifier	%	GHS-US classification
Distillates, petroleum, solvent-dewaxed heavyparaffinic	(CAS No)64742-65-0	40 - 70	Asp. Tox. 1
Petroleum distillates, hydrotreated light	(CAS No)64742-47-8	10 - 30	Flam. Liq. 3 Asp. Tox. 1
Isopropylalcohol	(CAS No) 67-63-0	5 - 10	Flam. Liq. 2 Eye Irrit. 2A STOT SE 3
Carbon dioxide	(CAS No) 124-38-9	1 - 5	Compressed gas
Polypropylene glycol monobutyl ether	(CAS No) 9003-13-8	1 - 5	Skin Irrit. 2 Eye Irrit. 2A
N-Phenyl-1-naphthylamine	(CAS No) 90-30-2	0.1 - 1	Acute Tox. 4 (Oral) Skin Sens. 1 STOT RE 2

* The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

SECTION 4: First aid measures		
4.1. Description of first aid measure	S	
First-aid measures after inhalation	: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feelunwell.	
First-aid measures after skin contact	: In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.	
First-aid measures after eye contact	: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. If irritation persists, get medical attention.	
First-aid measures after ingestion	: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Get immediate medicaladvice/attention.	
4.2. Most important symptoms and effects, both acute and delayed		
Symptoms/injuries after inhalation	: Harmful if inhaled. May cause respiratory tractirritation.	
Symptoms/injuries after skin contact	: May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin. May cause sensitization by skincontact.	
Symptoms/injuries after eye contact	: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.	
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.	
4.2 Indication of any immediate me	diast attention and analist treatment needed	

Indication of any immediate medical attention and special treatment needed 4.3.

Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

SECTION 5: Firefighting me	asures	
5.1. Extinguishing media		
Suitable extinguishing media	: Carbon dioxide, dry chemical, foam.	
Unsuitable extinguishing media	: Water may beineffective.	
5.2. Special hazards arising from the substance or mixture		
Fire hazard	: Flammable aerosol. Products of combustion may include, and are not limited to: oxides of carbon, hydrocarbons.	
Explosion hazard	: Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.	
5.3. Advice for firefighters		
Firefighting instructions	: Cool closed containers exposed to fire with water.	
Protection during firefighting	: Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).	

SECTIO	ON 6: Accidental releasemeasur	es
6.1.	Personal precautions, protective equip	nent and emergency procedures
General r		Jse personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate sources of ignition.



Safety Data Sheet according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

6.2. Methods and material for co	ntainment and cleaning up
For containment	 Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).
Methods for cleaning up	: Scoop up material and place in a disposal container. Vapours may be heavier than air and may travel along the ground to a distant ignition source and flash back. Provide ventilation.
6.3. Reference to other sections	

SECTION 7: Handling and storage	
7.1. Precautions for safehandling	
Precautions for safe handling	: Keep away from sources of ignition No smoking. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not swallow. When using do not eat, drink or smoke. Do not spray on an open flame or other ignition source. Use only outdoors or in a well-ventilated area. Pressurized container: Do not pierce or burn, even after use.
Hygiene measures	: Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.
7.2. Conditions for safe storage, includin	ig any incompatibilities
Technical measures	: Proper grounding procedures to avoid static electricity should be followed.
Storage conditions	: Keep locked up and out of reach of children. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store away from direct sunlight or other heat sources. Keep dry.
Storage area	: Store in a well-ventilated place.
7.3. Specific end use(s)	

Not available.

SECTION 8: Expo	sure controls/personalprotection		
3.1. Control para	meters		
Distillates, petroleun	n, solvent-dewaxed heavy paraffinic (64742-65-0)		
USA ACGIH	ACGIH TWA	Not applicable	
USA OSHA	OSHA PEL (TWA)	Not applicable	
Petroleum distillates	s, hydrotreated light(64742-47-8)		
USA ACGIH	ACGIH TWA	Not applicable	
USA OSHA	OSHA PEL (TWA)	Not applicable	
Isopropyl alcohol(67	7-63-0)		
USA ACGIH	ACGIH TWA (ppm)	200 ppm	
USA ACGIH	ACGIH STEL (ppm)	400 ppm	
USA OSHA	OSHA PEL (TWA) (mg/m ³)	980 mg/m³	
USA OSHA	OSHA PEL (TWA) (ppm)	400 ppm	
Carbon dioxide (124-	-38-9)		
USA ACGIH	ACGIH TWA (ppm)	5000 ppm	
USA ACGIH	ACGIH STEL (ppm)	30000 ppm	
USA OSHA	OSHA PEL (TWA) (mg/m ³)	9000 mg/m³	
USA OSHA	OSHA PEL (TWA) (ppm)	5000 ppm	
Polypropylene glyco	ol monobutyl ether(9003-13-8)		
USA ACGIH	ACGIH TWA	Not applicable	
USA OSHA	OSHA PEL (TWA)	Not applicable	
N-Phenyl-1-naphthyla	umine (90-30-2)		
USA ACGIH	ACGIH TWA	Not applicable	
USA OSHA	OSHA PEL (TWA)	Not applicable	



Safety Data Sheet according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

8.2. Exposure controls	
Appropriate engineering controls	: Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits. Ensure that eyewash stations and safety showers are close to the workstation location.
Hand protection	: Wear chemically resistant protective gloves.
Eye protection	: Safety glasses or goggles are recommended when using product.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selectedrespirator.
Environmental exposure controls	: Maintain levels below Community environmental protection thresholds.
Other information	: Do not eat, smoke or drink where material is handled, processed or stored. Wash handscarefully before eating or smoking. Handle according to established industrial hygiene and safety practices.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and o	chemical properties
Physical state	: Gas / PressurizedLiquid.
Appearance	: Viscous / Oily.
Color	: Red.
Odor	: Moderate aliphatic.
Odor threshold	: No dataavailable.
рН	: No data available.
Relative evaporation rate (butylacetate=1)	: >1
Melting point	: No data available.
Freezing point	: No data available.
Boiling point	: 177.8 °C (352°F)
Flash point	: 23.9 °C (75 °F)TCC
Auto-ignition temperature	: No dataavailable.
Decomposition temperature	: No dataavailable.
Flammability (solid, gas)	: Flammable.
Vapor pressure	: No dataavailable.
Relative vapor density at 20 °C	: > 1(Air=1)
Relative density	: 0.8
Solubility	: Negligible.
Log Pow	: No dataavailable.
Log Kow	: No dataavailable.
Viscosity, kinematic	: No data available.
Viscosity, dynamic	: No data available.
Explosive properties	: No data available.
Oxidising properties	: No data available.
Explosive limits	: No data available.
9.2. Other information	
VOC content	: <10%
Flame projection length	: 0 cm
Heat of combustion	: 46.4 kJ/g

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reaction known under conditions of normal use.

10.2. **Chemical stability**

Stable under normal storage conditions. Flammable aerosol. Contents under pressure. Container may explode if heated. Do not puncture. Do not burn.

10.3. Possibility of hazardous reactions

No dangerous reaction known under conditions of normaluse.

EN (English)



Safety Data Sheet according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

10.4. **Conditions to avoid**

Heat. Incompatible materials. Sources of ignition. Excessivewater.

10.5. **Incompatible materials**

Strong oxidizing agents. Strong reducing agents. Water.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon, hydrocarbons.

SECTION 11: Toxicological inform	
11.1. Information on toxicological effec	
Acute toxicity	: Harmful if inhaled.
SET Small EngineTune-up	
LD50 oral rat	> 2000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat	>1.0 but ≤5.0 mg/l/4h
Distillates, petroleum, solvent-dewaxed he	eavy paraffinic (64742-65-0)
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 5000 mg/kg
LC50 inhalation rat	2.18 mg/l/4h
Petroleum distillates, hydrotreated light(6	4742-47-8)
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat	> 5.2 mg/l/4h
Isopropyl alcohol(67-63-0)	
LD50 oral rat	4396 mg/kg
LD50 dermal rat	12800 mg/kg
LD50 dermal rabbit	12870 mg/kg
LC50 inhalation rat	72.6 mg/l/4h
Polypropylene glycol monobutyl ether(90	
LD50 oral rat	5840 mg/kg
LD50 dermal rabbit	13340 mg/kg
N-Phenyl-1-naphthylamine (90-30-2)	
LD50 oral rat	1625 mg/kg
LD50 dermal rabbit	> 5000 mg/kg
Skin corrosion/irritation	: Based on available data, the classification criteria are not met.
Serious eye damage/irritation	: Based on available data, the classification criteria are not met.
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Based on available data, the classification criteria are not met.
Carcinogenicity	: Based on available data, the classification criteria are not met.
Isopropyl alcohol(67-63-0)	
IARC group	3 - Not classifiable
Reproductive toxicity	: Based on available data, the classification criteria are not met.
Specific target organ toxicity (single exposure)	: Based on available data, the classification criteria are not met.
Specific target organ toxicity (repeated exposure): Based on available data, the classification criteria are not met.
Aspiration hazard	: May be fatal if swallowed and entersairways.
Symptoms/injuries after inhalation	: Harmful if inhaled. May cause respiratory tractirritation.
Symptoms/injuries after skin contact	: May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin. May cause sensitization by skincontact.
Symptoms/injuries after eye contact	: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness andswelling.

EN (English)



Safety Data Sheet according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Symptoms/injuries after ingestion

: May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.

	cause chemical pheumonilis. May cause stomach distress, hausea of voniding.
SECTION 12: Ecological information	
12.1. Toxicity	
Ecology - general	: May cause long-term adverse effects in the aquatic environment.
12.2. Persistence and degradability	
SET Small EngineTune-up	
Persistence and degradability	Not established.
12.3. Bioaccumulative potential	
SET Small EngineTune-up	
Bioaccumulative potential	Not established.
12.4. Mobility in soil	
No additional information available	
12.5. Other adverse effects	
Effect on ozone layer	: No additional information available
Effect on the global warming	: No known ecological damage caused by this product.
SECTION 13: Disposal consideratio	ns
13.1. Waste treatment methods	
Waste disposal recommendations	: This material must be disposed of in accordance with all local, state, provincial, and federal regulations. The generation of waste should be avoided or minimized wherever possible.
Additional information	: Flammable vapors may accumulate in the container. Do not incinerate empty containers.
SECTION 14: Transport information	
In accordance with DOT	
14.1. UN number	
UN-No.(DOT)	: UN1950
14.2. UN proper shipping name	
Proper Shipping Name (DOT)	: AEROSOLS, flammable, limited quantities
Department of Transportation (DOT) Hazard Classes	: 2.1
Hazard labels (DOT)	
Packing group (DOT)	: Not applicable
14.3. Additionalinformation	
Other information	: No supplementary information available.
Other information Special transport precautions	: No supplementary information available. : Do not handle until all safety precautions have been read and understood.
	: Do not handle until all safety precautions have been read and understood.

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA)inventory.

Isopropyl alcohol (67-63-0)	
Listed on United States SARA Section 313	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
SARA Section 313 - EmissionReporting	1.0 % (only if manufactured by the strong acid process, no supplier notification)



Safety Data Sheet according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

15.3. US State regulations	
SET Small EngineTune-up	
State or local regulations	This product does not contain a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.
SECTION 16: Other information	h
Date of issue	: 01/04/2016
Revision date	: 12/02/2016

Other information : None.

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

