

SAFETY DATA SHEET.

Issuing date 26-May-2017

Revision Date 16-Nov-2018

Version 1.02

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product name 6744-0 STONE/CHIP GUARD COATIN

Recommended use of the chemical and restrictions on use

Product code F02420

Product Type Extremely Flammable Aerosol
Synonyms None

Supplier's details

Recommended Use Automotive bumper and trim product.
Uses advised against No information available

Manufactured For:
Imperial Supplies LLC
789 Armed Forces Drive
P.O. Box 11008
Green Bay, WI 53407-1008
1-800-558-2808

Manufacturer
American Jetway Corporation
34136 Myrtle Street
Wayne, MI 48184-0126
Phone:(734) 721-5930

Emergency telephone number

Chemical Emergency Phone Number CHEMTREC: 1-800-262-8200 ID 1195 (UNITED STATES)

2. HAZARDS IDENTIFICATION

Classification

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Carcinogenicity	Category 2
Reproductive Toxicity	Category 1B
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration toxicity	Category 1
Flammable Aerosols	Category 1
Gases under pressure	Compressed Gas

GHS Label elements, including precautionary statements

Emergency Overview

DANGER

Hazard Statements

Causes skin irritation.
Causes serious eye irritation.
Suspected of causing cancer.
May damage fertility or the unborn child
May cause respiratory irritation. May cause drowsiness or dizziness.
May cause damage to organs (Central Nervous System, Eyes, Kidneys, Liver, Respiratory System, and Skin) through prolonged or repeated exposure.
May be fatal if swallowed and enters airways.
Extremely Flammable Aerosol
Contains gas under pressure; may explode if heated



Appearance Opaque

Physical state Aerosol

Odor Solvent

Precautionary Statements - Prevention

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Wear protective gloves, protective clothing, eye protection, face protection.
Wash face, hands and any exposed skin thoroughly after handling.
Do not breathe dust, fume, gas, mist, vapors, spray.
Use only outdoors or in a well-ventilated area.
Keep away from heat, sparks, open flames, hot surfaces - No smoking.
Do not spray on an open flame or other ignition source.
Pressurized container: Do not pierce or burn, even after use.

Precautionary Statements - Response

If exposed or concerned: Get medical advice, attention.
Specific treatment (see first aid on this label).
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice, attention
IF ON SKIN: Wash with plenty of soap and water.

If skin irritation occurs: Get medical advice, attention.
Take off contaminated clothing and wash it before reuse.
IF INHALED : Remove person to fresh air and keep comfortable for breathing.
Call a POISON CENTER or doctor, physician if you feel unwell.
IF SWALLOWED: Immediately call a POISON CENTER, doctor, physician.
Do NOT induce vomiting.

Precautionary Statements - Storage

Store locked up.
Store in a well-ventilated place. Keep container tightly closed.
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Precautionary Statements - Disposal

Dispose of contents, container to an approved waste disposal plant.

Hazards not otherwise classified (HNOC)

None

Other information

0% of the mixture consists of ingredient(s) of unknown toxicity.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %*
2-BUTANONE	78-93-3	10-20
DIMETHYLETHER	115-10-6	10-20
RESIN BLEND	MIXTURE	10-20
TOLUENE	108-88-3	10-20
CALCIUM CARBONATE	1317-65-3	10-20
BUTYL BENZYL PHTHALATE	85-68-7	1-10
BUTYL ACETATE	123-86-4	1-10
CARBON BLACK	1333-86-4	<1
SILICA, CRYSTALLINE	14808-60-7	<0.1

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES**First aid measures for different exposure routes**

General advice	Avoid contact with skin, eyes, and clothing. Avoid breathing vapors, mist, or gas.
Eye contact	Immediately flush with plenty of water for at least 15 minutes. After initial flushing, remove any contact lenses and continue flushing. If eye irritation persists, consult a doctor.
Skin contact	Wash off immediately with soap and plenty of water for at least 15 minutes. If skin irritation persists, call a physician.
Inhalation	Move to fresh air. If not breathing, give artificial respiration. If breathing has stopped, contact emergency medical services immediately.
Ingestion	Call a physician or Poison Control Center immediately. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Risk of product entering the lungs on vomiting after ingestion.

Most important symptoms/effects, acute and delayed

Main Symptoms Causes skin and serious eye irritation. Suspected of causing cancer. May damage fertility or the unborn child. May cause respiratory irritation. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. May be fatal if swallowed and enters airways.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES**Suitable Extinguishing Media**

Water fog. Dry chemical. Foam. Carbon dioxide (CO₂). Cool containers/tanks with water spray.

Unsuitable Extinguishing Media Do not use a solid water stream as it may scatter and spread fire. Keep away from sources of ignition - No smoking.

Specific hazards arising from the chemical

Extremely Flammable / Flammable. Keep product and empty container away from heat and sources of ignition. In the event of fire and/or explosion do not breathe fumes. In the event of fire, cool tanks with water spray.

Explosion Data

Sensitivity to Mechanical Impact none.

Sensitivity to Static Discharge Yes.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use shielding to protect fire-fighters from bursting containers.

6. ACCIDENTAL RELEASE MEASURES**Personal precautions, protective equipment and emergency procedures**

Personal precautions Use with adequate ventilation to keep the exposure levels below the OELS. Follow safe handling advice and personal protective equipment recommendations.

Environmental precautions

Environmental precautions Vapors can accumulate in low areas. Report spills as required by local and federal regulations. Do not flush into surface water or sanitary sewer system. Do not allow material to contaminate ground water system. Should not be released into the environment.

Methods and materials for containment and cleaning up

Methods for Containment Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from entering drains.

Methods for cleaning up Soak up with inert absorbent material. Contain liquid and collect with an inert, non-combustible material. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly. After cleaning, flush away traces with water. Prevent product from entering drains. Take precautionary measures against static discharges.

7. HANDLING AND STORAGE**Precautions for safe handling**

Advice on safe handling Avoid breathing vapors or mists. Avoid contact with skin, eyes and clothing. Keep away from open flames, hot surfaces and sources of ignition. Contents under pressure. Do not puncture or incinerate cans. Handle in accordance with good industrial hygiene and safety

practice. Take precautionary measures against static discharges.

Conditions for safe storage, including any incompatibilities

Technical measures/Storage conditions

Keep container tightly closed in a dry and well-ventilated place. Keep away from open flames, hot surfaces, and sources of ignition. Keep in properly labeled containers. Keep out of the reach of children. Store locked up.

Incompatible products

Strong acids, alkalis, oxidizing agents.

Aerosol Level

2

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
2-BUTANONE 78-93-3	STEL: 300 ppm TWA: 200 ppm	TWA: 200 ppm TWA: 590 mg/m ³ (vacated) TWA: 200 ppm (vacated) TWA: 590 mg/m ³ (vacated) STEL: 300 ppm (vacated) STEL: 885 mg/m ³	IDLH: 3000 ppm TWA: 200 ppm TWA: 590 mg/m ³ STEL: 300 ppm STEL: 885 mg/m ³
DIMETHYLETHER 115-10-6	STEL: 500 PPM TWA: 400PPM	TWX: 400 PPM TWA: 1200 mg/m ³	IDLH: 1900 PPM (10 % LEL)
TOLUENE 108-88-3	TWA: 20 ppm	TWA: 200 ppm (vacated) TWA: 100 ppm (vacated) TWA: 375 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 560 mg/m ³ Ceiling: 300 ppm	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m ³ STEL: 150 ppm STEL: 560 mg/m ³
CALCIUM CARBONATE 1317-65-3	-	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 15 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust
BUTYL ACETATE 123-86-4	STEL: 150 ppm TWA: 50 ppm	TWA: 150 ppm TWA: 710 mg/m ³ (vacated) TWA: 150 ppm (vacated) TWA: 710 mg/m ³ (vacated) STEL: 200 ppm (vacated) STEL: 950 mg/m ³	IDLH: 1700 ppm TWA: 150 ppm TWA: 710 mg/m ³ STEL: 200 ppm STEL: 950 mg/m ³
CARBON BLACK 1333-86-4	TWA: 3 mg/m ³ inhalable particulate matter	TWA: 3.5 mg/m ³ (vacated) TWA: 3.5 mg/m ³	IDLH: 1750 mg/m ³ TWA: 3.5 mg/m ³ TWA: 0.1 mg/m ³ Carbon black in presence of Polycyclic aromatic hydrocarbons PAH
SILICA, CRYSTALLINE 14808-60-7	TWA: 0.025 mg/m ³ respirable particulate matter	TWA: 50 µg/m ³ (vacated) TWA: 0.1 mg/m ³ respirable dust : (250)/(%SiO ₂ + 5) mppcf TWA respirable fraction : (10)/(%SiO ₂ + 2) mg/m ³ TWA respirable fraction	IDLH: 50 mg/m ³ respirable dust TWA: 0.05 mg/m ³ respirable dust
2-BUTOXYETHANOL 111-76-2	TWA: 20 ppm	TWA: 50 ppm TWA: 240 mg/m ³ (vacated) TWA: 25 ppm (vacated) TWA: 120 mg/m ³ (vacated) S* S*	IDLH: 700 ppm TWA: 5 ppm TWA: 24 mg/m ³

ACGIH: (American Conference of Governmental Industrial Hygienists)

OSHA: (Occupational Safety & Health Administration)

NIOSH IDLH: Immediately Dangerous to Life or Health

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Carbon Black is classified by IARC as a suspected carcinogen(2B). Carbon Black is bound in the polymer matrix and no inhalation exposure will occur during the handling or use of this product in this application. Carbon Black is not classified as a carcinogen for this product.

Exposure controls

Engineering Measures Ventilation systems. Use adequate ventilation to keep the exposure levels below the occupational exposure limits.

Individual protection measures, such as personal protective equipment

Eye/Face Protection Safety glasses with side-shields.

Skin and body protection Chemical resistant apron. Protective gloves.

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

Hygiene measures Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and chemical properties

Physical state	Aerosol		
Appearance	Opaque	Odor	Solvent
Color	Black	Odor Threshold	

<u>Property</u>	<u>Values</u>	<u>Remarks • Methods</u>
pH	No information available	
Melting/freezing point	No information available	
Boiling point/boiling range		
Flash Point	-41 °C / -42 °F	Based on propellant
Evaporation rate	No information available	
Flammability (solid, gas)	No information available	
Flammability Limits in Air		
upper flammability limit		
lower flammability limit		
Vapor pressure		
Vapor density		
Specific Gravity	1.001	
Water solubility	No information available	
Partition coefficient: n-octanol/water		
Autoignition temperature	No information available	Not applicable
Decomposition temperature		
Viscosity	No information available	
Explosive properties		

Other information

VOC Content(%) 62.24

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to Avoid

Extremes of temperature and direct sunlight.

Incompatible Materials

Strong acids, alkalis, oxidizing agents.

Hazardous Decomposition Products

Carbon oxides , Hydrocarbons, Fumes.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure**Product Information**

Inhalation	May cause respiratory irritation. May cause drowsiness or dizziness.
Eye contact	Causes serious eye irritation.
Skin contact	Causes skin irritation.
Ingestion	May be fatal if swallowed and enters airways.

Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
2-BUTANONE 78-93-3	= 2483 mg/kg (Rat)	= 5000 mg/kg (Rabbit)	= 11700 ppm (Rat) 4 h
DIMETHYLETHER 115-10-6	-	-	= 164000 ppm (Rat) 4 h
TOLUENE 108-88-3	= 2600 mg/kg (Rat)	= 12000 mg/kg (Rabbit)	= 12.5 mg/L (Rat) 4 h
BUTYL BENZYL PHTHALATE 85-68-7	= 2330 mg/kg (Rat)	= 6700 mg/kg (Rat)	> 6.7 mg/L (Rat) 4 h
BUTYL ACETATE 123-86-4	= 10768 mg/kg (Rat)	> 17600 mg/kg (Rabbit)	= 390 ppm (Rat) 4 h
CARBON BLACK 1333-86-4	> 15400 mg/kg (Rat)	-	-

Information on toxicological effects

Symptoms	Causes skin and serious eye irritation. Suspected of causing cancer. May damage fertility or the unborn child. May cause drowsiness or dizziness. May cause respiratory irritation. May cause damage to organs (listed below) through prolonged or repeated exposure. May be fatal if swallowed and enters airways.
-----------------	---

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	Irritating to skin.
Eye damage/irritation	Irritating to eyes.
Sensitization	Not a known sensitizer.
Germ cell mutagenicity	Not a germ cell mutagen.
Carcinogenicity	The table below indicates whether each agency has evaluated a listed ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
TOLUENE	-	Group 3	-	-

108-88-3				
BUTYL BENZYL PHTHALATE 85-68-7	-	Group 3	-	-
CARBON BLACK 1333-86-4	A3	Group 2B	-	X
SILICA, CRYSTALLINE 14808-60-7	A2	Group 1	Known	X

ACGIH: (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

A2 - Suspected Human Carcinogen

IARC: (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

Group 1 - Carcinogenic to Humans

NTP: (National Toxicity Program)

Known - Known Carcinogen

OSHA: (Occupational Safety & Health Administration)

X - Present

Reproductive toxicity

Product is or contains a chemical which is a known or suspected reproductive hazard.

Specific target organ systemic toxicity (single exposure)

May cause respiratory irritation. May cause drowsiness and dizziness.

Specific target organ systemic toxicity (repeated exposure)

May cause damage to target organs listed below through prolonged and repeated exposure.

Chronic toxicity

Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Chronic hydrocarbon abuse has been associated with irregular heart rhythms and potential cardiac arrest.

Target Organ Effects

Eyes, Skin, Liver, Kidneys, Respiratory System, Central Nervous System.

Neurological effects

Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.

Aspiration hazard

May be fatal if swallowed and enters airways.

Numerical measures of toxicity - Product Information

Unknown Acute Toxicity

0% of the mixture consists of ingredient(s) of unknown toxicity.

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 25108 mg/kg

ATEmix (dermal) 6506 mg/kg

ATEmix (inhalation-gas) 64286 mg/l

ATEmix (inhalation-dust/mist) 56.7 mg/l

ATEmix (inhalation-vapor) 699 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to microorganisms	Toxicity to daphnia and other aquatic invertebrates
2-BUTANONE 78-93-3	-	3130 - 3320 mg/L LC50 Pimephales promelas 96h flow-through	-	520 mg/L EC50 Daphnia magna 48h 5091 mg/L EC50 Daphnia magna 48h 4025 - 6440 mg/L EC50 Daphnia magna 48h Static
TOLUENE 108-88-3	433 mg/L EC50 Pseudokirchneriella subcapitata 96h 12.5 mg/L EC50 Pseudokirchneriella subcapitata 72h static	15.22 - 19.05 mg/L LC50 Pimephales promelas 96h flow-through 12.6 mg/L LC50 Pimephales promelas 96h static 5.89 - 7.81 mg/L LC50 Oncorhynchus mykiss 96h flow-through 14.1 - 17.16 mg/L LC50 Oncorhynchus mykiss 96h static 5.8 mg/L LC50 Oncorhynchus mykiss 96h semi-static 11.0 - 15.0 mg/L LC50 Lepomis macrochirus 96h static 54	-	5.46 - 9.83 mg/L EC50 Daphnia magna 48h Static 11.5 mg/L EC50 Daphnia magna 48h

		mg/L LC50 Oryzias latipes 96h static 28.2 mg/L LC50 Poecilia reticulata 96h semi-static 50.87 - 70.34 mg/L LC50 Poecilia reticulata 96h static		
BUTYL BENZYL PHTHALATE 85-68-7	0.02 - 0.25 mg/L EC50 Pseudokirchneriella subcapitata 96h 0.2 - 28.2 mg/L EC50 Pseudokirchneriella subcapitata 72h	1.0 - 10.0 mg/L LC50 Oncorhynchus mykiss 96h static 0.82 mg/L LC50 Oncorhynchus mykiss 96h flow-through 1.39 - 3.88 mg/L LC50 Pimephales promelas 96h flow-through 0.78 mg/L LC50 Pimephales promelas 96h static 1.0 - 10.0 mg/L LC50 Lepomis macrochirus 96h static	-	0.9 - 1.1 mg/L EC50 Daphnia magna 48h Static 0.76 mg/L EC50 Daphnia magna 48h Flow through 1.28 mg/L EC50 Daphnia magna 48h semi-static 0.97 mg/L EC50 Daphnia magna 48h
BUTYL ACETATE 123-86-4	674.7 mg/L EC50 Desmodesmus subspicatus 72h	100 mg/L LC50 Lepomis macrochirus 96h static 17 - 19 mg/L LC50 Pimephales promelas 96h flow-through	-	-

Persistence and degradability

.

Bioaccumulation

.

Chemical Name	log Pow
2-BUTANONE 78-93-3	0.3
DIMETHYLETHER 115-10-6	-0.18
TOLUENE 108-88-3	2.7
BUTYL BENZYL PHTHALATE 85-68-7	4.91
BUTYL ACETATE 123-86-4	1.81

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS**Waste treatment****Waste Disposal Methods**

This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261). Dispose of in accordance with federal, state, and local regulations. Dispose of in accordance with federal, state, and local regulations.

Contaminated packaging

Do not re-use empty containers.

14. TRANSPORT INFORMATION**DOT Ground**

CONSUMER COMMODITY ORM-D
or
LIMITED QUANTITY

IATA

UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD.QTY.

IMDG

UN1950, AEROSOLS, 2.1, LTD. QTY.

15. REGULATORY INFORMATION**SCHEDULE B CODE: 3811.90.1000.****International Inventories**

Chemical Name	TSCA	DSL/NDSL	EINECS/ELINCS	ENCS	IECSC	KECL	PICCS	AICS
2-BUTANONE	X	X	X	X	X	X	X	X
DIMETHYLETHER	X	X	X	X	X	X	X	X
TOLUENE	X	X	X	X	X	X	X	X
CALCIUM CARBONATE	X	X	X	X	X	X	X	X
BUTYL BENZYL PHTHALATE	X	X	X	X	X	X	X	X
BUTYL ACETATE	X	X	X	X	X	X	X	X
CARBON BLACK	X	X	X	X	X	X	X	X
SILICA, CRYSTALLINE	X	X	X	X	X	X	X	X

Legend:**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances**ENCS** - Japan Existing and New Chemical Substances**CHINA** - China Inventory of Existing Chemical Substances**KECL** - Korean Existing and Evaluated Chemical Substances**PICCS** - Philippines Inventory of Chemicals and Chemical Substances**AICS** - Australian Inventory of Chemical Substances**U.S. Federal Regulations****SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does contain a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %*	SARA 313 - Threshold Values %
TOLUENE - 108-88-3	108-88-3	10-20	1.0
2-BUTOXYETHANOL - 111-76-2	111-76-2	<0.1	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Star Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	Yes
Reactive Hazard	No

Clean Water Act

This product does contain the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
TOLUENE 108-88-3	1000 lb	X	X	X

BUTYL BENZYL PHTHALATE 85-68-7		X	X	
BUTYL ACETATE 123-86-4	5000 lb			X

CERCLA

This material, as supplied, does contain substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
2-BUTANONE 78-93-3	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
TOLUENE 108-88-3	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ
BUTYL BENZYL PHTHALATE 85-68-7	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
BUTYL ACETATE 123-86-4	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

U.S. State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals:

Carbon Black (CAS # 1333-86-4), must be airborne, unbound, and of a particle size < 10 micrometers in diameter to be considered a Proposition 65 chemical. For this product, Carbon Black is bound in the product and no inhalation exposure will occur during the handling or use of this product in this application.

This product as supplied, does not contain respirable particles of crystalline silica. (CAS # 14808-60-7) Such bound and non-respirable particles are not considered to be hazardous under Proposition 65.



This product can expose you to chemicals including those listed below, which is [are] known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Chemical Name	California Prop. 65
TOLUENE - 108-88-3	Developmental/10-20%
BUTYL BENZYL PHTHALATE - 85-68-7	Developmental 1-10%
CARBON BLACK - 1333-86-4	Cancer / <1%
SILICA, CRYSTALLINE - 14808-60-7	Cancer / <0.1%

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
2-BUTANONE 78-93-3	X	X	X
DIMETHYLETHER 115-10-6	X	X	X
TOLUENE 108-88-3	X	X	X
CALCIUM CARBONATE 1317-65-3	X	X	X
BUTYL BENZYL PHTHALATE 85-68-7	X	X	X
BUTYL ACETATE 123-86-4	X	X	X
CARBON BLACK 1333-86-4	X	X	X

SILICA, CRYSTALLINE 14808-60-7	X	X	X
2-BUTOXYETHANOL 111-76-2	X	X	X

EPA Pesticide Registration Number Not applicable

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all the information required by the CPR.

16. OTHER INFORMATION

NFPA	Health Hazard 2	Flammability 4	Instability 0	Physical and chemical hazards -
HMIS	Health Hazard 2	Flammability 4	Physical Hazard 2 1	Personal protection B
<i>Chronic Hazard Star Legend</i>				
<i>Chronic Health Star Hazard: Aromatic solvents. Severe overexposure may cause liver or kidney damage. Repeated or prolonged exposure may cause central nervous system damage.</i>				

Prepared By American Jetway Corporation
34136 Myrtle Street
Wayne, MI 48184-0126

Issuing date 26-May-2017
Revision Date 16-Nov-2018
Revision Note

Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet