

# **SAFETY DATA SHEET**

### SECTION 1: IDENTIFICATION

Product identifier used on the label:

Product Name: Thin Wheel - Depressed Center

Product Code: Thin Wheels UPC Number: 66252843583

Other means of identification:

Recommended use of the chemical and restrictions on use: Product Use/Restriction: Abrasive Product.

Chemical manufacturer address and telephone number:

Manufacturer Name: Saint-Gobain Abrasives, Inc.

Address: 1 New Bond Street

Worcester, MA 01615

Website: www.Nortonabrasives.com

General Phone Number: 508-795-5000

Emergency phone number:

Emergency Phone Number: 508-795-5000

# SECTION 2: HAZARD(S) IDENTIFICATION

# Classification of the chemical in accordance with CFR 1910.1200(d)(f):

Signal Word: Not applicable.

GHS Class: Not classified as hazardous according to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Hazard Statements: Not applicable. Precautionary Statements: Not applicable.

# Hazards not otherwise classified that have been identified during the classification process:

Route of Exposure: Eyes. Skin. Inhalation. Ingestion.

Eye: Causes eye irritation. Skin: Causes skin irritation.

Inhalation: Prolonged or excessive inhalation may cause respiratory tract irritation.

Ingestion: May be harmful if swallowed. May cause vomiting.

Chronic Health Effects: Prolonged or repeated contact may cause skin irritation.

Overexposure may cause headaches and dizziness. Signs/Symptoms: Target Organs: Eyes. Skin. Respiratory system. Digestive system.

Thin Wheel - Depressed Center Revison Date: 03/31/2015 66252843583 1 of 8 Aggravation of Pre-Existing Conditions:

None generally recognized.

**Fiberglass** 

Inhalation:

Fiberglass contained in wheels have fiber diameters greater than 10 um, therefore considered non-respirable.

# SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

#### Mixtures:

Chemical Name	CAS#	Ingredient Percent	EC Num.
Resin	9003-35-4	10 - 30 by weight	
Fiberglass	65997-17-3	1 - 5 by weight	266-046-0
Inorganic fluorides	Not Applicable	10 - 30 by weight	
Aluminum Oxide, Non-fibrous	1344-28-1	60 - 100 by weight	215-691-6
Notes:	Actual grinding tests with wheels k of respirable free Crystalline Silica.	nown to contain Crystalline Silica did not pro	oduce any detectable amount

### **SECTION 4: FIRST AID MEASURES**

<u>Description of necessary measures:</u>

Immediately flush eyes with plenty of water for at least 15 to 20 minutes. Ensure adequate flushing of the Eye Contact:

eyes by separating the eyelids with fingers. Remove contacts if present and easy to do. Continue rinsing. Get medical attention, if irritation or symptoms of overexposure persists.

Immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists. Skin Contact:

Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained

personnel. Seek immediate medical attention.

Ingestion: If swallowed, do NOT induce vomiting. Call a physician or poison control center immediately. Never give

anything by mouth to an unconscious person.

Most important symptoms/effects, acute and delayed:

Other First Aid: Not applicable.

<u>Indication of immediate medical attention and special treatment needed:</u>

Note to Physicians: Not applicable.

### SECTION 5: FIRE FIGHTING MEASURES

### Suitable and unsuitable extinguishing media:

Thin Wheel - Depressed Center Revison Date: 03/31/2015 66252843583 Suitable Extinguishing Media: Use alcohol resistant foam, carbon dioxide, dry chemical, or water fog or spray when fighting fires

involving this material.

Unsuitable extinguishing media: Not applicable.

Specific hazards arising from the chemical:

Hazardous Combustion

Byproducts:

Not applicable.

Unusual Fire Hazards: Not applicable.

Special protective equipment and precautions for fire-fighters:

As in any fire, wear Self-Contained Breathing Apparatus (SCBA), MSHA/NIOSH (approved or equivalent) Protective Equipment:

and full protective gear.

Fire Fighting Instructions: Not applicable.

**NFPA Ratings**:

NFPA Health: 1 NFPA Flammability: 1 NFPA Reactivity: n



### SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures:

Personal Precautions: Evacuate area and keep unnecessary and unprotected personnel from entering the spill area. Use proper

personal protective equipment as listed in Section 8.

**Environmental precautions:** 

**Environmental Precautions:** Avoid runoff into storm sewers, ditches, and waterways.

Methods and materials for containment and cleaning up:

Spill Cleanup Measures: Not applicable.

Methods and materials for containment and cleaning up:

Methods for containment: Contain spills with an inert absorbent material such as soil or sand. Prevent from spreading by covering,

diking or other means. Provide ventilation.

Clean up spills immediately observing precautions in the protective equipment section. Place into a Methods for cleanup:

suitable container for disposal. Provide ventilation. After removal, flush spill area with soap and water to

remove trace residue.

Reference to other sections:

Other Precautions: Not applicable.

### SECTION 7: HANDLING and STORAGE

Precautions for safe handling:

Handling: Use with adequate ventilation. Avoid breathing vapor and contact with eyes, skin and clothing.

Hygiene Practices: Wash thoroughly after handling. Avoid contact with eyes and skin. Avoid inhaling vapor or mist.

Conditions for safe storage, including any incompatibilities:

Storage: Store in a cool, dry, well ventilated area away from sources of heat, combustible materials, and

incompatible substances. Keep container tightly closed when not in use.

Thin Wheel - Depressed Center Revison Date: 03/31/2015 66252843583

### SECTION 8: EXPOSURE CONTROLS, PERSONAL PROTECTION

#### **EXPOSURE GUIDELINES:**

Ingredient	Guideline OSHA	Guideline NIOSH	Guideline ACGIH	Quebec Canada	Ontario Canada
Fiberglass	PEL-TWA: 1 f/cc as Continuous filament glass		TLV-TWA: 1 f/cc as Continuous filament glass TLV-TWA: 5 mg/m3 as Continuous filament glass		
Inorganic fluorides	PEL-TWA 2.5 mg/m3	REL-TWA 2.5 mg/m3	TLV-TWA 2.5 mg/m3		
Aluminum Oxide, Non-fibrous	PEL-TWA: 5 mg/m3 Respirable fraction (R) PEL-TWA: 15 mg/m3 Total particulate/dust (T)		TLV-TWA: 10 mg/m3	VEMP-TWA: 10 mg/m3 Total particulate/dust (T)	OEL-TWAEV: 10 mg/m3 Total particulate/dust (T)
Ingredient	Alberta Canada	Mexico	British Columbia Canada		
Aluminum Oxide, Non-fibrous	OEL-TWA: 10 mg/m3	MPE-PPT: 0.1 mg/m3 Respirable fraction (R)	OEL-TWA: 3 mg/m3 Respirable fraction (R) OEL-TWA: 10 mg/m3 OEL-TWA: 10 mg/m3 Total particulate/dust (T) OEL-STEL: 20 mg/m3 Total particulate/dust (T)		

#### Appropriate engineering controls:

Engineering Controls:

Use appropriate engineering control such as process enclosures, local exhaust ventilation, or other engineering control sixthern levels below recommended exposure limits. Good general

engineering controls to control airborne levels below recommended exposure limits. Good general ventilation should be sufficient to control airborne levels. Where such systems are not effective wear suitable personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards. Consult with local procedures for selection, training, inspection and maintenance of

the personal protective equipment.

Individual protection measures:

PPE Pictograms:

Eye/Face Protection: Wear appropriate protective glasses or splash goggles as described by 29 CFR 1910.133, OSHA eye and

face protection regulation, or the European standard EN 166.

Skin Protection Description: Chemical-resistant gloves and chemical goggles, face-shield and synthetic apron or coveralls should be

used to prevent contact with eyes, skin or clothing.

Respiratory Protection: A NIOSH approved air-purifying respirator with an organic vapor cartridge or canister may be permissible

under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if

there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

Other Protective: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

**9** 

# SECTION 9: PHYSICAL and CHEMICAL PROPERTIES

#### PHYSICAL AND CHEMICAL PROPERTIES:

Physical State Appearance: Solid article.

Color: Not determined.

Odor: Odorless.

Odor Threshold: Not determined.

Boiling Point: Not determined.

 Thin Wheel - Depressed Center
 66252843583

 Revison Date: 03/31/2015
 4 of 8

Melting Point: Not determined.

Density: Not determined.

Solubility: Not determined.

Vapor Density: Not determined.

Vapor Pressure: Not determined.

**Evaporation Rate:** Not determined.

pH: Not determined.

Viscosity: Not determined.

Coefficient of Water/Oil Not determined.

Distribution:

Flammability: Not determined.

Flash Point: None.

Lower Flammable/Explosive Limit: Not applicable. Upper Flammable/Explosive Limit: Not applicable. Auto Ignition Temperature: Not applicable.

**Explosive Properties:** Excessive dust accumulation could present a potential combustible dust hazard.

VOC Content: Not determined.

# SECTION 10: STABILITY and REACTIVITY

Reactivity:

Reactivity: Not applicable.

Chemical Stability:

Chemical Stability: Stable under normal temperatures and pressures.

Possibility of hazardous reactions:

Hazardous Polymerization: Not reported.

Conditions To Avoid:

Conditions to Avoid: Heat, flames, incompatible materials, and freezing or temperatures below 32 deg. F.

Incompatible Materials:

Oxidizing agents. Strong acids and alkalis. Incompatible Materials:

<u>Hazardous Decomposition Products:</u>

Special Decomposition Products: Not applicable.

# SECTION 11: TOXICOLOGICAL INFORMATION

### TOXICOLOGICAL INFORMATION:

Acute Toxicity: This product has not been tested for its toxicity.

Carcinogens:						
	ACGIH	NIOSH	OSHA	IARC	NTP	MEXICO

Thin Wheel - Depressed Center Revison Date: 03/31/2015 66252843583 5 of 8

Aluminum Oxide,	A4 Not	No Data	No Data	No Data	No Data	A4 Not
Non-fibrous	Classifiable as a					Classifiable as a
	Human					Human
	Carcinogen					Carcinogen

**Resin**:

RTECS Number: SM8542500

Skin: Administration onto the skin - Rat LD50 : >2 gm/kg [Details of toxic effects not reported other than

lethal dose value ] (RTECS)

Ingestion: Oral - Rat LD50 : >5 gm/kg [Details of toxic effects not reported other than lethal dose value ] (RTECS)

Fiberglass:

RTECS Number: LK3651000

**Aluminum Oxide, Non-fibrous:** 

RTECS Number: BD1200000

Inhalation: Inhalation - Rat TCLo: 200 mg/m3/5H/28W (Intermittent) [Lungs, Thorax, or Respiration - Structural or

functional change in trachea or bronchi; Lungs, Thorax, or Respiration - Chronic pulmonary edema;

Related to Chronic Data - death] (RTECS)

### SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity:

Ecotoxicity: Please contact the phone number or address of the manufacturer listed in Section 1 for information on

ecotoxicity.

# SECTION 13: DISPOSAL CONSIDERATIONS

Description of waste:

Waste Disposal: Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the classifications of hazardous waste

prior to disposal. Furthermore, consult with your state and local waste requirements or guidelines, if applicable, to ensure compliance. Arrange disposal in accordance to the EPA and/or state and local

guidelines.

# **SECTION 14: TRANSPORT INFORMATION**

UN number: Not regulated as hazardous material for transportation.

UN proper shipping name: Not regulated as hazardous material for transportation.

Transport hazard class(es): Not regulated as hazardous material for transportation.

Packing group: Not regulated as hazardous material for transportation.

Environmental hazards: Not regulated as hazardous material for transportation.

Special precautions for user: Not regulated as hazardous material for transportation.

 Thin Wheel - Depressed Center
 66252843583

 Revison Date: 03/31/2015
 6 of 8

# **SECTION 15: REGULATORY INFORMATION**

Safety, health and environmental regulations specific for the product:

# **Inventory Status**

	Japan ENCS	EINECS Number	South Korea KECL	Australia AICS	Canada DSL
Resin					Listed
Fiberglass					Listed
Aluminum Oxide, Non-fibrous	(1) -23	262-373-8	KE-01012	Listed	Listed

	TSCA Inventory Status		
Resin	Listed		
Fiberglass	Listed		
Aluminum Oxide, Non-fibrous	Listed		

## **Aluminum Oxide, Non-fibrous:**

Canada IDL: Identified under the Canadian Hazardous Products Act Ingredient Disclosure List: 0.1%.50(1298)

Fiberglass:

EC Number: 266-046-0

**Aluminum Oxide, Non-fibrous:** 

EC Number: 215-691-6

# **State Right To Know**

	RI	MN	IL	PA	MA
Aluminum Oxide, Non-fibrous	Listed	Listed	No Data	Listed	Listed

	NJ		
Aluminum Oxide, Non-fibrous	Listed: NJ Hazardous List; Substance Number: 2891		

# SECTION 16: ADDITIONAL INFORMATION

# **HMIS Ratings**:

HMIS Health Hazard: 1 HMIS Fire Hazard: 1 0 HMIS Reactivity:

Health Hazard	1
Fire Hazard	1
Reactivity	0
Personal Protection	

SDS Creation Date: August 15, 2009

Thin Wheel - Depressed Center Revison Date: 03/31/2015

SDS Revision Date: March 31, 2015

SDS Revision Notes: GHS Update

 $\label{lem:copyright} \textbf{Copyright} \textcircled{$0$ 1996-2015 Actio Corporation. All Rights Reserved.}$ 

 Thin Wheel - Depressed Center
 66252843583

 Revison Date: 03/31/2015
 8 of 8