

Safety Data Sheet

Printing date 06/29/2015

Revised On 06/29/2015

1 Identification of the substance and manufacturer

Trade name: FLAT SAND
Product code: IM00085064
Product category: PC9a Paints and coatings.
Manufacturer/Supplier: Seymour of Sycamore
 917 Crosby Avenue
 Sycamore, IL 60178
 Phone: 815-895-9101 www.seymourpaint.com
Emergency telephone number: CHEMTEL 1-800-255-3924, or 813-248-0585.



2 Hazard(s) identification

Classification of the substance or mixture

Flam. Aerosol 1 H222 Extremely flammable aerosol.
 Press. Gas H280 Contains gas under pressure; may explode if heated.
 Skin Irrit. 2 H315 Causes skin irritation.
 Eye Irrit. 2A H319 Causes serious eye irritation.
 Carc. 2 H351 Suspected of causing cancer.
 STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

GHS Hazard pictograms



GHS02 GHS04 GHS07 GHS08

Signal word

Hazard statements

Danger
 Extremely flammable aerosol.
 Contains gas under pressure; may explode if heated.
 Causes skin irritation.
 Causes serious eye irritation.
 Suspected of causing cancer.
 May cause respiratory irritation. May cause drowsiness or dizziness.
Precautionary statements
 Obtain special instructions before use.
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 Do not spray on an open flame or other ignition source.
 Pressurized container: Do not pierce or burn, even after use.
 Wash hands thoroughly after handling.
 Use only outdoors or in a well-ventilated area.
 Wear protective gloves/protective clothing/eye protection/face protection.
 Do not handle until all safety precautions have been read and understood.
 Avoid breathing dust/fume/gas/mist/vapors/spray.
 Wear protective gloves.
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 Call a poison center/doctor if you feel unwell.
 If skin irritation occurs: Get medical advice/attention.
 If on skin: Wash with plenty of water.
 If eye irritation persists: Get medical advice/attention.
 Take off contaminated clothing and wash it before reuse.
 Store locked up.
 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
 Store in a well-ventilated place. Keep container tightly closed.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Chemical Description:

This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:

67-64-1	Acetone	18.11%
74-98-6	propane	15.75%
1317-65-3	Calcium Carbonate	12.05%
106-97-8	n-butane	9.25%
64742-89-8	VM&P Naphtha	5.08%
2807-30-9	Glycol Ether EP	4.89%
108-10-1	methyl isobutyl ketone	4.87%
13463-67-7	titanium dioxide	4.26%
110-19-0	isobutyl acetate	3.36%
108-65-6	PM acetate	2.66%
107-87-9	Methyl Propyl Ketone	1.55%
1330-20-7	xylene (mix)	1.53%

4 First-aid measures

After inhalation:

Supply fresh air; consult doctor in case of complaints.

After skin contact:

Remove contaminated clothing. Wash exposed area with soap and water.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing:

Rinse mouth with water. Do not induce vomiting.

(Contd. on page 2)

Safety Data Sheet

Printing date 06/29/2015

Revised On 06/29/2015

Trade name: FLAT SAND

(Contd. of page 1)

Most important symptoms and effects:

Dizziness

Indication of any immediate medical attention needed:

No further relevant information available.

5 Fire-fighting measures**Extinguishing agents:**CO₂, extinguishing powder or water spray. Fight larger fires with water spray.**Special hazards:**

Can form explosive gas-air mixtures.

Protective equipment for firefighters:

A respiratory protective device may be necessary.

6 Accidental release measures**Personal precautions, protective equipment and emergency procedures:**

Use respiratory protective device against the effects of fumes/dust/aerosol.

Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to section 13.

7 Handling and storage**Precautions for safe handling**

Use only in well ventilated areas.

Storage requirements:

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.

8 Exposure controls/personal protection**Components with limit values that require monitoring at the workplace:****67-64-1 Acetone**

PEL (USA)	Long-term value: 2400 mg/m ³ , 1000 ppm
REL (USA)	Long-term value: 590 mg/m ³ , 250 ppm
TLV (USA)	Short-term value: (1782) NIC-1187 mg/m ³ , (750) NIC-500 ppm Long-term value: (1188) NIC-594 mg/m ³ , (500) NIC-250 ppm BEI

74-98-6 propane

PEL (USA)	Long-term value: 1800 mg/m ³ , 1000 ppm
REL (USA)	Long-term value: 1800 mg/m ³ , 1000 ppm
TLV (USA)	refer to Appendix F

106-97-8 n-butane

REL (USA)	Long-term value: 1900 mg/m ³ , 800 ppm
TLV (USA)	Short-term value: 2370 mg/m ³ , 1000 ppm

108-10-1 methyl isobutyl ketone

PEL (USA)	Long-term value: 410 mg/m ³ , 100 ppm
REL (USA)	Short-term value: 300 mg/m ³ , 75 ppm Long-term value: 205 mg/m ³ , 50 ppm
TLV (USA)	Short-term value: 307 mg/m ³ , 75 ppm Long-term value: 82 mg/m ³ , 20 ppm BEI

110-19-0 isobutyl acetate

PEL (USA)	Long-term value: 700 mg/m ³ , 150 ppm
REL (USA)	Long-term value: 700 mg/m ³ , 150 ppm
TLV (USA)	Long-term value: 713 mg/m ³ , 150 ppm

108-65-6 PM acetate

WEEL (USA)	Long-term value: 50 ppm
------------	-------------------------

107-87-9 Methyl Propyl Ketone

PEL (USA)	Long-term value: 700 mg/m ³ , 200 ppm
REL (USA)	Long-term value: 530 mg/m ³ , 150 ppm
TLV (USA)	Short-term value: 529 mg/m ³ , 150 ppm

1330-20-7 xylene (mix)

PEL (USA)	Long-term value: 435 mg/m ³ , 100 ppm
REL (USA)	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV (USA)	Short-term value: 651 mg/m ³ , 150 ppm Long-term value: 434 mg/m ³ , 100 ppm BEI

Ingredients with biological limit values:**67-64-1 Acetone**

BEI (USA)	50 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific)
-----------	--

(Contd. on page 3)

Safety Data Sheet

Printing date 06/29/2015

Revised On 06/29/2015

Trade name: FLAT SAND

(Contd. of page 2)

108-10-1 methyl isobutyl ketone

BEI (USA) 1 mg/L
 Medium: urine
 Time: end of shift
 Parameter: MIBK

1330-20-7 xylene (mix)

BEI (USA) 1.5 g/g creatinine
 Medium: urine
 Time: end of shift
 Parameter: Methylhippuric acids

Hygienic protection: Immediately remove all soiled and contaminated clothing.
 Wash hands after use.
 Store protective clothing separately.
 Avoid contact with the eyes and skin.
 Do not eat or drink while working.

Breathing equipment: A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.

Hand protection: Protective gloves. The glove material must be impermeable and resistant to the substance.

Eye protection: Tightly sealed goggles

9 Physical and chemical properties

Appearance: Aerosol.
Odor: Aromatic
Odor threshold: Not determined.

pH-value: Not determined.
Melting point/Melting range: Undetermined.
Boiling point: -44 °C (-47 °F)

Flash point: -19 °C (-2 °F)
Flammability (solid, gas): Extremely flammable.

Decomposition temperature: Not determined.
Auto igniting: Product is not self-igniting.

Danger of explosion: In use, may form flammable/explosive vapour-air mixture.
Lower Explosion Limit: 1.7 Vol %
Upper Explosion Limit: 10.9 Vol %

Vapor pressure: Not determined.
Relative Density: Between 0.77 and 0.85 (Water equals 1.00)
Vapour density: Not determined.
Evaporation rate: Not applicable.
Partition coefficient: n-octanol/water: Not determined.

Solubility: Not determined.
Viscosity: Not determined.

VOC content: 522.4 g/l / 4.36 lb/gl
VOC content (less exempt solvents): 49.8 %
MIR Value: 1.02
Solids content: 31.6 %

10 Stability and reactivity

Reactivity: Stable at normal temperatures.
Conditions to avoid: Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures.

Chemical stability: Not fully evaluated.
Possibility of hazardous reactions: No dangerous reactions known.
Incompatible materials: No further relevant information available.
Hazardous decomposition: No dangerous decomposition products known.

11 Toxicological information**LD/LC50 values that are relevant for classification:****106-97-8 n-butane**

Inhalative	LC50/4 h	658 mg/l (rat)
------------	----------	----------------

108-10-1 methyl isobutyl ketone

Oral	LD50	2100 mg/kg (rat)
Dermal	LD50	16000 mg/kg (rab)
Inhalative	LC50/4 h	8.3-16.6 mg/l (rat)

13463-67-7 titanium dioxide

Oral	LD50	>20000 mg/kg (rat)
Dermal	LD50	>10000 mg/kg (rbt)
Inhalative	LC50/4 h	>6.82 mg/l (rat)

(Contd. on page 4)

Safety Data Sheet

Printing date 06/29/2015

Revised On 06/29/2015

Trade name: FLAT SAND

(Contd. of page 3)

110-19-0 isobutyl acetate

Oral LD50 4763 mg/kg (rbt)

108-65-6 PM acetate

Oral LD50 8500 mg/kg (rat)

Inhalative LC50/4 h 35.7 mg/l (rat)

1330-20-7 xylene (mix)

Oral LD50 8700 mg/kg (rat)

Dermal LD50 2000 mg/kg (rbt)

Inhalative LC50/4 h 6350 mg/l (rat)

Information on toxicological effects: No data available.**Skin effects:** No irritant effect.**Eye effects:** Irritating effect.**Sensitization:** No sensitizing effects known.**Carcinogenic categories****IARC (International Agency for Research on Cancer)**

108-10-1 methyl isobutyl ketone

2B

13463-67-7 titanium dioxide

2B

1330-20-7 xylene (mix)

3

NTP (National Toxicology Program)

None of the ingredients is listed.

12 Ecological information**Aquatic toxicity:**

Hazardous for water, do not empty into drains.

Persistence and degradability:

The product is degradable after prolonged exposure to natural weathering processes.

Bioaccumulative potential:

No further relevant information available.

Mobility in soil:

No further relevant information available.

Other adverse effects:

No further relevant information available.

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation: Completely empty cans should be recycled.**14 Transport information****UN-Number**

UN1950

DOT

N/A

DOT

Consumer Commodity ORM-D

Aerosols, flammable

1950 Aerosols

ADR**Transport hazard class(es):****Class**

2.1

Marine pollutant:

No

Special precautions for user:

Warning: Gases

EMS Number:

F-D,S-U

Quantity limitations

On passenger aircraft/rail: 75 kg

On cargo aircraft only: 150 kg

ADR**Excepted quantities (EQ)**

Code: E0

Not permitted as Excepted Quantity

IMDG**Limited quantities (LQ)**

1L

Excepted quantities (EQ)

Code: E0

Not permitted as Excepted Quantity

Packaging Group:

--

UN "Model Regulation":

UN1950, Aerosols, 2.1

15 Regulatory information**SARA Section 355 (extremely hazardous substances):**

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

108-10-1 methyl isobutyl ketone

1330-20-7 xylene (mix)

CPSC: This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.**California Proposition 65 chemicals known to cause cancer:**

108-10-1 methyl isobutyl ketone

13463-67-7 titanium dioxide

100-41-4 ethyl benzene

1333-86-4 Carbon black

(Contd. on page 5)

Safety Data Sheet

Printing date 06/29/2015

Revised On 06/29/2015

Trade name: FLAT SAND

(Contd. of page 4)

**CANADIAN ENVIRONMENTAL
PROTECTION ACT:**

All hazardous ingredients for this product appear on the Canadian Domestic Substance List.

EPA:

67-64-1	Acetone	I
108-10-1	methyl isobutyl ketone	I
110-19-0	isobutyl acetate	D
1330-20-7	xylene (mix)	I

16 Other information

Contact: Regulatory Affairs
Date of preparation / last revision 06/29/2015 / -