

SAFETY DATA SHEET.

Issuing date 18-May-2015

Revision Date 18-May-2015

Version 1

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product name 6564 CARB & CHOKE CLNR-12 PK

Recommended use of the chemical and restrictions on use

Product code F00297

Product Type Extremely flammable aerosol
Synonyms None

Supplier's details

Recommended Use Carburetor cleaner.
Uses advised against No information available

Manufactured For:
Imperial Supplies LLC
789 Armed Forces Drive
P.O. Box 11008
Green Bay, WI 53407-1038

Manufacturer
American Jetway Corporation
34136 Myrtle Street
Wayne, MI 48184-0126

Emergency telephone number
Chemical Emergency Phone Number Chemtrec 1-800-424-9300

Precautionary Statements - Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

None

Other information

• Toxic to aquatic life with long lasting effects

0% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %*
ACETONE	67-64-1	70-80
METHYL ACETATE	79-20-9	1-10
XYLENE	1330-20-7	1-10
CARBON DIOXIDE	124-38-9	1-10
ETHYL BENZENE	100-41-4	1-10
HYDROTREATED LIGHT DISTILLATES	64742-47-8	0.1-1
NAPHTHENIC OIL, SEVERLY HYDROT	64742-52-5	0.1-1

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES**First aid measures for different exposure routes**

Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. If symptoms persist, call a physician.
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.
Inhalation	Move to fresh air. If breathing is difficult, give oxygen. Artificial respiration and/or oxygen may be necessary. If breathing has stopped, contact emergency medical services immediately.
Ingestion	Rinse mouth. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Drink plenty of water. Call a physician or Poison Control Center immediately.

Most important symptoms/effects, acute and delayed

Main Symptoms Causes skin and eye irritation. Inhalation causing Central Nervous System effects. Ingestion causing lung damage.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Water fog. Dry chemical. Carbon dioxide (CO₂). Cool containers/tanks with water spray.

Unsuitable Extinguishing Media Keep away from heat and sources of ignition. Do not smoke. Cool containers / tanks with water spray.

Specific hazards arising from the chemical

Extremely flammable.

Explosion Data

Sensitivity to Mechanical Impact none.

Sensitivity to Static Discharge Yes.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions

Absorb with sand, clay, or other suitable material. Hard surfaces may be mopped with water. Remove all sources of ignition. Evacuate personnel to safe areas. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. Take precautionary measures against static discharges.

Environmental precautions

Environmental precautions

Do not flush into surface water or sanitary sewer system. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas. Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from entering drains.

Methods and materials for containment and cleaning up

Methods for Containment

Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers. Prevent further leakage or spillage if safe to do so.

Methods for cleaning up

Soak up with inert absorbent material. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly. After cleaning, flush away traces with water. Take precautionary measures against static discharges.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling

Avoid contact with eyes. Avoid breathing vapors or mists. Contents under pressure. Do not puncture or incinerate cans. Do not stick pin or any other sharp object into opening on top of can.

Conditions for safe storage, including any incompatibilities

Technical measures/Storage conditions

Keep container tightly closed in a dry and well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition. Keep in properly labeled containers. Keep out of the reach of children. Store locked up.

Incompatible products

Strong acids, alkalis, or oxidizing agents.

Aerosol Level

2

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
ACETONE 67-64-1	STEL: 750 ppm TWA: 500 ppm	TWA: 1000 ppm TWA: 2400 mg/m ³ (vacated) TWA: 750 ppm (vacated) TWA: 1800 mg/m ³ (vacated) STEL: 2400 mg/m ³ The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors (vacated) STEL: 1000 ppm	IDLH: 2500 ppm TWA: 250 ppm TWA: 590 mg/m ³
METHYL ACETATE 79-20-9	STEL: 250 ppm TWA: 200 ppm	TWA: 200 ppm TWA: 610 mg/m ³ (vacated) TWA: 200 ppm (vacated) TWA: 610 mg/m ³ (vacated) STEL: 250 ppm (vacated) STEL: 760 mg/m ³	IDLH: 3100 ppm TWA: 200 ppm TWA: 610 mg/m ³ STEL: 250 ppm STEL: 760 mg/m ³
XYLENE 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m ³	-
CARBON DIOXIDE 124-38-9	STEL: 30000 ppm TWA: 5000 ppm	TWA: 5000 ppm TWA: 9000 mg/m ³ (vacated) TWA: 10000 ppm (vacated) TWA: 18000 mg/m ³ (vacated) STEL: 30000 ppm (vacated) STEL: 54000 mg/m ³	IDLH: 40000 ppm TWA: 5000 ppm TWA: 9000 mg/m ³ STEL: 30000 ppm STEL: 54000 mg/m ³
ETHYL BENZENE 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m ³	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m ³ STEL: 125 ppm STEL: 545 mg/m ³
HYDROTREATED LIGHT DISTILLATES 64742-47-8	TWA: 200 PPM 8 hours	-	-

ACGIH: (American Conference of Governmental Industrial Hygienists)

OSHA: (Occupational Safety & Health Administration)

NIOSH IDLH: Immediately Dangerous to Life or Health

Other Exposure Guidelines

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Exposure controls

Engineering Measures

Showers
Eyewash stations
Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/Face Protection

Safety glasses with side-shields.

Skin and body protection

Chemical resistant apron. Protective gloves.

Respiratory protection

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

Hygiene measures

Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and chemical properties

Physical state	Aerosol	Odor	Solvent
Appearance	Clear	Odor Threshold	No information available
Color	clear		
<u>Property</u>	<u>Values</u>	<u>Remarks • Methods</u>	
pH	No information available		
Melting/freezing point	No information available		
Boiling point/boiling range	No information available		
Flash Point	-20 °C / -4 °F	Based on lowest flashpoint of the products constituent.	
Evaporation rate	No information available		
Flammability (solid, gas)	No information available		
Flammability Limits in Air			
upper flammability limit	No information available		
lower flammability limit	No information available		
Vapor pressure	No information available		
Vapor density	No information available		
Specific Gravity	0.814		
Water solubility	Practically insoluble		
Partition coefficient: n-octanol/water	No information available	Not applicable	
Autoignition temperature	No information available		
Decomposition temperature	No information available		
Viscosity	No information available		
Explosive properties	No information available		
<u>Other information</u>			
VOC Content(%)	9.09		
MIR Value	0.93		

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to Avoid

Extremes of temperature and direct sunlight.

Incompatible Materials

Strong acids, alkalis, or oxidizing agents.

Hazardous Decomposition Products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation	Vapors may irritate throat and respiratory system. May cause drowsiness and dizziness based on components. May cause irritation of respiratory tract. Avoid breathing vapors or mists.
Eye contact	Irritating to eyes. Avoid contact with eyes.
Skin contact	Irritating to skin. Repeated exposure may cause skin dryness or cracking. Prolonged skin contact may defat the skin and produce dermatitis. Avoid contact with skin.
Ingestion	May be harmful or fatal if swallowed. Aspiration into the lungs during swallowing may cause serious lung damage which may be fatal.

Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
ACETONE 67-64-1	= 5800 mg/kg	20,000 mg/kg (Rabbit)	= 50100 mg/m ³ (Rat) 8 h
METHYL ACETATE 79-20-9	> 5000 mg/kg (Rat)	> 5 g/kg (Rabbit)	= 16000 ppm (Rat) 4 h
XYLENE 1330-20-7	= 3500 mg/kg (Rat)	> 4350 mg/kg (Rabbit)	= 29.08 mg/L (Rat) 4 h
ETHYL BENZENE 100-41-4	-	= 15400 mg/kg (Rabbit)	-
HYDROTREATED LIGHT DISTILLATES 64742-47-8	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat) 4 h

Information on toxicological effects

Symptoms	Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Irritating to skin and eyes. Causes respiratory system irritation. May be harmful or fatal if ingested.
-----------------	--

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	Irritating to skin.
Eye damage/irritation	Irritating to eyes.
Irritation	Irritating to eyes, respiratory system and skin.
Sensitization	None known.
Germ Cell Mutagenicity	None known.
Carcinogenicity	The table below indicates whether each agency has evaluated a listed ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
XYLENE 1330-20-7	-	Group 3	-	-
ETHYL BENZENE 100-41-4	A3	Group 2B	-	-

ACGIH: (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC: (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

OSHA: (Occupational Safety & Health Administration)

X - Present

Reproductive toxicity	This product does not contain any known or suspected reproductive hazards.
Specific target organ systemic toxicity (single exposure)	May cause respiratory irritation. May cause drowsiness and dizziness.
Specific target organ systemic toxicity (repeated exposure)	None under normal use conditions.

Target Organ Effects Neurological effects	Central nervous system, Central Vascular System (CVS), Eyes, Respiratory system, Skin. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.
Aspiration hazard	May be fatal if swallowed and enters airways.

Numerical measures of toxicity - Product Information

Unknown Acute Toxicity 0% of the mixture consists of ingredient(s) of unknown toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (dermal)	15104 mg/kg
ATEmix (inhalation-dust/mist)	16.7 mg/l

12. ECOLOGICAL INFORMATION**Ecotoxicity**

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to microorganisms	Toxicity to daphnia and other aquatic invertebrates
ACETONE 67-64-1	-	4.74 - 6.33 mL/L LC50 Oncorhynchus mykiss 96h 6210 - 8120 mg/L LC50 Pimephales promelas 96h static 8300 mg/L LC50 Lepomis macrochirus 96h	-	10294 - 17704 mg/L EC50 Daphnia magna 48h Static 12600 - 12700 mg/L EC50 Daphnia magna 48h
METHYL ACETATE 79-20-9	120 mg/L EC50 Desmodesmus subspicatus 72h	250 - 350 mg/L LC50 Brachydanio rerio 96h static 295 - 348 mg/L LC50 Pimephales promelas 96h flow-through	-	1026.7 mg/L EC50 Daphnia magna 48h
XYLENE 1330-20-7	-	13.1 - 16.5 mg/L LC50 Lepomis macrochirus 96h flow-through 13.5 - 17.3 mg/L LC50 Oncorhynchus mykiss 96h 2.661 - 4.093 mg/L LC50 Oncorhynchus mykiss 96h static 23.53 - 29.97 mg/L LC50 Pimephales promelas 96h static 30.26 - 40.75 mg/L LC50 Poecilia reticulata 96h static 7.711 - 9.591 mg/L LC50 Lepomis macrochirus 96h static 13.4 mg/L LC50 Pimephales promelas 96h flow-through 19 mg/L LC50 Lepomis macrochirus 96h 780 mg/L LC50 Cyprinus carpio 96h semi-static 780 mg/L LC50 Cyprinus carpio 96h	-	0.6 mg/L LC50 Gammarus lacustris 48h 3.82 mg/L EC50 water flea 48h
ETHYL BENZENE 100-41-4	4.6 mg/L EC50 Pseudokirchneriella subcapitata 72h 438 mg/L EC50 Pseudokirchneriella subcapitata 96h 2.6 - 11.3 mg/L EC50 Pseudokirchneriella subcapitata 72h static 1.7 - 7.6 mg/L EC50 Pseudokirchneriella subcapitata 96h static	11.0 - 18.0 mg/L LC50 Oncorhynchus mykiss 96h static 7.55 - 11 mg/L LC50 Pimephales promelas 96h flow-through 9.1 - 15.6 mg/L LC50 Pimephales promelas 96h static 32 mg/L LC50 Lepomis macrochirus 96h static 4.2 mg/L LC50 Oncorhynchus mykiss 96h semi-static 9.6 mg/L LC50 Poecilia reticulata 96h static	-	1.8 - 2.4 mg/L EC50 Daphnia magna 48h

HYDROTREATED LIGHT DISTILLATES 64742-47-8	-	2.2 mg/L LC50 Lepomis macrochirus 96h static 2.4 mg/L LC50 Oncorhynchus mykiss 96h static 45 mg/L LC50 Pimephales promelas 96h flow-through	-	-
NAPHTHENIC OIL, SEVERLY HYDROT 64742-52-5	-	5000 mg/L LC50 Oncorhynchus mykiss 96h	-	1000 mg/L EC50 Daphnia magna 48h

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical Name	log Pow
ACETONE 67-64-1	-0.24
METHYL ACETATE 79-20-9	0.18
XYLENE 1330-20-7	3.15
ETHYL BENZENE 100-41-4	3.118

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment**Waste Disposal Methods**

This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).

Contaminated packaging

Do not re-use empty containers.

14. TRANSPORT INFORMATION

DOT GroundCONSUMER COMMODITY ORM-D
or
LIMITED QUANTITY**IATA**

UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD. QTY.

IMDG

UN1950, AEROSOLS, 2.1, LTD. QTY.

15. REGULATORY INFORMATION

SCHEDULE B CODE: 2914.11.0000.

International Inventories

Chemical Name	TSCA	DSL/NDL	EINECS/ELI NCS	ENCS	IECSC	KECL	PICCS	AICS
ACETONE	X	X	X	X	X	X	X	X
METHYL ACETATE	X	X	X	X	X	X	X	X
XYLENE	X	X	X	X	X	X	X	X
CARBON DIOXIDE	X	X	X	X	X	X	X	X
ETHYL BENZENE	X	X	X	X	X	X	X	X
HYDROTREATED LIGHT DISTILLATES	X	X	X	X	X	X	X	X
NAPHTHENIC OIL, SEVERLY HYDROT	X	X	X	X	X	X	X	X

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

CHINA - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

U.S. Federal Regulations**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %*	SARA 313 - Threshold Values %
XYLENE - 1330-20-7	1330-20-7	1-10	1.0
ETHYL BENZENE - 100-41-4	100-41-4	1-10	0.1

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	Yes
Reactive Hazard	no

Clean Water Act

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
XYLENE 1330-20-7	100 lb			X
ETHYL BENZENE 100-41-4	1000 lb	X	X	X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
ACETONE 67-64-1	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
XYLENE 1330-20-7	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
ETHYL BENZENE 100-41-4	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

U.S. State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:

Chemical Name	California Prop. 65
ETHYL BENZENE - 100-41-4	Carcinogen

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
ACETONE 67-64-1	X	X	X
METHYL ACETATE 79-20-9	X	X	X
XYLENE 1330-20-7	X	X	X
CARBON DIOXIDE 124-38-9	X	X	X
ETHYL BENZENE 100-41-4	X	X	X

EPA Pesticide Registration Number Not applicable

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

WHMIS Hazard Class

- A Compressed gases
- B5 Flammable aerosol
- D2B Toxic materials



16. OTHER INFORMATION

NFPA	Health Hazard 2	Flammability 4	Instability 0	Physical and chemical hazards -
HMIS	Health Hazard 2*	Flammability 4	Physical Hazard 1	Personal protection B

Prepared By Regulatory Affairs
 Issuing date 18-May-2015
 Revision Date 18-May-2015

Revision Note
 No information available

Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet