

SAFETY DATA SHEET.

Issuing date 12-Dec-2014

Revision Date 30-Apr-2018

Version 4

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product name 6570-1 ANTI-SEIZE-6 PK

Recommended use of the chemical and restrictions on use

Product code F00263

Product Type Extremely Flammable Aerosol
Synonyms None

Supplier's details

Recommended Use Anti-Seize Lubricant.
Uses advised against No information available

Manufactured For:
Imperial Supplies LLC
789 Armed Forces Drive
P.O. Box 11008
Green Bay, WI 53407-1008
1-800-558-2808

Manufacturer
American Jetway Corporation
34136 Myrtle Street
Wayne, MI 48184-0126
Phone:(734) 721-5930

Emergency telephone number
Chemical Emergency Phone Number CHEMTREC: 1-800-262-8200 ID 1195 (UNITED STATES)

2. HAZARDS IDENTIFICATION

Classification

Acute toxicity - Inhalation (Vapors)	Category 4
Aspiration toxicity	Category 1
Flammable aerosols	Category 1
Gases under pressure	Compressed Gas

GHS Label elements, including precautionary statements

Emergency Overview

DANGER

Hazard Statements

Harmful if inhaled
 May be fatal if swallowed and enters airways
 Extremely Flammable Aerosol
 Contains gas under pressure; may explode if heated



Appearance Opaque

Physical state Aerosol

Odor Solvent

Precautionary Statements - Prevention

Do not breathe dust/fume/gas/mist/vapors/spray.
 Use only outdoors or in a well-ventilated area
 Keep away from heat/sparks/open flames/hot surfaces.-No smoking.
 Do not spray on an open flame or other ignition source.
 Pressurized container: Do not pierce or burn, even after use

Precautionary Statements - Response

Call a POISON CENTER or doctor/physician if you feel unwell
 IF INHALED : Remove person to fresh air and keep comfortable for breathing.
 IF SWALLOWED: Immediately call a POISON CENTER /doctor/physician
 Do NOT induce vomiting.

Precautionary Statements - Storage

Store locked up
 Protect from sunlight. Store in a well-ventilated place
 Do not expose to temperatures exceeding 122°F (50°C)

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

None

Other information

0% of the mixture consists of ingredient(s) of unknown toxicity.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %*
NAPHTHENIC OIL, SEVERLY HYDROT	64742-52-5	30-40
PROPANE/ISOBUTANE/N-BUTANE	68476-86-8	20-30
HYDROTREATED LIGHT DISTILLATES	64742-47-8	20-30
HEPTANE	64742-49-0	1-10
ALUMINUM POWDER	7429-90-5	1-10
HYDROTREATED HEAVY NAPHTHENIC	64742-48-9	1-10
GRAPHITE	7782-42-5	1-10

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

First aid measures for different exposure routes

General advice	Avoid contact with eyes, skin, and clothing. Avoid breathing vapors, mist, or gas.
Eye contact	Immediately flush with plenty of water for at least 15 minutes. After initial flushing, remove any contact lenses and continue flushing. If eye irritation persists, consult a doctor.
Skin contact	Wash off with soap and plenty of water. Remove and wash contaminated clothing before re-use. If skin irritation persists, call a physician.
Inhalation	Move to fresh air. If not breathing, give artificial respiration. If breathing has stopped, contact emergency medical services immediately.
Ingestion	Call a physician or Poison Control Center immediately. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Risk of product entering the lungs on vomiting after ingestion.

Most important symptoms/effects, acute and delayed

Main Symptoms Harmful if inhaled. May be fatal if swallowed and enters airways.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Do not give chemical antidotes. Asphyxia from glottal edema may occur. Marked decrease in blood pressure may occur with moist rales, frothy sputum, and high pulse pressure. Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Water fog. Dry chemical. Foam. Carbon dioxide (CO₂). Cool containers/tanks with water spray. Water fog. Foam. Carbon dioxide (CO₂). Cool containers / tanks with water spray.

Unsuitable Extinguishing Media Do not use a solid water stream as it may scatter and spread fire. Cool containers / tanks with water spray. Keep away from sources of ignition - No smoking.

Specific hazards arising from the chemical

Extremely Flammable / Flammable. Keep product and empty container away from heat and sources of ignition. The product causes burns of eyes, skin and mucous membranes. Thermal decomposition can lead to release of irritating gases and vapors. In the event of fire and/or explosion do not breathe fumes. Keep product and empty container away from heat and sources of ignition.

Explosion Data**Sensitivity to Mechanical Impact** none.**Sensitivity to Static Discharge** Yes.**Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use shielding to protect fire-fighters from bursting containers. In the event of fire and/or explosion do not breathe fumes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Use with adequate ventilation to keep the exposure levels below the OELS. Follow safe handling advice and personal protective equipment recommendations.

Environmental precautions

Environmental precautions Vapors can accumulate in low areas. Report spills as required by local and federal regulations. Prevent product from entering drains. Do not allow material to contaminate ground water system. Should not be released into the environment.

Methods and materials for containment and cleaning up

Methods for Containment Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from entering drains.

Methods for cleaning up Soak up with inert absorbent material. Contain liquid and collect with an inert, non-combustible material. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly. After cleaning, flush away traces with water. Prevent product from entering drains. Take precautionary measures against static discharges.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Avoid breathing vapors or mists. Avoid contact with skin, eyes and clothing. Keep away from open flames, hot surfaces and sources of ignition. Do not puncture or incinerate cans. Contents under pressure. Handle in accordance with good industrial hygiene and safety practice. Take precautionary measures against static discharges.

Conditions for safe storage, including any incompatibilities

Technical measures/Storage conditions Keep container tightly closed in a dry and well-ventilated place. Keep away from open flames, hot surfaces, and sources of ignition. Keep in properly labeled containers. Keep out of the reach of children. Store locked up.

Incompatible products Strong acids, alkalis, oxidizing agents.

Aerosol Level 3

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters**Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH

PROPANE/ISOBUTANE/N-BUTANE 68476-86-8	74-98-6: TWA: 1000 ppm 106-97-8: STEL: 1000 ppm 75-28-5: STEL: 1000 ppm	74-98-6:TWA: 1000 ppm TWA: 1800 mg/m ³ (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m ³ 106-97-8: (vacated) TWA: 800 ppm (vacated) TWA: 1900 mg/m ³	74-98-6:IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m ³ 106-97-8:TWA: 800 ppm TWA: 1900 mg/m ³ 75-28-5:TWA: 800 ppm TWA: 1900 mg/m ³
HYDROTREATED LIGHT DISTILLATES 64742-47-8	TWA: 200 PPM 8 hours	-	-
HEPTANE 64742-49-0	TLV: 400 ppm STEL: 500 ppm	TWA: 500 ppm	-
ALUMINUM POWDER 7429-90-5	TWA: 1 mg/m ³ respirable fraction	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 15 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 5 mg/m ³ Al Aluminum	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust TWA: 5 mg/m ³ Al
GRAPHITE 7782-42-5	TWA: 2 mg/m ³ respirable fraction all forms except graphite fibers	TWA: 15 mg/m ³ total dust synthetic TWA: 5 mg/m ³ respirable fraction synthetic (vacated) TWA: 2.5 mg/m ³ respirable dust natural (vacated) TWA: 10 mg/m ³ total dust synthetic (vacated) TWA: 5 mg/m ³ respirable fraction synthetic TWA: 15 mppcf natural	IDLH: 1250 mg/m ³ TWA: 2.5 mg/m ³ natural respirable dust

ACGIH: (American Conference of Governmental Industrial Hygienists)

OSHA: (Occupational Safety & Health Administration)

NIOSH IDLH: Immediately Dangerous to Life or Health

Other Exposure Guidelines

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Exposure controls

Engineering Measures

Ventilation systems. Use adequate ventilation to keep the exposure levels below the occupational exposure limits.

Individual protection measures, such as personal protective equipment

Eye/Face Protection

Tightly fitting safety goggles.

Skin and body protection

Chemical resistant apron. Protective gloves.

Respiratory protection

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

Hygiene measures

When using, do not eat, drink or smoke. Provide regular cleaning of equipment, work area and clothing. Keep away from food, drink and animal feeding stuffs. Contaminated work clothing should not be allowed out of the workplace. Avoid breathing vapors or mists. Avoid contact with skin, eyes and clothing. Keep away from open flames, hot surfaces and sources of ignition. Handle in accordance with good industrial hygiene and safety practice. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. For environmental protection, remove and wash all contaminated protective equipment before re-use. Wear suitable gloves and eye/face protection.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and chemical properties

Physical state	Aerosol	Odor	Solvent
Appearance	Opaque	Odor Threshold	
Color	Dark Silvery Gray /Copper		
Property	Values	Remarks • Methods	
pH	No information available		
Melting/freezing point	No information available		
Boiling point/boiling range			
Flash Point	-104 °C / -156 °F	Based on propellant	
Evaporation rate	No information available		
Flammability (solid, gas)	No information available		
Flammability Limits in Air			
upper flammability limit			
lower flammability limit			
Vapor pressure			
Vapor density			
Specific Gravity	0.792		
Water solubility	No information available		
Partition coefficient: n-octanol/water			
Autoignition temperature	No information available	Not applicable	
Decomposition temperature			
Viscosity	No information available		
Explosive properties			
Other information			
VOC Content(%)	33.47		

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to Avoid

Heat, flames and sparks.

Incompatible Materials

Strong acids, alkalis, oxidizing agents.

Hazardous Decomposition Products

Carbon oxides , Hydrocarbons, Fumes.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation	Harmful if inhaled.
Eye contact	Eye irritation may occur if excessive exposure to product occurs.
Skin contact	Skin irritation may occur if person excessively exposes product to the skin.
Ingestion	May be fatal if swallowed and enters airways.

Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
HYDROTREATED LIGHT DISTILLATES 64742-47-8	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat) 4 h
HEPTANE 64742-49-0	> 5000 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	= 73680 ppm (Rat) 4 h
HYDROTREATED HEAVY NAPHTHENIC 64742-48-9	> 5000 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	-

Information on toxicological effects

Symptoms Harmful if inhaled. May be fatal if swallowed and enters airways.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Under normal conditions there is no skin irritation. Excessive exposure of product with skin may cause skin irritation.

Eye damage/irritation Under normal conditions there is no eye irritation . Excessive conditions to product may cause eye irritation.

Sensitization Not a known sensitizer.

Germ Cell Mutagenicity Not a germ cell mutagen.

Carcinogenicity There are no known carcinogenic chemicals in this product.

IARC: (International Agency for Research on Cancer)

Group 3 - Not Classifiable as to Carcinogenicity in Humans

Reproductive toxicity This product does not contain any known or suspected reproductive hazards.

Specific target organ systemic toxicity (single exposure) None under normal use conditions.

Specific target organ systemic toxicity (repeated exposure) None under normal use conditions.

Chronic toxicity Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Chronic hydrocarbon abuse has been associated with irregular heart rhythms and potential cardiac arrest.

Target Organ Effects No known effects under normal use conditions.

Neurological effects Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.

Aspiration hazard May be fatal if swallowed and enters airways.

Numerical measures of toxicity - Product Information

Unknown Acute Toxicity 0% of the mixture consists of ingredient(s) of unknown toxicity.

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral)	8248 mg/kg
ATEmix (dermal)	33806 mg/kg
ATEmix (inhalation-gas)	1610354 mg/l
ATEmix (inhalation-dust/mist)	35.8 mg/l
ATEmix (inhalation-vapor)	13 mg/l

12. ECOLOGICAL INFORMATION**Ecotoxicity**

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to microorganisms	Toxicity to daphnia and other aquatic invertebrates
NAPHTHENIC OIL, SEVERLY HYDROT 64742-52-5	-	5000 mg/L LC50 Oncorhynchus mykiss 96h	-	1000 mg/L EC50 Daphnia magna 48h

HYDROTREATED LIGHT DISTILLATES 64742-47-8	-	45 mg/L LC50 Pimephales promelas 96h flow-through 2.2 mg/L LC50 Lepomis macrochirus 96h static 2.4 mg/L LC50 Oncorhynchus mykiss 96h static	-	-
HYDROTREATED HEAVY NAPHTHENIC 64742-48-9	-	2200 mg/L LC50 Pimephales promelas 96h	-	-

Persistence and degradability

.

Bioaccumulation

Chemical Name	log Pow
PROPANE/ISOBUTANE/N-BUTANE 68476-86-8	<=2.8

Other adverse effects No information available**13. DISPOSAL CONSIDERATIONS****Waste treatment****Waste Disposal Methods**

This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261). Dispose of in accordance with federal, state, and local regulations. Dispose of in accordance with federal, state, and local regulations.

Contaminated packaging

Do not re-use empty containers.

14. TRANSPORT INFORMATION**DOT Ground**

CONSUMER COMMODITY ORM-D
or
LIMITED QUANTITY

IATA

UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD.QTY.

IMDG

UN1950, AEROSOLS, 2.1, LTD. QTY.

15. REGULATORY INFORMATION**International Inventories**

Chemical Name	TSCA	DSL/NDL	EINECS/ELI NCS	ENCS	IECSC	KECL	PICCS	AICS
NAPHTHENIC OIL, SEVERLY HYDROT	X	X	X	Not listed	X	X	X	X
PROPANE/ISOBUTANE/N-BUTANE	X	X	X	Not listed	X	X	X	X

HYDROTREATED LIGHT DISTILLATES	X	X	X	Not listed	X	X	X	X
HEPTANE	X	X	X	Not listed	X	X	X	X
ALUMINUM POWDER	X	X	X	Not listed	X	X	X	X
HYDROTREATED HEAVY NAPHTHENIC	X	X	X	Not listed	X	X	X	X
GRAPHITE	X	X	X	Not listed	X	X	X	X

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

CHINA - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

U.S. Federal Regulations**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does contain a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %*	SARA 313 - Threshold Values %
ALUMINUM POWDER - 7429-90-5	7429-90-5	1-10	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Star Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	Yes
Reactive Hazard	No

Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

U.S. State Regulations**California Proposition 65**

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

This product does not contain any chemicals subject to state reporting regulations that are not already listed elsewhere in this document.

Chemical Name	New Jersey	Massachusetts	Pennsylvania
ALUMINUM POWDER 7429-90-5	X	X	X
GRAPHITE 7782-42-5	X	X	X

EPA Pesticide Registration Number Not applicable

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all the information required by the CPR.

WHMIS Hazard Class

- A Compressed gases
- B5 Flammable aerosol
- D2B Toxic materials

16. OTHER INFORMATION

<u>NFPA</u>	Health Hazard 2	Flammability 4	Instability 0	Physical and chemical hazards -
<u>HMIS</u>	Health Hazard 2*	Flammability 4	Physical Hazard 1	Personal protection B

Prepared By American Jetway
 34136 Myrtle Street
 Wayne, MI 48184
 Tel.734-721-5930

Issuing date 12-Dec-2014
Revision Date 30-Apr-2018

Revision Note
 (M)SDS sections updated

Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet