

Multi-Purpose Lubricator and Penetrating Oil (Aerosol)

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Date of issue: 03/08/2017

Revision date: 03/08/2017

Version: 1.0

SECTION 1: Identification

1.1. Identification

Product name : Multi-Purpose Lubricator and Penetrating Oil (Aerosol)
Product code : HMP051, HMP053, HMP055, HMP056

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Petroleum lubricant

1.3. Details of the supplier of the safety data sheet

Manufacturer

R.B. Howes & Co., Inc.
3511 North Ohio Street
Wichita, 67219 - USA
T 401-294-5500, 1-800 GET HOWES (438-4693)

Manufacturer

R.B. Howes & Co., Inc.
35 Regan Road
Brampton, L7A 1B2 - Canada
T 401-294-5500, 1-800 GET HOWES (438-4693)

1.4. Emergency telephone number

Emergency number : CHEMTREC 1 (800) 424-9300

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

GHS classification

Flam. Aerosol 1
Press. Gas (Liq.)
Skin Irrit. 2
Repr. 1A
Asp. Tox. 1

2.2. Label elements

GHS labelling

Hazard pictograms (GHS) :



Signal word (GHS) :

Danger

Hazard statements (GHS) :

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. May damage fertility or the unborn child. May be fatal if swallowed and enters airways.

Precautionary statements (GHS) :

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Wash hands, forearms and face thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. If swallowed: Immediately call a doctor. Do NOT induce vomiting. If on skin: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. If exposed or concerned: Get medical advice/attention. Store locked up. Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

Multi-Purpose Lubricator and Penetrating Oil (Aerosol)

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

3.2. Mixtures

Name	Product identifier	%
Distillates, petroleum, hydrotreated heavy naphthenic	(CAS-No.) 64742-52-5	55.60
Kerosine, petroleum	(CAS-No.) 8008-20-6	36.75
Carbon dioxide	(CAS-No.) 124-38-9	2.00
Barium dinonylnaphthalenesulfonate	(CAS-No.) 25619-56-1	1.47
Pine oil	(CAS-No.) 8002-09-3	1.32
Methyl salicylate	(CAS-No.) 119-36-8	0.79

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.
- First-aid measures after skin contact : IF ON SKIN: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention.
- First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- First-aid measures after ingestion : IF SWALLOWED: immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. Never give anything by mouth to an unconscious person.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/effects after inhalation : May cause irritation to the respiratory tract.
- Symptoms/effects after skin contact : Causes skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.
- Symptoms/effects after eye contact : May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
- Symptoms/effects after ingestion : May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Foam. Carbon dioxide. Water spray or fog.
- Unsuitable extinguishing media : Do not use water jet.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Extremely flammable aerosol. Products of combustion may include, and are not limited to: oxides of carbon.
- Explosion hazard : Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.
- Reactivity : No dangerous reactions known under normal conditions of use.

5.3. Advice for firefighters

- Firefighting instructions : Containers may explode when heated.
- Protection during firefighting : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA). Cool down the containers exposed to heat with a water spray. Vapors may be heavier than air and may travel along the ground to a distant ignition source and flash back.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate sources of ignition. Use only non-sparking tools. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

Multi-Purpose Lubricator and Penetrating Oil (Aerosol)

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

6.2. Environmental precautions

Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

- For containment : Absorb and/or contain spill with inert material (sand, vermiculite or other appropriate material), then place in suitable container. Do not flush into surface water or sewer system. Wear recommended personal protective equipment.
- Methods for cleaning up : Sweep or shovel spills into appropriate container for disposal. Provide ventilation. Spilled material may present a slipping hazard.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Pressurized container: Do not pierce or burn, even after use. Keep away from sources of ignition - No smoking. Hazardous waste due to potential risk of explosion.
- Precautions for safe handling : Keep away from sources of ignition - No smoking. Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Avoid contact with skin and eyes. Avoid breathing vapour or mist. Do not swallow. When using do not eat, drink or smoke. Use only outdoors or in a well-ventilated area.
- Hygiene measures : Wash contaminated clothing before reuse. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Proper grounding procedures to avoid static electricity should be followed.
- Storage conditions : Keep out of the reach of children. Store in a well-ventilated place. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store away from direct sunlight or other heat sources. Keep in fireproof place. Store locked up.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Distillates, petroleum, hydrotreated heavy naphthenic (64742-52-5)

Not applicable

Kerosine, petroleum (8008-20-6)

ACGIH	ACGIH TWA (mg/m ³)	200 mg/m ³ (application restricted to conditions in which there are negligible aerosol exposures-total hydrocarbon vapor)
NIOSH	NIOSH REL (TWA) (mg/m ³)	100 mg/m ³

Carbon dioxide (124-38-9)

ACGIH	ACGIH TWA (ppm)	5000 ppm
ACGIH	ACGIH STEL (ppm)	30000 ppm
OSHA	OSHA PEL (TWA) (mg/m ³)	9000 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	5000 ppm
IDLH	US IDLH (ppm)	40000 ppm
NIOSH	NIOSH REL (TWA) (mg/m ³)	9000 mg/m ³
NIOSH	NIOSH REL (TWA) (ppm)	5000 ppm
NIOSH	NIOSH REL (STEL) (mg/m ³)	54000 mg/m ³
NIOSH	NIOSH REL (STEL) (ppm)	30000 ppm

Barium dinonylnaphthalenesulfonate (25619-56-1)

Not applicable

Pine oil (8002-09-3)

Not applicable

Methyl salicylate (119-36-8)

Not applicable

Multi-Purpose Lubricator and Penetrating Oil (Aerosol)

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

8.2. Exposure controls

Appropriate engineering controls	: Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.
Hand protection	: Wear suitable gloves resistant to chemical penetration.
Eye protection	: Safety glasses or goggles are recommended when using product.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Environmental exposure controls	: Avoid release to the environment.
Other information	: Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Gas
Appearance	: No data available
Colour	: Dark amber
Odour	: Distinctive
Odour threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 164 °C (327 °F)
Flash point	: 65.6 °C (150 °F) Rapid Flash Point Closed-Cup, ASTM D3243 (Liquid)
Relative evaporation rate (butylacetate=1)	: No data available
Flammability (solid, gas)	: Extremely flammable aerosol.
Vapour pressure	: < 0.1 mm Hg
Relative vapour density at 20 °C	: > 1 (air = 1)
Relative density	: < 0.9 (water = 1)
Solubility	: Insoluble.
Partition coefficient n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: < 20.5 cSt @ 40 °C (104 °F)
Viscosity, dynamic	: No data available
Explosive limits	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

10.2. Chemical stability

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Extreme risk of explosion by shock, friction, fire or other sources of ignition.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Sources of ignition. Heat. Incompatible materials. Direct sunlight.

Multi-Purpose Lubricator and Penetrating Oil (Aerosol)

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

10.5. Incompatible materials

Strong oxidizers.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified.
Acute toxicity (dermal) : Not classified.
Acute toxicity (inhalation) : Not classified.

Distillates, petroleum, hydrotreated heavy naphthenic (64742-52-5)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg

Kerosine, petroleum (8008-20-6)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat	> 5.28 mg/l/4h

Barium dinonylnaphthalenesulfonate (25619-56-1)	
LD50 oral rat	1750 mg/kg
LD50 dermal rabbit	> 1000 mg/kg
LC50 inhalation rat	> 21 mg/l (Exposure time: 1 h)

Pine oil (8002-09-3)	
LD50 oral rat	3200 mg/kg
LD50 dermal rabbit	400 mg/kg
LC50 inhalation rat	> 3.79 mg/l/4h

Methyl salicylate (119-36-8)	
LD50 oral rat	887 mg/kg
LD50 dermal rabbit	> 5000 mg/kg

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Not classified.
Respiratory or skin sensitisation : Not classified.
Germ cell mutagenicity : Not classified.
Carcinogenicity : Not classified.
Reproductive toxicity : May damage fertility or the unborn child.
STOT-single exposure : Not classified.
STOT-repeated exposure : Not classified.
Aspiration hazard : May be fatal if swallowed and enters airways.

Multi-Purpose Lubricator and Penetrating Oil (Aerosol)	
Vaporizer	Aerosol
Viscosity, kinematic (calculated value)	< 20.5 mm ² /s @ 40 °C (104 °F)

Symptoms/effects after inhalation : May cause irritation to the respiratory tract.
Symptoms/effects after skin contact : Causes skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.
Symptoms/effects after eye contact : May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
Symptoms/effects after ingestion : May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : May cause long-term adverse effects in the aquatic environment.

Multi-Purpose Lubricator and Penetrating Oil (Aerosol)

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Distillates, petroleum, hydrotreated heavy naphthenic (64742-52-5)	
LC50 fish 1	> 5000 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
EC50 Daphnia 1	> 1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)

Pine oil (8002-09-3)	
EC50 Daphnia 1	17 - 28 mg/l (Exposure time: 48 h - Species: Daphnia magna [Flow through])

12.2. Persistence and degradability

Multi-Purpose Lubricator and Penetrating Oil (Aerosol)	
Persistence and degradability	Not established.

12.3. Bioaccumulative potential

Multi-Purpose Lubricator and Penetrating Oil (Aerosol)	
Bioaccumulative potential	Not established.

Carbon dioxide (124-38-9)	
BCF fish 1	(no bioaccumulation)

Methyl salicylate (119-36-8)	
Partition coefficient n-octanol/water	2.55

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on the global warming : No known effects from this product.
Other information : No other effects known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.
Additional information : Flammable vapours may accumulate in the container.

SECTION 14: Transport information

Department of Transportation (DOT) and Transportation of Dangerous Goods (TDG)

In accordance with DOT/TDG

UN-No.(DOT/TDG) : UN1950
Proper Shipping Name (DOT/TDG) : Aerosols
Class (DOT/TDG) : Class 2.1 - Flammable gas 49 CFR 173.115
Hazard labels (DOT/TDG) :



SECTION 15: Regulatory information

15.1. Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

All components of this product are listed, or excluded from listing, on the Canadian DSL (Domestic Substances List) and NDSL (Non-Domestic Substances List) inventories.

Distillates, petroleum, hydrotreated heavy naphthenic (64742-52-5)	
Listed on the Canadian DSL (Domestic Substances List)	

Kerosine, petroleum (8008-20-6)	
Listed on the Canadian DSL (Domestic Substances List)	

Carbon dioxide (124-38-9)	
Listed on the Canadian DSL (Domestic Substances List)	

Multi-Purpose Lubricator and Penetrating Oil (Aerosol)

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Barium dinonylnaphthalenesulfonate (25619-56-1)

Listed on the Canadian DSL (Domestic Substances List)

Pine oil (8002-09-3)

Listed on the Canadian DSL (Domestic Substances List)

Methyl salicylate (119-36-8)

Listed on the Canadian DSL (Domestic Substances List)

15.2. International regulations

No additional information available

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

Kerosine, petroleum (8008-20-6)

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

Carbon dioxide (124-38-9)

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

Pine oil (8002-09-3)

U.S. - New Jersey - Right to Know Hazardous Substance List

Methyl salicylate (119-36-8)

U.S. - Pennsylvania - RTK (Right to Know) List

NFPA health hazard


: 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

NFPA fire hazard

: 4 - Materials that rapidly or completely vaporize at atmospheric pressure and normal ambient temperature or that are readily dispersed in air and burn readily.

NFPA reactivity

: 0 - Material that in themselves are normally stable, even under fire conditions.



SECTION 16: Other information

Revision date

: 03/08/2017

Other information

: None.

Prepared by

: Nexreg Compliance Inc.

www.Nexreg.com



SDS HazCom 2012 - WHMIS 2015 (NexReg_Howes Lubricator)

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.