

SAFETY DATA SHEET.

Issuing date 15-May-2017

Revision Date 20-Nov-2018

Version 1.02

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product name 5536 DIESEL TNK ADDTV ANTI-GEL

Recommended use of the chemical and restrictions on use

Product code F01960

Product Type Flammable Liquid and Vapour
Synonyms None

Supplier's details

Recommended Use Diesel Fuel Additive.
Uses advised against No information available

Manufactured For:	Manufacturer
Imperial Supplies LLC	American Jetway Corporation
789 Armed Forces Drive	34136 Myrtle Street
P.O. Box 11008	Wayne, MI 48184-0126
Green Bay, WI 53407-1008	Phone:(734) 721-5930
1-800-558-2808	

Emergency telephone number
Chemical Emergency Phone Number CHEMTREC: 1-800-262-8200 ID 1195 (UNITED STATES)

2. HAZARDS IDENTIFICATION

Classification

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Carcinogenicity	Category 1A
Specific target organ toxicity (single exposure)	Category 3
Aspiration toxicity	Category 1
Flammable Liquids	Category 3

GHS Label elements, including precautionary statements

Emergency Overview

DANGER

Hazard Statements

Causes skin irritation.
Causes serious eye irritation.
May cause cancer.
May cause respiratory irritation. May cause drowsiness or dizziness.
May be fatal if swallowed and enters airways.
Flammable Liquid and Vapour



Appearance Hazy

Physical state Liquid

Odor Solvent

Precautionary Statements - Prevention

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Wear protective gloves/protective clothing/eye protection/face protection.
Wash face, hands and any exposed skin thoroughly after handling.
Avoid breathing dust/fume/mist/vapors/spray.
Use only outdoors or in a well-ventilated area.
Keep away from heat/sparks/open flames/hot surfaces.-No smoking.
Keep container tightly closed
Ground/Bond container and receiving equipment
Use explosion-proof electrical, ventilating, lighting, equipment
Use only non-sparking tools
Take precautionary measures against static discharge

Precautionary Statements - Response

If exposed or concerned: Get medical advice, attention.
Specific treatment (see first aid on this label).
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice, attention
If skin irritation occurs: Get medical advice, attention.
IF ON SKIN (or hair:) Take off immediately all contaminated clothing. Rinse skin with water, shower
Wash contaminated clothing before reuse
IF INHALED : Remove person to fresh air and keep comfortable for breathing.
Call a POISON CENTER or doctor/physician if you feel unwell.

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
Do NOT induce vomiting.
In case of fire: Use CO₂, dry chemical, or foam to extinguish.

Precautionary Statements - Storage

Store locked up.
Store in a well-ventilated place. Keep container tightly closed.
Keep cool.

Precautionary Statements - Disposal

Dispose of contents, container to an approved waste disposal plant.

Hazards not otherwise classified (HNOC)

None

Other information

0.00003% of the mixture consists of ingredient(s) of unknown toxicity.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %*
KEROSENE	8008-20-6	50-60
2-ETHYLHEXYL NITRATE	27247-96-7	10-20
AROMATIC HYDROCARBON	64742-95-6	1-10
2-BUTOXYETHANOL	111-76-2	1-10
1,2,4-TRIMETHYL BENZENE	95-63-6	1-10
SOLVENT NAPHTHA	64742-94-5	1-10
NAPHTHALENE	91-20-3	1-10

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES**First aid measures for different exposure routes**

General advice	Avoid contact with eyes, skin, and clothing. Avoid breathing vapors, mist, or gas.
Eye contact	Immediately flush with plenty of water for at least 15 minutes. After initial flushing, remove any contact lenses and continue flushing. If eye irritation persists, consult a doctor.
Skin contact	Remove and wash contaminated clothing before re-use. If on skin (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower. If skin irritation persists, call a physician.
Inhalation	Move to fresh air. If not breathing, give artificial respiration. If breathing has stopped, contact emergency medical services immediately.
Ingestion	Call a physician or Poison Control Center immediately. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Risk of product entering the lungs on vomiting after ingestion.

Most important symptoms/effects, acute and delayed

Main Symptoms	Causes skin and serious eye irritation. May cause cancer. May cause respiratory irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways.
----------------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES**Suitable Extinguishing Media**

Water fog. Dry chemical. Foam. Carbon dioxide (CO₂). Cool containers/tanks with water spray.

Unsuitable Extinguishing Media Do not use a solid water stream as it may scatter and spread fire. Keep away from sources of ignition - No smoking.

Specific hazards arising from the chemical

Flammable. Keep product and empty container away from heat and sources of ignition. In the event of fire and/or explosion do not breathe fumes. In the event of fire, cool tanks with water spray.

Explosion Data

Sensitivity to Mechanical Impact none.

Sensitivity to Static Discharge Yes.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES**Personal precautions, protective equipment and emergency procedures**

Personal precautions Use with adequate ventilation to keep the exposure levels below the OELS. Follow safe handling advice and personal protective equipment recommendations.

Environmental precautions

Environmental precautions Vapors can accumulate in low areas. Report spills as required by local and federal regulations. Do not allow material to contaminate ground water system. Do not flush into surface water or sanitary sewer system. Should not be released into the environment.

Methods and materials for containment and cleaning up

Methods for Containment Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from entering drains.

Methods for cleaning up Soak up with inert absorbent material. Contain liquid and collect with an inert, non-combustible material. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly. After cleaning, flush away traces with water. Prevent product from entering drains. Take precautionary measures against static discharges.

7. HANDLING AND STORAGE**Precautions for safe handling**

Advice on safe handling Avoid breathing vapors or mists. Avoid contact with skin, eyes and clothing. Keep away from open flames, hot surfaces and sources of ignition. Handle in accordance with good industrial hygiene and safety practice. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded.

Conditions for safe storage, including any incompatibilities

Technical measures/Storage conditions Keep container tightly closed in a dry and well-ventilated place. Keep away from open flames, hot surfaces, and sources of ignition. Keep in properly labeled containers. Keep out of the reach of children. Store locked up. Keep cool.

Incompatible products Strong acids, alkalis, oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
KEROSENE 8008-20-6	TWA: 200 mg/m ³ total hydrocarbon vapor application restricted to conditions in which there are negligible aerosol exposures Skin - potential significant contribution to overall exposure by the cutaneous route	-	TWA: 100 mg/m ³
2-BUTOXYETHANOL 111-76-2	TWA: 20 ppm	TWA: 50 ppm TWA: 240 mg/m ³ (vacated) TWA: 25 ppm (vacated) TWA: 120 mg/m ³ (vacated) S* S*	IDLH: 700 ppm TWA: 5 ppm TWA: 24 mg/m ³
1,2,4-TRIMETHYL BENZENE 95-63-6	-	-	TWA: 25 ppm TWA: 125 mg/m ³
NAPHTHALENE 91-20-3	TWA: 10 ppm Skin - potential significant contribution to overall exposure by the cutaneous route	TWA: 10 ppm TWA: 50 mg/m ³ (vacated) TWA: 10 ppm (vacated) TWA: 50 mg/m ³ (vacated) STEL: 15 ppm (vacated) STEL: 75 mg/m ³	IDLH: 250 ppm TWA: 10 ppm TWA: 50 mg/m ³ STEL: 15 ppm STEL: 75 mg/m ³

ACGIH: (American Conference of Governmental Industrial Hygienists)

OSHA: (Occupational Safety & Health Administration)

NIOSH IDLH: Immediately Dangerous to Life or Health

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Exposure controls

Engineering Measures Showers
Eyewash stations
Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/Face Protection Tightly fitting safety goggles.

Skin and body protection Chemical resistant apron. Protective gloves.

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

Hygiene measures Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and chemical properties

Physical state	Liquid		
Appearance	Hazy	Odor	Solvent
Color	Amber	Odor Threshold	

<u>Property</u>	<u>Values</u>	<u>Remarks • Methods</u>
pH	No information available	
Melting/freezing point	No information available	
Boiling point/boiling range		
Flash Point	42 °C / 108 °F	Based on lowest flashpoint of the products constituents.
Evaporation rate	No information available	
Flammability (solid, gas)	No information available	
Flammability Limits in Air		
upper flammability limit		
lower flammability limit		
Vapor pressure		
Vapor density		
Specific Gravity	0.84	
Water solubility	No information available	
Partition coefficient: n-octanol/water		
Autoignition temperature	No information available	
Decomposition temperature		
Viscosity	No information available	
Explosive properties		

Other information

VOC Content(%)	86.59
----------------	-------

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to Avoid

Heat, flames and sparks.

Incompatible Materials

Strong acids, alkalis, oxidizing agents.

Hazardous Decomposition Products

Carbon oxides , Hydrocarbons, Fumes.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure**Product Information**

Inhalation	May cause respiratory irritation, May cause drowsiness or dizziness.
Eye contact	Causes serious eye irritation.
Skin contact	Causes skin irritation .
Ingestion	May be fatal if swallowed and enters airways.

Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
KEROSENE 8008-20-6	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.28 mg/L (Rat) 4 h
2-ETHYLHEXYL NITRATE 27247-96-7	> 9600 mg/kg (Rat)	> 4800 mg/kg (Rabbit)	> 14 mg/L (Rat) 4 h
AROMATIC HYDROCARBON 64742-95-6	= 8400 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	= 3400 ppm (Rat) 4 h
2-BUTOXYETHANOL 111-76-2	= 470 mg/kg (Rat)	= 99 mg/kg (Rabbit)	= 450 ppm (Rat) 4 h = 486 ppm (Rat) 4 h
1,2,4-TRIMETHYL BENZENE 95-63-6	= 3280 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	= 18 g/m ³ (Rat) 4 h
SOLVENT NAPHTHA 64742-94-5	> 5000 mg/kg (Rat)	> 2 mL/kg (Rabbit)	> 590 mg/m ³ (Rat) 4 h
NAPHTHALENE 91-20-3	= 1110 mg/kg (Rat)	= 1120 mg/kg (Rabbit)	> 340 mg/m ³ (Rat) 1 h

Information on toxicological effects**Symptoms**

Causes skin and serious eye irritation. May Cause Cancer. May cause drowsiness or dizziness. May cause respiratory irritation. May be fatal if swallowed and enters airways.

Delayed and immediate effects as well as chronic effects from short and long-term exposure**Skin corrosion/irritation**

Irritating to skin.

Eye damage/irritation

Irritating to eyes.

Sensitization

Not a known sensitizer.

Germ cell mutagenicity

Not a germ cell mutagen.

Carcinogenicity

The table below indicates whether each agency has evaluated a listed ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
KEROSENE 8008-20-6	A3	Group 3	-	-
2-ETHYLHEXYL NITRATE 27247-96-7	-	Group 2A	-	X
2-BUTOXYETHANOL 111-76-2	A3	Group 3	-	-
NAPHTHALENE 91-20-3	A3	Group 2B	Reasonably Anticipated	X

ACGIH: (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC: (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

Group 2A - Probably Carcinogenic to Humans

NTP: (National Toxicity Program)

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

OSHA: (Occupational Safety & Health Administration)

X - Present

Reproductive toxicity

This product does not contain any known or suspected reproductive hazards.

Specific target organ systemic toxicity (single exposure)

May cause respiratory irritation. May cause drowsiness or dizziness.

Specific target organ systemic toxicity (repeated exposure)

No known effect based on information supplied.

Chronic toxicity

Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Chronic hydrocarbon abuse has been associated with irregular heart rhythms and potential cardiac arrest.

Target Organ Effects

Skin, Eyes, Respiratory System, and Central Nervous System.

Neurological effects

Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.

Aspiration hazard

May be fatal if swallowed and enters airways.

Numerical measures of toxicity - Product Information**Unknown Acute Toxicity**

0.00003% of the mixture consists of ingredient(s) of unknown toxicity.

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral)	2383 mg/kg
ATEmix (dermal)	5614 mg/kg
ATEmix (inhalation-dust/mist)	5.8 mg/l
ATEmix (inhalation-vapor)	48 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to microorganisms	Toxicity to daphnia and other aquatic invertebrates
AROMATIC HYDROCARBON 64742-95-6	-	9.22 mg/L LC50 Oncorhynchus mykiss 96h	-	6.14 mg/L EC50 Daphnia magna 48h
2-BUTOXYETHANOL 111-76-2	-	1490 mg/L LC50 Lepomis macrochirus 96h static 2950 mg/L LC50 Lepomis macrochirus 96h	-	1000 mg/L EC50 Daphnia magna 48h
1,2,4-TRIMETHYL BENZENE 95-63-6	-	7.19 - 8.28 mg/L LC50 Pimephales promelas 96h flow-through	-	6.14 mg/L EC50 Daphnia magna 48h
SOLVENT NAPHTHA 64742-94-5	-	19 mg/L LC50 Pimephales promelas 96h static 2.34 mg/L LC50 Oncorhynchus mykiss 96h 1740 mg/L LC50 Lepomis macrochirus 96h static 45 mg/L LC50 Pimephales promelas 96h flow-through 41 mg/L LC50 Pimephales promelas 96h	-	0.95 mg/L EC50 Daphnia magna 48h
NAPHTHALENE 91-20-3	-	5.74 - 6.44 mg/L LC50 Pimephales promelas 96h flow-through 1.6 mg/L LC50 Oncorhynchus mykiss 96h flow-through 0.91 - 2.82 mg/L LC50 Oncorhynchus mykiss 96h static 1.99 mg/L LC50 Pimephales promelas 96h static 31.0265 mg/L LC50 Lepomis macrochirus 96h static	-	2.16 mg/L LC50 Daphnia magna 48h 1.96 mg/L EC50 Daphnia magna 48h Flow through 1.09 - 3.4 mg/L EC50 Daphnia magna 48h Static

Persistence and degradability

.

Bioaccumulation

.

Chemical Name	log Pow
2-ETHYLHEXYL NITRATE 27247-96-7	4.14
2-BUTOXYETHANOL 111-76-2	0.81
1,2,4-TRIMETHYL BENZENE 95-63-6	3.63
SOLVENT NAPHTHA 64742-94-5	6.1
NAPHTHALENE 91-20-3	3.6

Other adverse effects No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment

Waste Disposal Methods	This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261). Dispose of in accordance with federal, state, and local regulations.
Contaminated packaging	Do not re-use empty containers.

14. TRANSPORT INFORMATION

DOT Ground	CONSUMER COMMODITY ORM-D or LIMITED QUANTITY
IATA	UN1993, FLAMMABLE LIQUID, N.O.S. (KEROSENE), 3, PG III
IMDG	UN1993, FLAMMABLE LIQUID, N.O.S. (KEROSENE), 3, PG III

15. REGULATORY INFORMATION

SCHEDULE B CODE: 3811.90.1000.

International Inventories

Chemical Name	TSCA	DSL/NDSL	EINECS/ELINCS	ENCS	IECSC	KECL	PICCS	AICS
KEROSENE	X	X	X	x	X	X	X	X
2-ETHYLHEXYL NITRATE	X	X	X	X	X	X	X	X
AROMATIC HYDROCARBON	X	X	X	Not listed	X	X	X	X
2-BUTOXYETHANOL	X	X	X	X	X	X	X	X
1,2,4-TRIMETHYL BENZENE	X	X	X	X	X	X	X	X
SOLVENT NAPHTHA	X	X	X	Not listed	X	X	X	X
NAPHTHALENE	X	X	X	X	X	X	X	X

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

CHINA - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does contain a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %*	SARA 313 - Threshold Values %
---------------	--------	-----------	-------------------------------

2-BUTOXYETHANOL - 111-76-2	111-76-2	1-10	1.0
1,2,4-TRIMETHYL BENZENE - 95-63-6	95-63-6	1-10	1.0
NAPHTHALENE - 91-20-3	91-20-3	1-10	0.1

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Star Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

Clean Water Act

This product does contain the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
NAPHTHALENE 91-20-3	100 lb	X	X	X

CERCLA

This material, as supplied, does contain substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
NAPHTHALENE 91-20-3	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ

U.S. State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals:



This product can expose you to chemicals including those listed below, which is [are] known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Chemical Name	California Prop. 65
NAPHTHALENE - 91-20-3	Cancer/1-10%

U.S. State Right-to-Know Regulations

This product does not contain any substances regulated by state right-to-know regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
KEROSENE 8008-20-6	X	X	X
2-ETHYLHEXYL NITRATE 27247-96-7	X		
2-BUTOXYETHANOL 111-76-2	X	X	X
1,2,4-TRIMETHYL BENZENE 95-63-6	X	X	X
NAPHTHALENE 91-20-3	X	X	X

EPA Pesticide Registration Number Not applicable

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and

the SDS contains all the information required by the CPR.

16. OTHER INFORMATION

NFPA	Health Hazard 2	Flammability 3	Instability 0	Physical and chemical hazards -
HMIS	Health Hazard 2*	Flammability 3	Physical Hazard 0	Personal protection B

Prepared By American Jetway Corporation
34136 Myrtle Street
Wayne, MI 48184-0126

Issuing date 15-May-2017

Revision Date 20-Nov-2018

Revision Note

(M)SDS sections updated: 2, 6

Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet