



SAFETY DATA SHEET

Classified in accordance 29 CFR 1910.1200

1. Identification

Product identifier: CUTTING AND TAPPING FLUID - SW-461

Other means of identification

SDS number: RE1000043354

Recommended restrictions

Recommended use: Lubricant

Restrictions on use: Not known.

Manufacturer Information

Manufacturer

Company Name: Sprayway, Inc.
Address: 1000 INTEGRAM DR.
Pacific, MO 63069
US
Telephone: 1-630-628-3000

Emergency telephone number: 1-866-836-8855

2. Hazard(s) identification

Hazard Classification

Physical Hazards

Flammable aerosol Category 1

Health Hazards

Serious Eye Damage/Eye Irritation Category 2A
Specific Target Organ Toxicity - Category 3
Single Exposure (Narcotic effect.)

Label Elements

Hazard Symbol:



Signal Word: Danger

Hazard Statement: Extremely flammable aerosol.
Causes serious eye irritation.
May cause drowsiness or dizziness.



Precautionary Statements

- Prevention:** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area.
- Response:** IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Call a POISON CENTER/doctor if you feel unwell.
- Storage:** Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Keep container tightly closed. Store locked up.
- Disposal:** Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Hazard(s) not otherwise classified (HNOC): None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
2-Propanone	67-64-1	20 - <50%
Butane	106-97-8	10 - <20%
Propane	74-98-6	5 - <10%
Distillates (petroleum), hydrotreated light	64742-47-8	1 - <5%
Polyethylene glycol mono(branched p-nonylphenyl) ether	127087-87-0	1 - <5%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition Comments: The components are not hazardous or are below required disclosure limits.
The exact concentration has been withheld as a trade secret.

4. First-aid measures

Description of necessary first-aid measures

- Inhalation:** Move to fresh air.
- Skin Contact:** Wash skin thoroughly with soap and water. If skin irritation occurs: Get medical advice/attention.
- Eye contact:** Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention.
- Ingestion:** Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.



Personal Protection for First-aid Responders: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Most important symptoms/effects, acute and delayed

Symptoms: No data available.

Hazards: No data available.

Indication of immediate medical attention and special treatment needed

Treatment: Get medical attention if symptoms occur.

5. Fire-fighting measures

General Fire Hazards: Use water spray to keep fire-exposed containers cool. Fight fire from a protected location. Move containers from fire area if you can do so without risk.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical: Vapors may travel considerable distance to a source of ignition and flash back.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No data available.

Special protective equipment for fire-fighters: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind.

Accidental release measures: Prevent entry into waterways, sewer, basements or confined areas. Stop the flow of material, if this is without risk. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop leak if you can do so without risk.

Methods and material for containment and cleaning up: Absorb spill with vermiculite or other inert material, then place in a container for chemical waste.

Environmental Precautions: Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so.



7. Handling and storage

Handling

Technical measures (e.g. Local and general ventilation): No data available.

Safe handling advice: Avoid contact with eyes. Wash hands thoroughly after handling. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use.

Contact avoidance measures: No data available.

Storage

Safe storage conditions: Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Aerosol Level 2

Safe packaging materials: No data available.

Storage Temperature: No data available.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values	Source
2-Propanone	STEL	1,000 ppm 2,400 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	PEL	1,000 ppm 2,400 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
	TWA	250 ppm	US. ACGIH Threshold Limit Values, as amended
	TWA	750 ppm 1,800 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	STEL	500 ppm	US. ACGIH Threshold Limit Values, as amended
	REL	250 ppm 590 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Butane	REL	800 ppm 1,900 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	STEL	1,000 ppm	US. ACGIH Threshold Limit Values, as amended
	TWA	800 ppm 1,900 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
Propane	REL	1,000 ppm 1,800 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	PEL	1,000 ppm 1,800 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
	TWA	1,000 ppm 1,800 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
Distillates (petroleum), hydrotreated light	REL	100 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	TWA	200 mg/m3	US. ACGIH Threshold Limit Values, as amended
Oxirane	TWA	200 mg/m3	US. ACGIH Threshold Limit Values, as amended
	Ceil_Time	5 ppm 9 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	TWA	1 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053), as amended
	STEL	5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053), as amended
	OSHA_ACT	0.5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053), as amended



	REL	0.1 ppm	0.18 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	TWA	1 ppm		US. ACGIH Threshold Limit Values, as amended
	TWA	1 ppm		US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	STEL	5 ppm		US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
1,4-Dioxane	TWA	25 ppm	90 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	Ceil_Time	1 ppm	3.6 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	TWA	20 ppm		US. ACGIH Threshold Limit Values, as amended
	PEL	100 ppm	360 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
Acetic acid	STEL	15 ppm	37 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	PEL	10 ppm	25 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
	REL	10 ppm	25 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	TWA	10 ppm		US. ACGIH Threshold Limit Values, as amended
	TWA	10 ppm	25 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	STEL	15 ppm		US. ACGIH Threshold Limit Values, as amended

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
2-Propanone (acetone: Sampling time: End of shift.)	25 mg/l (Urine)	ACGIH BEL
Oxirane (N-(2-hydroxyethyl)-valine (HEV) hemoglobin adducts: Sampling time: Not critical.)	5000 pmol/g (Hemoglobin adducts)	ACGIH BEL
Oxirane (S-(2-hydroxyethyl) mercapturic acid (HEMA): Sampling time: End of shift.)	5 µg/g (Creatinine in urine)	ACGIH BEL

Exposure guidelines

Distillates (petroleum), hydrotreated light	US. ACGIH Threshold Limit Values, as amended	Can be absorbed through the skin.
	US. ACGIH Threshold Limit Values, as amended	Can be absorbed through the skin.
1,4-Dioxane	US. ACGIH Threshold Limit Values, as amended	Can be absorbed through the skin.

Appropriate Engineering Controls

No data available.

Individual protection measures, such as personal protective equipment

Eye/face protection:

Wear safety glasses with side shields (or goggles).

Skin Protection

Hand Protection:

No data available.

Skin and Body Protection:

No data available.

Respiratory Protection:

In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor.

Hygiene measures:

Avoid contact with eyes. Observe good industrial hygiene practices. When using do not smoke.



9. Physical and chemical properties

Appearance

Physical state:	liquid
Form:	Spray Aerosol
Color:	No data available.
Odor:	No data available.
Odor Threshold:	No data available.
pH:	No data available.
Freezing point:	No data available.
Boiling Point:	Estimated 56.05 °C
Flash Point:	-104.44 °C
Evaporation Rate:	No data available.
Flammability (solid, gas):	No data available.
Explosive limit - upper (%):	Estimated 12.4 %(V)
Explosive limit - lower (%):	Estimated 2.5 %(V)
Vapor pressure:	2,757 - 4,136 hPa (20 °C)
Vapor density (air=1):	No data available.
Density:	Estimated 0.784 g/cm ³
Relative density:	No data available.
Solubility in Water:	No data available.
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Self Ignition Temperature:	Estimated 447.88 °C
Decomposition Temperature:	No data available.
Kinematic viscosity:	No data available.
Dynamic viscosity:	No data available.
Explosive properties:	No data available.
Oxidizing properties:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	No data available.
Hazardous Decomposition Products:	No data available.

11. Toxicological information

Information on likely routes of exposure

Inhalation:	No data available.
Skin Contact:	No data available.



Eye contact: No data available.

Ingestion: No data available.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation: No data available.

Skin Contact: No data available.

Eye contact: No data available.

Ingestion: No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product: ATEmix: 120,445.81 mg/kg

Dermal

Product: Not classified for acute toxicity based on available data.

Inhalation

Product: Not classified for acute toxicity based on available data.

Repeated dose toxicity

Product: No data available.

Components:

2-Propanone NOAEL (Rat(Male), Oral, 13 Weeks): 10,000 ppm(m) Oral Experimental result, Key study
Butane LOAEL (Rat(Female, Male), Inhalation, >= 28 d): 12,000 ppm(m) Inhalation Experimental result, Key study
NOAEL (Rat(Female, Male), Inhalation, >= 28 d): 4,000 ppm(m) Inhalation Experimental result, Key study
Propane NOAEL (Rat(Female, Male), Inhalation, >= 28 d): 4,000 ppm(m) Inhalation Experimental result, Key study
LOAEL (Rat(Female, Male), Inhalation, >= 28 d): 12,000 ppm(m) Inhalation Experimental result, Key study
Distillates (petroleum), hydrotreated light NOAEL (Rat(Female, Male), Inhalation): >= 24 mg/m3 Inhalation Experimental result, Key study
NOAEL (Rat(Female), Oral, 70 - 147 d): 750 mg/kg Oral Experimental result, Key study

Skin Corrosion/Irritation

Product: No data available.

Components:

2-Propanone in vivo (Rabbit): Not irritant
Distillates (petroleum), hydrotreated light in vivo (Rabbit): Not irritant
Polyethylene glycol mono(branched p-nonylphenyl) ether Assessment Irritating.

Serious Eye Damage/Eye Irritation

Product: No data available.



Components:

2-Propanone Irritating.
Rabbit, 24 hrs: Minimum grade of severe eye irritant

Distillates (petroleum),
hydrotreated light Rabbit, 24 - 72 hrs: Not irritating

Respiratory or Skin Sensitization

Product: No data available.

Components:

2-Propanone Skin sensitization:, in vivo (Guinea pig): Non sensitising

Distillates (petroleum),
hydrotreated light Skin sensitization:, in vivo (Guinea pig): Non sensitising

Carcinogenicity

Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

No carcinogenic components identified

US. National Toxicology Program (NTP) Report on Carcinogens:

No carcinogenic components identified

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended:

No carcinogenic components identified

Germ Cell Mutagenicity

In vitro

Product: No data available.

In vivo

Product: No data available.

Reproductive toxicity

Product: No data available.

Specific Target Organ Toxicity - Single Exposure

Product: No data available.

Components:

2-Propanone Inhalation - vapor: Narcotic effect. - Category 3 with narcotic effects.

Specific Target Organ Toxicity - Repeated Exposure

Product: No data available.

Target Organs

Specific Target Organ Toxicity - Single Exposure: Narcotic effect.

Aspiration Hazard

Product: No data available.

Components:

Distillates (petroleum),
hydrotreated light May be fatal if swallowed and enters airways.

Other effects: No data available.



12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product: No data available.

Components:

2-Propanone LC 50 (Oncorhynchus mykiss, 96 h): 5,540 mg/l Experimental result, Key study

Butane LC 50 (Various, 96 h): 147.54 mg/l QSAR QSAR, Key study

Propane LC 50 (Various, 96 h): 147.54 mg/l QSAR QSAR, Key study

Polyethylene glycol mono(branched p-nonylphenyl) ether LC 50 (96 h): 84.7 mg/l European Chemicals Agency, <http://echa.europa.eu/> - REACH registration dossiers submitted by companies to ECHA

Aquatic Invertebrates

Product: No data available.

Components:

2-Propanone LC 50 (Daphnia pulex, 48 h): 8,800 mg/l Experimental result, Key study

Butane LC 50 (Daphnia sp., 48 h): 69.43 mg/l QSAR QSAR, Key study

Polyethylene glycol mono(branched p-nonylphenyl) ether EC 50 (48 h): 23.06 mg/l European Chemicals Agency, <http://echa.europa.eu/> - REACH registration dossiers submitted by companies to ECHA

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Components:

Distillates (petroleum), hydrotreated light NOAEL (Oncorhynchus mykiss): 0.098 mg/l QSAR QSAR, Key study

Aquatic Invertebrates

Product: No data available.

Components:

2-Propanone LOAEL (Daphnia magna): 2,212 mg/l Experimental result, Key study
NOAEL (Daphnia magna): 2,212 mg/l Experimental result, Key study

Toxicity to Aquatic Plants

Product: No data available.

Components:

Polyethylene glycol mono(branched p-nonylphenyl) ether EC 50 (72 h): 19.5 mg/l European Chemicals Agency, <http://echa.europa.eu/> - REACH registration dossiers submitted by companies to ECHA
NOEC (96 h): 8 mg/l European Chemicals Agency, <http://echa.europa.eu/> - REACH registration dossiers submitted by companies to ECHA



Persistence and Degradability

Biodegradation

Product:	No data available.
Components:	
2-Propanone	90.9 % (28 d) Detected in water. Experimental result, Key study
Butane	100 % (385.5 h) Detected in water. Experimental result, Key study
Propane	100 % (385.5 h) Detected in water. Experimental result, Key study 50 % (3.19 d) Detected in water. QSAR, Weight of Evidence study
Distillates (petroleum), hydrotreated light	61 % Detected in water. Experimental result, Supporting study
Polyethylene glycol mono(branched p-nonylphenyl) ether	Not readily degradable.

BOD/COD Ratio

Product: No data available.

Bioaccumulative potential

Bioconcentration Factor (BCF)

Product:	No data available.
Components:	
2-Propanone	Haddock, adult, Bioconcentration Factor (BCF): 0.69 Aquatic sediment Experimental result, Not specified

Partition Coefficient n-octanol / water (log Kow)

Product:	No data available.
Components:	
Polyethylene glycol mono(branched p-nonylphenyl) ether	Log Kow: 5.669 25 °C

Mobility in soil: No data available.

Components:	
2-Propanone	No data available.
Butane	No data available.
Propane	No data available.
Distillates (petroleum), hydrotreated light	No data available.
Polyethylene glycol mono(branched p-nonylphenyl) ether	No data available.

Other adverse effects: No data available.

13. Disposal considerations

Disposal instructions: Wash before disposal. Dispose to controlled facilities.

Contaminated Packaging: No data available.



14. Transport information

DOT

UN Number:	UN 1950
UN Proper Shipping Name:	Aerosols, flammable
Transport Hazard Class(es)	
Class:	2.1
Label(s):	–
EmS No.:	–
Packing Group:	–
Special precautions for user:	Not regulated.

IATA

UN Number:	UN 1950
UN Proper Shipping Name:	Aerosols, flammable
Transport Hazard Class(es):	
Class:	2.1
Label(s):	–
Packing Group:	–
Special precautions for user:	Not regulated.
Other information	
Passenger and cargo aircraft:	Allowed. 203
Cargo aircraft only:	Allowed. 203

IMDG

UN Number:	UN 1950
UN Proper Shipping Name:	Aerosols, flammable
Transport Hazard Class(es)	
Class:	2
Label(s):	–
EmS No.:	–
Packing Group:	–
Special precautions for user:	Not regulated.

15. Regulatory information

US Federal Regulations

Restrictions on use: Not known.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

US. Toxic Substances Control Act (TSCA) Section 5(a)(2) Final Significant New Use Rules (SNURs) (40 CFR 721, Subpt E)

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended

<u>Chemical Identity</u>	<u>OSHA hazard(s)</u>
Oxirane	Skin sensitization
	Acute toxicity
	Cancer
	Reproductive toxicity
	Mutagenicity
	Central nervous system
	Eye irritation
	Respiratory tract irritation
	Skin irritation
	Flammability



CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical Identity

ACETONE
UNLISTED HAZARDOUS WASTES CHARACTERISTIC OF IGNITABILITY
RCRA HAZARDOUS WASTE NO. D001
Distillates (petroleum), hydrotreated light
ETHYLENE OXIDE
OXIRANE
1,4-DIETHYLENEOXIDE
ACETIC ACID

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Flammable aerosol, Serious Eye Damage/Eye Irritation, Specific Target Organ Toxicity - Single Exposure

US. EPCRA (SARA Title III) Section 304 Extremely Hazardous Substances Reporting Quantities and the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) Hazardous Substances

US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 313 Toxic Chemicals (40 CFR 372.65) - Supplier Notification Required

None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

US State Regulations

US. California Proposition 65

For more information go to www.P65Warnings.ca.gov.

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity

2-Propanone
Butane
Propane
Distillates (petroleum), hydrotreated light

US. Massachusetts RTK - Substance List

No ingredient regulated by MA Right-to-Know Law present.

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity

2-Propanone
Butane
Propane
Distillates (petroleum), hydrotreated light

US. Rhode Island RTK

No ingredient regulated by RI Right-to-Know Law present.

International regulations

Montreal protocol

2-Propanone
Distillates (petroleum), hydrotreated light



Stockholm convention

2-Propanone
Distillates (petroleum), hydrotreated light

Rotterdam convention

2-Propanone
Distillates (petroleum), hydrotreated light

Kyoto protocol

Inventory Status:

Australia AICS	On or in compliance with the inventory
Canada DSL Inventory List	On or in compliance with the inventory
Canada NDSL Inventory	Not in compliance with the inventory.
Ontario Inventory	Not in compliance with the inventory.
China Inv. Existing Chemical Substances	On or in compliance with the inventory
Japan (ENCS) List	Not in compliance with the inventory.
Japan ISHL Listing	Not in compliance with the inventory.
Japan Pharmacopoeia Listing	Not in compliance with the inventory.
Korea Existing Chemicals Inv. (KECI)	On or in compliance with the inventory
Mexico INSQ	Not in compliance with the inventory.
New Zealand Inventory of Chemicals	On or in compliance with the inventory
Philippines PICCS	On or in compliance with the inventory
Taiwan Chemical Substance Inventory	On or in compliance with the inventory
US TSCA Inventory	On or in compliance with the inventory
EINECS, ELINCS or NLP	Not in compliance with the inventory.

16. Other information, including date of preparation or last revision

Issue Date: 12/22/2020

Revision Information: No data available.

Version #: 1.0

Further Information: No data available.

Disclaimer: This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.