Revision Date: 01/15/2021

SAFETY DATA SHEET

Classified in accordance 29 CFR 1910.1200

1. Identification

Product identifier: BATTERY PROTECTOR - 6528

Other means of identification

SDS number: RE1000044989

Recommended restrictions
Recommended use: Coating
Restrictions on use: Not known.

Manufacturer Information

Manufacturer

Company Name: IMPERIAL SUPPLIES LLC

Address: PO BOX 11008

GREEN BAY,WI 54307-1008

US

Telephone: 800-558-2808

Emergency telephone number: 1-866-836-8855

2. Hazard(s) identification

Hazard Classification

Physical Hazards

Flammable aerosol Category 1

Health Hazards

Skin Corrosion/Irritation Category 2
Serious Eye Damage/Eye Irritation Category 2A
Toxic to reproduction Category 2
Specific Target Organ Toxicity - Category 3
Single Exposure (Narcotic effect.)
Specific Target Organ Toxicity - Category 2

Repeated Exposure

Aspiration Hazard Category 1

Environmental Hazards

Acute hazards to the aquatic Category 3

Danger

environment

Label Elements

Hazard Symbol:



Signal Word:

Revision Date: 01/15/2021

Hazard Statement: Extremely flammable aerosol.

Causes skin irritation.

Causes serious eye irritation.

Suspected of damaging fertility or the unborn child.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

Harmful to aquatic life.

Precautionary Statements

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Use only outdoors or in a well-ventilated area. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid release to the

environment.

Response: IF INHALED: Remove person to fresh air and keep comfortable for

breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN: Wash with plenty of water If skin irritation occurs: Get medical advice/attention. IF SWALLOWED: Immediately call a POISON CENTER/doctor Do NOT induce vomiting. Call a POISON CENTER/doctor if you feel unwell. Specific

treatment (see on this label). Take off contaminated clothing.

Storage: Protect from sunlight. Do not expose to temperatures exceeding

50°C/122°F. Store locked up. Store in a well-ventilated place. Keep

container tightly closed.

Disposal: Dispose of contents/container to an appropriate treatment and disposal

facility in accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Hazard(s) not otherwise classified (HNOC):

None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Petrolatum	8009-03-8	20 - <50%
Toluene	108-88-3	10 - <25%
Propane	74-98-6	10 - <20%
Butane	106-97-8	10 - <20%
2-Propanone	67-64-1	10 - <20%
Distillates (petroleum), hydrotreated light	64742-47-8	5 - <10%

^{*} All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

The exact concentration has been withheld as a trade secret.

4. First-aid measures

Description of necessary first-aid measures

Inhalation: Move to fresh air.

Revision Date: 01/15/2021

Skin Contact: Immediately flush with plenty of water for at least 15 minutes while

removing contaminated clothing and shoes. Wash contaminated

clothing before reuse. Get medical attention.

Eye contact: Immediately flush with plenty of water for at least 15 minutes. If easy

to do, remove contact lenses. Get medical attention.

Ingestion: Call a physician or poison control center immediately. Rinse mouth.

Never give liquid to an unconscious person. If vomiting occurs, keep

head low so that stomach content doesn't get into the lungs.

Personal Protection for First-

aid Responders:

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in

enclosed spaces, SCBA.

Most important symptoms/effects, acute and delayed

Symptoms: No data available.

Hazards: No data available.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: Use water spray to keep fire-exposed containers cool. Fight fire from a

protected location. Move containers from fire area if you can do so without

risk.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing

media:

Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing

media:

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical:

Vapors may travel considerable distance to a source of ignition and flash

back.

Special protective equipment and precautions for firefighters

Special fire fighting

procedures:

No data available.

Special protective equipment

for fire-fighters:

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in

enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind. See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away.

Revision Date: 01/15/2021

Accidental release measures: Prevent entry into waterways, sewer, basements or confined areas. Stop

the flow of material, if this is without risk. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop leak if you

can do so without risk.

Methods and material for containment and cleaning

up:

Absorb spill with vermiculite or other inert material, then place in a container

for chemical waste.

Environmental Precautions: Do not contaminate water sources or sewer. Prevent further leakage or

spillage if safe to do so. Avoid release to the environment.

7. Handling and storage

Handling

Technical measures (e.g. Local and general ventilation):

No data available.

Safe handling advice: Avoid contact with eyes. Wash hands thoroughly after handling. Keep away

from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Avoid contact with skin.

Contact avoidance measures: No data available.

Storage

Safe storage conditions: Store locked up. Pressurized container: protect from sunlight and do not

expose to temperatures exceeding 50°C. Do not pierce or burn, even after

use. Aerosol Level 2

Safe packaging materials: No data available.

Storage Temperature: No data available.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Туре	Exposure	Limit Values	Source
Petrolatum - Mist.	STEL		10 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	PEL		5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
	TWA		5 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
Petrolatum - Inhalable fraction.	TWA		5 mg/m3	US. ACGIH Threshold Limit Values, as amended
Petrolatum - Mist.	REL		5 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Toluene	STEL	150 ppm	560 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	REL	100 ppm	375 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	TWA	100 ppm	375 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	Ceiling	300 ppm		US. OSHA Table Z-2 (29 CFR 1910.1000), as amended
	TWA	20 ppm		US. ACGIH Threshold Limit Values, as amended
	TWA	200 ppm		US. OSHA Table Z-2 (29 CFR 1910.1000), as amended
	MAX. CONC	500 ppm	-	US. OSHA Table Z-2 (29 CFR 1910.1000), as amended

Revision Date: 01/15/2021

	STEL	150 ppm	560 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Propane	REL	1,000 ppm	1,800 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	PEL	1,000 ppm	1,800 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
	TWA	1,000 ppm	1,800 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
Butane	REL	800 ppm	1,900 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	STEL	1,000 ppm		US. ACGIH Threshold Limit Values, as amended
	TWA	800 ppm	1,900 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
2-Propanone	STEL	1,000 ppm	2,400 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	PEL	1,000 ppm	2,400 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
	TWA	250 ppm		US. ACGIH Threshold Limit Values, as amended
	TWA	750 ppm	1,800 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	STEL	500 ppm		US. ACGIH Threshold Limit Values, as amended
	REL	250 ppm	590 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Distillates (petroleum), hydrotreated light	REL		100 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Distillates (petroleum), hydrotreated light - Non- aerosol as total hydrocarbon vapor	TWA		200 mg/m3	US. ACGIH Threshold Limit Values, as amended
	TWA		200 mg/m3	US. ACGIH Threshold Limit Values, as amended
Distillates (petroleum), hydrotreated heavy naphthenic	TWA	400 ppm	1,600 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	PEL	500 ppm	2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
Distillates (petroleum), hydrotreated heavy naphthenic - Mist.	REL		5 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
-,	STEL		10 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	PEL		5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
	TWA		5 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
Distillates (petroleum), hydrotreated heavy naphthenic	Ceil_Time		1,800 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Distillates (petroleum), hydrotreated heavy naphthenic - Inhalable fraction.	TWA		5 mg/m3	US. ACGIH Threshold Limit Values, as amended
Distillates (petroleum), hydrotreated heavy naphthenic	REL		350 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended

Biological Limit Values

gu.:				
Chemical Identity	Exposure Limit Values	Source		
Toluene (toluene: Sampling time: End of shift.)	0.03 mg/l (Urine)	ACGIH BEL		
Toluene (o-Cresol, with hydrolysis: Sampling time: End of shift.)	0.3 mg/g (Creatinine in urine)	ACGIH BEL		
Toluene (toluene: Sampling time: Prior to last shift of work week.)	0.02 mg/l (Blood)	ACGIH BEL		
2-Propanone (acetone: Sampling time: End of shift.)	25 mg/l (Urine)	ACGIH BFI		

Exposure guidelines

Distillates (petroleum),	US. ACGIH Threshold Limit Values, as	Can be absorbed through
hydrotreated light	amended	the skin.
	US. ACGIH Threshold Limit Values, as	Can be absorbed through
	amended	the skin.

Appropriate Engineering Controls

No data available.

Individual protection measures, such as personal protective equipment

Revision Date: 01/15/2021

Eye/face protection: Wear safety glasses with side shields (or goggles).

Skin Protection

Hand Protection: No data available.

Skin and Body Protection: Wear suitable protective clothing. Wear chemical-resistant gloves,

footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific

information.

Respiratory Protection: In case of inadequate ventilation use suitable respirator. Seek advice from

local supervisor.

Hygiene measures: Observe good industrial hygiene practices. Avoid contact with eyes. When

using do not smoke. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Wash contaminated clothing before reuse. Avoid contact with skin. Wash hands

before breaks and immediately after handling the product.

9. Physical and chemical properties

Appearance

Physical state: liquid

Form: Spray Aerosol Color: No data available. Odor: No data available. **Odor Threshold:** No data available. pH: No data available. Freezing point: No data available. **Boiling Point:** Estimated 56.05 °C Flash Point: Estimated -104.4 °C **Evaporation Rate:** No data available. Flammability (solid, gas): No data available. Explosive limit - upper (%): Estimated 10.3 %(V) Explosive limit - lower (%): Estimated 2.1 %(V)

Vapor pressure: 2,757 - 4,136 hPa (20 °C) Vapor density (air=1): No data available. Density: No data available. Relative density: No data available. Solubility in Water: No data available. Solubility (other): No data available. Partition coefficient (n-octanol/water): No data available. **Self Ignition Temperature:** No data available. **Decomposition Temperature:** No data available.

Kinematic viscosity:No data available.Dynamic viscosity:No data available.Explosive properties:No data available.Oxidizing properties:No data available.

10. Stability and reactivity

Reactivity: No data available.

Chemical Stability: Material is stable under normal conditions.

Revision Date: 01/15/2021

Possibility of hazardous

reactions:

No data available.

Conditions to avoid: Avoid heat or contamination.

Incompatible Materials: No data available.

Hazardous Decomposition

Products:

No data available.

11. Toxicological information

Information on likely routes of exposure

Inhalation: No data available.

Skin Contact: No data available.

Eye contact: No data available.

Ingestion: No data available.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation: No data available.

Skin Contact: No data available.

Eye contact: No data available.

Ingestion: No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product: Not classified for acute toxicity based on available data.

Dermal

Product: Not classified for acute toxicity based on available data.

Inhalation

Product: Not classified for acute toxicity based on available data.

Repeated dose toxicity

Product: No data available.

Components:

Petrolatum NOAEL (Rat(Female, Male), Dermal, 13 Weeks): > 2,000 mg/kg Dermal

Read-across from supporting substance (structural analogue or surrogate),

Key study

Toluene LOAEL (Rat(Female, Male), Oral, 13 Weeks): 1,250 mg/kg (Target

Organ(s): Liver, Kidney) Oral Experimental result, Key study NOAEL (Rat(Female, Male), Inhalation): 625 ppm(m) Inhalation

Experimental result, Key study

NOAEL (Rat(Female, Male), Inhalation - vapor): 2,355 mg/l Inhalation

Experimental result, Key study

Propane NOAEL (Rat(Female, Male), Inhalation, >= 28 d): 4,000 ppm(m) Inhalation

Experimental result, Key study

LOAEL (Rat(Female, Male), Inhalation, >= 28 d): 12,000 ppm(m) Inhalation

Experimental result, Key study

Revision Date: 01/15/2021

LOAEL (Rat(Female, Male), Inhalation, >= 28 d): 12,000 ppm(m) Inhalation **Butane**

Experimental result, Key study

NOAEL (Rat(Female, Male), Inhalation, >= 28 d): 4,000 ppm(m) Inhalation

Experimental result, Key study

NOAEL (Rat(Male), Oral, 13 Weeks): 10,000 ppm(m) Oral Experimental 2-Propanone

result. Kev study

Distillates (petroleum). NOAEL (Rat(Female, Male), Inhalation); >= 24 mg/m3 Inhalation

hydrotreated light Experimental result, Key study

NOAEL (Rat(Female), Oral, 70 - 147 d): 750 mg/kg Oral Experimental result,

Key study

Skin Corrosion/Irritation

Product: No data available.

Components:

Petrolatum in vivo (Rabbit): Not irritant Toluene in vivo (Rabbit): Irritating in vivo (Rabbit): Not irritant 2-Propanone Distillates (petroleum), in vivo (Rabbit): Not irritant

hydrotreated light

Serious Eye Damage/Eye Irritation

Product: No data available.

Components:

Petrolatum Rabbit, 24 - 72 hrs: Not irritating

Toluene Rabbit, 24 - 72 hrs: Not irritating

2-Propanone Irritating.

Rabbit, 24 hrs: Minimum grade of severe eye irritant

Distillates (petroleum),

hydrotreated light

Rabbit, 24 - 72 hrs: Not irritating

Respiratory or Skin Sensitization

Product: No data available.

Components:

Petrolatum Skin sensitization:, in vivo (Guinea pig): Non sensitising Toluene Skin sensitization:, in vivo (Guinea pig): Non sensitising 2-Propanone Skin sensitization:, in vivo (Guinea pig): Non sensitising Distillates (petroleum), Skin sensitization:, in vivo (Guinea pig): Non sensitising

hydrotreated light

Carcinogenicity

Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

No carcinogenic components identified

US. National Toxicology Program (NTP) Report on Carcinogens:

No carcinogenic components identified

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended:

No carcinogenic components identified

Germ Cell Mutagenicity

In vitro

Product: No data available.

Revision Date: 01/15/2021

In vivo

Product: No data available.

Reproductive toxicity

Product: No data available.

Components:

Toluene Suspected of damaging fertility or the unborn child.

Specific Target Organ Toxicity - Single Exposure
Product:
No data available.

Components:

Toluene Inhalation - vapor: Narcotic effect. - Category 3 with narcotic effects. 2-Propanone Inhalation - vapor: Narcotic effect. - Category 3 with narcotic effects.

Specific Target Organ Toxicity - Repeated Exposure
Product:
No data available.

Components:

Toluene Category 2

Target Organs

Specific Target Organ Toxicity - Single Exposure: Narcotic effect.

Aspiration Hazard

Product: No data available.

Components:

Toluene May be fatal if swallowed and enters airways. Distillates (petroleum), May be fatal if swallowed and enters airways.

hydrotreated light

Other effects: No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product: No data available.

Components:

Petrolatum NOAEL (Pimephales promelas, 96 h): >= 100 mg/l Read-across from

supporting substance (structural analogue or surrogate), Key study

Toluene LC 50 (Oncorhynchus kisutch, 96 h): 5.5 mg/l Experimental result, Key study

Propane LC 50 (Various, 96 h): 147.54 mg/l QSAR QSAR, Key study

Butane LC 50 (Various, 96 h): 147.54 mg/l QSAR QSAR, Key study

2-Propanone LC 50 (Oncorhynchus mykiss, 96 h): 5,540 mg/l Experimental result, Key

study

Aquatic Invertebrates

Product: No data available.

Components:

Petrolatum EC 50 (Daphnia magna, 48 h): > 10,000 mg/l Read-across from supporting

substance (structural analogue or surrogate), Key study

Revision Date: 01/15/2021

Toluene LC 50 (Water flea (Daphnia magna), 48 h): 54.6 - 174.7 mg/l Mortality

LC 50 (Ceriodaphnia dubia, 2 d): 3.78 mg/l Experimental result, Key study

Butane LC 50 (Daphnia sp., 48 h): 69.43 mg/l QSAR QSAR, Key study

2-Propanone LC 50 (Daphnia pulex, 48 h): 8,800 mg/l Experimental result, Key study

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Components:

Toluene NOAEL (Oncorhynchus kisutch): 1.39 mg/l Experimental result, Key study

LOAEL (Oncorhynchus kisutch): 2.77 mg/l Experimental result, Key study

Distillates (petroleum), hydrotreated light

NOAEL (Oncorhynchus mykiss): 0.098 mg/l QSAR QSAR, Key study

Aquatic Invertebrates

Product: No data available.

Components:

Toluene LOAEL (Ceriodaphnia dubia): 2.76 mg/l Experimental result, Key study

NOAEL (Ceriodaphnia dubia): 0.74 mg/l Experimental result, Key study

2-Propanone LOAEL (Daphnia magna): 2,212 mg/l Experimental result, Key study

NOAEL (Daphnia magna): 2,212 mg/l Experimental result, Key study

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

Components:

Petrolatum 31 % (28 d) Detected in water. Read-across from supporting substance

(structural analogue or surrogate), Supporting study

Toluene 100 % (14 d) Detected in water. Experimental result, Weight of Evidence

study

86 % Detected in water. Experimental result, Weight of Evidence study

Propane 100 % (385.5 h) Detected in water. Experimental result, Key study

50 % (3.19 d) Detected in water. QSAR, Weight of Evidence study

Butane 100 % (385.5 h) Detected in water. Experimental result, Key study

2-Propanone 90.9 % (28 d) Detected in water. Experimental result, Key study

Distillates (petroleum),

hydrotreated light

61 % Detected in water. Experimental result, Supporting study

BOD/COD Ratio

Product: No data available.

Bioaccumulative potential

Bioconcentration Factor (BCF)

Product: No data available.

Revision Date: 01/15/2021

Components:

Toluene Leuciscus idus, Bioconcentration Factor (BCF): 90 Aquatic sediment

Experimental result, Key study

2-Propanone Haddock, adult, Bioconcentration Factor (BCF): 0.69 Aquatic sediment

Experimental result, Not specified

Partition Coefficient n-octanol / water (log Kow)

Product: No data available.

Mobility in soil: No data available.

Components:

Petrolatum
No data available.
Toluene
Propane
No data available.
No data available.
No data available.
Propanone
No data available.

Other adverse effects: Harmful to aquatic organisms.

13. Disposal considerations

Disposal instructions: Discharge, treatment, or disposal may be subject to national, state, or local

laws.

Contaminated Packaging: No data available.

14. Transport information

DOT

UN Number: UN 1950

UN Proper Shipping Name: Aerosols, flammable

Transport Hazard Class(es)

Class: 2.1
Label(s): –
EmS No.:

. .

Packing Group: -

Special precautions for user: Not regulated.

IATA

UN Number: UN 1950

UN Proper Shipping Name: Aerosols, flammable

Transport Hazard Class(es):

Class: 2.1
Label(s): –

Packing Group: –

Special precautions for user:

Not regulated.

Other information

Passenger and cargo aircraft: Allowed. 203
Cargo aircraft only: Allowed. 203

IMDG

UN Number: UN 1950

UN Proper Shipping Name: Aerosols, flammable

Transport Hazard Class(es)

Class: 2.1 Label(s): – EmS No.:

Packing Group: –

Special precautions for user: Not regulated.

Revision Date: 01/15/2021

15. Regulatory information

US Federal Regulations

Restrictions on use: Not known.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

US. Toxic Substances Control Act (TSCA) Section 5(a)(2) Final Significant New Use Rules (SNURs) (40 CFR 721, Subpt E)

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended None present or none present in regulated quantities.

CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical Identity

BENZENE, METHYL-UNLISTED HAZARDOUS WASTES CHARACTERISTIC OF IGNITABILITY RCRA HAZARDOUS WASTE NO. D001 **ACETONE** Distillates (petroleum), hydrotreated light

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Flammable aerosol, Skin Corrosion/Irritation, Serious Eye Damage/Eye Irritation, Toxic to reproduction, Specific Target Organ Toxicity - Single Exposure, Specific Target Organ Toxicity -Repeated Exposure, Aspiration Hazard

US. EPCRA (SARA Title III) Section 304 Extremely Hazardous Substances Reporting Quantities and the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) Hazardous **Substances**

US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 313 Toxic Chemicals (40 CFR 372.65) - Supplier Notification Required

Chemical Identity % by weight Toluene 1.0%

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

US State Regulations

US. California Proposition 65

For more information go to www.P65Warnings.ca.gov.

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity

Petrolatum

Toluene Propane

Butane

2-Propanone

Distillates (petroleum), hydrotreated light

US. Massachusetts RTK - Substance List

No ingredient regulated by MA Right-to-Know Law present.

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity

Petrolatum

Toluene

Propane

Revision Date: 01/15/2021

Butane 2-Propanone

Distillates (petroleum), hydrotreated light

US. Rhode Island RTK

No ingredient regulated by RI Right-to-Know Law present.

International regulations

Montreal protocol

2-Propanone

Distillates (petroleum), hydrotreated light

Stockholm convention

2-Propanone

Distillates (petroleum), hydrotreated light

Rotterdam convention

2-Propanone

Distillates (petroleum), hydrotreated light

Kyoto protocol

Inventory Status:

Australia AICS On or in compliance with the inventory

Canada DSL Inventory List On or in compliance with the inventory

Canada NDSL Inventory Not in compliance with the inventory.

Ontario Inventory Not in compliance with the inventory.

China Inv. Existing Chemical Substances

On or in compliance with the inventory

Japan (ENCS) List Not in compliance with the inventory.

Japan ISHL Listing Not in compliance with the inventory.

Japan Pharmacopoeia Listing

Not in compliance with the inventory.

Korea Existing Chemicals Inv. (KECI)

On or in compliance with the inventory

Mexico INSQ Not in compliance with the inventory.

New Zealand Inventory of Chemicals

Not in compliance with the inventory.

Philippines PICCS On or in compliance with the inventory

Taiwan Chemical Substance Inventory

On or in compliance with the inventory

US TSCA Inventory

On or in compliance with the inventory

EINECS, ELINCS or NLP Not in compliance with the inventory.

16. Other information, including date of preparation or last revision

Issue Date: 01/15/2021

Revision Information: No data available.

Version #: 1.0

Further Information: No data available.

Disclaimer: This information is provided without warranty. The information is believed to

be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.