

ZEP LUBEZE DRILL CHILL AERO DZ

Version 3.0 Revision Date 02/20/2018 Print Date 05/22/2018

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : ZEP LUBEZE DRILL CHILL AERO DZ

Material number : 000000000000004501

Manufacturer or supplier's details

Company : Zep Inc.

Address : 350 Joe Frank Harris Parkway, SE

Emerson, GA 30137

Telephone : 404-352-1680

Emergency telephone numbers

For SDS Information: Compliance Services 1-877-428-9937For a Medical Emergency: 877-541-2016 Toll Free - All Calls RecordedFor a Transportation: CHEMTREC: 800-424-9300 - All Calls Recorded.

Emergency In the District of Columbia 202-483-7616

Recommended use of the chemical and restrictions on use

Recommended use : Lubricant

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	Aerosol containing a liquefied gas
Colour	brown, opaque
Odour	characteristic

GHS Classification

Flammable aerosols : Category 1
Gases under pressure : Liquefied gas
Skin irritation : Category 2
Eye irritation : Category 2A
Aspiration hazard : Category 1

GHS label elements

Hazard pictograms :







Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.



Version 3.0 Revision Date 02/20/2018 Print Date 05/22/2018

Precautionary statements : **Prevention:**

P210 Keep away from heat, hot surfaces, sparks, open flames

and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source. P251 Pressurized container: Do not pierce or burn, even after

use.

P264 Wash skin thoroughly after handling.

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON

CENTER/doctor.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing. P331 Do NOT induce vomiting.

P332 + P313 If skin irritation occurs: Get medical advice/

attention.

P337 + P313 If eye irritation persists: Get medical advice/

attention.

P362 Take off contaminated clothing and wash before reuse.

Storage:

P410 + P412 Protect from sunlight. Do not expose to

temperatures exceeding 50 °C/ 122 °F.

Disposal:

P501 Dispose of contents/container in accordance with local

regulation.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration [%]
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	>= 30 - < 50
Distillates (petroleum), hydrotreated middle	64742-46-7	>= 30 - < 50
propane	74-98-6	>= 5 - < 10
butane	106-97-8	>= 1 - < 5

The exact percentages of disclosed substances are withheld as trade secrets.

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : If skin irritation persists, call a physician.

Wash off immediately with plenty of water for at least 15



ZEP LUBEZE DRILL CHILL AERO DZ

Version 3.0 Revision Date 02/20/2018 Print Date 05/22/2018

minutes.

If on clothes, remove clothes.

In case of eye contact : Remove contact lenses.

Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

Rinse immediately with plenty of water for at least 15 minutes.

If swallowed : Keep respiratory tract clear.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

DO NOT induce vomiting unless directed to do so by a

physician or poison control center.

Most important symptoms and effects, both acute and

delayed

Effects are immediate and delayed.

Symptoms may include irritation, redness, pain, and rash. Aspiration may cause pulmonary oedema and pneumonitis. Effects are dependent on exposure (dose, concentration,

contact time).

Causes skin irritation.

Causes serious eye irritation.

Review section 2 of SDS to see all potential hazards.

Notes to physician : Treat symptomatically. Symptoms may be delayed.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical Water spray jet

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: Carbon dioxide (CO2)

Carbon monoxide

Smoke

Specific extinguishing

methods

: Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Further information : For safety reasons in case of fire, cans should be stored

separately in closed containments.

Use a water spray to cool fully closed containers.

Special protective equipment

for firefighters

: Wear self-contained breathing apparatus for firefighting if

necessary.



Version 3.0 Revision Date 02/20/2018 Print Date 05/22/2018

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.

Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions

: Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

: Sweep up or vacuum up spillage and collect in suitable

container for disposal.

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Avoid contact with skin and eyes.

For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms.

Always replace cap after use.

Dispose of rinse water in accordance with local and national

regulations.

Do not breathe vapours or spray mist.

Conditions for safe storage

: BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or

red-hot objects. No smoking.

Observe label precautions.

Keep in a dry, cool and well-ventilated place.

Electrical installations / working materials must comply with

the technological safety standards.

Materials to avoid : Strong oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum),	64742-52-5	TWA (Mist)	5 mg/m3	OSHA Z-1



ZEP LUBEZE DRILL CHILL AERO DZ

Version 3.0 Revision Date 02/20/2018 Print Date 05/22/2018

hydrotreated heavy naphthenic				
		TWA (Inhalable fraction)	5 mg/m3	ACGIH
propane	74-98-6	TWA	1,000 ppm	ACGIH
		TWA	1,000 ppm 1,800 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,800 mg/m3	OSHA Z-1
		TWA	1,000 ppm 1,800 mg/m3	OSHA P0
		PEL	1,000 ppm 1,800 mg/m3	CAL PEL
butane	106-97-8	TWA	800 ppm 1,900 mg/m3	NIOSH REL
		TWA	800 ppm 1,900 mg/m3	OSHA P0
		PEL	800 ppm 1,900 mg/m3	CAL PEL

Engineering measures : effective ventilation in all processing areas

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Material : Protective gloves

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Safety glasses

Ensure that eyewash stations and safety showers are close to

the workstation location.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Aerosol containing a liquefied gas

Colour : brown, opaque
Odour : characteristic



ZEP LUBEZE DRILL CHILL AERO DZ

Version 3.0 Revision Date 02/20/2018 Print Date 05/22/2018

Odour Threshold : No data available pH : Not applicable Melting point/freezing point : No data available Boiling point : No data available

Flash point

Not applicable

Evaporation rate : No data available

Flammability (solid, gas) : Extremely flammable aerosol.

Upper explosion limit : No data available
Lower explosion limit : No data available
Vapour pressure : No data available
Density : 0.910 g/cm3

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : not determined

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : not determined

Thermal decomposition : No data available

Viscosity

Viscosity, kinematic : No data available

Heat of combustion : 42.46 kJ/g

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Stable

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

: Vapours may form explosive mixture with air.

No decomposition if stored and applied as directed.

Conditions to avoid : Heat, flames and sparks.

Extremes of temperature and direct sunlight.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition

products

: Carbon oxides

Sulphur oxides



Version 3.0 Revision Date 02/20/2018 Print Date 05/22/2018

SECTION 11. TOXICOLOGICAL INFORMATION

Potential Health Effects

Aggravated Medical

: None known.

Condition

Symptoms of Overexposure

: Effects are immediate and delayed.

Symptoms may include irritation, redness, pain, and rash. Aspiration may cause pulmonary oedema and pneumonitis. Effects are dependent on exposure (dose, concentration,

contact time).

Carcinogenicity:

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

ACGIH No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by ACGIH.

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

Acute toxicity

Components:

Distillates (petroleum), hydrotreated heavy naphthenic:Acute oral toxicity : LD50 Rat: > 5,000 mg/kg

Acute inhalation toxicity : LC50 Rat: > 5 mg/l

Exposure time: 4 h

Acute dermal toxicity : LD50 Rabbit: > 5,000 mg/kg

Skin corrosion/irritation

Product:

Remarks: May cause skin irritation and/or dermatitis.

Serious eye damage/eye irritation

Product:

Remarks: Severe eye irritation

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity



ZEP LUBEZE DRILL CHILL AERO DZ

Version 3.0 Revision Date 02/20/2018 Print Date 05/22/2018

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

Product:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

Product:

Partition coefficient: n-

: Remarks: No data available

octanol/water **Components:**

butane :

Partition coefficient: n-

: Pow: 2.89

octanol/water

Mobility in soilNo data available

Other adverse effects

No data available

Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of



ZEP LUBEZE DRILL CHILL AERO DZ

Version 3.0 Revision Date 02/20/2018 Print Date 05/22/2018

Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks This product neither contains, nor was manufactured

with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A

+ B).

Additional ecological

information

: No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA): ORM-D, CONSUMER COMMODITY

Transportation Regulation: IMDG (Vessel):

UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation: IATA (Cargo Air):

UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: IATA (Passenger Air): UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: TDG (Canada):

UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.



Version 3.0 Revision Date 02/20/2018 Print Date 05/22/2018

SECTION 15. REGULATORY INFORMATION

TSCA list : No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification

requirements.

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)

Gases under pressure Skin corrosion or irritation

Serious eye damage or eye irritation

Aspiration hazard

SARA 302 : No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop. 65

This product does not contain any chemicals known to State of

California to cause cancer, birth defects, or any other

reproductive harm.

The components of this product are reported in the following inventories:

DSL All components of this product are on the Canadian DSL

TSCA On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)


SECTION 16. OTHER INFORMATION



Version 3.0 Revision Date 02/20/2018 Print Date 05/22/2018

Further information

NFPA:



Special hazard.

HMIS III:

HEALTH	3
FLAMMABILITY	4
PHYSICAL HAZARD	3

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High 4 = Extreme, * = Chronic

OSHA - GHS Label Information:

Hazard pictograms









Signal word Hazard statements Danger:

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation.

Precautionary statements

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Wash skin thoroughly

after handling. Wear protective gloves/ eye protection/ face protection.

Response: IF SWALLOWED: Immediately call a POISON CENTER/doctor. IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Do NOT induce vomiting. If skin irritation occurs: Get medical advice/ attention. If eye irritation persists: Get medical advice/ attention. Take off contaminated clothing and wash before reuse.

Storage: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122

Disposal: Dispose of contents/container in accordance with local regulation.

Version:	3.0
Revision Date:	02/20/2018
Print Date:	05/22/2018

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

Zep Inc. markets products under well recognized and established brand names such as Zep®, Zep Commercial®, Zep Professional®, Enforcer®, National Chemical™, Selig™, Misty®, Next Dimension™, Petro®, i-Chem®, TimeMist®, TimeWick™, MicrobeMax®, Country Vet®,



ZEP LUBEZE DRILL CHILL AERO DZ

Version 3.0 Revision Date 02/20/2018 Print Date 05/22/2018

Konk®, Original Bike Spirits®, Blue Coral®, Black Magic®, Rain-X®, Niagara National™, FC Forward Chemicals®,Rexodan®, Mykal™, and a number of private labeled brands.