1 - PRODUCT IDENTIFICATION

PRODUCT NAME: Extreme Shine

PRODUCT TYPE: Solvent Based Tire Dressing

PRODUCT NUMBER: E1020XXX (Last 3 characters vary with the packaging)

CONTROL NUMBER:..... E1020XXX

COMPANY: Simoniz USA, Inc.

201 Boston Turnpike Bolton, CT 06043 1-800-227-5536

www.simoniz.com

EMERGENCY PHONE:.....(800) 255-3924 (CHEM-TEL)

2 - HAZARDS IDENTIFICATION

CLASSIFICATION OF SUBSTANCE/MIXTURE: Flammable (3) Eye Irritation (2B)
Aspiration Toxicity (1)

SYMBOLS:.....



SIGNAL WORD:..... DANGER!

HAZARD STATEMENT:..... Flammable liquid and vapor. May be fatal if swallowed and

enters airways Causes eye irritation.

PRECAUTIONARY STATEMENTS:

PREVENTION: Keep away from heat/sparks/open flames/hot surfaces – No

smoking. Keep container tightly closed. Ground/bond container

and receiving equipment. Use explosion-proof

electrical/ventilating/light/.../equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wash hands thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection.

RESPONSE:..... IF ON SKIN (or hair): Remove/Take off immediately all

contaminated clothing. Rinse skin with water/shower. IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing. If eye irritation persists get medical advice/attention. In case of fire: Use dry

sand, dry chemical or alcohol-resitant foam for extinction. **STORAGE:** Store in a well-ventilated place. Keep cool. Store locked up.

DISPOSAL: Dispose of container and contents in accordance with local

regulations.

3 - COMPOSITION / INFORMATION ON INGREDIENTS

INGREDIENT

C.A.S. NUMBER

Hydrotreated Light Distillates Polydimethylsiloxane 64742-47-8 63148-62-9

Percentages of ingredients are being withheld as trade secret information. This information will be disclosed as necessary to authorized individuals

4 - FIRST-AID MEASURES

BREATHING (INHALATION): ... If victim shows signs of discomfort or irritation, remove to fresh air. If symptoms persist, get immediate medical attention.

SWALLOWING (INGESTION): . DO NOT INDUCE VOMITING! Drink a large quantity of water or

milk. Do not attempt to give liquids to an unconscious person.

Get immediate medical attention!

EYES: Inhalation, skin absorption, or ingestion.

SKIN (DERMAL): Flush from skin and clothing with large amounts of fresh water. If

irritation persists, consult physician. Wash contaminated clothing

before wearing.

5 - FIRE-FIGHTING MEASURES

FLASHPOINT:...... 135 degrees F.

EXTINGUISHING MEDIA:....... Water fog or fine spray. Carbon dioxide, Dry chemical or Alcohol

resistant foam.

SPECIAL FIRE FIGHTING PROCEDURES:Firefighters working in areas where this

product is present should be equipped with an approved, fully

enclosed SCBA.

UNUSUAL FIRE AND EXPLOSION HAZARDS:......None known.

6 - ACCIDENTAL RELEASE MEASURES

SPILL PROCEDURES: Dike to prevent spillage into streams or sewer systems. Consult

local, state and federal authorities.

WASTE DISPOSAL: As recommended by local, state and federal authorities.

7 - HANDLING and STORAGE

STORAGE: Store in a cool, well ventilated area. Avoid overheating or

freezing.

protection should not be necessary. Wear eye protection if

product is likely to splash.Do not place this product in an unmarked container! Keep away from children! Spilled material is slippery.

8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

RESPIRATORY PROTECTION: Not usually needed in well-ventilated areas. If needed, use a

NIOSH approved respirator.

PROTECTIVE CLOTHING:...... Nitrile or PVC gloves, and chemical splash goggles.

ADDITIONAL MEASURES: Under normal use according to label instructions, special

protection should not be necessary. Wear eye protection if product is likely to splash.Do not place this product in an

unmarked container! Keep away from children! Spilled material is

slippery.

INGREDIENT C.A.S. NUMBER PEL

Hydrotreated Light Distillates 64742-47-8 500 ppm PEL Polydimethylsiloxane 63148-62-9 No limits established

9 - PHYSICAL / CHEMICAL PROPERITES

APPEARANCE & ODOR: Blue transparent liquid, citrus scented.

ODOR THRESHOLD: N/A **pH:** N/A

MELTING POINT: 210 degrees F.

FREEZING POINT: N/A

BOILING POINT:..... 210 degrees F.

BOILING POINT RANGE:..... N/A

FLASHPOINT:...... 135 degrees F.

EVAPORATION RATE:......N/A
FLAMMABILITY (solid/gas):.... N/A
EXPLOSION LIMITS:.....N/A

VAPOR PRESSURE:0005 PSIA@ 68 F

VAPOR DENSITY (AIR=1):...... Greater than 1.

SPECIFIC GRAVITY: 0.81 SOLUBILITY IN WATER: Insoluble.

PARTITION COEFFICIENT: N/A

AUTO-IGNITION TEMPERATURE:N/A
DECOMPOSITION TEMPERATURE:N/A

VISCOSITY: Water thin

10 - STABILITY and REACTIVITY

11 - TOXICOLOGICAL INFORMATION

ROUTE(S) OF ENTRY:..... Inhalation, skin absorption, or ingestion.

LISTED CARCINOGEN: None over 0.1%.

MEDICAL CONDITION AGGRAVATED:......May aggravate pre-existing dermatitis.

INHALATION:..... Not likely to be inhaled in hazardous amounts. Avoid exposure to

mists or vapors. Maintain adequate ventilation in the work area.

INGESTION:......Swallowing even small amounts may be harmful. Effects may be

nausea, headache, vomiting and central nervous system depression.

EYES: May cause severe eye irritation.

SKIN (DERMAL): This product may cause irritation if not removed from the skin.

Prolonged exposure may cause central nervous system depression.

ACUTE TOXICITY* (ORAL):....>2000 mg/kg

ACUTE TOXICITY* (DERMAL):...>2000 mg/kg

ACUTE TOXCITY* (INHALATION):.....>20,000 ppm V (Gas), >20 mg/l (Vapor), >5

mg/I (Dust)

*Determined using the additivity formula for mixtures (GHS Purple Book, 3.1.3.6)

12 - ECOLOGICAL INFORMATION

ENVIRONMENTAL FATE AND DISTRIBUTION: N/A

13 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL: As recommended by local, state and federal authorities.

14 - TRANSPORTATION INFORMATION

DOT: Non-hazardous in non-bulk

IMDG:

PROPER SHIPPING NAME:..... Pretroleum Distillates, n.o.s

HAZARD CLASS:......3

UN/NA NUMBER: UN1268

PACKAGING GROUP :..... III

SEA (IMDG) TRANSPORT DOCUMENT DECLARATION: UN 1268, PETROLEUM

DISTILLATES, N.O.S., 3, PG III, FP 58 C c.c.

15 - REGULATIONS

Contents of this MSDS comply with the OSHA Hazard Communication Standard 29CFR 1910.1200

16 – OTHER INFORMATION

NFPA HEALTH: 1
NFPA FLAMMABILITY: 2
NFPA REACTIVITY: 0
NFPA OTHER: None

ADDITIONAL: The information contained in this SDS is based on the data

available to us from sources we believe to be reliable. No warranty or guaranty expressed or implied is made regarding the accuracy of this data or the results obtained from the reliance on this data. The manufacturer assumes no responsibility for injury from the use of this product. Be safe- read this product safety information and pass it on to all persons who may be exposed to this product. Federal law requires it. This product and/or all of its components are either included on or exempt from the TSCA

Inventory of Chemical Substances.

REVISION DATE:......5/22/2015