

COLOR-CODED PRIMARY WIRE GUIDE

PLASTIC PRIMARY WIRE

- Thermoplastic insulated primary wire is suitable for wiring lights, signals and instrument circuits.
- Resistant to abrasion, temperature variation, oils, greases, gasoline, solvents and acids.
- Complies with SAE specifications J1128 and J738.
- Maximum: 50 V
- Assortments Available



| Wire Gauge | Color | Part No. | Qty. Feet |
|------------|-------|----------|-----------|
| 8 | Black | 71349-6 | 50 |
| | Red | 71349-5 | 50 |

| Wire Gauge | Color | Part No. | Qty. Feet |
|------------|--------|----------|-----------|
| 10 | Black | 71350-6 | 100 |
| | Blue | 71350-4 | 100 |
| | Brown | 71350-2 | 100 |
| | Green | 71350-3 | 100 |
| | Red | 71350-5 | 100 |
| | White | 71350-7 | 100 |
| | Yellow | 71350-1 | 100 |

| Wire Gauge | Color | Part No. | Qty. Feet |
|------------|--------|----------|-----------|
| 12 | Black | 71351-6 | 100 |
| | Blue | 71351-4 | 100 |
| | Brown | 71351-2 | 100 |
| | Green | 71351-3 | 100 |
| | Red | 71351-5 | 100 |
| | White | 71351-7 | 100 |
| | Yellow | 71351-1 | 100 |

| Wire Gauge | Color | Part No. | Qty. Feet |
|------------|---------|----------|-----------|
| 14 | Black | 71352-6 | 100 |
| | Blue | 71352-4 | 100 |
| | Blue | 71362-4 | 1,000 |
| | Brown | 71352-2 | 100 |
| | Brown | 71362-2 | 1,000 |
| | Green | 71352-3 | 100 |
| | Green | 71362-3 | 1,000 |
| | Orange | 71352-8 | 100 |
| | Red | 71352-5 | 100 |
| | Red | 71362-5 | 1,000 |
| | Violet | 71352-9 | 100 |
| | White | 71352-7 | 100 |
| White | 71362-7 | 1,000 | |
| Yellow | 71352-1 | 100 | |
| Yellow | 71362-1 | 1,000 | |

| Wire Gauge | Color | Part No. | Qty. Feet |
|------------|--------|----------|-----------|
| 16 | Black | 71353-6 | 100 |
| | Black | 71262-6 | 500 |
| | Blue | 71353-4 | 100 |
| | Brown | 71353-2 | 100 |
| | Green | 71353-3 | 100 |
| | Red | 71353-5 | 100 |
| | White | 71353-7 | 100 |
| | Yellow | 71353-1 | 100 |

| Wire Gauge | Color | Part No. | Qty. Feet |
|------------|--------|----------|-----------|
| 18 | Black | 71354-6 | 100 |
| | Blue | 71354-4 | 100 |
| | Brown | 71354-2 | 100 |
| | Green | 71354-3 | 100 |
| | Red | 71354-5 | 100 |
| | White | 71354-7 | 100 |
| | Yellow | 71354-1 | 100 |

| Wire Gauge | Color | Part No. | Qty. Feet |
|------------|--------|----------|-----------|
| 20 | Black | 74420-6 | 100 |
| | Blue | 74420-4 | 100 |
| | Brown | 74420-2 | 100 |
| | Green | 74420-3 | 100 |
| | Red | 74420-5 | 100 |
| | White | 74420-7 | 100 |
| | Yellow | 74420-1 | 100 |

| Wire Gauge | Color | Part No. | Qty. Feet |
|------------|--------|----------|-----------|
| 22 | Black | 74421-6 | 100 |
| | Blue | 74421-4 | 100 |
| | Brown | 74421-2 | 100 |
| | Green | 74421-3 | 100 |
| | Red | 74421-5 | 100 |
| | White | 74421-7 | 100 |
| | White | 74421-1 | 100 |
| | Yellow | 74421-1 | 100 |

CROSS-LINK PRIMARY WIRE

- Remains flexible in -40° F temperatures.
- Noted superior to any other primary wire in pinch, abrasion and heat aging testing.
- Superior resistance to elements, abrasion and where temperature extremes are encountered.
- Perfect for truck and marine use.
- Non-flammable.
- Temperature range: -51° C to 125° C
- Complies with SAE specification J1128.
- Maximum: 50 V



| Wire Gauge | Color | Part No. | Qty. Feet |
|------------|--------|----------|-----------|
| 10 | Black | 71390-6 | 100 |
| | Blue | 71390-4 | 100 |
| | Brown | 71390-2 | 100 |
| | Green | 71390-3 | 100 |
| | Orange | 71390-8 | 100 |
| | Red | 71390-5 | 100 |
| | White | 71390-7 | 100 |
| | Yellow | 71390-1 | 100 |

| Wire Gauge | Color | Part No. | Qty. Feet |
|------------|--------|----------|-----------|
| 12 | Black | 71391-6 | 100 |
| | Blue | 71391-4 | 100 |
| | Brown | 71391-2 | 100 |
| | Green | 71391-3 | 100 |
| | Red | 71391-5 | 100 |
| | White | 71391-7 | 100 |
| | White | 71391-1 | 100 |
| | Yellow | 71391-1 | 100 |

| Wire Gauge | Color | Part No. | Qty. Feet |
|------------|---------|----------|-----------|
| 14 | Black | 71392-6 | 100 |
| | Black | 71993-6 | 500 |
| | Blue | 71392-4 | 100 |
| | Blue | 71993-4 | 500 |
| | Brown | 71392-2 | 100 |
| | Brown | 71993-2 | 500 |
| | Green | 71392-3 | 100 |
| | Green | 71993-3 | 500 |
| | Red | 71392-5 | 100 |
| | Red | 71993-5 | 500 |
| | White | 71392-7 | 100 |
| | White | 71993-7 | 500 |
| Yellow | 71392-1 | 100 | |
| Yellow | 71993-1 | 500 | |

| Wire Gauge | Color | Part No. | Qty. Feet |
|------------|--------|----------|-----------|
| 16 | Black | 71393-6 | 100 |
| | Blue | 71393-4 | 100 |
| | Brown | 71393-2 | 100 |
| | Green | 71393-3 | 100 |
| | Red | 71393-5 | 100 |
| | White | 71393-7 | 100 |
| | Yellow | 71393-1 | 100 |

| Wire Gauge | Color | Part No. | Qty. Feet |
|------------|--------|----------|-----------|
| 18 | Black | 71994-6 | 100 |
| | Blue | 71994-4 | 100 |
| | Brown | 71994-2 | 100 |
| | Green | 71994-3 | 100 |
| | Red | 71994-3 | 100 |
| | White | 71994-7 | 100 |
| | Yellow | 71994-1 | 100 |