

PAINTS

IMPERIAL® ECOSAFE® ENAMEL PAINT

- Available exclusively from Imperial!
- Imperial has lowered the solvents and added more solids, which means:
 - » LOW VOC (Volatile Organic Compounds). Up to 70% less VOC per ounce of solids for a cleaner, healthier environment.
 - » Big cost savings with more coverage that lasts longer.
 - » No fluorocarbons—protects the ozone layer.
- Includes a rust inhibitor and dries to touch in 5 minutes at 70° F., 50% relative humidity.
- Resists abrasion and corrosive chemicals.
- Retains smooth finish and resists fading longer than most spray paints.
- Maximum heat resistance to 300° F.



See our
paint chart on
the inside
back cover.



WHITE PAINT FORMULAS

PART No.	COLOR	CAN SIZE	QTY.
85127	Colonial White	16 oz.	6
85145	Custom White	16 oz.	6
85159	Drop Box White	16 oz.	6
85102	Gloss White	16 oz.	6
85165	Rainbow White	16 oz.	6
85002	Gloss White	20 oz.	6
85211 ★	Sandable White Primer	16 oz.	6

BLACK PAINT FORMULAS

PART No.	COLOR	CAN SIZE	QTY.
85110	Flat Black	16 oz.	6
85101	Gloss Black	16 oz.	6
85120	Satin Black	16 oz.	12
85001	Gloss Black	20 oz.	6

GRAY PAINT FORMULAS

PART No.	COLOR	CAN SIZE	QTY.
85147	Blue Gray	16 oz.	6
85013	Bumper Chrome Brite	16 oz.	6
85049	Custom Gray	16 oz.	6
85054	Dark Gray	16 oz.	6
85146	Dark Gray	16 oz.	6
85074	Dark Trailer Gray	16 oz.	6
85150	DD Silver	16 oz.	6
85161	Drop Box Metal Gray	16 oz.	6
85112	Dull Aluminum	16 oz.	6
85072	Light Trailer Gray	16 oz.	6
85149	Medium Gray	16 oz.	6
85069	Navy Gray	16 oz.	6
85039	PMT Gray	16 oz.	6
85018	Self-Etch Gray Primer	16 oz.	12
85212 ★	Sandable Gray Primer	16 oz.	6
85044	Universal Gray	16 oz.	6
85117	Argent Gray Bumper	20 oz.	6
85090	Black Gray	20 oz.	6
85093	Excavator Gray	20 oz.	6
85200 ★	Gray Primer	20 oz.	6
85020	Gray Rim	20 oz.	12
85098	IHC Gray	20 oz.	6
85095	Lift Semi Gloss Gray	20 oz.	6
85116	Light Gray Rim	20 oz.	6
85017	Light Machine Gray	20 oz.	6

★ Primer Paint

BROWN PAINT FORMULAS

PART No.	COLOR	CAN SIZE	QTY.
85142	Dark Brown	16 oz.	6
85143	Tractor Beige	16 oz.	6
85092	Beige	20 oz.	6
85091	Cream	20 oz.	6
85096	Power Tan	20 oz.	6

RED PAINT FORMULAS

PART No.	COLOR	CAN SIZE	QTY.
85148	Burgundy	16 oz.	6
85103	Gloss Red	16 oz.	6
85056	Tractor Red	16 oz.	6
85008	CC Red	20 oz.	6
85003	Gloss Red	20 oz.	6
85202 ★	Red Oxide Primer	20 oz.	6

ORANGE PAINT FORMULAS

PART No.	COLOR	CAN SIZE	QTY.
85045	Construction Orange	16 oz.	6
85162	Drop Box Orange	16 oz.	6
85014	JCT Orange	16 oz.	6
85119	Lift Orange	16 oz.	6
85077	Omaha Orange	16 oz.	6
85154	Orange	16 oz.	6
85070	Swamp Holly Orange	16 oz.	6
85053	Road-Ohama Orange	16 oz.	6
85208	Universal Orange	20 oz.	6

YELLOW PAINT FORMULAS

PART No.	COLOR	CAN SIZE	QTY.
85141	Bright Yellow	16 oz.	6
85153	Equipment Yellow	16 oz.	6
85097	Forklift Yellow	16 oz.	6
85105	Gloss Yellow	16 oz.	6
85180	Leasing Yellow	16 oz.	6
85151	School Bus Yellow	16 oz.	6
85126	SW Gold	16 oz.	6
85135	WM Safety Tail Yellow	16 oz.	6
85005	Gloss Yellow	20 oz.	6
85207	New Yellow	20 oz.	6
85158	Dynamic Yellow	20 oz.	6

GREEN PAINT FORMULAS

PART No.	COLOR	CAN SIZE	QTY.
85144	Alpine Green	16 oz.	6
85128	Dark Green	16 oz.	6
85166	Forest Green	16 oz.	6
85171	Medium Green	16 oz.	6
85021	Blue Green	20 oz.	6
85094	Equipment Green	20 oz.	6
85028	SB Green	20 oz.	6
85089	Teal Green	20 oz.	6

BLUE PAINT FORMULAS

PART No.	COLOR	CAN SIZE	QTY.
85140	Canyon Blue	16 oz.	6
85052	GW Blue	16 oz.	6
85198	Dark Blue	16 oz.	6
85152	FL Blue	16 oz.	6
85104	Gloss Blue	16 oz.	6
85048	MC Blue	16 oz.	6
85139	PB Blue	16 oz.	6
85167	Royal Blue	16 oz.	6
85157	URS Blue	16 oz.	6
85209	Bright Blue	20 oz.	6
85004	Gloss Blue	20 oz.	6
85210	Leasing Blue	20 oz.	6
85115	Midnight Blue	20 oz.	6
85114	Rainbow Blue	20 oz.	6
85205	True Blue	20 oz.	6

PURPLE PAINT FORMULAS

PART No.	COLOR	CAN SIZE	QTY.
85160	Drop Box Purple	16 oz.	6

CAN SIZE: 16 OZ.
NET WEIGHT: 12 OZ.

CAN SIZE: 20 OZ.
NET WEIGHT: 16 OZ.



PAINTS

SEYMOUR® INVERTED TIP MARKING PAINTS

- Water based. No-clog, fast drying formula.
- Specially designed cap that does not need to be removed before using.
- 1/8" width line. Tips are long lasting.

PART NO.	COLOR	NET WEIGHT	QTY.
85080	Fluor. Orange	17 oz.	12
85081	White	17 oz.	12
85082	Fluor. Red/Orange	17 oz.	12
85083	Utility Yellow	17 oz.	12
85084	Safety Red	17 oz.	12
85086	Alert Orange	17 oz.	12
85087	Safety Green	17 oz.	12
85088	Fluor. Hot Pink	17 oz.	12



SEYMOUR® SPRAY-GLO FLUORESCENT SPRAY PAINT

- An ultra high visibility spray paint for any project that requires a brilliant color.
- It has 400% greater visibility than regular paint.

PART NO.	COLOR	NET WEIGHT	QTY.
85015	Fluorescent Orange	12 oz.	6
85019	Fluorescent Green	12 oz.	6



SEYMOUR® HIGH TEMP PAINT

- Special formulation that can withstand temperatures up to 1200° F on a continuous basis.
- Porcelain-like bond is formed at high temperatures.
- Resists blistering, peeling, discoloration or loss of adhesion.

PART NO.	COLOR	NET WEIGHT	QTY.
85156	Black	12 oz.	6



SEYMOUR® HI-TECH® SPRAY PAINT

- Durable, fast drying enamel.
- Resists scratches, cracking and chipping.
- Protects against rust and corrosion.
- Resists gasoline and many chemicals.

PART NO.	COLOR	NET WEIGHT	QTY.
85130	Black Semi Gloss	12 oz.	6
85030	Clear Acrylic Gloss	12 oz.	6



SEYMOUR® SPRUCE® ENAMEL PAINT

- A top quality coating that provides a tough, durable finish.
- Fast drying with reduced over-spray that provides good adhesion to most metal and wood surfaces.

PART NO.	COLOR	NET WEIGHT	QTY.
85016	Medium Blue	12 oz.	6
85050	Gloss Purple	12 oz.	6



SEYMOUR® SPRAY GALV® WELD THRU PRIMER

- Protects welds on bare metal.
- Has excellent weld thru characteristics.
- Can be top coated or used as the final protective coating.
- VOC compliant.

PART NO.	COLOR	NET WEIGHT	QTY.
85136	Galvanize	15 oz.	6



SEYMOUR® STAINLESS STEEL

- A special formulation containing 100% stainless steel pigment to provide maximum corrosion resistance and protection against weather, sunlight, oil and water.
- Authorized for use in food processing plants, USA and Canada.
- Dries quickly to a satin sheen finish.
- Recommended as a topcoat and not a primer.

PART NO.	COLOR	NET WEIGHT	QTY.
85118	Stainless Steel	12 oz.	6



SEYMOUR® MRO INDUSTRIAL ENAMEL

- A superior industrial spray paint formulated for maintenance operations where maximum performance is required.
- This high solids paint does not run or sag, and gives twice the coverage of conventional spray paints.
- Can be applied to bare metal

PART NO.	COLOR	NET WEIGHT	QTY.
85006	Safety Green	11 oz.	6



SEYMOUR® CAST BLAST

- A professional grade coating that restores rebuilt cast iron engine parts to their original luster.
- Quick drying, durable and non-abrasive.
- Prevents rust and can be top coated with OEM colors.

PART NO.	COLOR	NET WEIGHT	QTY.
85076	Iron Gray	12 oz.	6



SEYMOUR® ALUMI BLAST

- A high quality coating that provides rebuilt cast aluminum parts with a factory-fresh appearance.
- Easy to apply without smudging.
- Resists corrosion and protects against abrasions.

PART NO.	COLOR	NET WEIGHT	QTY.
85201	Aluminum	12 oz.	6



SEYMOUR® TRACTOR PAINT

- Superior, premium grade enamel formulated for maximum exterior durability and outstanding weather resistance.
- Restores original factory color of leading manufacturers of farm and construction equipment.
- Gasoline, oil and grease resistant. Heat resistant to 300° F.
- Protects against fading, chipping and cracking.

PART NO.	COLOR	NET WEIGHT	QTY.
85107	IHC Red	12 oz.	6
85108	JD Green	12 oz.	6
85106	Ford Blue	12 oz.	6



SEYMOUR® GREEN ZINC PHOSPHATE PRIMER

- Prime bare metal and bare wood surfaces.
- Provides maximum rust protection.
- Fast drying, sag free spray.
- Effective against rust and chemicals.

PART NO.	COLOR	NET WEIGHT	QTY.
85199	Green	12 oz.	6



PAINTS

KRYLON® H2O LATEX PAINT

- Low odor, non-flammable, water-based latex paint.
- Easy clean up with soap and water.
- Fast drying, durable finish.
- Sprayable indoors and outdoors.
- Can be used on metal, wood, wicker and more.

PART NO.	COLOR	NET WEIGHT	QTY.
85300	Red Sea	12 oz.	6
85301	Yellow Sea	12 oz.	6
85302	Caribbean Blue	12 oz.	6
85303	Black Sea	12 oz.	6
85304	Arctic White	12 oz.	6
85305	Gulf Grey	12 oz.	6
85306	White Primer	12 oz.	6
85307	Black Sea Satin	12 oz.	6
85308	Arctic White Satin	12 oz.	6



DUPLI-COLOR® VINYL AND FABRIC COATING

- Dress up or add new life to your interior vinyl and fabric.
- Used on vinyl seats, dashes, door panels, shifter boots and consoles.
- Formulated with a maximum adhesion promoter so there is no need for a primer.
- Fast drying, will not crack, peel or chip.

PART NO.	COLOR	NET WEIGHT	QTY.
85172	Flat Black	11 oz.	6
85173	Medium Gray	11 oz.	6
85174	Charcoal Gray	11 oz.	6



KRYLON® IRON GUARD® WATER BASED ACRYLIC ENAMEL PAINT

- Iron Guard is a high gloss, 100% acrylic, waterborne coating.
- Can be applied directly to new and clean metal without a primer.
- Chemical resistant. Fast Drying.
- Corrosion resistant.
- Early rust resistance. Low odor.
- Outstanding adhesion.

PART NO.	COLOR	NET WEIGHT	QTY.
85350	Gloss Black	1 gallon	4
85351	Gloss White	1 gallon	4
85352	Gloss Yellow	1 gallon	4
85353	Light Machine Gray	1 gallon	4
85354	Gray Primer	1 gallon	4
85355	Custom White	1 gallon	2



TRADES-MARKER® GREASE PEN

- Refillable grease pen.
- Includes orange, white, yellow, black and red.

PART NO.	DESCRIPTION	QTY.
9628	Refillable Pen, 5 colors	1
9629	Black Refills	5



GREASE PENCILS/CHINA MARKERS

- Paper wrapped marker, smooth writing.
- Moisture resistant.
- Non-toxic pigments.

PART NO.	COLOR	QTY.
9630	Black	6



IMPERIAL® TOUCH UP PAINT

- 2-in-1 technology: roller ball tip and tapered brush end.
- Formulated to make nick, chips and scratches disappear.

PART NO.	COLOR	NET WEIGHT	QTY.
9700	Drop Box White	.5 oz.	1
9701	Drop Box Silver	.5 oz.	1
9702	Drop Box Purple	.5 oz.	1
9703	Drop Box Orange	.5 oz.	1



IMPERIAL® PAINT PENS

- Fast drying, high gloss enamel paint.
- Marks on metal, plastic, printed circuit boards, glass, wood, paper and leather.
- Writes on any surface, porous or non-porous; rough or smooth; wet, oily or dry.
- Chip, peel or fade resistant. 1/8" width line. Tips are long lasting.

PART NO.	COLOR	QTY.
9640	White	1
9641	Yellow	1
9642	Black	1
9643	Red	1
9644	Blue	1
9645	Green	1
9646	Orange	1
9647	Silver	1
9648	Gold	1



IMPERIAL® SOLID PAINT MARKERS

- Marks on metal, wood, plastic, glass, cardboard, textiles, etc.
- Writes on any surface; rough or smooth; wet, oily, dry, under water.
- Marks are permanent; they won't chip, peel, fade or rub off.
- Withstands heat and weathering under adverse conditions.
- If needed, marks can be removed with standard industrial solvents.
- Lead free. Line width: 5/16"

PART NO.	COLOR	QTY.
9660	White	2
9661	Yellow	2
9662	Red	2



SPRAY CAN NOZZLES

PART NO.	TYPE	QTY.
85100	Cone	10
85111	Fan	10



SPRAY CAN GUN HANDLE

- Use on various spray cans such as paints and lubricants.
- Less mess, eliminates finger/wrist fatigue.
- 100% post consumer recycled plastic.

PART NO.	QTY.
6598	2



PROFESSIONAL SPRAY CAN GUN HANDLE

- Easy pull FullGrip™ EZ Pull Trigger.
- Up to 8 times easier to spray.
- Easy to use with gloves.
- Ergonomic, arthritis-friendly design.
- Snaps onto any standard aerosol can with a push and twist motion.
- Easy on and off, reusable.

PART NO.	QTY.
6639	1



LUBRICANTS

IMPERIAL® PENETRATING LUBE WITH PTFE

- Special formulation provides a long lasting lubrication that bonds quickly to most clean surfaces.
- Will not pick up dust, dirt, mud or grit.
- Excellent resistance to rain, snow, dirt and heat.
- Lubricates loads of up to 18,000 psi.
- Methylene chloride free.

PART NO.	NET WEIGHT	QTY.
6502	10.5 oz.	12
6502-1	10.5 oz.	6



IMPERIAL® HEAVY-DUTY PENETRATING OIL

- Specially formulated to quickly free stubborn rusted nuts, bolts or any threaded product.
- Lubricating action protects parts from dirt and corrosion.
- Will penetrate quickly into the tightest crevices.
- CA and OTC compliant.

PART NO.	NET WEIGHT	QTY.
6568	11.75 oz.	12
6568-1	11.75 oz.	6



IMPERIAL® PENETRATING LUBE WITH PTFE

- Designed to help loosen rusted assemblies while leaving behind a film of PTFE to help lubricate metal.
- Displaces moisture and prevents corrosion.

PART NO.	NET WEIGHT	QTY.
4602	1 gallon	2
4702	16 oz. trigger bottle	12
2602	16 oz. empty trigger bottle	4



IMPERIAL® PENETRATING OIL

- Superior penetration helps loosen rusted assemblies.
- Protects metal from rusting as it lubricates.

PART NO.	NET WEIGHT	QTY.
4600	1 gallon	2
4700	16 oz. trigger bottle	12
2600	16 oz. empty trigger bottle	4



IMPERIAL® CHILLING PENETRATING OIL

- Fast-acting penetrating oil that super cools bolts to -30° F, causing a cold cracking action of the rust and corrosion.
- Promotes easy removal of rusted nuts/bolts.
- Works effectively on bolts up to 3" diameter.
- Protects steel surfaces from corrosion.
- Will not break down in temperature variations.
- Oil will not wash away or evaporate.

PART NO.	NET WEIGHT	QTY.
6617	3.5 oz.	6



IMPERIAL® 4-WAY LUBE

- Forms an invisible barrier to block moisture and other corrosive elements to stop metal from rusting.
- Loosens rusted assemblies.

PART NO.	NET WEIGHT	QTY.
4601	1 gallon	2
4701	16 oz. trigger bottle	12
2601	16 oz. empty trigger bottle	4



IMPERIAL® BIODEGRADABLE PENETRATING OIL

- Fast acting penetrating oil and general lubricant.
- Superior wetting ability and a high affinity for metal surfaces.
- Offers excellent penetrating and loosening of frozen, rusted or stuck components. Excellent water displacement properties.
- The "Green Solvents" used in the product are excellent for dissolving dirt while leaving behind a light lubricating film which helps to control corrosion.
- Safe for the environment. Low toxicity.
- Special care should be taken when used around certain plastics.
- Some products may be incompatible with this formula, like foams, urethanes and paint surfaces.

PART NO.	NET WEIGHT	QTY.
6626	11 oz.	12
6626-1	11 oz.	6



L4

IMPERIAL® MULTI-PURPOSE LUBRICANT AND RUST PREVENTATIVE

- This multi-purpose lubricant can be used to free and protect rusted parts (bolts, fasteners) on a variety of machinery found in industrial, marine, automotive and residential applications.
- Designed and formulated for fast penetration into tight fitting parts as well as to quickly release frozen or corroded bolts and lugs.
- Low surface tension for fast and deep penetration of lubricant.
- Protects steel surfaces against salt and moisture.
- This product also meets or exceeds the following:
 - » NSF (H-2) Lubricants, general (no contact).
 - » The NSF H-2 classification certifies lubricants for applications where no contact with food products is expected

PART NO.	NET WEIGHT	QTY.
4626	1 gallon	2
2626	16 oz. empty trigger bottle	4



Use Plastic Funnels on page M44 for convenient filling.



LUBRICANTS

B'LASTER® PB PENETRATING CATALYST

- Powerful, concentrated penetrant that frees rusted or frozen parts by releasing the surface tension that causes parts to stick.
- Lubricates to protect against future rust or corrosion.
- Capillary action actually pulls itself uphill.
- Quickly breaks loose the surface tension of frozen parts and protects against further rust and corrosion.
- Reaches into cracks and crevices.
- Dielectric to displace moisture.

PART NO.	NET WEIGHT	QTY.
6503	11 oz.	12
6503-1	11 oz.	6
4603-4	1 gal with trigger bottle	4
2603	16 oz. empty trigger bottle	12
820003 ★	55 gallon drum	1

★ Freight not included.



B'LASTER® DRY LUBE

- Superior, long-lasting lubrication.
- Does not contain silicone.
- Use on almost any surface, even plastics.
- Applications: locks and catches, hinges, cables, window tracks and glass, rope, door tracks and conveyor belts.

PART NO.	NET WEIGHT	QTY.
6574	9.3 oz.	12
6574-1	9.3 oz.	6



B'LASTER® ALL-PURPOSE LUBRICANT

- Lubricates moving parts such as: hinges, valves, wheels, rollers, chains, glides and gears
- Protects against rust and corrosion.
- Penetrates to free rusted or stuck tools and parts: nuts, bolts, hinges, valves, dials, chains and locks
- Displaces and repels moisture.

PART NO.	NET WEIGHT	QTY.
6504	8 oz.	12
4604-4	1 gallon	4



SPRAYWAY® L1 LUBRICANT PROTECTANT

- Heavy duty penetrant is designed to work fast, loosening rust and corrosion.
- Non-conductive formula.
- Displaces moisture, never dries.
- No chlorinated solvents.

PART NO.	NET WEIGHT	QTY.
6608	15 oz.	12
6608-1	15 oz.	6



SPRAYWAY® L3 MOLY PTFE LUBRICANT PROTECTANT

- Formulated with PTFE and fortified with Moly to provide long lasting lubrication and protection from friction, wear and corrosion.
- The light viscosity of this product allows for deep penetration into hard to reach moving parts.
- Safe for use on most surfaces.
- Heat stable up to 500° F.
- Displaces moisture.

PART NO.	NET WEIGHT	QTY.
6610	15 oz.	12
6610-1	15 oz.	6



IMPERIAL® IMPENETRATOR

- Penetrating lubricant that seeps in cracks and crevices of rusted parts, to help break them apart.
- Comes with an extension tube to get into hard to reach areas.
- Capillary action causes the product to wick up the surface.
- Use as a preventative against future rusting of parts.

PART NO.	NET WEIGHT	QTY.
6605	12 oz.	12



JET LUBE® LUBRICANT/ PENETRANT FOOD GRADE

- USDA H-2 authorized for use in federally inspected meat and poultry plants.
- Non-flammable blend of lubricants and special additives that provide environmentally safe performance.
- A thin film adheres to all metal to lubricate, penetrate, remove moisture and prevent rust and corrosion.
- 35 KC dielectric strength.

PART NO.	NET WEIGHT	QTY.
5526	16 oz.	12
5526-4	1 gallon	4



LIQUIFIX® BULK LUBRICANT & PROTECTANT

- Lubricates all metal, rubber and plastic by creating a corrosion resistant barrier, forming an ultra thin, non-drying, anti-static film.
- Loosens nuts and bolts.
- Displaces moisture and provides a lasting corrosion-resistant barrier.
- Cleans electrical panels, circuit boards, fuse boxes.
- Non-conductive; high dielectric rating 35,000 volt.
- Unaffected in sub zero temperatures.
- High flash point: 230° F.
- Acceptable as a lubricant and protective anti-rust film for seals, gaskets and machinery parts in and around food processing areas (H-1 Classification).
- Non-toxic, non-aerosol, no VOCs, non-staining.

PART NO.	NET WEIGHT	QTY.
4642	16 oz.	12
4642-4	1 gallon	4



LUBRICANTS

SPRAYWAY® L2 MOISTURE DISPLACER DEEP PENETRANT

- Heavy-duty penetrant cleans, loosens and protects faster than traditional products, saving you time.
- For institutional, commercial and industrial use.
- This moisture displacer reaches deep down to loosen nuts and bolts where corrosion and rust have collected.
- Saves production, maintenance and repair time by protecting equipment with its rust inhibitor.
- Stops corrosion on battery terminals and contains no ozone-depleting chemicals.

PART NO.	NET WEIGHT	QTY.
6592	20 oz.	12
6592-1	20 oz.	6



JET LUBE® SUPER PENETRANT FOOD GRADE

- USDA H-1 authorized for use in federally inspected meat and poultry plants.
- Premium, synthetic product that can be used as a light machine oil, penetrating oil or rust preventative.
- Excellent for both food grade and non-food grade applications.
- Non-evaporating formula.

PART NO.	NET WEIGHT	QTY.
6577	13 oz.	12



DRI-SLIDE® MULTI PURPOSE LUBRICANT

- A special moly-penetrating formula.
- For use on sliding tandems, 5th wheels, kingpins, bearings, cables, hinges or any other friction-producing areas.
- Contains corrosion inhibitors to prevent rust.
- Under normal conditions will not harm rubber, steel, paint or plastics.
- Withstands pressures to 100,000 psi.
- Temperature range -20° F to 750° F
- Dry film leaves long-lasting protection.
- Resists dirt, dust and water.

PART NO.	NET WEIGHT	QTY.
7608	1 gallon	1
7608-4	1 gallon	4
6552	5.25 oz.	12



PERMATEX® ULTRA SLICK® SYNTHETIC MULTI-PURPOSE LUBRICANT WITH PTFE

- Ultra Slick Lubricant is a GC/LB grease.
- Product can be used on any moving part to provide better, long lasting lubrication.
- Withstands temperatures up to 350° F.

PART NO.	NET WEIGHT	QTY.
6595	11 oz.	6



SUPER LUBE® SYNTHETIC LUBRICANT

- A patented synthetic lubricant that outperforms and outlasts petroleum-based products.
- Synthetic formula that contains no petroleum distillates.
- Protects against friction, wear, rust and corrosion.
- Machinery and equipment are protected from wear and corrosion while maintenance and service requirements are reduced.
- Contains PTFE. Won't evaporate.

PART NO.	NET WEIGHT	QTY.
5594	1 gallon	4
5594-1	1 gallon	1
5593	32 oz.	12



DOOR EASE® STICK LUBRICANT

- Clean, easy way to lubricate exposed surfaces.
- Prevents squeaks, wear and rust.
- Apply like a crayon.

PART NO.	NET WEIGHT	QTY.
7600	4.5 x 1"	2



O-RING LUBRICANT

- Specifically made for O-rings, gaskets, seals and bushings.
- May be used on natural rubber, synthetic elastomers and felt.
- Prevents abrasion, freeze-ups and premature failure.

PART NO.	NET WEIGHT	QTY.
7515	1.5 oz.	2



L6



*Kristy
Sales Manager*

Responsive...

"When customers call, I assume they need the part now. Not tomorrow, not next week, but right now."

All first time chemical product orders from Imperial include MSDS for maintaining OSHA Compliance.

View MSDS 24/7 on our website at www.imperialsupplies.com



LUBRICANTS

IMPERIAL® DRY GRAPHITE LUBRICANT

- Contains no chlorinated solvents—won't contaminate waste oil (1, 1, 1 trichloroethane free).
- Special formulation provides long-lasting lubrication that bonds quickly to any clean metal, wood, concrete or plastic surface.
- Will not pick up dust, dirt, mud or grit.
- Excellent resistance to rain, snow, dirt and heat.
- Effective temperature range -80° F to 1060° F
- Will effectively lubricate loads of up to 18,000 psi.
- Methylene chloride free.

PART No.	NET WEIGHT	QTY.
6507	10.25 oz.	12
6507-1	10.25 oz.	6



IMPERIAL® BORON NITRIDE LUBRICANT

- Unique formula that functions as a smooth, quick drying and greaseless white film lubricant for all types of surfaces.
- Boron Nitride (White Graphite) is a ceramic powder lubricant, but unlike graphite, it has excellent electrical insulation and retains lubricity even in vacuum environments.
- Applications: lubricates and seals packing glands, saw blades, conveyors, channels sliding frames, cutting blades, pipe threads, etc
- Stops galling/cold-welding/binding of metal surfaces.
- Adheres to surfaces that liquids and greases cannot.

PART No.	NET WEIGHT	QTY.
6554	8.5 oz.	12
6554-1	8.5 oz.	6



IMPERIAL® 5TH WHEEL LUBRICANT

- Heavy bodied lubricant that is ideal for extreme pressure applications.
- Extends kingpin life by eliminating binding and seizing.
- Decreases wear on truck channels and uprights, thereby extending parts life.
- Excellent adhesion—won't rub off.
- Resists water washout in all weather conditions.
- Contains rust and corrosion inhibitors.
- Methylene chloride free.

PART No.	NET WEIGHT	QTY.
6505	10 oz.	12
6505-1	10 oz.	6



IMPERIAL® OPEN GEAR LUBE AEROSOL

- Has excellent adhesion and heavy viscosity that provides for tough lubrication that will not drop or be thrown off.
- Protects and lubricates open gears, gear boxes, wire ropes, cables, and pulleys.
- Contains anti-corrosive features impervious to elements and prevents rust.
- Color: Brown

PART No.	NET WEIGHT	QTY.
6550	10 oz.	12



IMPERIAL® WHITE GREASE

- White lithium grease is a heavy duty, highly penetrating lubricant that is convenient and easy to use.
- Fortified lithium base contains anti-corrosion additives.
- High viscosity causes it to cling readily to all types of surfaces.
- Will not break down, freeze, melt or wash off.
- Methylene chloride free.

PART No.	NET WEIGHT	QTY.
6510	13.75 oz.	12
6510-1	13.75 oz.	6



SLIP PLATE® NO. 1 HEAVY-DUTY GRAPHITE DRY FILM LUBRICANT

- A dry film lubricant that bonds to any clean metal, wood, concrete and most plastic surfaces.
- Formulated to provide the most lubricious surface coating available for tough wear applications.
- Operating temperature range: -75° F to 400° F
- Tack free dry time: 70-90 minutes
- Coverage: 200 square feet

PART No.	NET WEIGHT	QTY.
5590	1 gallon	4
5591	1 quart	1



SLIP PLATE® GRAPHITE AEROSOL

- Fast drying, graphite dry film lubricant.
- Can be sprayed on metal, wood and plastic.
- Forms a dry non-stick surface.
- Adheres rapidly with little pretreatment.
- Reduces friction, prevents parts wear.
- Prevents build-up of dirt and rust.

PART No.	NET WEIGHT	QTY.
6590	12 oz.	12



LOCK-EASE® GRAPHITE LOCK FLUID

- Prevents sticking. Guards against rust and wear.
- Helps seal out moisture.
- Leaves a long lasting graphite film.
- Can be used in hot or cold climates.
- For use on all types of locks.

PART No.	NET WEIGHT	QTY.
7609	3.4 oz.	1



PERMATEX® 5TH WHEEL GREASE

- Pre-measured grease comes in a sealed pouch.
- Package disintegrates leaving no waste.
- Effectively lubricates 5th wheel top plates.
- Graphite lubricant designed for heavy-duty applications and extreme temperatures and conditions.
- Requires no tools, creates no mess.

PART No.	CROSS REFERENCE	NET WEIGHT	QTY.
6611	01010	2 oz. pouch	60
6611-4	01020	2 oz. pouch	350



Avoid overspray on hands by using Nitrile or Vinyl Gloves found on pages K5 and K6.



LUBRICANTS

IMPERIAL® HEAVY-DUTY RED PENETRATING GREASE

- Non-chlorinated formula.
- The grease penetrates as a liquid, then solidifies into a thick red grease.
- Operating Temperature: 0° F. to 400° F.
- Can be used on: chains, door hinges, gears, slides, etc.

PART NO.	NET WEIGHT	QTY.
6509	13.75 oz.	12
6509-1	13.75 oz.	6



IMPERIAL® SILICONE LUBRICANT

- Formulation designed to prevent almost anything from sticking or squeaking.
- Highest quality non-toxic silicone and solvents.
- Oil-free. Will not stain, gum or bind.
- Lubricates, waterproofs, protects and conditions.
- Rejuvenates rubber products.
- Safe for use on plastics and painted surfaces.
- Effective temperature range: -100° F to 550° F
- USDA approved H2.
- Methylene chloride free.

PART NO.	NET WEIGHT	QTY.
6530	9.25 oz.	12
6530-1	9.25 oz.	6



IMPERIAL® GEL-LUBE

- Clear formula.
- Sprays out as a liquid, then solidifies as a thick clear grease.
- Resists wash-out.
- Provides superior lubrication and prevents corrosion.
- Temperature range: -35° F to 500° F

PART NO.	NET WEIGHT	QTY.
6571	14 oz.	12
6571-1	14 oz.	6



IMPERIAL® SILICONE LUBE

- Designed to prevent almost anything from sticking or squeaking.
- Rejuvenates rubber products.

PART NO.	NET WEIGHT	QTY.
4630	32 oz.	8
4730	16 oz. trigger bottle	12
2630	16 oz. empty trigger bottle	4



IMPERIAL® BIODEGRADABLE EP2 GREASE

- Biodegradable non-toxic lithium grease.
- High temperature, high performance grease that excels at extreme pressures.
- Formulated to exhibit excellent stability and extended lubricant life.
- High load carrying and anti-wear characteristics.
- Designed for heavy duty use in variety of industrial, mobile and marine applications.
- Advance rust and corrosion protection.
- NLGI grade: ASTM D217 2
- Texture: Smooth

PART NO.	COLOR	NET WEIGHT	QTY.
6625	Amber	11 oz.	12
6625-1	Amber	11 oz.	6



B'LASTER® SILICONE LUBE

- Safe, non-staining, silicone-based lubricant
- Provides a protective, lubricating film on a wide variety of equipment and material.
- Restores life to vinyl, leather and rubber.
- Non-evaporating formula.

PART NO.	NET WEIGHT	QTY.
6512	11 oz.	12
6512-1	11 oz.	6



SPRAYWAY® S1 SILICONE SPRAY

- Light duty silicone spray.
- Non-staining, non-corrosive.
- Quick drying.
- NSF approved - H2 (no contact with edible food).

PART NO.	NET WEIGHT	QTY.
6618	11 oz.	12
6618-1	11 oz.	6



B'LASTER® WHITE LITHIUM GREASE

- Clean white grease with a very low odor.
- Long lasting lubrication and protection for a wide range of applications and conditions.
- Excellent for heavy duty applications.
- Primary applications: gears, shafts, heavy duty chains, axles, bearings, fan motors, couplings, automotive hinges, heavy machinery, conveyor belts and chains, mechanical mechanisms, non-disc brake parts, springs, plumbing fixtures and more

PART NO.	NET WEIGHT	QTY.
6522	11 oz.	12
6522-1	11 oz.	6



JET LUBE® FOOD GRADE SILICONE

- USDA H-1 authorized for use in federally inspected meat and poultry plants.
- Stops sticking, squeaking and binding of moving parts.
- Will not gum or form unwanted residues.
- Leaves a clear film that is moisture resistant, long wearing, odorless, colorless, non staining and non toxic.
- Will not melt, freeze or become rancid.

PART NO.	NET WEIGHT	QTY.
6576	12 oz.	12



LUBRICANTS

IMPERIAL® GEAR AND CHAIN LUBE

- Non-chlorinated (1, 1, 1 trichloroethane free).
- Lubricates, protects and prolongs the life of chains, cables and open gears.
- Quick-drying, high-penetrating foaming formula that repels dirt, sand and rust.
- Produces a thin, transparent film that acts as a demoisurant, providing a long-lasting barrier to salt water and atmospheric moisture.
- Withstands high temperatures and pressures while resisting throw-off.
- **Methylene chloride free.**

PART No.	NET WEIGHT	QTY.
6566	12 oz.	12
6566-1	12 oz. empty trigger bottle	6



IMPERIAL® CHAIN LUBE

- Lubricates, protects and prolongs the life of chains, cables and open gears.
- Produces a thin film that repels moisture and corrosion.
- CA/OTC approved, low VOC formula.

PART No.	NET WEIGHT	QTY.
4666	1 gallon	2
2666	16 oz. empty trigger bottle	4



3M™ SILICONE LUBRICANT PLUS

- Wet type lubricant.
- Provides increased lubricating qualities, especially on sliding parts.
- Long lasting.
- Facilitates the installation of rubber set windshields.
- Will not freeze at -28° F.
- Will not degrade at 350° F.
- Seals out moisture.

PART No.	NET WEIGHT	QTY.
6633	9 oz.	12



3M™ SILICONE LUBRICANT

- Dry type lubricant.
- Eliminates rubber squeaks and prevents sticking.
- Contains no petroleum oils to stain fabrics.
- Will not freeze at -28° F.
- Will not degrade at 350° F.
- Seals out moisture.

PART No.	NET WEIGHT	QTY.
6634	8 oz.	12



LUBRIPLATE® X-357 EXTREME PRESSURE MOLY LUBRICANT

- Water resistant, unaffected by temperature extremes.
- Excellent for fifth wheels, pintle hooks, slides and open gears.

PART No.	NET WEIGHT	QTY.
7675	11 oz.	12



IMPERIAL® BIODEGRADABLE CHAIN & CABLE LUBRICANT

- Formulated from readily biodegradable solvents/environmentally friendly.
- Is a vegetable-based lubricant.
- Provides anti-corrosion protection.
- Contains a unique EP additive package that provides better anti-wear and EP protection than most industrial chain lubes.
- For all makes of chains and all types of roller link chains, like motorcycles and bicycles, as well as farm and industrial uses.
- Also contains rust protection, cleanliness additives and heat dissipating compounds.

PART No.	NET WEIGHT	QTY.
6624	11 oz.	12
6624-1	11 oz.	6



B'LASTER® GARAGE DOOR LUBE

- Prevents rust, corrosion, squeaking and sticking problems.
- Leaves a dry, tack-free film that will not accumulate dust and dirt.
- Used for fleet and tractor trailer door service, as well as residential and commercial garage door service.
- Unique formula combines silicone with extreme pressure agents.
- Spray bottle must be purchased separately for gallon size.

PART No.	NET WEIGHT	QTY.
6549	9.3 oz. net	12
6549-1	9.3 oz. net	6
4649-4	1 gallon	4



SPRAYWAY® M1 MOLY CHAIN AND CABLE LUBRICANT

- Provides superior penetrating action for rollers, pins, links and bushings of chains.
- Moly provides anti-wear and rust protection to the wire ropes and cables.
- Increases the life of chains and wire ropes.

PART No.	NET WEIGHT	QTY.
6616	15 oz.	12
6616-1	15 oz.	6



LUBRIPLATE® CHAIN & CABLE FLUID

- Superior penetrating oil.
- A cleansing, non-gumming oil.
- Lubricates wire rope, chains, cables and virtually any moving metal surface.
- Loosens rusty bolts and nuts.
- Prevents rust and corrosion.

PART No.	NET WEIGHT	QTY.
7676	12 oz.	12
4676-4	1 gallon	4



CHEMICALS & PAINTS

BRAKE PARTS CLEANER / GASKET REMOVER

IMPERIAL® NON-CHLORINATED DEGREASER & BRAKE PARTS CLEANER I & III

- Restores smooth brake operation.
- Flushes away contaminants without disassembling the brake unit.
- Removes dirt, grease, brake fluid and grime from brake components.
- For valve covers, brake shoes, clutch pressure plates and transmissions.
- Contains no chlorinated solvents (1,1,1 trichloroethane free).



PART NO.	DESCRIPTION	NET WEIGHT	QTY.
6622 ★	Cleaner I	12.25 oz.	12
6622-1 ★	Cleaner I	12.25 oz.	6
6536 ◆	Cleaner III	14.75 oz.	12
6536-1 ◆	Cleaner III	14.75 oz.	6

★ New 10% VOC formula. Compliant in 50 states!

◆ Not CA compliant.

IMPERIAL® BRAKE PARTS CLEANER

- Quickly removes grease, oil, brake fluid, dirt and tar.
- Does not leave a residue.

PART NO.	NET WEIGHT	QTY.
4637 ◆	32 oz.	8
4736 ◆	16 oz. trigger bottle	12
2636 ◆	16 oz. empty trigger bottle	4
4639	32 oz.	8
4739	16 oz. trigger bottle	12
2639	16 oz. empty trigger bottle	4

◆ Not CA compliant.



IMPERIAL® BIODEGRADABLE BRAKE PARTS CLEANER

- Non-Chlorinated formula will not contaminate solvent cleaning dip tanks or other recyclable waste solvent cleaning systems.
- Formulated from readily biodegradable solvents.
- Can be used to clean and degrease brake systems, discs, drums, electric motors (non-electrified), cables, bearings, gears, fans, hoists, gold and silver contacts, guns, air conditioners, etc.
- High-pressure delivery system will not leave a residue and air-dries very quickly.
- Compliant in all 50 states.

PART NO.	NET WEIGHT	QTY.
6623	12.25 oz.	12
6623-1	12.25 oz.	6



All first time chemical product orders from Imperial include MSDS for maintaining OSHA Compliance.

View MSDS 24/7 on our website at www.imperialsupplies.com

SPRAYON® BRAKE AND PARTS CLEANER

- Instantly flushes away brake fluids, grease and dirt.
- Non-chlorinated formula.
- Fast evaporating and leaves no residue.

PART NO.	NET WEIGHT	QTY.
6569	14 oz.	12



SPRAYWAY® INDUSTRIAL GASKET REMOVER

- Saves time and labor for automotive and industrial personnel.
- Facilitates gasket removal even when difficult.
- Excellent for automotive, marine, industrial and farm machinery.
- Safe for use on metal surfaces.
- Leaves no film or residue.

PART NO.	NET WEIGHT	QTY.
6591	18 oz.	12
6591-1	18 oz.	6



L10

See page M10 for quality Shop Towels.



Dave
Project Manager

Experienced...

"My years of experience in the industry and product specific information are just one of the resources available for our customers."




CALL 1-800-558-2808 / FAX 1-800-553-8769 / WWW.IMPERIALSUPPLIES.COM

DEGREASERS & CLEANERS

IMPERIAL® CITRUS DEGREASER

- Fast acting, super penetrating cleaner/degreaser.
- Used to remove tar, grease, dirt and oils from most surfaces.
- Pleasant citrus smell.
- Does not contain any chlorinated solvents.
- Flammable.
- Not CA compliant.

PART No.	NET WEIGHT	QTY.
6535	13 oz.	12
6535-1	13 oz.	6



IMPERIAL® DEGREASER

- Quickly removes grease, oils and stains from washable surfaces.

PART No.	NET WEIGHT	QTY.
4635	1 gallon	2
4735	16 oz. trigger bottle	12
2635	16 oz. empty trigger bottle	4



IMPERIAL® BIODEGRADABLE CITRUS ENGINE DEGREASER

- 100% biodegradable, nontoxic cleaning formula.
- Leaves behind a fresh citrus fragrance.
- Foaming engine degreaser that quickly and easily cleans away grease and oils from engines, power mowers, marine and tractor engines.
- Contains no petroleum distillates and can be easily rinsed with water.
- Cleans and brightens surfaces.
- Not CA compliant.

PART No.	NET WEIGHT	QTY.
6636	16.25 oz.	12
6636-1	16.25 oz.	6



B'LASTER® CITRUS DEGREASER

- Fast-acting, solvent-type degreaser.
- Strong natural and distilled solvents help remove oils, grease, inks, adhesives, resins and more.
- Safe for use on a wide variety of materials.
- Dries without leaving a residue.

PART No.	NET WEIGHT	QTY.
6516	11 oz.	12
6516-1	11oz.	6



SPRAYWAY® D3 CITRUS DEGREASER

- Non-chlorinated.
- Natural citrus base.
- Attacks oil, grime, grease, tar and other oil-based contaminants on hard surfaces.
- Leaves little or no film.

PART No.	NET WEIGHT	QTY.
6553	15 oz.	12
6553-1	15 oz.	6



IMPERIAL® BIODEGRADABLE HIGH FLASH SOLVENT DEGREASER

- Used to clean parts, tools and other equipment.
- Do not use near certain plastics, painted surfaces, urethanes and foam.
- Meets the consumer products LVP-VOC exemption criterion established by CARB for consumer and institutional products.
- Meets the federal VOC exemption criteria for consumer products per the EPA 40CFR59.203(f)1.
- Non-flammable formula. Low toxicity.

PART No.	NET WEIGHT	QTY.
6619	13 oz.	12
6619-1	13 oz.	6



IMPERIAL® CARB & CHOKE CLEANER

- Cleans and removes gums, varnishes, grease, dirt and leak deposits.
- For use on automatic chokes, carburetor linkage and manifold heat controls.
- Oxygen sensor safe.
- Compliant in all 50 states.

PART No.	NET WEIGHT	QTY.
6564	11 oz.	12
6564-1	11 oz.	6



B'LASTER® AQUEOUS-BASED DEGREASER

- Exclusive formula, water-based degreaser handles the grimmest, greasiest industrial maintenance jobs because it's super concentrated.
- Makes short work of resins, printing inks and wet paints.
- Super-concentrated, dilute to needed concentration.
- Can be used in pressure washers and steam cleaners for a carpet stain remover.
- Biodegradable.

PART No.	NET WEIGHT	QTY.
5533	16 oz.	12



SPRAYWAY® D2 SOLVENT DEGREASER

- Non-Chlorinated degreaser removes oil, grease, adhesive, brake fluid and other contaminants from metal parts and surfaces.
- High flow spray and quick drying. Leaves no film.
- Does not contain chlorinated solvents or silicones.
- Not for use on plastic, rubber, polycarbonates and similar surfaces.

PART No.	NET WEIGHT	QTY.
6518	14 oz.	12
6518-1	14 oz.	6



CHEMICALS & PAINTS

DEGREASERS & CLEANERS

IMPERIAL® ALL PURPOSE CLEANER

- CA/OTC approved, low VOC formula.
- Used to clean multiple surfaces; carpets and upholstery, headliners, vinyl, leather trim, white wall tires, counter tops, concrete floors.
- Dilute as necessary (examples):
 - » Carpets (6 oz. to 10 quarts water)
 - » Exterior Surfaces (1 oz. to 10 quarts water)
 - » White wall tires (8 oz. to 10 quarts water)
 - » Vinyl & Leather Trim (6 oz. to 10 quarts water)

PART NO.	NET WEIGHT	QTY.
4617	1 gallon	2
4717	16 oz. trigger bottle	12
2617	16 oz. empty trigger bottle	4



SPRAYWAY® PLASTIC CLEANER

- Contains no chemicals or abrasives that cause damage to transparent surfaces.
- Effectively repels finger smudges, dirt and dust on a variety of surfaces and materials.
- Increased use will add protection against wear and scratching.
- Anti-fog—prevents fogging on bathroom and locker room mirrors.
- Dries in just the right time, keeping the surface free from streaks and hazing.
- Anti-static and reduces glare.

PART NO.	NET WEIGHT	QTY.
85529	19 oz.	12



IMPERIAL® VANDAL MARK REMOVER II

- Contains no chlorinated solvents—won't contaminate waste oil (1, 1, 1 trichloroethane free).
- Special high-strength formula removes marks that other cleaners won't.
- Harmless to most hard, painted surfaces.

PART NO.	NET WEIGHT	QTY.
6544	16 oz.	12
6544-1	16 oz.	6

◆ Not CA compliant.



CHEM-EEZ® HEAVY-DUTY DEGREASER CLEANER

- Potent, yet safe, degreaser/cleaner with superior detergents, safe solvents and high alkaline builders.
- Works great as a multi-purpose floor cleaner.
- Non-flammable and fast acting.
- USDA Authorized Class A-1, Kosher approved.

PART NO.	NET WEIGHT	QTY.
85506	1 gallon	1
85506-4	1 gallon	4
820000 ★	55 gallon	1

★ Freight not included.



CLAIRE® GRAFFITI REMOVER

- Green approved product by Design for the Environment – U.S. EPA.
- Non flammable, phosphate free, no VOC content, no harmful chemical run off, non ozone depleting substances.
- Removes paint, ink, permanent marker and unwanted graffiti from a variety of surfaces.
- Can be used diluted or undiluted.
- Clear, colorless with a mild odor.
- Includes 2 trigger sprayers.

PART NO.	NET WEIGHT	QTY.
85574	1 quart	6



If you can't find the products you are looking for, call us, and we will find it for you.

L12

JET LUBE® INDUSTRIAL GRADE DEGREASER SAFETY SOLVENT CLEANER

- USDA K-1 Solvents and solvent degreaser for use in non processing areas.
- Heavy duty, low foaming, chlorinated solvent that rapidly dissolves oil, grease, paint, tar and grime on contact.
- Leaves a clean, residue free finished surface.
- Nonacid, alkali free.
- Non conductive, 29 KV dielectric strength.
- Will not corrode or damage metal surfaces.

PART NO.	NET WEIGHT	QTY.
6578	18 oz.	12



*Melinda
Customer Service*

Devoted...

"It's not just finding the right part. It's keeping a shop going. You've got to know that and care about it."



CALL 1-800-558-2808 / FAX 1-800-553-8769 / WWW.IMPERIALSUPPLIES.COM

DEGREASERS & CLEANERS

SIMPLE GREEN® HEAVY-DUTY CLEANER

- Powerful pressure washing concentrate, designed to remove tough grease and grime deposits from a variety of non-porous surfaces.
- Removes oils, grease, soot and ash, exhaust, sap, pollen, mold and mildew stains, road tar and other tough soils.
- Non-toxic, biodegradable and safe for pressure washing machinery or manual cleaning.

PART NO.	NET WEIGHT	QTY.
85576-4	1 gallon	4



CRYSTAL SIMPLE GREEN® CONCENTRATED INDUSTRIAL CLEANER

- Industrial formula.
- No color or scents added.
- Nontoxic, biodegradable, nonabrasive and nonflammable.
- Mild 9.3 to 9.5 pH.
- USDA authorized: A4, A8
- Concentrated formula.

PART NO.	NET WEIGHT	QTY.
85575-4	1 gallon	6



SIMPLE GREEN® CONCENTRATED CLEANER

- Nontoxic, biodegradable, nonabrasive and nonflammable.
- A safer alternative to hazardous chemicals and solvents.
- Mild 9.3 to 9.5 pH.
- USDA authorized: A4, A8, B2
- Concentrated formula.

PART NO.	NET WEIGHT	QTY.
85573	24 oz. trigger bottle	12
85574-4	1 gallon	6



FOAMING CRYSTAL SIMPLE GREEN® INDUSTRIAL CLEANER

- Industrial cleaner and degreaser.
- Foaming formula penetrates hard to reach areas and clings to vertical surfaces.
- No color or scent added.
- Nontoxic, biodegradable, nonabrasive and nonflammable.
- Mild 9.3 to 9.5 pH.

PART NO.	NET WEIGHT	QTY.
6527	20 oz.	12



SIMPLE GREEN® APPLICATIONS & DILUTIONS CHART

DILUTIONS: L - LIGHT [up to 150 parts water] • M - MEDIUM [30 to 100 pts. water] • H - HEAVY [1:1 up to 20 pts. water]

APPLICATION	SIMPLE GREEN®	CRYSTAL SIMPLE GREEN®
Aluminum	H	H-M
Automotive Exteriors	M	M
Buses & Vans	M	M-L
Car Wash - Automated	M	M-L
Carbon deposits	H	H
Carpets: General *1	M	M-L
Spot cleaning *2	H	H-M
Chrome	M	M-L
Computers: Cases	M	M
Screens	L	L
Concrete	H	H
Decks: Metal	H	H-M
Wooden	H	H-M
Diesel fuel	H	H
Dip tanks & Parts Washers	H	H
Engine degreasing	H	H-M
Fiberglass	H	H-M
Floor scrubbers	M	M
Floors: Concrete	H	H-M
No-Wax	M	M
Stripping Wax *3	H	H
Garbage receptacles	H	H
General cleaning	M	M-L

APPLICATION	SIMPLE GREEN®	CRYSTAL SIMPLE GREEN®
Glass & Mirrors	L	L
Grease filters & Traps	H	H-M
Grout	H	H-M
Kitchens: counters, walls, floors, appliances	H	H-M
Laundry: Full load *4	H	H
Spot cleaning *1	H	H
Pre-wash/soak	H	H-M
Lights	L	L
Lubricants - Machinery grease, oils	H	H-M
Machinery	H	H-M
Manufacturing - Equipment	H	H-M
Motors	H	H-M
Oil deposits	H	H-M
Paint preparation	H	H-M
Pressure sprayers	M	M-L
Showers, Tubs & Tile	H	H-M
Smoke & Soot	H	H-M
Sports equipment	M	M-L
Toilets	M	M-L
Tumblers	H	H-M
Upholstery *1	M	M-L
Vents	H	H-M
Windows	L	L

APPLICATION NOTES:

* 1 - Always spot test for colorfastness in an inconspicuous area first.

* 2 - Spot test as above. Dampen area to be cleaned with clean water. Apply Simple Green or Crystal Simple Green and let sit for 1 to 2 minutes. Agitate if necessary but don't "scrub". Wipe up with clean cloth and water

* 3 - Wet floor with hot water. Apply Simple Green or Crystal Simple Green. Let stand for several minutes and then rinse with hot water.

* 4 - Pour 1/4 cup of full strength Simple Green or Crystal Simple green into a full load of laundry and reduce normal detergent by 1/2.

ALWAYS READ PRODUCT LABELS BEFORE USE..

L13



CHEMICALS & PAINTS

GLASS CLEANERS

IMPERIAL® HEAVY-DUTY GLASS CLEANER

- Heavy-duty, fast foaming glass cleaner quickly cuts through the toughest dirt.
- No run foaming feature makes this product ideal for use on vertical surfaces.
- Contains ammonia for a beautiful streak-free shine.
- Easily dissolves smudges, film, bugs and all types of dirt.
- Methylene chloride free.

PART No.	NET WEIGHT	QTY.
6540	19 oz.	12
6540-1	19 oz.	6



SPRAYWAY® AMMONIATED GLASS CLEANER

- Superior spray provides uniform coverage with a clinging foam.
- Loosens soils on contact and holds them even on a vertical surface.
- Fast-drying, film-free formula.
- Contains ammonia, does not haze or stream.

PART No.	NET WEIGHT	QTY.
85550	19 oz.	12



IMPERIAL® GLASS CLEANER

- Non-ammoniated formula, safe to use on tinted windows.
- Easily dissolves road film, road salt, bugs and other residues.

PART No.	NET WEIGHT	QTY.
4640	1 gallon	2
4740	16 oz. trigger bottle	12
2640	16 oz. empty trigger bottle	4



SPRAYWAY® NON-AMMONIATED GLASS CLEANER

- Non-ammoniated formula.
- Cleans glass, windows, mirrors, windshields, enamel, chrome, tile, porcelain and other hard surfaces.
- Dissolves dirt, grease, grit and grime.
- Heavy-duty formula clings to vertical surfaces.
- Will not leave a film.

PART No.	NET WEIGHT	QTY.
6640	19 oz.	12



IMPERIAL® CITRUS GLASS CLEANER

- Heavy-duty, non runny, foaming formula great for vertical surfaces.
- Easily removes smudges, film, bugs and all types of dirt.
- Provides a streak-free shine.
- Pleasant citrus smell.

PART No.	NET WEIGHT	QTY.
6541	18.75 oz.	12
6541-1	18.75 oz.	6



PERMATEX® NO TOUCH AUTO GLASS STRIPPER/CLEANER

- Heavy-duty cleaner specially formulated for auto windshields.
- Removes silicone build up, hard water stains, mud, oil, bugs and tar.
- Primary applications: cars, trucks, vans, RVs, buses and semi-trucks

PART No.	NET WEIGHT	QTY.
4607	8 oz. bottle	12



L14



*Greg
Dedicated Service Advisor*

Creative...

"Sometimes you've got several options you can pursue. My customers love it. A little out-of-the box thinking."

**Imperial
continuously
adds new
products.**



ELECTRICAL PROTECTORS & CLEANERS

IMPERIAL® NON-CHLORINATED BATTERY PROTECTOR

- 1, 1, 1 trichloroethane free.
- Prevents corrosion and extends battery life.
- Assures maximum electrical conductivity.
- Provides an air-tight, waterproof seal.
- Resists oil, gasoline, dirt, grease and heat.
- Methylene chloride free.

PART No.	NET WEIGHT	QTY.
6528	12 oz.	12
6528-1	12 oz.	6



IMPERIAL® CONTACT CLEANER – FLAMMABLE

- CA/OTC approved, low VOC formula.
- Excellent precision product that removes contaminants from electrical/electronic components.
- Helps to prevent contact failure or malfunction.
- Quick-drying formula leaves no residue and is safe on most plastics.
- Ideal for applications where lower flash point solvents may be used.
- Not for use on energized equipment.

PART No.	NET WEIGHT	QTY.
4689	1 quart	8
4789	16 oz. trigger bottle	12
2689	16 oz. empty trigger bottle	4



B'LASTER® CONTACT CLEANER – NONFLAMMABLE

- Non-chlorinated
- Safe to use on most plastics.
- Highly dielectric, improves conductivity.
- Dries instantly and leaves no residue or odor.
- Ideal for fragile circuits, disc drives and optical gear.

PART No.	NET WEIGHT	QTY.
6597	12 oz.	12
6597-1	12 oz.	6
4697-4	128 oz.	4



SPRAYWAY® ELECTRONIC CONTACT CLEANER

- Excellent precision product that removes contaminants from electrical/electronic components.
- Helps to prevent contact failure or malfunction.
- Quick-drying formula leaves no residue and is safe on most plastics.
- Use with lower flash point solvents.
- Not for use on energized equipment.
- Flammable

PART No.	NET WEIGHT	QTY.
6589	13.5 oz.	12



IMPERIAL® BATTERY CLEANER

- Quickly removes corrosion from battery terminals, casing, cable connectors and retainer frames.
- Special formulation turns red on contact with battery acid.
- Prolongs the life of the battery and improves conductivity.
- Restores battery to full capacity and assures rated voltage output.
- Penetrates and lifts out dirt, oil, grease and road grime.
- Methylene chloride free.

PART No.	NET WEIGHT	QTY.
6515	12-3/4 oz.	12
6515-1	12-3/4 oz.	6



IMPERIAL® BATTERY CLEANER

- CA/OTC approved, low VOC formula.
- Quickly removes corrosion from battery terminals, casing, cable connectors and retainer frames.
- Special formulation turns red on contact with battery acid.
- Prolongs the life of the battery and improves conductivity.
- Restores battery to full capacity and assures rated voltage output.
- Penetrates and lifts out dirt, oil, grease and road grime.

PART No.	NET WEIGHT	QTY.
4615	1 gallon	2
4715	16 oz. trigger bottle	12
2615	16 oz. empty trigger bottle	4



BATTERY COTE

- Protects terminals against corrosion and seals against water, oils and corrosive acids.
- Easy brush-on applicator.
- Can be used on all electrical connections.

PART No.	NET WEIGHT	QTY.
7610	8 oz. brush top	1



ACID SPILL ABSORBER AND NEUTRALIZER

- Absorbs and neutralizes battery acid, with color change to show when acid is neutralized and safe for disposal.
- Safe and non-hazardous.
- Sweep up and dry, not dusty like kitty litter (clay).
- Durable, easy to store container with re-sealable lid.

PART No.	SIZE	QTY.
7687	1 pint jar, 1 lb contents	2



SPRAYWAY® RED INSULATING VARNISH

- An insulating spray for general coating, impregnating and insulating electrical and electronic work.
- Excellent adhesion to metals, windings and coils.
- Air dries faster than most insulating materials.
- Protects surfaces against oils, moisture, acid and alkalis.
- Perfect for small field and magnet coil; penetrates oil and new winding; has excellent flexibility and water resistance.
- Dielectric strength: 2,100 volts
- Appearance: Red
- Dry heat resistance: 310° F

PART No.	NET WEIGHT	QTY.
6638	15.25 oz.	12



RUST PROTECTORS

IMPERIAL® RUST INHIBITOR

- Protects up to two years.
- Stops rust and corrosion.
- Provides non-sling lubrication.
- Non-flammable propellant.
- Self-healing, waxy film.
- Provides anti-seize coating.
- Safe to use on rubber, fabric, plastic and paints.
- Not CA/OTC compliant.

PART NO.	NET WEIGHT	QTY.
6545 ★	11.75 oz.	12
6545-1 ★	11.75 oz.	6



CORROSION X® HEAVY DUTY PENETRANT

- This high performance, thick-film version provides a super long-term protection against rust.
- Specifically developed to provide maximum protection against moisture intrusion and resulting rust and corrosion.
- Forms a drip less, dynamic, non-hardening, self-healing film that stubbornly resists erosion by splash or spray, including complete submersion in saltwater.
- Slowly penetrates existing rust and corrosion, remove moisture and stop electrolysis, while sealing out moisture.
- Unlike wax-based coatings, it will not dry out, stiffen or crack under stress.

PART NO.	NET WEIGHT	QTY.
6596	12 oz.	12



IMPERIAL® RUST CONVERTER

- A converter treatment that neutralizes existing rust and acts as a smooth long lasting primer on both rusted metal and previously painted surfaces.
- It can be sanded, top coated, body puttied or left as is.
- Non-flammable, low VOC.
- Water-based formula.
- Sprays on white, then dries to a long lasting black protective coating.

PART NO.	NET WEIGHT	QTY.
4673	1 quart	8



CORROSION X® PENETRANT AND LUBRICANT

- Penetrates faster and further than other penetrants through rust and corrosion.
- Lubricates under heavy loads and high temperatures.
- Frees parts, bearings and valves that are seized.
- Wicking formula crawls up bold threads and rivet shanks.
- Prevents and stops corrosion, as well as displaces moisture, salt crystals and other corrosion-causing electrolytes.
- Creates a self-healing, dielectric film.
- Electronically safe. Will not short sensitive circuits or interfere with electrical connections.
- Cleans contact points and improves connectivity.
- Prevents and eliminates battery terminal corrosion.

PART NO.	NET WEIGHT	QTY.
6593	12 oz.	12
6594	6 oz.	12



PERMATEX® RUST TREATMENT

- Provides one-step rust treatment that destroys old rust, prevents new rust.
- Just brush or spray on. Within minutes, rust is replaced by a durable black polymer coating that may be painted.
- Excellent protective primer.
- Specially formulated to be used with body filler and fiberglass.
- Used when temperature is between 50° F and 90° F (10° C and 32° C) and on surfaces which do not exceed 200° F (93° C).

PART NO.	NET WEIGHT	QTY.
6573	10.25 oz.	12
6573-1	10.25 oz.	6



B'LASTER® CORROSION BLOCK

- Water-resistant spray grease.
- Protects metal from corrosion.
- Leaves a protective film on the applied surface.
- Also great for winterization, batteries, trim-pump, water pumps, exhaust manifolds, antique tractors, locks and padlocks, bike chains and clogs, etc.

PART NO.	NET WEIGHT	QTY.
6599	16 oz.	6



L16

All first time chemical product orders from Imperial include MSDS for maintaining OSHA Compliance.

View MSDS 24/7 on our website at www.imperialsupplies.com



*Dave
Product Trainer*

Detailed...

"Good enough isn't enough, you've got to get it right."



AIR TOOL CHEMICALS

B'LLASTER® AIR TOOL CONDITIONER

- Restores near factory original power and RPMs.
- Breaks loose deposits that create friction and impede smooth operation.
- Thoroughly cleans internal tool parts.
- Protects tools from freezing down to -25° F.
- Created specifically for use on all types and makes of air tools.

PART No.	NET WEIGHT	QTY.
6546	11 oz.	12
6546-1	11 oz.	6



MARVEL® AIR TOOL OIL

- Specially designed for piston-type and rotary air tools.
- Lubricates for smooth starting, longer tool life.
- Prevents rust formation, dissolves sludge.
- Use daily, several times a day, when tool use is frequent.

PART No.	NET WEIGHT	QTY.
7605	32 oz.	1
7585	4 oz.	4



B'LLASTER® AIR TOOL LUBRICANT

- Enhanced, low-viscosity, non-detergent lubricating oil.
- Manufactured with premium quality paraffinic-based oil that gives the product a high degree of oxidation resistance and lubricity.
- Lubricates, removes moisture and prevents rust all at the same time, giving air tools their maximum performance, by preventing unnecessary service.

PART No.	NET WEIGHT	QTY.
7638	12 oz.	12
4638-4	1 gallon	4



Imperial offers a complete line of Personal Protective Equipment Products.

CUTTING OILS

IMPERIAL® CUTTING OIL AEROSOL

- Greatly extends cutting tool life while speeding the cutting process.
- Ideal for all types of drilling, tapping, reaming, sawing and threading operations.
- Specially formulated reinforced cutting compound clings to exact work area.
- Virtually eliminates friction-heat, galling and seizing.
- Excellent for use on all metals.
- Methylene chloride free.

PART No.	NET WEIGHT	QTY.
6513	11.75 oz.	12
6513-1	11.75 oz.	6



IMPERIAL® CUTTING OIL LIQUID

- Extends cutting tool life while speeding the cutting process.
- Helps eliminate friction heat, galling and seizing.
- For use on drill bits, taps, reamers and other cutting tools.

PART No.	NET WEIGHT	QTY.
7636	4 oz.	2



See section I1-3 for Sabre® Drill Bits.

VINYL, LEATHER, & RUBBER DRESSINGS

IMPERIAL® VINYL PROTECTOR

- CA/OTC approved, low VOC formula.
- Contains UV inhibitors to extend the life of vinyl and rubber.
- Contains anti-static agents to help repel dust and dirt.
- Will not crack vinyl or turn yellow with repeat use.

PART No.	SIZE	QTY.
4629	1 gallon	2
4729	16 oz. trigger bottle	12
2629	16 oz. empty trigger bottle	4



PROTECTOR – VINYL, LEATHER & RUBBER DRESSING

- Ready-to-use silicone based formula.
- Protects vinyl, leather and rubber against cracking and drying out.
- Makes surfaces anti-static.
- Non-flammable and non-corrosive.
- For use with Chemical Resistant Trigger Sprayer, Part No. 2598.

PART No.	NET WEIGHT	QTY.
8512	32 oz.	12
85510-4	1 gallon	4



VEHICLE DETAILING

DAKOTA SHINE AEROSOL KIT

- Restores color, luster and value to faded and oxidized surfaces like paint, decals, plastics and more. Contains no silicone.
- Ready-to-use. Less waste and no disposal requirements.
- Consists of agricultural by-products and other ingredients; designed to penetrate the surface to rejuvenate the pigments to their original appearance.
- Cost-effective substitute to repainting oxidized surfaces or replacing faded decals.
- Compatible Surfaces: painted surfaces, decals/vinyl lettering, plastics, fiberglass, engine compartments.

KIT CONTAINS:

- » (1) 16 oz. aerosol can of Dakota Shine
- » (1) 16 oz. trigger bottle of Dakota Prep
- » (2) pads

PART NO.	NET WEIGHT	QTY.
5662	1 kit	1



UPHOLSTERY CLEANER & PROTECTANT

- Powerful cleaning action and gentle on your hands.
- Works on leather, cloth, vinyl and carpets in your auto, office or home.
- Contains no harsh solvents or chemicals, leaving a clean, fresh smell.
- Will not leave a chemical ring around the cleaned area.
- Removes odors, grease, smoke film and other tough stains with ease.
- Eliminates pet stains/odors and food odors.
- Can be used with an extractor/steam cleaner.

PART NO.	NET WEIGHT	QTY.
6647	16 oz.	12



MAGIC MIST - SHOWROOM SHINE

- Removes dust, fingerprints, smudges, bugs and other contaminants from painted and/or glass surfaces.
- Produces a flawless showroom shine without strenuous buffing and waxing.
- Will not scratch or streak.
- Use on painted surfaces, glass, chrome, mirrors and more.
- Works on glass TV screens and glass computer screens while producing a barrier from static electricity and dust.
- Will continually bead water and repel dust.

PART NO.	NET WEIGHT	QTY.
6648	16 oz.	12



SILVER BRITEPLUS MX ALUMINUM CLEANER

- Proven cleaner for polished aluminum and stainless trailers, tankers, polished wheels and tanks.
- Formulated from safe, effective and environmentally-friendly agriculture products.
- Professional cleaning results.
- Easy to use. Cost effective.

PART NO.	NET WEIGHT	QTY.
85534	2.5 gallon	1



BRITEPLUS MX ALUMINUM CLEANER

- Proven cleaner for tough jobs like over-the-road trailers, engine compartments, SUV wheels and vans.
- Designed for cleaning stained or oxidized aluminum and older stainless steel.
- Formulated from safe, effective and environmentally-friendly agricultural products.
- Professional cleaning results.
- Easy to apply and user safe. Cost effective.

PART NO.	NET WEIGHT	QTY.
85535	2.5 gallon	1



GLASS WIPES

- Removes road grime and film on glass.
- Streak-free formula.
- Ammonia free formula.
- Store in glove compartment, door pocket and center console.
- Snap lock lid to keep wipes fresh longer.

PART NO.	DESCRIPTION	SIZE	QTY.
4045	27 wipes	7" x 9"	1



PROTECTANT WIPES

- Protects and shines plastic, rubber and vinyl surfaces.
- UV protection, protects surface from discoloration and fading.
- Soft pack has a snap lock lid to keep the wipes moist longer.
- Lint free.

PART NO.	DESCRIPTION	SIZE	QTY.
4039	27 wipes	7" x 9"	1



CLEANING WIPES

- Cleans upholstery, plastic, vinyl and dashboards.
- Safe to use on most automotive surfaces.
- Cleans dust, dirt and grime.
- Snap lock lid to keep the wipes moist longer.
- Lint free.

PART NO.	DESCRIPTION	SIZE	QTY.
4038	27 wipes	7" x 9"	1



L18



*Kelli
Dedicated Service Advisor*

Accessible...

"I'm more than just a person on the phone. I'm an advocate. My customers know me, and they know I'll come through."



VEHICLE DETAILING

B'LLASTER® CONCENTRATED TIRE CLEANER

- Effective cleaner on rubber, vinyl, canvas, walls, floors, leather and more.
- Rejuvenates faded tire with unsurpassed cleaning power.
- Can be used to clean boat bilges and teak decks.
- Water-based formula.

PART NO.	NET WEIGHT	QTY.
5504	16 oz.	12



IMPERIAL® BUG & TAR REMOVER

- Concentrated cleaner that removes bugs and tar.
- Safe on all finishes.

PART NO.	NET WEIGHT	QTY.
4605	1 gallon	2



SPRAYWAY® FOAMING RUG & UPHOLSTERY CLEANER

- Use in any setting where rugs and upholstery requires deep cleaning.
- Releases ground-in dirt from rugs, carpets, and upholstery including velour.
- Perfect for spot-cleaning, spills and spot pickup.
- Not for use on silk upholstery.
- Clean fresh scent.

PART NO.	NET WEIGHT	QTY.
85548	19 oz.	12



SPRAYWAY® FURNITURE POLISH

- Designed for industrial and commercial use on wood and other surfaces that require special care.
- Dusts, cleans and polishes in one step.
- Removes stains, smudges and fingerprints.
- Protects fine furniture, woodwork, formica, plastic, chrome, marble, porcelain and leather.
- Contains lemon oil.

PART NO.	NET WEIGHT	QTY.
85549	19 oz.	12



SPRAYWAY® AUTO CARE INSTANT SHINE

- Instant shine, non-silicone spray.
- Creates a high finish on rubber, plastic, vinyl and most other surfaces.
- Designed for ease of use in all applications it shines and protects against weathering without the use of silicone.
- Body shop friendly.
- High gloss shine.
- No paint contamination.

PART NO.	NET WEIGHT	QTY.
6635	11 oz.	12



ARM & HAMMER® FABRIC & CARPET DEODORIZER

- Odors caused by pets, food, cigarette or cigar smoke are completely neutralized.
- Neutralize odors at their source, unlike products that only mask smells.
- All fabric surfaces can be deodorized including seats, door panels, headliners, upholstery, carpet, floor mats and truck liners.
- Odors are eliminated without leaving a residue or making fabric wet.
- Environmentally safe and user-friendly.

PART NO.	NET WEIGHT	QTY.
85519	15 oz.	6



ARM & HAMMER® DEODORIZING AIR FRESHENER

- Absorbs odors with the power of baking soda.
- Has a light fresh scent.
- Eliminates odors caused by germs and smoke.

PART NO.	NET WEIGHT	QTY.
85551	7 oz.	12



SPRAYWAY® INSTANT DETAIL CLEANER AND POLISH

- A quick detail touch up spray for use between waxes to maintain a showroom quality shine.
- Gentle enough to use everyday and safe for all paint types.
- Lightly mist and wipe to remove harmful contaminants, fingerprints, water spots and surface dirt will maintaining a glossy shine.
- Color: Off White
- Fragrance: Fruity

PART NO.	NET WEIGHT	QTY.
6644	16 oz.	12



SPRAYWAY® INSTANT DETAIL WAX

- Quick method for adding a showroom quality shine.
- Wax entire vehicle in minutes with protection, water beading and shine that lasts for weeks.
- No buffing needed. Will not leave residue on your finish.
- Apply a light mist to the clean surface of your vehicle.
- Wipe with a dry, clean towel or micro fiber.

PART NO.	NET WEIGHT	QTY.
6645	16 oz.	12



SPRAYWAY® INSTANT SHINE SILICONE BASED

- A final detail product designed and specially formulated for the auto detailing professional.
- Just spray on and buff off or let dry for a like new shine.
- Use to spruce up vinyl interiors, bumpers, bumper guards, body moldings, door jambs, engine compartments and hard to reach air conditioner ducts.

PART NO.	NET WEIGHT	QTY.
6646	11 oz.	12



L19



VEHICLE DETAILING

3M™ ROCKER PANEL SPRAY

- For aerosol application over acrylic lacquer top-coats or under acrylic lacquer or enamel color coats.
- **Do not apply over OEM or factory paint finishes.**
- Designed to match fine to medium textures on stone throw areas of automobiles.
- Color: Clear
- Cure time: 15 minutes
- Paint time: 30 minutes

PART NO.	NET WEIGHT	QTY.
6632	18 oz.	12



TURTLE WAX® 1-STEP WAX & DRY

- The quickest and easiest way to a high gloss Turtle Wax® shine, just spray and dry.
- Provides all the shine and protection of a traditional wax in a fraction of the time.
- Formulated with a blend of carnauba wax and protective polymers for a maximum shine and protection.

PART NO.	NET WEIGHT	QTY.
5648	26 oz.	6



TURTLE WAX® RUBBING COMPOUND PASTE

- A heavy duty paste that cleans dull, oxidized finishes.
- Helps remove scratches and blemishes.

PART NO.	SIZE	QTY.
5650	10.5 oz.	6



SALT ERASER®

- A revolutionary new product that removes stubborn salt stains from any fabric quickly and effortlessly – without scrubbing.
- Penetrates the fiber deeply while breaking up and evaporating the salt within minutes of application.
- Safely eliminates salt from floor mats, carpets, rugs and runners. It cleans, freshens and revitalizes complete car interiors without any odor.
- This product is great for applications such as cloth seats, rugs, carpet, shoes and pants.

PART NO.	NET WEIGHT	QTY.
6555	12 oz.	6



3M® SUPER DUTY RUBBING COMPOUND

- Aggressive compound.
- Remains wet on the job with little or no mess.
- Maintains high rate of cut with constant pressure.
- Buffs to high gloss with minimal swirl marks.
- Can be used by hand or machine.

PART NO.	NET WEIGHT	QTY.
5592	1 gallon	4



CHEWING GUM REMOVER WITH "FREEZE ACTION"

- Use in auto-detailing shops and commercial or industrial situations.
- Removes gummy substances, candle wax, and putty with minimum effort.
- The "freeze action" feature hardens the gummy substance to easily remove from carpeting, fabrics or hard surfaces.
- Leaves no residue.

PART NO.	NET WEIGHT	QTY.
85528	7 oz.	12



TURTLE WAX® POLISHING COMPOUND

- Pre-softened paste that instantly shines new life and color into dull faded finishes.
- Quickly and safely removes oxidized pigment, heavy road film, dirt and stains.
- Goes on smoothly, contains no harsh abrasives.
- Cleans all painted metal, chrome and porcelain surfaces.

PART NO.	SIZE	QTY.
5657	10.5 oz.	6



RIGHT STUFF® CITRUS DEGREASER

- Natural orange terpenes.
- Contains no petroleum distillates.
- Biodegradable.
- Citrus fragrance.
- Used to remove decals, tar, tire marks, chewing gum, adhesives and printing inks.
- Good spot remover, drain cleaner and degreaser.
- USDA - C1 rating.
- Must order Trigger Sprayers separately, Part No. 2598.

PART NO.	NET WEIGHT	QTY.
5527	22 fl oz.	12



TURTLE WAX® SUPER HARD SHELL PASTE

- Legendary super hard shell protection leaves a lasting Turtle Wax® shine.
- Easy on and easy off formula lasts up to 12 months.

PART NO.	NET WEIGHT	QTY.
5649	14 oz.	6



MISCELLANEOUS

B'BLASTER® SMALL ENGINE MAINTENANCE KIT

- Preventative maintenance for 2 or 4 cycle equipment.
- Cleans the fuel system of deposits, restoring performance.
- Cleans and conditions three critical engine systems: ignition, fuel and lubrication.
- Kit includes:
 - » Fuel System Cleaner And Conditioner
 - » Small Engine Tune-Up, Engine Oil Conditioner
 - » Dielectric Tune-Up Grease
 - » Thread Lube and Anti-Seize



PART No.	QTY.
409-1	1 kit

B'BLASTER® SMALL ENGINE TUNE-UP

- Starts and keeps all 2 and 4 cycle engines in tune.
- Restores power and compression. Frees rings and valves.
- Helps prevent vapor lock and stalling.
- Conditions gas during layover periods.
- Removes moisture and smooths engine performance.
- Removes carbon, gum and varnish deposits that can cause engine failure.
- Primary applications: small engines, outboard engines, generators, compressors, welders, pumps, chain saws, tractors, etc



PART No.	NET WEIGHT	QTY.
6531	11 oz.	12
6531-1	11 oz.	6

GUNK® CARBURETOR CHOKE & VALVE PARTS CLEANER

- Dissolves dirt, varnish, gum and deposits.
- Use with carbureted vehicles and equipment
- Chlorinated.
- Clear, Transparent.
- Boiling Point: 102° F
- Specific Gravity: 1.12
- VOC Content: 44%



PART No.	NET WEIGHT	QTY.
6562	12.5 oz.	12



Ray
Sales Trainer

Reliable...

"Continual product and sales training gives our Dedicated Service Advisors the expertise our customers value."

IMPERIAL® A/C COIL CLEANER & DEODORIZER

- Quickly and easily clears foul odors from vehicles air/heat duct systems and interiors.
- Cleans and neutralizes a variety of foul odors including odors from mold, mildew and algae.
- Controls stale odors.
- Non-toxic.



PART No.	NET WEIGHT	QTY.
6586	11.75 oz.	12
6586-1	11.75 oz.	6

IMPERIAL® RUBBERIZED UNDERCOAT

- Deadens sound and protects against corrosion.
- Displaces water.
- Remains flexible and stretches to provide longer protection.



PART No.	NET WEIGHT	QTY.
6525	15.5 oz.	12
6525-1	15.5 oz.	6

SPRAYWAY® C1 PENETRATING COIL CLEANER

- Features a delayed foaming action that allows the non-acid, non-chlorinated formula to attack dirt, grime, soil deposits and contaminants on the evaporators and condenser coils.
- Dual quad formula deodorizes coils and drain pans.
- For use on: HVAC units, fan blades, auto radiators, refrigeration systems, small air cooled equipment, metal filters
- Powerful pin-point spray.
- Fresh citrus scent.



PART No.	NET WEIGHT	QTY.
6560	19 oz.	12
6560-1	19 oz.	6

RESCUE 911® MULTI PURPOSE LEAK SEALER

- Stops small leaks on almost any surface instantly.
- Flexible, waterproof and weather-resistant.
- Resists cracking, freezing, peeling or sagging.
- Seals out rust and corrosion.
- One can covers approximately 20 square feet.



PART No.	NET WEIGHT	QTY.
6583	18 oz.	12

STOP GAP® MINIMAL EXPANDING INSULATING FOAM

- Fill cracks and gaps to form an airtight and waterproof bond.
- Dries tack free in 15 minutes, cures in eight hours.
- Can be applied at temperatures between 60° F and 100° F.
- Cured product can be trimmed, shaped, sanded, painted or stained.
- Can be applied on: metal, wood, masonry, glass and most plastics.



PART No.	NET WEIGHT	QTY.
6575	12 oz.	8



MISCELLANEOUS

CLAIRE® WASP AND HORNET KILLER

- Rapid contact kill and rapid knockdown wasp, hornet and yellow jackets.
- Contains Tetramethrins and other ingredients that stop pests in flight.
- Long-range spray allows killing these insects while standing up to 20 feet above the ground away from their nests.
- Together with the instant knock down effect, this prevents the chances of being stung by attacking insects.
- A powerful blast valve allows rapid delivery and saturation of nests.
- Indoor or outdoor use, with blaster valve and long-range spray.
- Primary applications: garages, walls, chimneys, utility poles and outdoor lighting

PART NO.	NET WEIGHT	QTY.
6567	14 oz.	12
6567-1	14 oz.	6



SPRAYON® INSECT REPELLENT II

- Effectively repels mosquitoes, chiggers, ticks, deer flies, stable flies, black flies, gnats and fleas.
- Also protects against Lyme disease.
- Does not contain R-11.
- EPA registered.
- Apply to skin or clothing.

PART NO.	NET WEIGHT	QTY.
6628	6 oz.	12



PERMATEX® BELT DRESSING

- Extends the life of the belt.
- Penetrates the cord fibers of V belts to restore pliability and flexibility.
- Prevents belt slippage due to heat, cold, dampness, dust and glazing.
- Eliminates squeaking and slipping.

PART NO.	CROSS REFERENCE	NET WEIGHT	QTY.
9180	80073	12 oz.	12



SPRAYWAY® CLEAN JET 100

- Compact, portable source of ultra-clean gas for precision removal of particles.
- Non-flammable, high-pressure spray.
- Safe to use on all electronic energized equipment.

PART NO.	NET WEIGHT	QTY.
6587	10 oz.	12



3M™ WOOD GRAIN AND STRIPE REMOVER

- For removing wood grain vinyl and vinyl stripes from acrylic enamel surfaces.
- Jelly-like consistency keeps remover in place on vertical surfaces to promote fast action when sprayed from the aerosol can.

PART NO.	NET WEIGHT	QTY.
6649	1 lb 2 oz.	6



IMPERIAL® LIQUID DE-ICER

- Melts frost and ice on all types of surfaces.
- For use on locks, headlights, wiper blades, doors and windshields.
- Helps prevent fogging when applied on the inside of a window.

PART NO.	NET WEIGHT	QTY.
4711	16 oz.	12



SPRAYWAY® DE-ICER

- Melts ice and frost quickly and easily from locks, wipers, windows, windshields or headlights.
- Apply before freezing weather is expected to prevent frozen windshields and locks.
- This spray will not harm a vehicle's finish.

PART NO.	NET WEIGHT	QTY.
6588	16 oz.	12
6588-1	16 oz.	6



NON-SLIP COATINGS WITH GRIT

- Protects against slipping accidents.
- USDA accepted.
- Helps meet OSHA requirements.
- No solvent odor.
- Fast cure.
- Non-flammable, water-borne coating.
- Can be used on concrete, wood and metal surfaces.
- Covers 100-150 square feet per gallon.

PART NO.	COLOR	NET WEIGHT	QTY.
5617	Black	1 gallon	2
5616	Gray	1 gallon	2



GOOP® ANTI-SKID EPOXY AEROSOL

- Provides a hard, flat, textured finish that helps avoid slip and fall accidents.
- Lead free. Chemical, gas and oil resistant.
- Use indoors and outdoors.
- Ideal for areas where water is present or slippery conditions exist.
- Can be used on properly prepared wood, concrete, metal, fiberglass, tile, porcelain and many more surfaces.
- Dry to touch: 10 to 20 minutes at 77° F
- Application temperature: 50° F to 90° F
- Recoat: approximately 1 hour
- Coverage: up to 15 square feet per can
- Primary applications: stairs, walkways, porches, decks, ladders, play equipment, boats, trailers, ramps, patios, basement or garage floors, forklift loading docks, handicapped areas

PART NO.	COLOR	NET WEIGHT	QTY.
6641	Clear	11 oz.	6
6642	White	11 oz.	6
6643	Black	11 oz.	6



DISPENSING & ACCESSORIES

CHEMICAL DISPENSING SYSTEM

- Single Product Proportioning/Diluting System.
- One product bucket fill station with remote bucket fill pistol grip.
- Flow rate of four gallons per minute.
- On/Off button is on the pistol grip handle, for spill proof dispensing.
- Connects to a standard garden hose.
- CAUTION: Cannot be used with hot or high pressure water

PART No.	DESCRIPTION	QTY.
85619	Dilution Dispensing System	1
85621	Top Mounting Rack	1
85622	Locking Wire Rack	1



DILUTION DISPENSING SYSTEM

- Eight-product capacity with four dial settings for bottle and four dial settings for bucket fill.
- No assembly required.
- Simply mount dispenser to the wall and hook up water and chemical lines.
- Rolled steel cover with powder-coated finish.
- One-hand bottle fill.
- 16 different dilution rates.
- Remote bucket fill pistol grip.
- Large labeling surface.
- Short installation time.
- Includes instruction sheet for dilution ratios and installation.

PART No.	DESCRIPTION	QTY.
85620	Dilution Dispensing System	1
85621	Top Mounting Rack	1
85622	Locking Wire Rack	1



CONTAINER WITH FAUCET

- Heavy-duty plastic.
- User friendly for easy filling and pouring.
- 16"L x 10"H x 5"W
- 63 mm angled front opening for filling.
- Includes faucet with 38 mm opening.
- Excellent option for bulk ready-to-use chemicals and refilling of trigger bottles.

PART No.	DESCRIPTION	SIZE	QTY.
70334-7	Container	2-1/2 gal	1
3843	Faucet Nozzle	38mm	5
3844	Push Tap Nozzle	38mm	5
3853	PVC Nozzle (PB Blaster)	38mm	1




IMPERIAL® TRIGGER BOTTLE & SPRAYERS

PART No.	SIZE	QTY.
70300	Chemical Resistant Bottle	1
2598	Chemical Resistant Sprayer	5
2604	Trigger Sprayer for 16 oz. Bottles	2



Applicator Filling Instructions:

1. Fill container with one quart of chemicals. This will be 2/3 full.*
2. Charge with shop air. Chemical applicator is then ready to use.



*NOTE: A convenient check method is to carefully lie the can on its side with the handle down. The can is 2/3 full when the chemical is level with the hole and no chemical spills out the can's opening.

IMPERIAL® APPLICATORS

- Black enamel coated steel applicator.
- Customize your own environmentally-safe aerosols at a fraction of the cost of ready-mades.
- Uses air-safe, clean air, not CFCs or other potentially dangerous propellants.
- Pre-labeled canisters for convenience and safety.
- Not for use with water-based chemicals or paint.
- Chemicals not included.
- Nozzle adjusts from stream to spray.
- Shop air is used to charge and recharge can.



PART No.	DESCRIPTION	LABEL PART No.	NET WEIGHT	QTY.
3852	Penetrating Oil	4600	32 oz.	1
3857	4-Way Penetrant	4601	32 oz.	1
3869	Silicone Lube	4630	32 oz.	1
3860	Brake Parts Cleaner II	4637	32 oz.	1
3880	Penetrating Lube w/PTFE	4602	32 oz.	1
3883	All-Purpose Cleaner	4617	32 oz.	1
3884	Vinyl Protector	4629	32 oz.	1
3885	Degreaser	4635-4	32 oz.	1
3888	Chain Lube	4666	32 oz.	1

STEEL APPLICATOR ACCESSORIES

PART No.	DESCRIPTION	USE WITH PART No.	QTY.
3864	Adjustable Plastic Nozzle	All Imperial applicators	1
3865	Replacement Hex Filler Cap	All Imperial applicators	1
3866	Replacement Bar Type Filler Cap	All Imperial applicators	1
3868	Valve Repair Kit	All Imperial applicators	1
3848	Repair Kit for Canister Valve	All Imperial applicators	1
3849	Repair Kit for Nozzle Attachment	All Imperial applicators	1
3873	Pin Stream Extension	3839, All Imperial applicators	1
3841	Regular Spray Nozzle	3839 3860	1
3840	Coarse Spray Nozzle	3839, 3860	1
3839	Steel Applicator Valve Seat Adaptor	3873, All Imperial applicators	1
3854	Mixing Balls	7608, 3850	5

NOZZLE KIT

PART No.	DESCRIPTION	QTY.
3851	(1) Extra Fine Spray (1) Fine Spray (1) Coarse Spray (1) Flat Spray Plastic Nozzle	1 Kit



BRUSH OR DAUBER TOP CANS

- Sturdy, chemical-resistant aluminum can.
- High quality bristle brush or dauber.
- Tight-fitting, lined screw caps make cans leakproof.

PART No.	SIZE	QTY.
3994	4 oz. can with brush top	10
3996	4 oz. can with dauber	10



CHEMICALS & PAINTS

SPRAY ADHESIVES

IMPERIAL® WEB TRIM ADHESIVE

- Superior resistance to moisture, high temperatures and water.
- Non-chlorinated and non-staining formula.
- Three different spray patterns to choose from.

PART NO.	NET WEIGHT	QTY.
6585	11.25 oz.	12
6585-1	11.25 oz.	6



3M™ SUPER TRIM ADHESIVE

- Aerosol contact adhesive designed for bonding vinyl tops, heavyweight liners and hood silencer pads where high strength and heat resistance are needed.
- Color: Yellow

PART NO.	CROSS REFERENCE	NET WEIGHT	QTY.
7525	08090	19 oz.	6



PERMATEX® ALL PURPOSE SPRAY ADHESIVE

- For permanent or repositioning applications.
- Dries clear with superior bonding strength.
- Unique formula resists water and humidity.
- Works with porous and non-porous materials.

PART NO.	CROSS REFERENCE	NET WEIGHT	QTY.
9133	82019	11 oz.	12
9133-1	82019	11 oz.	6



3M™ GENERAL PURPOSE ADHESIVE CLEANER

- Specially blended solvent for removal of light paint over spray, adhesive residue, wax, grease, tree sap, dirt, road tar, oil and bugs in aerosol form.
- Will not harm most thoroughly cured automotive paint, vinyls or fabrics when properly used.

PART NO.	CROSS REFERENCE	NET WEIGHT	QTY.
7524	08987	15 oz.	12



PERMATEX® HEAVY DUTY HEADLINER & CARPET ADHESIVE

- High strength spray adhesive for repairing interior parts.
- Bonds to fabrics, foam, plastics, rubber and other automotive materials.
- Resistant to weather conditions.
- Water resistant, clear formula (when dry).
- Primary applications: headliners, carpets, truck linings and inside door panels


PART NO.	CROSS REFERENCE	NET WEIGHT	QTY.
9134	27828	16.75 oz.	6



3M™ GENERAL PURPOSE ADHESIVE CLEANER

- Specially blended solvent for easy cleanup of most types of adhesives, bugs, greases and oils, over spray, silicone, waxes and tars.
- Will not harm most thoroughly cured automotive paint, vinyl or fabrics when properly used.

PART NO.	CROSS REFERENCE	NET WEIGHT	QTY.
85553	08984	1 quart	6



L24



*Ron
Dedicated Service Advisor*

Involved...

"I know my customers well. I understand their businesses and their needs. It helps me do the job better."

**Imperial continuously
adds new products.**

**See section K for a large
selection of Safety Products.**



ADDITIVES

IMPERIAL® DIESEL FUEL ADDITIVE WITH ANTI GEL

- Proprietary blend specifically formulated to control the growth of wax crystals which can form during cold weather operation in both low sulfur and ultra low sulfur diesel.
- Dramatically reduces the cold flow pour point of the fuel to flow through filters at much lower temperatures.
- Offers protection of metals throughout the fuel distribution system.
- Enhances stability to reduce fuel oxidation.
- Shows no negative impact on diesel fuel and motor oil.
- 32 oz. will treat up to 100 gallons of diesel fuel.

PART No.	NET WEIGHT	QTY.
5536	32 fl oz.	6



IMPERIAL® GASOLINE FUEL ANTIFREEZE

- Ties up water in the fuel so it can pass through the engine in very small amounts.
- In cold and damp environments, water can contaminate gas storage tanks. It is not necessarily condensation that affects gasoline, it can also be attributed to direct water contamination from leaking fill caps.
- Heavier than gasoline and water. When added to the fuel in the gasoline tank, it binds to water in the fuel system and allows it to pass freely through combustion process.
- 16 fl oz. will treat up to 22 gallons of gasoline.

PART No.	NET WEIGHT	QTY.
5556	16 fl oz.	6



HEET® ALL SEASON DIESEL FLO

- Helps prevent gelling at sub-zero temperatures.
- Helps stabilize fuel water disbursement.
- Keeps injectors clean.
- Prevents filter icing and waxing.
- 12 oz. bottle treats up to 20 gallons of diesel fuel.
- **May vary under certain conditions (see label).**

PART No.	NET WEIGHT	QTY.
5511	12 oz.	12



HEET® GAS-LINE ANTIFREEZE

- Helps prevent gas-line freeze up.
- Aids in cold weather starts by preventing frozen fuel lines.
- Keeps fuel system clear of gum condensation and corrosion.
- Can be used in fuel-injected and carbureted engines.
- Safe for catalytic converters and oxygen sensors.

PART No.	NET WEIGHT	QTY.
5506	12 oz.	24



CRC® DIESEL FUEL CONDITIONER WITH ANTI-GEL

- Re-liquifies gelled fuel, stabilizes fuel and cleans injectors.
- 12 oz. bottle treats:
 - » Pre-existing gelled fuel up to 18 gallons.
 - » Preventative for gelling up to 35 gallons.
- 30 oz. bottle treats:
 - » Pre-existing gelled fuel up to 50 gallons.
 - » Preventative for gelling up to 125 gallons.
- Lowers pour point of diesel as much as 27° F.
- Disperses water and contains no harmful alcohol.
- Lubricates upper cylinders.

PART No.	NET WEIGHT	QTY.
5523	12 oz.	12
5524	30 oz.	12



ISO-HEET® FUEL SYSTEM DRYER AND ANTIFREEZE

- Removes water to prevent gas line freeze-ups.
- Absorbs five times more water than regular gas-line antifreeze.

PART No.	NET WEIGHT	QTY.
5512	12 oz.	24



CRC® QUICK FLOW EMERGENCY DIESEL FUEL GEL RELIEF

- Quickly dissolves gelled diesel fuel.
- Thaws frozen fuel filters.
- Contains anti-gel, which protects against gelling.

PART No.	NET WEIGHT	QTY.
5522	30 oz.	12



JOHNSEN'S® PREMIUM STARTING FLUID

- 50% ether blend.
- Helps start stubborn engines fast in cold weather.
- Saves batteries and contains an upper cylinder lubricant.

PART No.	NET WEIGHT	QTY.
6580	7.2 oz.	12
6680	10.7 oz.	12



ADDITIVES

IMPERIAL® FUEL TANK ADDITIVE

- Premium fuel tank additive (concentrated detergent formula) that aids in preventing and elimination of harmful deposits from building up in your fuel tank, fuel pump filter, intake valves and fuel injectors or carburetor.
- Restores performance lost due to carbon build up in the gasoline engines of passenger cars and light duty trucks.
- Improves fuel economy: 2% due to valve deposits and up to 15% due to fuel injector deposits

PART NO.	SIZE	QTY.
5541	16 fl oz.	6



IMPERIAL® TRANSMISSION CONDITIONER

- Formulated to extend the life of transmission fluid.
- Efficient way of softening seals and O-rings to prevent leaks.
- Prevents of oxidation and deposits which can lead to transmission wear and breakdowns.
- Can be used with all automatic transmission fluids, including high temperature and heavy load applications.

PART NO.	SIZE	QTY.
5539	16 fl oz.	6



GOLD EAGLE® FUEL INJECTOR CLEANER

- Keeps injectors clean and corrosion free.
- Helps stop hard starting, rough idling and stalling.
- Dissolves gum and varnish.
- Absorbs water to prevent fuel line freeze up.
- 8 oz. treats up to 15 gallons.

PART NO.	NET WEIGHT	QTY.
5508	8 oz.	12



IMPERIAL® RADIATOR CONDITIONER

- Radiator conditioner is formulated to combat and maintain the essential additives in antifreeze that deplete over time.
- Acts as a water pump lubricant/conditioner.
- Replaces the depleted inhibitors, but also adds a long lasting alkaline reserve to the coolant.
- Protects the interior radiator system and parts from corrosion.
- Stops cooling system rust, scale and corrosion.

PART NO.	SIZE	QTY.
5538	16 fl oz.	6



B'LASTER® FUEL INJECTOR CLEANER

- Cleans and conditions fuel injectors, fuel pumps and fuel systems.
- Feed ports and tips become clean, lubricated, in balance and clog free.
- Fuel Injector cleaner/system conditioner.
- Super concentrated - 1 bottle treats 2 tankfuls.
- Allows moisture to be burned off.
- Lubricates, conditions and coats.
- Restores lost power, improves performance and mileage.
- Removes harmful carbon and varnish deposits from upper cylinders, manifolds, exhausts and converters.

PART NO.	NET WEIGHT	QTY.
5530	15.5 oz.	12



IMPERIAL® RADIATOR FLUSH

- Radiator Flush is a safe and effective cleaning solution for radiators.
- Helps loosen and removes tough organic deposits that result from oil, fouling, grease and glycol oxidations residues.
- Does not contain harsh residues.
- Safe for use on all cooling system components.
- Use in both diesel and gasoline engines.

PART NO.	SIZE	QTY.
5537	16 fl oz.	6



DYNATEX® TRANSMISSION ASSEMBLY LUBE

- Specially formulated for use as an assembly lubricant for automatic and manual transmissions.
- Remains stable and smooth at working temperatures, soluble in transmission fluids and will not clog transmission filters.
- Apply to bearings, seals, O-rings, gaskets, bushings, sealing rings, thrust washers and hydraulic seals.
- Blue color eliminates misdiagnosing leaks.

PART NO.	SIZE	QTY.
6620	1 lb tub	1



B'LASTER TRANS VALVE FIX

- Instantly boosts compression in all combustion and diesel engines.
- Add to crankcase oil to clean and lubricate piston rings.
- Stops sludge, varnish and carbon build-up providing cleaner, cooler running engines.
- Multi-purpose cleaner and friction reducer.
- Reduces wear, extends transmission life.
- Removes harmful carbon and varnish deposits.
- Rejuvenates seals, stops leaks and restores performance to sluggish transmissions.

PART NO.	NET WEIGHT	QTY.
5503	15.5 fl oz.	12



JOHNSEN'S® AUTOMATIC TRANSMISSION FLUID

- Multi-Purpose Automatic Transmission Fluid.
- Used for "topping-off" applications.

PART NO.	NET WEIGHT	QTY.
5507	12 oz.	12



If you can't find the products you are looking for, call us, and we will find it for you.



ADDITIVES

IMPERIAL® AIR BRAKE ANTI-FREEZE & CONDITIONER

- Protects all air brake systems and helps to prevent freezing.
- Removes moisture from the air brake system.
- Contains a lubricant and rust inhibitor that provides excellent lubricating characteristic.
- Can be used year-round for maximum protection.

PART No.	SIZE	QTY.
5557	32 fl oz.	6



IMPERIAL® ENGINE OIL SUPPLEMENT

- Prevents motor oil from thickening at high temperatures and extreme pressures.
- EP additive fortifies high quality motor oil by preventing sludge and varnish from forming.
- EP additive keeps hydraulic lifters and other engine components clean to ensure optimum engine performance.
- Improves bearing life.
- Adds lubrication protection.
- Improves fuel efficiency.

PART No.	SIZE	QTY.
5543	16 fl oz.	6



SILOO® AIR BRAKE CONDITIONER

- Provides complete winter protection for air brake systems.
- Eliminates and prevents moisture accumulation and icing.
- Prevents damage to air brake seals.
- Anti-freeze and anti-rust formula.
- Compatible with all brake systems.

PART No.	NET WEIGHT	QTY.
5514	32 fl oz.	12



IMPERIAL® POWER STEERING CONDITIONER

- Specially formulated to provide maximum protection to power steering fluid and increase optimal performance.
- A number of additives (anti-foam agents, corrosion inhibitors, anti-oxidants, friction modifiers and dispersants) help to reduce system wear and stop squeals.
- Formulated to help prevent power steering unit leaks, provide smooth operation and eliminate squealing.

PART No.	SIZE	QTY.
5542	16 fl oz.	6



JOHNSEN'S® HEAVY DUTY DOT 3 BRAKE FLUID

- Minimum boiling point of 450° F.
- Meets and exceeds DOT 3 and all other Federal and SAE specifications and standards for motor vehicle brake fluids.
- Mixes with all DOT 3 approved brake fluids.
- Designed for use in disc, drum and ABS brake systems.

PART No.	NET WEIGHT	QTY.
5532	12 fl oz.	12



GOLD EAGLE® POWER STEERING FLUID

- Compatible with all power steering fluids.
- Protects seals and hoses; and stops squeaks.
- Meets service requirements of GM, Ford, Chrysler and most imports.
- Guards against wear and slippage.

PART No.	NET WEIGHT	QTY.
5509	12 fl oz.	12



JOHNSEN'S® PREMIUM DOT 4 BRAKE FLUID

- Premium quality brake fluid that contains special ingredients to guard against vapor lock and moisture absorption.
- Exceeds requirements for both DOT 3 and DOT 4 brake fluids.

PART No.	NET WEIGHT	QTY.
5518	12 fl oz.	12



JOHNSEN'S WINDSHIELD WASHER CONCENTRATE

- Cleans windshields and prevents freezing to -25° F.
- Dilution: Cleaner: 1 oz. per each quart of water
 - » 2 oz. Solvent, Protects to 27° F
 - » 4 oz. Solvent, Protects to 20° F
 - » 6 oz. Solvent, Protects to 13° F
 - » 8 oz. Solvent, Protects to 5° F
 - » 10 oz. Solvent, Protects to 4° F

PART No.	NET WEIGHT	QTY.
5521 ★	12 fl oz.	12

★ Not CA/OTC Compliant



IMPERIAL® TRAILER/DOLLY BRAKE LINE DE-ICER

- Contains isopropyl alcohol.
- Use as a last resort to remove ice from air lines and valves.
- Use in the Service (Blue)/Emergency (Red) lines only.
- Use 3-4 ounces per use.
- Does not contain methanol.

PART No.	SIZE	QTY.
5618	32 fl oz.	8



JOHNSEN'S WINDSHIELD WASHER CONCENTRATE

- CA compliant.
- Cleans windshields and prevents freezing to -25° F.
- Add (1) 12 oz. bottle per gallon of water.

PART No.	NET WEIGHT	QTY.
5519	12 oz.	12



L27



TIRE MOUNTING PRODUCTS

REMA TIP TOP® TIRE MOUNTING LIQUID LUBRICANT

- Bead Butter Blue, concentrate.
- For mounting tubeless tires or natural and synthetic tubes.
- Rust inhibitor added for rim protection.
- Makes tire mounting/dismounting faster and easier.
- Lubricates all rubber parts, stops rubber squeaks.
- Will not affect aluminium, brass, magnesium or alloy rims.
- Ideal for lubricating bead seaters.

PART No.	NET WEIGHT	QTY.
5599	1 gallon	4



BLACK ICE TIRE MOUNTING LUBRICANT

- Black-Ice Stop Rust Rim Release Lubricant.
- Lubricates rim and tire for easy mounting and demounting.
- Protects against rust and corrosion.
- Prevents rim and bead from bonding.

PART No.	NET WEIGHT	QTY.
5607	25 lb	1



REMA TIP TOP® PRE-BUFF CLEANER

- For cleaning inner liner of tire around injury.
- Dissolves mold-release lubricants.
- Creates a clean surface for tire repair.
- Also great for crayon marks and grease or oil smears.

PART No.	NET WEIGHT	QTY.
73941	32 oz.	12



FREYLUBE® NO RIM RUST® PREMA TIRE LUBRICANT & RUST RETARDANT

- Single, ready-to-use, multi-purpose product for tire mounting, dismounting and protection of the rim or wheel against rust.
- Won't evaporate or harden, ensuring long shelf life.
- Recommended by fleet owners and major tire and wheel manufacturers for use on steel and aluminum wheels.
- Designed for a wide temperature range (-40° F to 275° F) helping to prevent tires from fusing to rim.

PART No.	NET WEIGHT	QTY.
5596	25 lb	1



RU-GLYDE® TIRE MOUNTING & RUBBER LUBRICANT

- Lubricates tires for mounting and demounting.
- Protects beads against scuffing during mounting.
- Assures proper bead seating on rim.
- Protects against tire slippage after mounting.
- Removes rubber squeaks in bushings and grommets.

PART No.	NET WEIGHT	QTY.
5584	1 gallon	4



FREYLUBE® EZ-ON TIRE LUBE APPLICATOR

- Will keep your hands clean.
- Applies a thin, even coat to provide superior coverage without waste.
- Contoured to fit the shape of the rim or wheel for easy, time-saving application.

PART No.	QTY.
85577	1



L28

TIRE MOUNTING PASTE BRUSH

- Apply paste, compound or liquid products without waste or mess.
- Head: 2"
- 45° handle.

PART No.	QTY.
85589	1



See Page K5 for
Green Nitrile Gloves.



Bill
Dedicated Service Advisor

Connected...

"The fleet industry doesn't stand still. It's changing all the time, and I enjoy that."



BRAKE PRODUCTS

PERMATEX® DISC BRAKE QUIET

- Stops brake squeal by dampening vibration at caliper/brake pad interface.
- Provides tighter fit and allows for easier disassembly.
- Protects against corrosion.
- Compatible with anti-lock brake systems.

PART No.	CROSS REFERENCE	NET WEIGHT	QTY.
9109	80077	9 oz.	12



PERMATEX® ULTRA DISC BRAKE CALIPER LUBE

- An environmentally-friendly green, non melting synthetic lubricant.
- Prevents disc brakes from squealing.
- Prevents long bolt and sleeve seizing and galling.
- Outperforms ordinary caliper greases and traditional disc brake quite.
- Non-silicone, non-petroleum based formula.

PART No.	CROSS REFERENCE	NET WEIGHT	QTY.
9110	24110	8 oz. brush top	1



PERMATEX® EXTREME CERAMIC BRAKE PARTS LUBE

- Silences brake noise for the life of the pads and shoes.
- Resists corrosion, dirt, salt and water. Will not wash away.
- Resists extreme temperatures from -65° F to 2,800° F.
- 100% Synthetic formula, no silicones or petroleum.
- Applications: Long and short bolts, sleeves, bushings, outboard pad backing plate, inboard pad backing plate, disc brake calipers, caliper pins and pistons


PART No.	CROSS REFERENCE	NET WEIGHT	QTY.
9116	24125	8 oz. brush top	1



DYNATEX® BRAKE SYSTEM SILICONE COMPOUND

- Contains no petroleum or by-products and will not attack rubber.
- An excellent release agent and lubricant for rubber and plastic parts, such as O-rings, valves and plastic gears.
- Locks out moisture and has excellent wash-away resistance.
- Temperature range from -40° F to 500° F.
- Extends brake system life and stops disc brake squeal, prevents drying and cracking.

PART No.	SIZE	QTY.
7555	5.3 oz. tube	1



3M™ BRAKE LUBE/ANTI-SEIZE COPPER

- Silences brake noise for the life of the pads and shoes.
- Resists corrosion, dirt, salt and water.
- A premium grade lubricant designed to prevent the seizure of close fitting metal parts.

PART No.	CROSS REFERENCE	NET WEIGHT	QTY.
9141	08945	9 oz. brush top	6



3M™ SILICONE PASTE

- A non-melting, water resistant, 100% solids, silicone compound designed to protect surfaces from oxidation.
- Use as a general purpose lubricant for brakes (metal to rubber applications); great for O-rings and weather stripping.

PART No.	CROSS REFERENCE	NET WEIGHT	QTY.
9142	08946	8 oz. brush top	6



CRC® DISC BRAKE QUIET

- Red paste forms a water resistant, high-temperature film that absorbs noise while quieting squeaks and squeals.
- Specially formulated to dampen the vibrations that cause brake noise.
- For use on the back of non-shimmed disc pads.
- Primary applications: backing plates, brake pad contact points, disc brake pads
- Non-flammable.

PART No.	NET WEIGHT	QTY.
9113	4 oz.	12



Experience our dedicated customer service.

L29



Stacy
Dedicated Service Advisor

Willing...

"Vehicles that are down in the shop aren't making money. I'll do whatever it takes to get them back on the road."



GREASES

LUBRIPLATE® LITHIUM COMPLEX MULTI-PURPOSE GREASE

- NLGI 2 grease which provides high film strength, excellent shear stability, long lubricant life and exceptional anti-wear properties.
- For a variety of industrial, automotive, construction or mining applications in adverse conditions.

PART NO.	NET WEIGHT	QTY.
7673	14.5 oz. cartridge	10



BIO-BASED MOLY EP GREASE

- Bio-based grease that is manufactured from renewable vegetable based stocks which have a natural higher viscosity index. Meaning that bio-based oil is less likely to thin at higher temperatures.
- NLGI grade: 2
- Appearance and odor: Silver to black grease with characteristic vegetable oil odor

PART NO.	NET WEIGHT	QTY.
6630	14 oz.	10



PENNZOIL® 705 MULTI-PURPOSE WHITE GREASE

- Lithium based grease which contains rust and corrosion inhibitors.
- Whitening agent allows differentiation from other products and easy detection of contaminants.
- Minimum change in consistency.
- Saves on inventory investment because it covers a wide range of applications.
- USDA H-2 listed.

PART NO.	NET WEIGHT	QTY.
7690	14 oz.	10



JET LUBE® FOOD MACHINERY GREASE

- USDA H-1 authorized for use in federally inspected meat and poultry plants.
- Premium aluminum complex based grease with polymer additives.
- Will not pound out of bearings and bushings during shock loads.
- Contains bacteriostatic agents to fight bacteria and fungus growth.
- Extremely water-resistant grease.
- Service rating: 0° F to 400° F

PART NO.	NET WEIGHT	QTY.
6603	14 oz. cartridge	30



CHEVRON® ULTRA DUTY GREASE EP

- High shock load and load carrying protection.
- High corrosion and rust protection (passed the ASTM D 1743 bearing corrosion test).
- Less frequent regreasing.
- Water resistant.
- NLGI grades: 0, 1 and 2
- Used for operating in water, mud or dusty conditions.

PART NO.	NET WEIGHT	QTY.
6601	14 oz. cartridge	10



ULTRA-LUBE® GENERAL PURPOSE LITHIUM GREASE

- Versatile, extremely stable grease.
- Designed for light duty applications requiring long grease life.
- Highly water resistant.
- NLGI grade 2 smooth, buttery consistency.
- Ideal for automatic dispensing systems.

PART NO.	NET WEIGHT	QTY.
6600	14 oz. cartridge	10



L30

CHEVRON® DELO® HD EP2 GREASE

- Technically advanced, extreme pressure grease.
- Temperature Range: 0°F to 350°F
- Primary applications: highway trucks, heavy duty trucks, wheel bearing and chassis applications including steering drag links, king pins, transmission cross shaft spring pins, shackle pins, brake cam shafts and fifth wheel faceplates and pivots
- Off highway trucks: haul trucks, loaders, tractors, cherry pickers
- Medium- and light-duty trucks and buses: Class 7 and Class 6 vehicles requiring extreme duty greases

PART NO.	NET WEIGHT	COLOR	QTY.
6627	14 oz.	Red	10



*Jason
Dedicated Service Advisor*

Focused...

"Knowing the everyday issues and demands of the guys in the maintenance shop. That's my job."



GREASES

DYNATEX® WHITE LITHIUM GREASE

- General purpose lubricant, protects against rust and corrosion.
- Reduces wear to equipment and increases service life.
- Can be used on door, hood and truck latches.
- Hinges and compartment springs, seats, regulators and tracks, wiper mechanisms, brake parts and distributors cams.
- Meets USDA specifications.
- NLGI grade - 2.

PART No.	SIZE	QTY.
6629	1 lb tub	1



SIL-GLYDE LUBRICATING COMPOUND

- Long lasting, high film strength lubricant for all surfaces including: rubber, metal, wood and glass.
- Weatherproofs and performs from -20°F to +500°F.
- Will not drip off like silicone oils.
- Silicone base.
- Primary applications: truck seals, window channels, hood strips and pads, rubber gaskets and belts

PART No.	NET WEIGHT	QTY.
7514	8 oz. tube	2



LUBRIPLATE® WHEEL BEARING GREASE

- A superior, long lasting, water resistant, extreme pressure, wheel bearing grease.
- NLGI GC-LB certified.

PART No.	NET WEIGHT	QTY.
7674	16 oz. tub	1



DYNATEX® WHITE LITHIUM GREASE

- General purpose lubricant.
- Protects against rust and corrosion.
- USDA approved H2.

PART No.	SIZE	QTY.
7595	1.5 oz. tube	4



PENNZOIL® 707L WHEEL BEARING GREASE

- A high temperature, NLGI Grade 2, lithium complex grease which contains high quality petroleum base oils.
- Operating temperature: 375° F intermittent to 450° F
- Resists washout and flows readily at cold temperatures.
- Exceeds NLGI GC-LB specifications.
- Increased rust, corrosion and oxidation protection.
- USDA approved H2.

PART No.	NET WEIGHT	QTY.
6606	1 lb tub	1



BIO-BASED DISC/DRUM BRAKE WHEEL BEARING GREASE

- Bio-based wheel bearing grease is manufactured from renewable vegetable based stocks which have a naturally higher viscosity index. Meaning that bio-based oil is less likely to thin down at higher temperatures.
- NLGI grade: 2 GC-LB
- Amber grease with characteristic vegetable oil odor

PART No.	NET WEIGHT	QTY.
6631	1 lb tub	1



LUBRIPLATE® NO. 105 MOTOR ASSEMBLY GREASE

- Provides lubrication during the initial start up before the motor oil has circulated.
- Protects freshly machined engine parts from rust and corrosion.

PART No.	NET WEIGHT	QTY.
7671	10 oz. tube	4



All first time chemical product orders from Imperial include MSDS for maintaining OSHA Compliance.

View MSDS 24/7 on our website at www.imperialsupplies.com



*Ryan
IT Support Specialist*

Committed...

"My job is to make the ordering process fast, simple and accurate. Our customers expect it, and I make it happen."



MEDIUM STRENGTH THREADLOCKERS

THREADLOCKER USE CHART

PRODUCT	COLOR	SIZE FASTENER TO USE ON	TORQUE IN LBS. BREAK/PREVAL	CURE FIXTURE/FULL	FIXTURE WITH PRIMER	TEMPERATURE RANGE	USE /COMMON APPLICATIONS
Medium Strength Threadlocker	Blue	1/4" to 3/4" (6-20 mm)	115/53	20 min./24 hours	5 min.	-65°F to °F	Applied before assembly for oil pans; bolts; case cover bolts; shift lever nuts; alternator mounts; intake manifold; valve cover and disc brake caliper bolts.
Permanent Strength Threadlocker	Red	3/8" to 1" (10-25 mm)	168/150	20 min./24 hours	5 min.	-6°F to °F	Applied before assembly of air tools, cylinders block bolts, ring bearing bolts, transmission shaft bolts.
High Strength Threadlocker	Red	3/8" to 1" (10-25 mm)	230/225	20 min./24 hours	5 min.	-65°F to 300°F	Applied before assembly for threaded and slip fit joints on cylinder block and rocker arm studs; shock absorber bolts; ring gear bolts; frame bolts.
Penetrating Grade Threadlocker	Green	#2 to 1/2" (2.2-12 mm)	90/310	20 min./24 hours	3 min.	-65°F to 300°F	Applied AFTER assembly for carb adjustment screws; distributor bolts; pre-assembled nuts and bolts; set screws.

IMPERIAL® MEDIUM STRENGTH THREADLOCKER

- Medium strength threadlocker compound.
- Locks and seals small diameter threaded parts.
- Prevents nuts and bolts from vibrating loose.
- Seals out rust and corrosion.
- Parts can be disassembled with a screwdriver or wrench.

PART NO.	CROSS REFERENCE	COLOR	NET WEIGHT	QTY.
9101 ★	24200	Blue	6 ml tube	2
9500	—	Blue	35 ml bottle	4
9500-1	—	Blue	35 ml bottle	1

★ Permatex Brand



DYNATEX® BOLTLOCKER™ MEDIUM STRENGTH THREADLOCKER COMPOUND

- Fills gaps up to .006".
- Applied prior to assembly.
- Eliminates need for stocking lock nuts and lock washers.
- Can be removed without special tool.

PART NO.	NET WEIGHT	COLOR	QTY.
7546	6 ml bottle	Blue	2
7547	24 ml bottle	Blue	2



PERMATEX® MEDIUM STRENGTH THREADLOCKER GEL

- Gel Twist pin-point applicator puts the threadlocker where you want it.
- No more dripping threadlocker.
- Great for putting threadlocker on female threads.
- Provides "liquid quality" reliability without problems from liquids or sticks.



PART NO.	CROSS REFERENCE	COLOR	NET WEIGHT	QTY.
9100	24010	Blue	.35 oz.	1

PERMATEX® MEDIUM STRENGTH THREAD LOCKER SQUEEZE TUBE

- Gel thread locker in a convenient squeeze tube.
- Allows for easy overhead and vertical applications.
- Accurate dispensing eliminates waste and clean up.

PART NO.	CROSS REFERENCE	COLOR	NET WEIGHT	QTY.
9108	24005	Blue	.20 oz.	1



PERMATEX® MEDIUM STRENGTH OIL RESISTANT THREADLOCKER

- General purpose medium strength threadlocker with improved oil tolerance.
- For fasteners between 1/4" and 3/4" diameters.
- Temperature range: -65° F to 300° F

PART NO.	CROSS REFERENCE	COLOR	NET WEIGHT	QTY.
9136	24310	Blue	10 ml bottle	2
9137	24350	Blue	50 ml bottle	1



PERMATEX® COUNTERMAN'S CHOICE MEDIUM STRENGTH THREADLOCKER

- Single-use chemicals that deliver just the right amount of material for typical automotive repair jobs.
- Convenient single-use pouches feature an Easy Squeeze Spout with a tapered channel to provide for more accurate dispensing of compounds while minimizing waste and mess.
- Apply to nuts and bolts 1/4" to 3/4".
- Blue: Medium Strength, All Purpose

PART NO.	COLOR	NET WEIGHT	QTY.
9144	Blue	1 ml pouch	24



PERMATEX® HYDRAULIC THREAD SEALANT

- Fast curing, low strength anaerobic sealant, which seals hydraulic and pneumatic fittings up to 2" in diameter
- Resists high pressure and vibration loosening.
- Hydraulic Sealant, in its liquid state, readily disperses in liquid hydraulic fluid and is virtually non-fouling in all types of hydraulic systems.
- The adhesive/sealant contains no fillers or particles and will not foul valves or screens.
- Cure: Let harden a minimum of 30 minutes before applying pressure.
- Pressure resistance: Seals up to 3,000 psi after 4 hour room temperature cure. Seals to burst pressure rating of pipe after a 24 hour room temperature cure.
- Temperature range: -65° F to 300° F, -54° C to 149° C
- **This product is not recommended for use on plastic piping. May attack some thermoplastics.**

PART NO.	CROSS REFERENCE	COLOR	NET WEIGHT	QTY.
9126	54540	Purple	36 ml bottle	1



HIGH STRENGTH THREADLOCKERS

THREADLOCKER USE CHART

PRODUCT	COLOR	SIZE FASTENER TO USE ON	TORQUE IN LBS. BREAK/PREVAL	CURE FIXTURE/FULL	FIXTURE WITH PRIMER	TEMPERATURE RANGE	USE /COMMON APPLICATIONS
Medium Strength Threadlocker	Blue	1/4" to 3/4" (6-20 mm)	115/53	20 min./24 hours	5 min.	-65°F to °F	Applied before assembly for oil pans; bolts; case cover bolts; shift lever nuts; alternator mounts; intake manifold; valve cover and disc brake caliper bolts.
Permanent Strength Threadlocker	Red	3/8" to 1" (10-25 mm)	168/150	20 min./24 hours	5 min.	-6°F to °F	Applied before assembly of air tools, cylinders block bolts, ring bearing bolts, transmission shaft bolts.
High Strength Threadlocker	Red	3/8" to 1" (10-25 mm)	230/225	20 min./24 hours	5 min.	-65°F to 300°F	Applied before assembly for threaded and slip fit joints on cylinder block and rocker arm studs; shock absorber bolts; ring gear bolts; frame bolts.
Penetrating Grade Threadlocker	Green	#2 to 1/2" (2.2-12 mm)	90/310	20 min./24 hours	3 min.	-65°F to 300°F	Applied AFTER assembly for carb adjustment screws; distributor bolts; pre-assembled nuts and bolts; set screws.

IMPERIAL® HEAVY-DUTY THREADLOCKER

- High strength threadlocker compound.
- Locks and seals large diameter threaded parts.
- Prevents studs and bolts from vibrating loose.
- Seals out rust and corrosion.
- Disassembly of parts may require extra effort.

PART NO.	CROSS REFERENCE	COLOR	NET WEIGHT	QTY.
9103 ★	27100	Red	6 ml tube	2
9502	—	Red	35 ml bottle	4
9502-1	—	Red	35 ml bottle	1

★ Permatex Brand



PERMATEX® PERMANENT STRENGTH THREADLOCKER

- A permanent high strength product that is applied to fasteners 3/8" to 1" (10 to 27 mm) in size before assembly.
- Designed for securing parts that must withstand heavy shock, vibration, extreme chemical or environmental conditions.
- Localized heating and hand tools are required to separate parts.

PART NO.	CROSS REFERENCE	COLOR	NET WEIGHT	QTY.
9104	26250	Red	50 ml bottle	4
9104-1	26250	Red	50 ml bottle	1
9198	26210	Red	10 ml bottle	1



DYNATEX® BOLTLOCKER™ HIGH STRENGTH THREADLOCKER COMPOUND

- Fills gaps up to .008".
- Applied prior to assembly.
- Locks and seals metal threaded assemblies where high strength is required.
- Protects against thread corrosion.

PART NO.	COLOR	NET WEIGHT	QTY.
7543	Red	6 ml bottle	2
7544	Red	24 ml bottle	2



PERMATEX® COUNTERMAN'S CHOICE HIGH STRENGTH THREADLOCKER

- Single-use chemicals that deliver just the right amount of material for typical automotive repair jobs.
- Convenient single-use pouches feature an "Easy Squeeze Spout" with a tapered channel to provide for more accurate dispensing of compounds while minimizing waste and mess.
- High strength, permanent.
- Apply to fasteners 3/8" to 1".

PART NO.	COLOR	SIZE	QTY.
9145	Red	1 ml pouch	24



PERMATEX® HIGH STRENGTH THREADLOCKER GEL

- Gel Twist pin-point applicator puts the threadlocker where you want it.
- No more dripping threadlocker.
- Great for putting threadlocker on female threads.
- Provides "liquid quality" reliability without problems from liquids or sticks.

PART NO.	CROSS REFERENCE	COLOR	NET WEIGHT	QTY.
9102	27010	Red	.35 oz.	1



PERMATEX® HIGH STRENGTH THREAD LOCKER SQUEEZE TUBE RED

- Gel thread locker in a convenient squeeze tube.
- Allows for easy overhead and vertical applications.
- Accurate dispensing eliminates waste and clean up.

PART NO.	CROSS REFERENCE	COLOR	NET WEIGHT	QTY.
9111	27005	Red	.20 oz.	1



PERMATEX® SURFACE PREP ACTIVATOR

- Long lasting solvent-based aerosol primer.
- Decreases set-up time of threadlockers and increases breakaway torque on most fastener surfaces.
- Allows cold weather applications.
- Certified to NSF/ANSI Standard 61.

PART NO.	CROSS REFERENCE	NET WEIGHT	QTY.
9138	24163	4.5 oz. aerosol	1



Imperial continuously adds new products.



GREEN MEDIUM STRENGTH THREADLOCKERS

THREADLOCKER USE CHART

PRODUCT	COLOR	SIZE FASTENER TO USE ON	TORQUE IN LBS. BREAK/PREVAL	CURE FIXTURE/FULL	FIXTURE WITH PRIMER	TEMPERATURE RANGE	USE /COMMON APPLICATIONS
Medium Strength Threadlocker	Blue	1/4" to 3/4" (6-20 mm)	115/53	20 min./24 hours	5 min.	-65°F to °F	Applied before assembly for oil pans; bolts; case cover bolts; shift lever nuts; alternator mounts; intake manifold; valve cover and disc brake caliper bolts.
Permanent Strength Threadlocker	Red	3/8" to 1" (10-25 mm)	168/150	20 min./24 hours	5 min.	-6°F to °F	Applied before assembly of air tools, cylinders block bolts, ring bearing bolts, transmission shaft bolts.
High Strength Threadlocker	Red	3/8" to 1" (10-25 mm)	230/225	20 min./24 hours	5 min.	-65°F to 300°F	Applied before assembly for threaded and slip fit joints on cylinder block and rocker arm studs; shock absorber bolts; ring gear bolts; frame bolts.
Penetrating Grade Threadlocker	Green	#2 to 1/2" (2.2-12 mm)	90/310	20 min./24 hours	3 min.	-65°F to 300°F	Applied AFTER assembly for carb adjustment screws; distributor bolts; pre-assembled nuts and bolts; set screws.

PERMATEX® MID-STRENGTH WICKING THREADLOCKER

- Formulated for pre-assembled bolts.
- Eliminates bolt removal, wicks in to penetrate bolt threads.
- Fills voids to .005".
- Secures set screws and other adjustable assemblies after settings are completed.
- Removable with hand tools.
- Apply to assembled bolts.

PART No.	COLOR	CROSS REFERENCE	NET WEIGHT	QTY.
9139	Green	29050	50 ml bottle	1



PERMATEX® BEARING MOUNT FOR CLOSE FITS

- Low viscosity, rapid curing anaerobic adhesive that augments the strength of press fit assemblies or slip fit assemblies up to 0.005" in diameter.
- Adds up to 3,000 psi holding power.
- Primary applications: bushings, bearings, oil seals, ring gear bolts, differential lock pins, etc

PART No.	CROSS REFERENCE	COLOR	NET WEIGHT	QTY.
9131	60950	Green	50 ml	1
9132	60925	Green	250 ml	1



DYNATEX® BOLTLOCKER™ MEDIUM STRENGTH WICKING THREADLOCKER

- Fills gaps up to .005".
- Locks and seals metal threads after assembly and adjustments are complete.
- Secures adjustments and sets screws.

PART No.	COLOR	NET WEIGHT	QTY.
7545	Green	24 ml bottle	2



PERMATEX® RETAINING COMPOUND

- High strength, anaerobic adhesive secures slip and press fit assemblies.
- Restores fit to worn or out-of-tolerance assemblies.
- Secures and seals cylinder sleeves, valve guides, valve seals, bearings and bushings, woodruff keys and liner assemblies.
- Requires special tools for removal.
- Use Primer, Part No. 9138 to speed cure.

PART No.	CROSS REFERENCE	COLOR	NET WEIGHT	QTY.
9143	64050	Blue	50 ml bottle	1



L34



James
Distribution Center

Hassle Free...

"We take the hassle out of purchasing small maintenance repair items."

All first time chemical product orders from Imperial include MSDS for maintaining OSHA Compliance.

View MSDS 24/7 on our website at www.imperialsupplies.com



ANTI-SEIZE

PERMATEX® NICKEL ANTI-SEIZE

- This lubricant offers special high temperature protection to 2,600° F.
- Protects metal parts from seizure and galling.
- Recommended for applications requiring protection from corrosive environments.

PART No.	CROSS REFERENCE	NET WEIGHT	QTY.
9195	77164	16 oz. brush top	1



PERMATEX® ANTI-SEIZE

- A highly refined blend of aluminum and graphite lubricants.
- Use during assembly to prevent galling, corrosion and seizing and to assure easier disassembly.
- Temperature range: -60° F to 1,600° F
- Meets MIL-907E specifications.

PART No.	CROSS REFERENCE	NET WEIGHT	QTY.
9179	80078	8 oz. brush top	1
9184	80208	16 oz. brush top	1



DYNATEX® NICKEL ANTI-SEIZE

- Heavy-duty anti-seize and lubricating paste containing a balanced blend of pure nickel and graphite, homogenized into a semi-synthetic, non-melting, grease base.
- Does not contain any sulfur, lead, copper, halogens or clay fillers.
- Protects to 2000° F.
- Prevents galling and seizing.
- Acid resistant and waterproof.

PART No.	NET WEIGHT	QTY.
9583	8 oz.	1



DYNATEX® ANTI-SEIZE & LUBRICATING COMPOUND

- Resists water, salt solutions, most shop and automotive fluids.
- Prevents seizing, fretting, pitting, galling and corrosion.
- Protects against corrosion between dissimilar metals.
- Temperature range: -200° F to 2,000° F
- Meets MIL-907 specifications.

PART No.	NET WEIGHT	QTY.
9576	8 oz. brush top	1
9578	16 oz. brush top	1



DYNATEX® COPPER ANTI-SEIZE

- Prevents seizing, fretting, pitting, galling and corrosion on all types of metal parts at temperatures between -200° F to 2,000° F.
- Extend component's life while increasing high temperature reliability.
- Resists water, salt solution and most shop and automotive fluids.
- Reduces coefficient of friction by a minimum of 20%.
- Protects against corrosion between dissimilar metals.
- Eases assembly and disassembly.
- Meets MIL-907 specifications.

PART No.	NET WEIGHT	QTY.
7568	8 oz. brush top	1



PERMATEX® COUNTERMAN'S CHOICE ANTI SEIZE

- Single-use chemicals that deliver just the right amount of material for typical automotive repair jobs.
- Anti-Seize is a heavy duty blend of aluminum, copper and graphite lubricants in a petroleum base.
- Use during assembly to prevent galling, corrosion and seizing and to assure easier disassembly.

PART No.	NET WEIGHT	QTY.
9147	5 gm pouch	24



Think safety first. Always.
Imperial offers a wide
range of Safety Products.



*Justin
Pricing Analyst*

Driven...

"I understand downtime. I understand what it costs. And I do everything I possibly can to prevent it."

L35



THREAD SEALANTS

IMPERIAL® PIPE SEALANT WITH PTFE

- Stops leaks on threaded metal pipe fittings and hydraulic fittings.
- Seals instantly. Lubricates worn or damaged threads for easier assembly and disassembly.
- Resists corrosive chemicals and gases and will not shred to contaminate systems.
- Seals out rust corrosion and allows adjustments up to 24 hours.
- Primer required on stainless steel or inert metals.
- Cure without primer: partial 12–24 hours; full 48 hours.
- **Not for use on plastic pipes.**

PART NO.	CROSS REFERENCE	NET WEIGHT	QTY.
9520	—	35 ml tube	4
9520-1	—	35 ml tube	1



PERMATEX® PIPE SEALANT WITH PTFE

- General-purpose sealant for tapered and straight/tapered fittings.
- Controlled strength for ease of disassembly.
- Temperature range: -65° F to 300° F
- Seals operating pressures to 10,000 psi.

PART NO.	CROSS REFERENCE	NET WEIGHT	QTY.
9119	59214	6 ml tube	2
9197	56521	50 ml tube	2
9122	59225	250 ml tube	1



DYNATEX® PIPE SEALANT

- Anaerobic sealant chemically cures in the absence of air.
- Prevents leakage and loosening from vibration and moisture in hydraulic, pneumatic, steam and process piping.
- Instant sealing to 200 psi.
- Allows final adjustments up to 24 hours after application.
- Lubricates and resists corrosion.

PART NO.	NET WEIGHT	QTY.
7540	50 ml tube	2



PERMATEX® PIPE JOINT COMPOUND

- Universal sealant. Lubricates and seals threaded joints on water, oil and fuel lines.
- Brush top lid.
- Temperature range: -65° to 300° F

PART NO.	CROSS REFERENCE	NET WEIGHT	QTY.
9191	80045	16 oz. brush top	1



PERMATEX® THREAD SEALANT WITH PTFE

- General purpose sealant with the added lubricity of PTFE for metal pipes.
- Won't shred like PTFE tape.
- Allows easy disassembly.
- Resists common shop fluids.

PART NO.	CROSS REFERENCE	NET WEIGHT	QTY.
9129	80632	4 oz. bottle	2
9130	80633	16 oz. bottle	1



Experience
our dedicated
customer
service.

L36



*Ken
Senior Product Manager*

Preparation...

"To me, it's more than just quality parts. It's a quality team, that is well trained, with knowledge of both our products and our customers."

Cut costs by reducing your vendors. Imperial's Specialty Programs can help.



GASKET MAKER / SEALANTS

DYNATEX® ANAEROBIC GASKET MAKER RED HIGH STRENGTH

- Can replace or be used as a dressing for conventional gaskets.
- Will not shrink due to solvent evaporation.
- Once cured, has an operating temperature range of -65° F to 300° F.
- Can be used on vacuum pump flanges, fuel pumps, gearbox covers, truck axle covers.

PART NO.	NET WEIGHT	QTY.
7542	50 ml tube	2



PERMATEX® GASKET MAKER

- Designed for aluminum, iron and steel.
- After curing between mating metal flanges and filling any surface imperfections, it provides a tough resilient seal that flexes with flange movement.
- Ready to use component gel-like material that cures at room temperature when it is isolated from air contact.
- Outstanding wetting and sealing characteristics have been exhibited on aluminum flanges.
- Authorized by USDA for use in federally inspected meat and poultry plants.
- Temperature range: -55° F to 300° F
- Gap fill: up to 0.010"
- Tensile strength: 500 psi

PART NO.	CROSS REFERENCE	COLOR	NET WEIGHT	QTY.
9158	51813	Red	50 ml tube	4
9158-4	51845	Red	300 ml cartr.	1



PERMATEX® HIGH TACK GASKET SEALANT

- Brush top
- Dries to a highly tacky, non-brittle film.
- Resists gasoline, oil, anti-freeze and axle lube.
- Temperature range: -65° F to 500° F

PART NO.	CROSS REFERENCE	NET WEIGHT	QTY.
9175	80063	16 oz.	1



PERMATEX® FLANGE SEALANT

- Ready to use component gel-like material that cures at room temperature when it is isolated from air contact.
- After curing between mating metal flanges and filling any surface imperfections, it provides a tough resilient seal that flexes with flange movement.
- Making gaskets for pumps, thermostats, compressors, PTO covers, transmission housing, axle covers and split crankcases.
- Coating or dressing spacer gaskets to improve their sealing effectiveness.
- Repairing damaged conventional gaskets.
- Temperature range: -65° F to 300° F
- Gap fill: up to 0.010"
- Tensile strength: 800 psi

PART NO.	CROSS REFERENCE	COLOR	NET WEIGHT	QTY.
9112	51531	Purple	50 ml tube	4



PERMATEX® FORM-A-GASKET NO. 1 SEALANT

- Fast drying, hard setting brown sealant designed for rigid materials and flanges or patching holes and joints where permanent assembly is desired.
- Temperature range: -65° F to 400° F

PART NO.	CROSS REFERENCE	NET WEIGHT	QTY.
9160	80008	3 oz. tube	6



PERMATEX® FORM-A-GASKET NO. 2 SEALANT

- Slow drying, non-hardening black sealant designed for sealing cut gaskets and stamped parts.
- Temperature range: -65° F to 400° F
- Use where sealing is more important than adhesion.

PART NO.	CROSS REFERENCE	NET WEIGHT	QTY.
9161	80010	3 oz. tube	6



DYNATEX® HI-TACK GASKET ADHESIVE/SEALANT

- Versatile spray adhesive seals gaskets.
- Temperature range: -65° F to 450° F
- Dries quickly.

PART NO.	NET WEIGHT	QTY.
7593	9 oz.	12



PERMATEX® AVIATION FORM-A-GASKET NO. 3 SEALANT

- Slow drying, non-hardening brush top sealant.
- For use in aviation and automotive applications.
- Temperature range: -65° F to 400° F

PART NO.	CROSS REFERENCE	NET WEIGHT	QTY.
9159	80019	4 oz. brush top	1



PERMATEX® COPPER SPRAY-A-GASKET

- Fast drying, metallic copper sealant helps dissipate heat, prevent gasket burnout and improve heat transfer.
- Fills minor surface irregularities.
- Seals instantly.
- Temperature range: -50° F to 500° F

PART NO.	CROSS REFERENCE	NET WEIGHT	QTY.
9167	80697	9 oz.	12



PERMATEX® HIGH TACK™ SPRAY-A-GASKET SEALANT AEROSOL

- Sets fast to seal and hold the heaviest of gaskets in place.
- Resist gasoline, oil, kerosene, propane and butane.
- Level 2 extremely flammable.

PART NO.	CROSS REFERENCE	NET WEIGHT	QTY.
9174	80065	9 oz.	12



RTV SILICONES

BLUE RTV SILICONE GASKET MAKER

- Outstanding resistance to oil and joint movement values.
- Eight times more flexible than cork/composite gaskets.
- Three times more oil resistant than conventional silicone.
- Temperature range: -75° F to 500° F intermittent
- Guaranteed not to leak.

PART NO.	BRAND	CROSS REFERENCE	NET WEIGHT	QTY.
7681	Imperial	—	8 oz.	6
9164 ★	Permatex	81724	3.35 oz. tube	6

★ Includes applicator tip



SENSOR SAFE HI-TEMP RED SILICONE GASKET MAKER

- First generation 1970-1980 gasket maker.
- Temperature range: -75° F to 650° F
- Guaranteed not to leak.

PART NO.	BRAND	CROSS REFERENCE	NET WEIGHT	QTY.
7679	Imperial	—	8 oz.	6
9162 ★	Permatex	81160	3 oz. tube	6

★ Includes applicator tip



CLEAR RTV SILICONE GASKET MAKER

- Seals, bonds, repairs, mends and secures glass, metal, plastics, vinyl, weather stripping and vinyl tops.
- Protects electrical wiring.
- Temperature range: -80° F to 450° F
- Resists oil, water, weather, vibration and grease.

PART NO.	BRAND	CROSS REFERENCE	NET WEIGHT	QTY.
7680	Imperial	—	8 oz.	6
9155 ★	Permatex	80050	3 oz. tube	6

★ Includes applicator tip



IMPERIAL® BLACK INSTANT GASKET

- Leak proof gasket in 1 minute.
- Protects against leaks caused by vibration and thermal expansion.
- Temperatures range: -75° F to 450° F

PART NO.	COLOR	NET WEIGHT	QTY.
7677	Black	8 oz.	6



BLACK SILICONE GASKET MAKER

- Designed for domestic engines.
- Meets dealership warranty requirements.
- Fast curing.
- Retains flexibility, oil resistance properties.
- Temperature range: -75° F to 625° F intermittent
- Guaranteed not to leak.

PART NO.	BRAND	CROSS REFERENCE	NET WEIGHT	QTY.
7678	Imperial	—	8 oz.	6
9171 ★	Permatex	82180	3.35 oz. tube	6

★ Includes applicator tip



IMPERIAL® SCHOOL BUS YELLOW SILICONE GASKET MAKER

- Retains flexibility, oil resistance properties.
- Temperature range: -75° F to 500° F
- Fast curing.

PART NO.	BRAND	COLOR	NET WEIGHT	QTY.
7682	Imperial	School Bus Yellow	8 oz. dispenser	6



L38

MANUS BOND 73A RTV SILICONE

- High quality RTV acetoxysilicone.
- FDA approved.
- Tack Free Time: 30 minutes
- Shore A Hardness: 25
- Tensile Strength: 280 psi
- Elongation: 300%
- Non-sagging formula.

PART NO.	COLOR	NET WEIGHT	QTY.
7734	Black	10.1 oz. cartridge	6
7735	White	10.1 oz. cartridge	6
7736	Clear	10.1 oz. cartridge	6
7737	Alum. Gray	10.1 oz. cartridge	6



Mike
Pricing Analyst

Nimble.....

"There's no standing still. You've got to know your product, know fleets, and you've got to be able to react."



SILICONES

PERMATEX® BLACK SILICONE ADHESIVE SEALANT

- General purpose black sealant.
- Can be used indoor or outdoors.
- Seals, bonds, repairs, mends and secures glass, metal, plastic, fabric, vinyl, weather stripping and vinyl tops.
- Protects and repairs electrical wiring.
- Waterproof and flexible.
- Temperature range: -75° to 450° F
- Resists oil, water, weather, vibration and grease.

PART No.	NET WEIGHT	QTY.
9163	3 oz. tube	6



PERMATEX® ULTRA GREY® RTV SILICONE GASKET MAKER

- Designed for high-torque applications.
- Remains flexible and withstands high vibration.
- Outstanding oil and shop fluid resistance.
- Non-corrosive, low odor.
- Temperature range: -75° F to 625° F
- Includes applicator tip.

PART No.	CROSS REFERENCE	NET WEIGHT	QTY.
9166	82194	3.5 oz. tube	12
9166-1	82194	3.5 oz. tube	6



PERMATEX® AUTOMATIC TRANSMISSION RTV SEALANT

- Withstands the harsh detergents and friction modifiers found in AT fluid.
- Developed with U.S. automotive OEMs and complies with extended warranty requirements.
- Resists aging, weathering and thermal cycling without hardening, shrinking or cracking.
- Improved transmission oil resistance, good adhesion while retaining flexibility, sensor-safe, noncorrosive and can be used as a gasket maker or dressing.
- Non-flammable, non-toxic, low odor.

PART No.	CROSS REFERENCE	NET WEIGHT	QTY.
9187	81180	3 oz. tube	2



PERMATEX® ULTRA COPPER® GASKET MAKER

- Use with four cylinder, turbocharged or high-performance engines.
- Sensor safe, low odor and non-corrosive.
- Three times more oil resistant than conventional silicone.
- Eight times more flexible than cut gaskets.
- Temperature range: -75° F to 700° F intermittent
- Guaranteed not to leak.
- Includes applicator tip

PART No.	CROSS REFERENCE	NET WEIGHT	QTY.
9169	81878	3 oz. tube	6



RTV SILICONE EXTENSION NOZZLE

- Item screws onto existing dispenser for those hard to reach areas.
- For use with Silicone Gasket Maker Dispensers.

PART No.	QTY.
7554	6



INSTANT GASKET MAKERS

RIGHT STUFF® INSTALLERS KIT

- More reliable and longer lasting than cut gaskets.
- Temperature range: -75°F to 450°F
- Resists ATF, coolant, oil and other shop fluids.
- Sensor safe.
- Kit includes:
 - » (2) 5 oz. cartridges.
 - » (1) caulking gun.
 - » Return equipment to service immediately when you make leak-proof gaskets, in just one minute, with the Right Stuff®.



PART No.	CROSS REFERENCE	NET WEIGHT	QTY.
9172	99070	(2) 5 oz.	1 kit

RIGHT STUFF® INSTANT GASKET MAKER

- Makes instant gaskets to get equipment back in service immediately.
- More reliable and lasts longer than cut gaskets.
- Temperature range: -75° F to 450° F
- Resists ATF, coolant, oil and other shop fluids.
- Sensor safe.

PART No.	CROSS REFERENCE	NET WEIGHT	QTY.
9170	25224	7 oz.	6
9181	25229	3 oz.	1



Visit the Imperial website.
www.imperialsupplies.com



RTV SILICONES

DYNATEX® BLACK RTV SILICONE GASKET MAKER – LOW VOLATILE

- Sensor safe and manufactured to meet OEM specifications.
- Makes instant, leak proof gaskets on all engines, drive train equipment and related components.
- Temperature resistant up to 500° F.
- Resists oil, water, anti-freeze and transmission fluid.

PART NO.	NET WEIGHT	QTY.
7569	3 oz. tube	6
7589	11 oz. cartridge	12



DYNATEX® CLEAR RTV SILICONE ADHESIVE SEALANT

- Provides transparent, water tight silicone rubber seal.
- Bonds with metal, plastic, glass, fabric, vinyl, wood and rubber.
- Use on windshields, sun roofs, tail lights, interior panels, firewalls and dashboards.
- Cures at room temperature.

PART NO.	NET WEIGHT	QTY.
7575	3 oz. tube	6
7577-1	11 oz. cartridge	1
7577	11 oz. cartridge	12



DYNATEX® BLUE RTV SILICONE GASKET MAKER

- All-purpose gasket maker.
- Temperature resistant up to 500° F.
- Resists shrinking, cracking and migration caused by thermal cycling.
- Not sensor safe.

PART NO.	NET WEIGHT	QTY.
7570	3 oz. tube	6



DYNATEX® ALUMINUM RTV SILICONE SEALANT

- Industrial grade sealant.
- Cures at room temperature.
- Seals and bonds terminals, connectors, mounting fixtures, mechanical gaskets, glass, metal, masonry, plastic, tile, rubber, wood and fabric.
- USDA approved H2.

PART NO.	NET WEIGHT	QTY.
7579	11 oz. cartridge	12



DYNATEX® DYNACOPPER RTV SILICONE GASKET MAKER

- Highly flexible and will not leak.
- Low odor, sensor safe.
- Non-corrosive and manufactured to exceed OEM specifications.
- Temperature resistant up to 700° F.

PART NO.	NET WEIGHT	QTY.
7549	3.35 oz. tube	6



DYNATEX® WHITE RTV SILICONE SEALANT

- Industrial grade sealant.
- Cures at room temperature.
- Seals and bonds terminals, connectors, mounting fixtures, mechanical gaskets, glass, metal, masonry, plastic, tile, rubber, wood and fabric
- USDA approved H2.

PART NO.	NET WEIGHT	QTY.
7588	11 oz. cartridge	12



L40

DYNATEX® BLUE RTV SILICONE GASKET MAKER - LOW VOLATILE

- Sensor safe and manufactured to meet OEM specifications.
- Resists cracking, shrinking and migration caused by thermal expansion.
- Temperature resistant up to 500° F.
- Resists oil, water, anti-freeze and transmission fluid.
- Use on valve covers, oil pans, transmission pans, rear-end housings, timing chain covers, thermostat housings, water pumps and oil pump flanges.

PART NO.	NET WEIGHT	QTY.
7580	3 oz. tube	6
7587-1	11 oz. cartridge	1
7587	11 oz. cartridge	12



DYNATEX® RED RTV SILICONE GASKET MAKER – LOW VOLATILE

- Sensor safe and manufactured to meet OEM specifications.
- Resists cracking and migration caused by thermal cycling.
- Temperature resistant up to 650° F.
- Resists oil, water, anti-freeze and transmission fluid.

PART NO.	NET WEIGHT	QTY.
7573	3 oz. tube	6
7586	11 oz. cartridge	12



If you can't find the products you are looking for, call us, and we will find it for you.



CAULKING AND SEALERS

SIKAFLEX® 221 SEALANT

- A fast curing, polyurethane-based adhesive/sealant.
- Moisture-cured, non-sagging, permanent elastic bond to fasten materials.
- Works excellent on aluminum, FRP, steel, wood and pre-painted metals.
- High solids, low VOCs.
- Cures rapidly, sandable, can be painted with water, oil and rubber based coatings.
- Odorless, non-staining, non-corrosive, non-shrinking.
- Resistant to road salt.
- Application temperature: 40° F to 100° F
- Tack-free time: 45 minutes (70° F at 65% RH)

PART No.	NET WEIGHT	COLOR	TENSILE STRENGTH	ELONGATION	QTY.
7643	10.3 oz.	White	225 psi	500%	24
7643-2	10.3 oz.	White	225 psi	500%	9
7596	10.3 oz.	Gray	225 psi	500%	24
7596-2	10.3 oz.	Gray	225 psi	500%	9



SIKAFLEX® 227 SEALANT

- One-component, fast-skinning polyurethane-based, elastomeric adhesive/sealant.
- Moisture cured and non-sagging.
- Adhesion to aluminum, FRP, steel, wood and pre-printed metals.
- Provides a permanent elastic seal that can be sanded or painted.
- Excellent for light bonding of dissimilar materials.
- USDA approved H1 for incidental food contact.
- Tack free time: 30-50 minutes

PART No.	NET WEIGHT	COLOR	TENSILE STRENGTH	ELONGATION	QTY.
7598	10.3 oz.	White	250 psi	600%	24
7598-2	10.3 oz.	White	250 psi	600%	9
7599	10.3 oz.	Alum. Gray	250 psi	600%	24
7599-2	10.3 oz.	Alum. Gray	250 psi	600%	9



MANUS BOND 75-AM CAULK

- One part sealant.
- Contains no solvents.
- No shrinking or yellowing.
- Paintable.
- Non-sagging formula.
- Meets ASTM C920 Class 25, AAMA 802.3-7 UL 723 listed
- Tack Time: 60 minutes (73° F at 60% RH)

PART No.	NET WEIGHT	COLOR	TENSILE STRENGTH	ELONGATION	QTY.
7691	10.3 oz.	Gray	225 psi	275%	6
7692	10.3 oz.	White	225 psi	275%	6
7709	10.3 oz.	Black	225 psi	275%	6



MANUS BOND 75-AM FAST CURE CAULK

- One part sealant.
- Contains no solvents.
- No shrinking or yellowing.
- Paintable.
- Non-sagging formula.
- Tack Time: 20 minutes (73° F, at 50% RH)

PART No.	NET WEIGHT	COLOR	TENSILE STRENGTH	ELONGATION	QTY.
7693	10.1 oz.	Gray	350 psi	300%	6
7694	10.1 oz.	White	350 psi	300%	6



WHITE LIGHTNING® 3006 CAULK

- Forms a tough, rubbery gasket. Superior flexibility and elasticity.
- Can be painted or stained.
- Dry to the touch in 2-4 hours, fully cured in 24 hours.
- Mildew and rust resistant.
- For paneling, molding, furring strips, plywood and hardwood.

PART No.	NET WEIGHT	COLOR	QTY.
7632	10.1 oz.	Almond	12



ECLECTIC® EXTREME PREMIUM ADHESIVE & SEALANT

- Engineered for strong adhesion and instant grab on virtually any substrate.
- High performance polyether moisture cure technology that is 100% solid.
- Less than 2% VOCs. Solvent free.
- Zero shrinkage. Will not sag, drip or run.
- Safe for indoor use or in confined spaces. No odor.
- Provides a long lasting weather tight seal.
- Withstands temperatures from -40°F to 200°F.
- Can be painted after 24 hours.
- Tack free: 35 minutes.

PART No.	NET WEIGHT	COLOR	TENSILE STRENGTH	ELONGATION	QTY.
7631	10.1 oz.	White	350 psi	300%	12



DAP® DOW CORNING® 100% SILICONE SEALANT

- Protect and seal with 100% silicone rubber.
- Waterproof, flexible, not paintable.
- 50 year durability guarantee.
- FMVSS: TT-S-001534A, Class A.

PART No.	NET WEIGHT	COLOR	QTY.
3504	10.1 oz.	White	12
3501	10.1 oz.	Aluminum	12
3502	10.1 oz.	Clear	12



NORTON® URETHANE WINDSHIELD SEALER

- A primer-less, one part urethane adhesive sealant for full-cut and short-cut methods of windshield and backlight installations.
- Easy handling and fast set properties.
- Passes FMVSS #212 windshield barrier test and #216 crush test.

PART No.	NET WEIGHT	QTY.
7664	11 oz.	12



CHEMICALS & PAINTS

CAULKING GUNS

BULK CAULKING GUN

- Works with:
 - » 10 oz. or 20 oz. sausage tubes
 - » 10 oz. Cartridges
 - » 24 oz. Bulk
- Comes with cone nozzle.
- 18:1 thrust ratio.
- One piece molded multi-chemical resistant twin Hytrel cup.
- Comes with push disk for use with cartridges.
- Steel T-Bar and zinc alloy handle.
- Rotating barrel.



PART No.	DESCRIPTION	QTY.
6904	Caulking gun	1
6903	Replacement nozzle	1

CAULKING GUN – PROFESSIONAL MODEL

- Drip free hex rod parallel frame.
- Has a seal puncture tool and built in spout cutter.
- 10:1 thrust ratio.
- Easy load front cap.



PART No.	QTY.
6906	1

CAULKING GUN – PROFESSIONAL II MODEL

- Super smooth rod.
- 18:1 thrust ratio.
- Revolving barrel.
- Zinc alloy handle.



PART No.	QTY.
6905	1

CAULKING GUN

- New welding technique assures reliability and durability.
- Fits all Imperial cartridges.
- 1/10th gallon model.
- Corrosion resistant.



PART No.	QTY.
6907	1

Imperial continuously adds new products.

MISCELLANEOUS

SIKATACK® ULTRAFAST II

- Hot applied windshield adhesive.
- Fast curing, one component polyurethane windshield adhesive with high green strength.
- Short cut off string, avoiding costly clean ups.
- SikaTack® Ultrafast II offers safe drive away time in as little as 30 minutes.
- SikaTack® Ultrafast II passes FMVSS 208/212 in its most severe interpretation with dual air bags and unrestrained occupants.
- Suitable for use in non-conductive applications.
- The adhesive can be heated up and cooled down several times.
- At 175° F the adhesive will remain stable for a total of 10 hours.



PART No.	NET WEIGHT	QTY.
7665	10.1 oz.	24

3M™ FAST TACK TRIM ADHESIVE

- Extremely fast-drying, non-stain adhesive with long tack for attaching vinyl and other kinds of trim fabric, upholstery, floor mats and carpeting.



PART No.	CROSS REFERENCE	COLOR	NET WEIGHT	QTY.
7522	08031	Light Amber	5 oz. tube	1

SIKA PRIMER® 206 G&P

- One-component, fast drying primer.
- Used to touch up pinchweld scratches, to act as a rust barrier on metals and as a UV protector when a frit is not present.
- Drying time: 10 minutes (73° F at 50% RH)
- Product receives hazardous material shipping charge.



PART No.	COLOR	NET WEIGHT	QTY.
7670	Black	250 ml	6

3M™ WINDOW-WELD™ RIBBON SEALER KIT

- Auto Glass Replacement Kit.
- Allows easy installation, yet will not squeeze out or allow light to contact pinchweld.
- Contains one roll of sealer and setting blocks.
- Replaces one windshield or backlight.



PART No.	CROSS REFERENCE	COLOR	SIZE	QTY.
7698	08611	Black	5/16" x 15'	1



*Alyce
Dedicated Service Advisor*

Decisive...

"It's my job to do the work and make recommendations. My customers appreciate that."



STRUCTURAL ADHESIVES

3M™ ALL-AROUND AUTOBODY SEALANT

- For sealing interior and exterior auto body joints and seams.
- Applies easily and can be smoothed to a featheredge with a wet finger.
- Sets to a firm, tough, rubber-like water resistant bead.
- Easy water cleanup and will not harm paint.
- Paint Time: 30 minutes

PART NO.	CROSS REFERENCE	COLOR	NET WEIGHT	QTY.
7695	08500	White	11 oz.	12



3M™ ULTRAPRO™ MSP SPRAYABLE SEAM SEALER

- High-performance, general-purpose seam sealer that can be caulked or sprayed.
- Adheres well to all primed surfaces except acrylic lacquer.
- Use on door skins, hemming flanges, quarter panel seams, floor and trunk pans.
- Non-shrinking, non-cracking, fast curing.
- Tack free in 30 minutes and immediately paintable.
- Extra applicator tips are supplied with the sealer.

PART NO.	CROSS REFERENCE	COLOR	NET WEIGHT	QTY.
7696	08374	Gray	10.5 oz.	6



3M™ BRUSHABLE SEAM SEALER

- Designed to seal sheet metal overlap joints that have been spot welded, riveted or bolted together.
- Remains flexible and resists oil, fuel and other automotive fluids.
- Seals floor pans, fire walls, trunk seams, shock absorber mounting towers, around wheel wells, fuel filler splash pans and around headlight and taillight openings.
- Paintable.

PART NO.	CROSS REFERENCE	COLOR	NET WEIGHT	QTY.
7697	08656	Gray	1 quart	1



3M™ AUTOMIX™ PANEL BONDING ADHESIVE

- Two-part epoxy bonds steel, aluminum, SMC and FRP (traditional fiberglass).
- Primary use is to replace quarter panels, roofs, box sides, van sides, utility vehicle sides and door skins.
- Use on outer body panels only.

PART NO.	CROSS REFERENCE	MATERIAL	COLOR	NET WEIGHT	QTY.
7711	08115	Epoxy	Black	200 ml	6



3M™ AUTOMIX™ UNIVERSAL ADHESIVE BLACK

- General purpose black adhesive for metal glass and plastic
- Strong and durable and works on a wide variety of substrates
- Bonds similar and dissimilar materials in minutes.

PART NO.	CROSS REFERENCE	MATERIAL	COLOR	NET WEIGHT	QTY.
7712	08223	Urethane	Black	200 ml	6



3M™ AUTOMIX™ FLEXIBLE FOAM

- Two part urethane which foams in place; designed to replace flexible foams found in OEM applications such as trunks, door cavities, door skins, roof beams, etc.
- This flexible foam expands to 10 times its original size.

PART NO.	CROSS REFERENCE	MATERIAL	COLOR	NET WEIGHT	QTY.
7713	08463	Urethane	Black	200 ml	6



3M™ AUTOMIX™ HEAVY-BODIED SEAM SEALER

- Two-part epoxy for use in vertical or horizontal seams to match OEM sealers
- Non-sagging, non-flowing and easy to tool.
- Paintable in 30 minutes, worktime, 10 minutes.

PART NO.	CROSS REFERENCE	MATERIAL	COLOR	NET WEIGHT	QTY.
7714	08308	Epoxy	Off White	200 ml	6



3M™ AUTOMIX™ ADHESIVE SEAM SEALER NOZZLES & TIPS

- Compatible with 3M Automix 200 ml products.



PART NO.	CROSS REFERENCE	STYLE	QTY.
7717	08193	Automix™ Mixing Nozzles 3/8"	6
7720	08201	1/4" Rounded Seam Sealer Tip	6
7721	08202	3/8" Rounded Seam Sealer Tip	6
7722	08203	1/2" Rounded Seam Sealer Tip	6
7723	08204	3/8" Flat Seam Sealer Tip	6
7724	08205	3/8" Double-Rounded Seam Sealer Tip	6

All first time chemical product orders from Imperial include MSDS for maintaining OSHA Compliance.

View MSDS 24/7 on our website at www.imperialsupplies.com



CHEMICALS & PAINTS

STRUCTURAL ADHESIVES

NORTON® SPEEDGRIP® STRUCTURAL ADHESIVES

- The OEM choice of adhesives due to their flexibility and high impact strength.
- Has the ability to handle the stress of vibration and thermal expansion/contraction.
- Bonds and repairs all types of metal, fiberglass, FRP and plastics.
- Fits in standard dual 200 ml cartridge guns.
- Meets the following OEM specifications:
 - » Ford ESB-M11P27-B
 - » GM 3629M; GM 9985454
 - » Chrysler MSCC 258.

PART NO.	NET WEIGHT	SET TIME	QTY.
7700	220 ml	1 minute	6
7701	220 ml	5 minute	6
7701-1	220 ml	5 minute	1
7702	220 ml	15 minute	6
7702-1	220 ml	15 minute	1
7744	220 ml	40 minute	6
7703-1	220 ml	40 minute	1



DUAL CARTRIDGE APPLICATOR GUN

- Manual applicator gun designed for Norton Structural Adhesive system.
- Can be used with 200 or 220 ml cartridges.

PART NO.	QTY.
6900	1



NORTON® SEAM SEALER

- Used to seal interior and exterior seams, joints and voids.
- Will not shrink, harden or crack and retains its flexibility.
- For use on vertical and horizontal seams.
- Matches OEM seams.
- Includes (2) 18 Element Mixing Tips, but can be used with 24 Mixing Element Tip as well.

PART NO.	NET WEIGHT	QTY.
7704	220 ml	6



NORTON® 24 ELEMENT TIP

PART NO.	QTY.
6902	6



NORTON® TPO ADHESION PROMOTER

- Formulated to provide maximum adhesion to the TPO family of plastics.

PART NO.	NET WEIGHT	QTY.
7708	4.2 oz. brush top	2



DIELECTRIC GREASE

PERMATEX® DIELECTRIC GREASE

- Prevents voltage leakage around any electrical connection.
- Insures a strong spark in high energy ignition systems.
- Great lubricant on rubber and plastic surfaces.
- Prevents fusing of spark plug boots to the spark plug.

PART NO.	CROSS REFERENCE	NET WEIGHT	QTY.
9182	81150	1/3 oz. tube	4



DYNATEX® DIELECTRIC GREASE

- Prevents voltage leakage around any electrical connection, thereby insuring a strong spark in high energy ignition systems.
- Great lubricant on rubber and plastic surfaces.
- Prevents fusing of spark plug boots to the spark plug.

PART NO.	NET WEIGHT	QTY.
7550	1/3 oz. tube	4
7551	5 oz. tube	1



PERMATEX® DIELECTRIC GREASE POWER CAN

- Dielectric grease in a convenient to use aerosol can.
- Protects electrical connections and wiring from salt, dirt and corrosion.
- Extends the life of bulb sockets.
- Prevents voltage leakage around any electrical connection.
- Also prevents spark plugs from fusing to boots.
- Suggested applications: Marine and Automotive electrical connections, spark plug boots, trailer hitches, battery terminals, etc

PART NO.	CROSS REFERENCE	NET WEIGHT	QTY.
9183	81153	3 oz.	1



SUPER LUBE® ANTI-CORROSION GEL

- Specially formulated as a dielectric compound and corrosion inhibitor.
- Does not contain silicone.
- Will not harden or crack and resists changes due to mechanical working.
- For use on: plugs and connectors, electrical terminals, electrical fittings, spark plugs and coil connectors.
- **Note: Should not be used as a lubricant**

PART NO.	NET WEIGHT	QTY.
7572	3 oz. tube	1



PERMATEX® COUNTERMAN'S CHOICE DIELECTRIC GREASE

- Single-use chemicals that deliver just the right amount of material for typical automotive repair jobs.
- Dielectric Grease provides a moisture-proof barrier that lubricates and protects electrical equipment from salt, dirt and corrosion.
- High dielectric strength.

PART NO.	CROSS REFERENCE	NET WEIGHT	QTY.
9146	09980	5 gm pouch	24



TRUCK-LITE® ELECTRICAL COMPOUND

- Corrosion preventive compound for electrical contact switches and junction boxes.

PART NO.	CROSS REFERENCE	NET WEIGHT	QTY.
80898	97940	8 oz.	2
80899	97944	2 oz.	4



GLUE

IMPERIAL® GENERAL PURPOSE INSTANT ADHESIVE

- A general purpose instant adhesive for bonding rubber, metal, plastic and ceramic. Ideal for close fitting parts.
- No primer required. Cures in 30 seconds.
- Temperature range: -110° F to 175° F

PART No.	TENSILE STRENGTH	NET WEIGHT	QTY.
9510	2,500 psi	1 oz. bottle	4
9510-1	2,500 psi	1 oz. bottle	1



PERMATEX® COLD WELD BONDING COMPOUND

- An alternative to welding.
- A 15 minute, two part adhesive and filler system that eliminates the need for welding or brazing. Once cured it can be drilled sanded, painted or filed.
- Withstands temperatures to 350° F intermittent.

PART No.	CROSS REFERENCE	NET WEIGHT	QTY.
9190	14600	Two 1 oz. tubes per package	4 pkg



DYNATEX® INSTANT BONDER

- Bonds close fitting parts in seconds.
- Instantly bonds glass, metals, plastics and rubber.
- Works on aluminum, copper, brass, steel, vinyl, PVC, polyester, nylon, fiberglass and wood.

PART No.	TENSILE STRENGTH	NET WEIGHT	QTY.
7548	5,000 psi	20 gm (.76 oz.)	5



PERMATEX® MULTI-METAL EPOXY STICK

- Multi-purpose epoxy putty sticks for metal, concrete and most plastics.
- Can be drilled, sanded, threaded or filed.
- Resistant to fuels and solvents.
- Ideal for vertical applications.

PART No.	CROSS REFERENCE	NET WEIGHT	QTY.
7710	84309	2 oz. carded	1



PERMATEX® INSTANT ADHESIVE

- Outperforms regular super glues.
- No-run formula for precise application, even on vertical surfaces.
- Works great for metal, plastics, rubber, leather, vinyl, paper, wood, textiles and cork gaskets.
- Store in a cool/dry place between 36° F and 46° F.

PART No.	CROSS REFERENCE	NET WEIGHT	QTY.
9118	81737	2 gram tube	6



PERMATEX® SUPER GLUE GEL

- No-run formula for precise application, even on vertical surfaces.
- Applicable tube is ideal for overhead or hard-to-reach surfaces.
- Works on both porous and non-porous materials.

PART No.	CROSS REFERENCE	NET WEIGHT	QTY.
9115	85554	2 gram tube	2



PERMATEX® SUPER GLUE

- Specially designed for a faster, long-lasting bond.
- Easily applied and works on nonporous materials including metal, plastics, rubber, vinyl, paper, wood, textiles and cork gaskets.
- Permanent transparent bond fills gaps to .004".

PART No.	NET WEIGHT	QTY.
9117-4	2 gram tube	12



PERMATEX® QUICK SET EPOXY – 1 MINUTE

- Bonds ceramic, chrome, fabric, fiberglass, glass, hard plastic, metal and rubber.
- Permanent strength up to 2500 psi.
- Clear appearance. Resists most liquids.
- Sets in only 1 minute.

PART No.	CROSS REFERENCE	NET WEIGHT	QTY.
9517	84160	.84 fl oz. syringe	1



PERMATEX® QUICK SET EPOXY – 5 MINUTE

- Bonds ceramic, chrome, fabric, fiberglass, glass, hard plastic, metal and rubber.
- Crystal clear appearance. Resists most liquids.
- Permanent strength up to 3,400 psi.
- Sets in 5 minutes.

PART No.	CROSS REFERENCE	NET WEIGHT	QTY.
9513	84101	.84 fl oz. syringe	1



PERMATEX® PERMAPOXY™ PLASTIC WELD - 5 MINUTE

- A structural adhesive designed for general purpose bonding of a wide variety of materials.
- Forms a tough, durable bond to most plastics, composites, ceramics, wood in any combination.
- Sets in 5 minutes.

PART No.	CROSS REFERENCE	NET WEIGHT	QTY.
9140	84115	.84 fl oz. syringe	1



Imperial continuously adds new products.



GLUES / CEMENT / SEALANTS

3M™ AUTOMIX™ FAST CURE EPOXY ADHESIVE

- Two-part, clear epoxy that delivers strong, durable bonds within minutes after application.
- Makes difficult repair jobs easy when used to join parts made of plastic, metal, glass, fiberglass, wood, etc.

PART No.	CROSS REFERENCE	MATERIAL	COLOR	SIZE	QTY.
7718	08107	Epoxy	Clear	2 oz.	6



3M™ AUTOMIX™ ADHESIVE SEAM SEALER NOZ.ZLE

- Compatible with 3M Automix 2 oz. products.

PART No.	CROSS REFERENCE	QTY.
7719	08193	12



3M™ DURAMIX™ SUPER FAST ADHESIVE

- Super fast-setting adhesive which does not require a separate accelerator like cyanoacrylate adhesives.
- Excellent wide gap filling capabilities and withstands a wide range of temperatures.

PART No.	CROSS REFERENCE	DESCRIPTION	SIZE	QTY.
7715	04747	Transparent Yellow	50 cc	12
7716	04909	Mixer Tip	—	6



PERMATEX® FAST CURE EPOXY

- Eliminates squeeze tube.
- (10) .12 oz. cups with pre-measured resin and hardener.
- No mess—no guess!
- Bonds to wood, glass, metal, plastic and more.
- Sets in 15 minutes. Full cure in 24 hours.

PART No.	CROSS REFERENCE	NET WEIGHT	QTY.
9114	21425	1.2 oz. total	1



E-6000® INDUSTRIAL STRENGTH ADHESIVE AND SEALANT

- Exceeds silicone, acrylics and rubber cements in strength and durability.
- High-performance adhesive with exceptional bonding to metals, glass, plastic, composites, tile, cement, rubber, leather, wood and vinyl.
- Provides a tough, waterproof bond that won't crack or become brittle.
- Exceptional flexibility and vibration resistance.
- Non-flammable and paintable.

PART No.	NET WEIGHT	QTY.
7505	3.7 oz. tube	4



HH-66 VINYL CEMENT

- Superior quality vinyl adhesive.
- Exceptional bond strength for vinyl coated and vinyl laminated fabrics.
- Also used to bond urethanes, vinyl foams and films, rigid plastics, synthetic fabrics, wood, leather and metals.
- Easy application. Fast drying—ready in minutes.
- Waterproof—outstanding resistance to temperature and weather.

PART No.	NET WEIGHT	QTY.
7506	8 oz. brush top	1
7508	16 oz. brush top	1
7507	32 oz. brush top	1



PERMATEX® WEATHERSTRIP CONTACT ADHESIVE

- A superior adhesive ideal for many applications including rubber, metal, auto/truck carpeting and fabric backed vinyl upholstery and automotive gaskets.
- Allows for repositioning parts after contact is made.

PART No.	CROSS REFERENCE	COLOR	NET WEIGHT	QTY.
9177	81731	Yellow	5 fl oz. tube	6
9193	81850	Black	5 fl oz. tube	6



DYNATEX® SUPER WEATHERSTRIP AND GASKET ADHESIVE

- High strength, fast drying, waterproof adhesive.
- Bonds rubber, vinyl, metal, fabrics and glass.
- Resists oil and most shop and automotive fluids.

PART No.	COLOR	NET WEIGHT	QTY.
7592	Yellow	5 oz. tube	6
7594	Black	5 oz. tube	6



3M™ SUPER WEATHERSTRIP

- A strong, flexible, rubbery adhesive that can withstand vibration, oil, grease and extreme temperature variations.
- Use to bond weatherstripping to car doors, trunks, T-tops, moon roofs and sun roofs.

PART No.	CROSS REFERENCE	COLOR	NET WEIGHT	QTY.
7516	08001	Yellow	5 oz.	1
7517	08008	Black	5 oz.	1



3M™ PLASTIC AND EMBLEM ADHESIVE

- Strong, quick drying adhesive can be used for bonding plastic or metal emblems, interior rigid plastic, tail light lenses, vinyl siding moldings or upholstery.
- Work Time: 5 minutes

PART No.	CROSS REFERENCE	COLOR	NET WEIGHT	QTY.
9185	08061	Clear	5 oz.	2



VINYL AND LEATHER REPAIR

- A clear, strong, flexible adhesive designed to mend rips, tears and small holes on most types of vinyl surfaces.
- Resists yellowing, matches all colors.

PART No.	NET WEIGHT	QTY.
9547	1 oz. tube	1



DYNATEX® MUFFLER & TAILPIPE SEALANT

- Repairs holes and leaks in mufflers, tailpipes and around joints.
- Run engine at idle speed for 20 minutes to harden quickly or allow to sit overnight.

PART No.	NET WEIGHT	QTY.
7591	4.5 oz. tube	6



KITS & MISCELLANEOUS PRODUCTS

PERMATEX® HEADLIGHT LENS RESTORATION KIT

- Restores clouded, pitted, yellowed, plastic headlight lens surfaces, which improves light output and appearance.
- Kit includes:
 - » (1) 4 oz. plastic restoration polish
 - » (4) industrial grade wet/dry sandpaper sheets (1000, 1500, 2000, 2500 grits)
 - » (1) polish cloth
 - » (1) instruction sheet
 - » (1) pair of disposable gloves

PART NO.	CROSS REFERENCE	QTY.
9173	09135	1 kit



CURING FILM STRIPS

- Used with PIT Filler Repair Resin, Part No. 7582 and Windshield Repair Resin, Part No. 7581.

PART NO.	SIZE	QTY.
7583	1" x 10"	100



PIT FILLER REPAIR RESIN

- Designed to be used as a finish filler for chip repairs
- Quick curing resin works well for surface chips and leaves a smooth and clear surface to prevent wiper streaks
- Enough to do over 100 repairs.

PART NO.	NET WEIGHT	QTY.
7582	7.5 ml	1



3M™ HEADLIGHT LENS RESTORATION SYSTEM

- Four step process restores the clarity of yellowed, hazed or dull headlight lenses.
- Kit contains:
 - » (1) Disc Pad Holder
 - » (1) 3M Soft Interface Pad
 - » (6) 3M Sanding Discs
 - » (4) 3M Finishing Discs
 - » (1) 3M Trizact Disc
 - » (1) 3M Headlight Lens Polish, 1 oz.
 - » (1) Buffing Pad
- Use with a standard drill (1200-1600 rpm).

PART NO.	CROSS REFERENCE	QTY.
9178	39008	1 kit



WINDSHIELD REPAIR RESIN

- One of the best windshield repair resins on the market.
- Gives a crystal clear fix
- Used to fill star breaks, bulls eyes, combination breaks and small cracks
- Enough to do over 50 repairs

PART NO.	NET WEIGHT	QTY.
7581	15 ml	1



LIGHTRITE™ HEADLAMP RESTORATION KIT

- LightRite is a state-of-the-art, sprayed on chemical formula that renews your old, hazy headlights, bringing them back to their original crystal clear brilliance.
- Kit contains:
 - » (1) aerosol can/Services 1 vehicle
 - » (2) sheets of 600 grit wet sandpaper
 - » (2) alcohol towels
 - » (2) lint free towels
 - » (1) instruction sheet (English & Spanish)

PART NO.	QTY.
9188	1 kit



PERMATEX® WINDSHIELD REPAIR KIT

- The first one-component windshield repair system designed to be used by the mechanic.
- Requires no mixing, no heat.
- Has the same index of refraction as the original glass to make repair virtually undetectable.

PART NO.	CROSS REFERENCE	NET WEIGHT	QTY.
9186	16067	.17 fl oz.	2 kits



WINDSHIELD REPAIR KIT

- Repairs 90% of stone damage up to 1".
- Not recommended for cracks.
- Makes crystal clear repair.
- Repair finished in approximately 30-35 minutes.
- Complete, easy-to-use kit includes:
 - » (3) syringes
 - » (1) instruction guide
 - » (1) sealing patch
 - » (1) sealant liquid applicator

PART NO.	NET WEIGHT	QTY.
7564	.17 fl oz.	2 kits



PERMATEX® REARVIEW MIRROR ADHESIVE KIT

- Single use applications.
- Approved and used by GM, Ford and Chrysler.
- Permanently remounts mirrors to windshields.
- Achieves handling strengths in seconds.
- Includes primer and adhesive.

PART NO.	CROSS REFERENCE	QTY.
9189	81844	12 kits



WARNING: Do not allow compound to spill on painted surfaces. Compound may remove paint.



KITS & MISCELLANEOUS PRODUCTS

PERMATEX® STRIPPED THREAD REPAIR KIT

- Makes reliable thread repairs without drills, taps, tools or inserts.
- Restores worn, stripped or damaged threads and eliminates future corrosion, galling, seizing and rust.
- Effective up to 128 feet lb of torque and between -65° F to 300° F.
- Repairs most metal-to-metal fasteners up to SAE Grade 5 English and 8.8 Metric (coarse and fine).

PART NO.	CROSS REFERENCE	QTY.
9176	81668	1 kit



PERMATEX® FUEL TANK REPAIR KIT

- Designed to harden within 8-10 minutes and cures in about 30 minutes.
- Repairs can be made on slow-leaking cracks up to 4" in length and holes up to 3/8" in diameter.
- Complete kit contains everything required for making professional-quality repairs in just minutes.
- Kit includes:
 - » (1) lens polish
 - » (1) instruction guide
 - » (4) sandpapers
 - » (1) pair of latex gloves

PART NO.	CROSS REFERENCE	QTY.
7567	09101	1 kit



3M™ DRY GUIDE COAT CARTRIDGE

- Use to highlight surface imperfections and sand scratches prior to finishing with abrasives.
- Dry powder with applicator.
- Can use on marine fillers, primers, paints and gel coat.
- Contains no solvents.

PART NO.	CROSS REFERENCE	NET WEIGHT	QTY.
8047	05860	50 grams	1



3M™ AUTOMOTIVE ADHESION PROMOTER

- When attaching plastic trim, use this as a liquid primer used to improve the adhesion of Automotive Attachment Tapes.
- Compatible with most low surface energy plastic materials as well as injection-molded body side moldings and claddings used for automotive exterior trims.

PART NO.	CROSS REFERENCE	NET WEIGHT	QTY.
8029	06396	2.5 cc	25



LIQUID ELECTRICAL TAPE

- Rubber insulation coating exhibits excellent acid, alkaline, abrasion protection and seals out moisture.
- Strongest dielectric protection on the market; 1,200 v/mil, 5 b 7 mils per coat.
- Rubber-based coating will not harden, unravel or become brittle in extreme weather conditions.
- Replaces electrical tape by providing electrical insulation to hard-to-reach places.
- Primary applications: boats, trailers, RVs, automotive, timers, outdoor wiring, instruments, circuit boards, switches
- For use on: outdoor lighting, cables, electronics, underground wiring, utility trailers, alarms or security systems, distributors, junction boxes, sleeves for LEDs, etc.
- Fast drying, safe and easy to use.

PART NO.	COLOR	NET WEIGHT	QTY.
6565	Black	6 oz. aerosol	6
6607	Clear	6 oz. aerosol	6



LIQUID ELECTRICAL TAPE

- Adheres to all metal, plastic, vinyl, rubber and composite surfaces.
- Holds wires and terminals together and prevents loose connections due to vibration.
- Forms a protective dielectric coating of flexible vinyl.
- Totally seals out moisture to prevent corrosion.
- Safe and easy to use.
- Fast drying.
- UL tested: test available upon request.

PART NO.	COLOR	NET WEIGHT	QTY.
9521	Black	4 oz. fl brush top	1
9527	Red	4 oz. fl brush top	1



PVC BONDING ADHESIVE

- Specially formulated solvent for extended working times.
- Provides exceptional sheet to sheet bonding

PART NO.	NET WEIGHT	QTY.
7521	16 oz. brush top	6



CPVC/PVC/ABS CLEANER

- For use on all schedules and diameters.
- Fast-acting cleaner removes surface dirt, grease and grime.
- Flows freely and evaporates quickly.
- Apply at temperatures 40° F to 100° F.

PART NO.	NET WEIGHT	QTY.
7520	16 oz. can	6



Experience our dedicated customer service.

