

EUREKA CHEMICAL COMPANY

SAFETY DATA SHEET

1. Identification		
Trade name:	Fluid Film Non-Aerosol Black	
Supplier:	Phone: 650-761-3536 Fax: 650-589-1943 Contact Phone: 1-650-761-3536 info@fluid-film.com	
Emergency number:	Chemtrec (800) 424-9300	
Issue date:	06/08/2020	
2. Hazard(s) identification		

Classification:

As a consumer product labeling is in accordance with the US Consumer Product Safety Commission. The elements below are not included on package label as they apply to industrial products.

Physical hazards	Health hazards
Not classified	Aspiration hazard Category 1

Label Elements:

Danger!



Hazard statements (GHS US)	Precautionary statements (GHS US)
H304 - May be fatal if swallowed and enters airways	 P301+P310 - If swallowed: Immediately call a poison center or doctor. P331 - Do NOT induce vomiting. P405 - Store locked up. P501 - Dispose of contents or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

3: Composition/Information on ingredients

Component	CAS-No.	Amount (%)
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	40 - 80
Benzenesulfonic acid, di-C10-18-alkyl derivs., calcium salts	93820-57-6	< 2
Carbon Black*	1333-86-4	0.1-<1

* Carbon black only presents a risk of cancer by inhalation of very fine dust. There is no exposure to respirable carbon black dust in the normal use of this product.

 $Chemical \ name, CAS \ number \ and/or \ exact \ concentration \ have \ been \ withheld \ as \ a \ trade \ secret$

4. First-aid measures

Inhalation: Move the affected person to the fresh air. Get medical attention if symptoms occur.

Skin: Gently wash with plenty of soap and water. Get medical advice if skin irritation persists.

Eyes: Rinse cautiously with water for several minutes. Get medical attention if irritation develops and persists.

Ingestion: Do NOT induce vomiting. Immediately call a poison center or doctor or physician. If vomiting occurs spontaneously, keep head below hips to prevent aspiration into the lungs.

Symptoms/effects: Aspiration hazard. Swallowing the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis.

Immediate medical attention and special treatment, if necessary: Immediate medical attention may be required for ingestion.

5. Fire-fighting measures

Suitable extinguishing media: Dry chemical, CO2, or water spray or regular foam.

Unsuitable extinguishing media: Do not use a heavy water stream.

Fire hazard: This product is not classified as flammable or combustible. Could burn but does not ignite readily. On burning: release of carbon monoxide - carbon dioxide.

Special protective equipment and precautions for fire-fighters: Positive pressure self-contained breathing apparatus (SCBA) and structural fire-fighters protective clothing. Do not attempt to take action without suitable protective equipment.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Wear suitable protective clothing. Avoid contact with eyes, skin and clothing.

Methods and material for containment and cleaning up: Take up liquid spill into absorbent material. Place in a suitable container for disposal in accordance with the waste regulations (see Section 13).

7. Handling and storage

Precautions for safe handling: Avoid contact with eyes, skin and clothing. Wash hands with water and soap. Ensure adequate ventilation.

Storage conditions: Store away from strong oxidizers, strong bases, strong acids. Store locked up.

8. Exposure controls/personal protection

Exposure guidelines:	
Distillates (petroleum), hydrotreated heavy	5 mg/m ³ TWA OSHA PEL;
paraffinic	5 mg/m ³ (Inhalable particulate matter) TWA ACGIH TLV

Benzenesulfonic acid, di-C10-18-alkyl derivs., calcium salts	None established.
Carbon Black	3.5 mg/m ³ TWA OSHA PEL; 3 mg/m ³ (Inhalable particulate matter) TWA ACGIH TLV

Appropriate engineering controls: Provide local exhaust or general room ventilation. **Environmental exposure controls**: Avoid release to the environment.

Personal protective equipment:

Hand protection: Wear suitable gloves

Eye protection: Use suitable eye protection

Skin and body protection: Wear suitable protective clothing

Respiratory protection: In case of insufficient ventilation, wear suitable respiratory equipment. In operations where exposure limits are exceeded or exposure levels are excessive, an approved respirator should be used. Respirator selection and use should be based on contaminant type, form and concentration. Follow applicable regulations and good Industrial Hygiene practice.

9. Physical and chemical properties

Appearance: Liqu	iid.				
Physical state	: Liquid		Relative density	:	0.88
Color	: Black		Solubility	:	Insoluble in water.
Odor	: Mild waxy		Log Pow	:	No data available
Odor threshold	: No data available		Auto-ignition	:	No data available
рН	: 7.8		temperature		
Melting point	: Not applicable		Decomposition	:	No data available
Freezing point	: No data available	2	temperature		
Boiling point	: No data available	2	Viscosity, kinematic	:	No data available
Flash point	: 405 °F		Viscosity,	:	No data available
Relative	: No data available		dynamic		
evaporation rate			Explosion limits	:	No data available
(butyl acetate=1) Flammability	: Not applicable.		Explosive properties	:	None.
(solid, gas)			Oxidizing	:	None.
Vapor pressure	: No data available		properties	-	
Relative vapor density at 20 °C	: No data available				
VOC content		: <1% CARB 310.			
voc content		. < 1% CARD 510.			

10. Stability and reactivity

Reactivity: The product is non-reactive under normal conditions of use, storage and transport.

Chemical stability: Stable under normal conditions.

Possibility of hazardous reactions: No dangerous reactions known under normal conditions of use. **Conditions to avoid**: None known.

Incompatible materials : Strong acids. Strong bases. Strong oxidizers.

Hazardous decomposition products: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

11. Toxicological information

Inhalation: May cause minor irritation to the respiratory tract and to other mucous membranes.

Skin: May cause slight irritation to the skin.

Eyes: May cause minor eye irritation.

Ingestion: Aspiration hazard. Swallowing the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Chronic symptoms: None known.

Carcinogenicity:	Not classified.	
Distillates (petroleum),	This component is not listed as a carcinogen or suspected carcinogen by IARC,	
hydrotreated heavy paraffinic:	NTP, ACGIH, or OSHA.	
Benzenesulfonic acid, di-C10-18-	This component is not listed as a carcinogen or suspected carcinogen by IARC,	
alkyl derivs., calcium salts:	NTP, ACGIH, or OSHA.	
Carbon Black:	IARC 2B - Possibly carcinogenic to humans; (Carbon black only presents a risk of	
	cancer by inhalation of very fine dust. There is no exposure to respirable carbon	
	black dust in the normal use of this product.)	
Germ cell mutagenicity:	Not classified	
Reproductive toxicity :	Not classified	
Numerical measures of toxicity:	Product does not present an acute toxicity hazard based on known or supplied	
	information.	
The following are the toxicity va	lues for the components:	
Distillates (petroleum),	lues for the components: Oral rat LD50- > 5000 mg/kg; Dermal rat LD50- > 2000 mg/kg body weight;	
8	1	
Distillates (petroleum),	Oral rat LD50- > 5000 mg/kg; Dermal rat LD50- > 2000 mg/kg body weight;	
Distillates (petroleum), hydrotreated heavy paraffinic:	Oral rat LD50- > 5000 mg/kg; Dermal rat LD50- > 2000 mg/kg body weight;	
Distillates (petroleum), hydrotreated heavy paraffinic: Benzenesulfonic acid, di-C10-18- alkyl derivs., calcium salts: Carbon Black:	Oral rat LD50- > 5000 mg/kg; Dermal rat LD50- > 2000 mg/kg body weight; Inhalation rat LC50- > 5000 mg/m ³	
Distillates (petroleum), hydrotreated heavy paraffinic: Benzenesulfonic acid, di-C10-18- alkyl derivs., calcium salts:	Oral rat LD50- > 5000 mg/kg; Dermal rat LD50- > 2000 mg/kg body weight; Inhalation rat LC50- > 5000 mg/m ³ No data available	
Distillates (petroleum), hydrotreated heavy paraffinic: Benzenesulfonic acid, di-C10-18- alkyl derivs., calcium salts: Carbon Black:	Oral rat LD50- > 5000 mg/kg; Dermal rat LD50- > 2000 mg/kg body weight; Inhalation rat LC50- > 5000 mg/m ³ No data available Oral rat LD50- > 10000 mg/kg;	
Distillates (petroleum), hydrotreated heavy paraffinic: Benzenesulfonic acid, di-C10-18- alkyl derivs., calcium salts: Carbon Black: Skin corrosion/irritation	Oral rat LD50- > 5000 mg/kg; Dermal rat LD50- > 2000 mg/kg body weight; Inhalation rat LC50- > 5000 mg/m ³ No data available Oral rat LD50- > 10000 mg/kg; Not classified Not classified	
Distillates (petroleum), hydrotreated heavy paraffinic: Benzenesulfonic acid, di-C10-18- alkyl derivs., calcium salts: Carbon Black: Skin corrosion/irritation Serious eye damage/irritation	Oral rat LD50- > 5000 mg/kg; Dermal rat LD50- > 2000 mg/kg body weight; Inhalation rat LC50- > 5000 mg/m ³ No data available Oral rat LD50- > 10000 mg/kg; Not classified Not classified	
Distillates (petroleum), hydrotreated heavy paraffinic: Benzenesulfonic acid, di-C10-18- alkyl derivs., calcium salts: Carbon Black: Skin corrosion/irritation Serious eye damage/irritation Respiratory or skin sensitization	Oral rat LD50- > 5000 mg/kg; Dermal rat LD50- > 2000 mg/kg body weight; Inhalation rat LC50- > 5000 mg/m ³ No data available Oral rat LD50- > 10000 mg/kg; Not classified Not classified Not classified	

12. Ecological information

Ecology - general: The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

Ecotoxicity : Distillates (petroleum), hydrotreated heavy paraffinic	100 mg/L Fish LC50; 10000 ml/l Daphnia EC50
Persistence and degradability: Bioaccumulative potential:	No data available No data available
06/08/2020	EN (English US)

Mobility in soil:

No data available

Other adverse effects:

No data available

13. Disposal considerations

Regional legislation (waste): Dispose of in accordance with applicable federal, state, and local regulations.

14. Transport information

Department of Transportation (DOT)

Not regulated for transport

Transport by sea

Not regulated for transport

Air transport

Not regulated for transport

15. Regulatory information

SARA Section 313 – Emission Reporting:

Not subject to reporting requirements of the United States SARA Section 313

CERCLA Section 103:

This product is not subject to reporting under CERLCA. However, many states have more stringent reporting requirements. Report all spills in accordance with local, state, and federal regulations.

SARA 302:

Not applicable

SARA Section 311/312 Hazard Classes: Refer to Section 2 for OSHA Hazard Classification.

California Proposition 65: This product does not require a Proposition 65 warning. Carbon black only presents a risk of cancer by inhalation of very fine dust. There is no exposure to respirable carbon black dust in the normal use of this product. For more information go to www.P65Warnings.ca.gov.

TSCA: All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

VOC Regulations: This product complies with the consumer product VOC limits of CARB, the US EPA and states adopting the OTC VOC rules.

16. Other information Revision date : 06/08/2020 Revision date : 06/08/2020

Supersedes	:	N/A
SDS Authored by	:	IHSC LLC.

NOTICE

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.