

# SAFETY DATA SHEET.

Issuing date 15-May-2017

Revision Date 21-Nov-2018

Version 2.03

## 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

### Product identifier

**Product name** 5664-0 DIESEL FUEL COND/ANTI 6

### Recommended use of the chemical and restrictions on use

**Product code** F02436

**Product Type** Flammable Liquid and Vapour  
**Synonyms** None

### Supplier's details

**Recommended Use** Diesel Additive.  
**Uses advised against** No information available

**Manufactured For:**  
Imperial Supplies LLC  
789 Armed Forces Drive  
P.O. Box 11008  
Green Bay, WI 53407-1008  
1-800-558-2808

**Manufacturer**  
American Jetway Corporation  
34136 Myrtle Street  
Wayne, MI 48184-0126  
Phone:(734) 721-5930

**Emergency telephone number**  
**Chemical Emergency Phone Number** CHEMTREC: 1-800-262-8200 ID 1195 (UNITED STATES)

## 2. HAZARDS IDENTIFICATION

### Classification

Skin corrosion/irritation	Category 2
Carcinogenicity	Category 2
Aspiration toxicity	Category 1
Flammable Liquids	Category 3

### GHS Label elements, including precautionary statements

#### Emergency Overview

#### DANGER

#### Hazard Statements

Causes skin irritation.

Suspected of causing cancer.

May be fatal if swallowed and enters airways.

Flammable Liquid and Vapour



**Appearance** Hazy

**Physical state** Liquid

**Odor** Solvent

#### Precautionary Statements - Prevention

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Wear protective gloves, protective clothing, eye protection, face protection.

Wash face, hands and any exposed skin thoroughly after handling.

Keep away from heat, sparks, open flames, hot surfaces - No smoking.

Keep container tightly closed

Ground/Bond container and receiving equipment

Use explosion-proof electrical, ventilating, lighting, equipment

Use only non-sparking tools

Take precautionary measures against static discharge

#### Precautionary Statements - Response

If exposed or concerned: Get medical advice, attention.

Specific treatment (see first aid on this label).

IF ON SKIN: Wash with plenty of soap and water.

IF ON SKIN (or hair:) Take off immediately all contaminated clothing. Rinse skin with water, shower

Wash contaminated clothing before reuse

If skin irritation occurs: Get medical advice, attention.

IF SWALLOWED: Immediately call a POISON CENTER, doctor, physician.

Do NOT induce vomiting.

In case of fire: Use CO<sub>2</sub>, dry chemical, or foam to extinguish.

#### Precautionary Statements - Storage

Store locked up.

Store in a well-ventilated place. Keep container tightly closed.

Keep cool.

#### Precautionary Statements - Disposal

Dispose of contents, container to an approved waste disposal plant.

**Hazards not otherwise classified (HNOC)**

None

**Other information**

0% of the mixture consists of ingredient(s) of unknown toxicity.

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical Name	CAS-No	Weight %*
KEROSENE	8008-20-6	70-80
SOLVENT NAPHTHA	64742-94-5	1-10
AROMATIC HYDROCARBON	64742-95-6	1-10
1,2,4-TRIMETHYL BENZENE	95-63-6	1-10
DIESEL FUEL ADDITIVE CONCENTRA	NJ 00850201001	1-10
XYLENE	1330-20-7	1-10
NAPHTHALENE	91-20-3	<1
ETHYL BENZENE	100-41-4	<1
VINYL ACETATE	108-05-4	<0.1

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

**4. FIRST AID MEASURES****First aid measures for different exposure routes**

<b>General advice</b>	Avoid contact with eyes, skin, and clothing. Avoid breathing vapors, mist, or gas.
<b>Eye contact</b>	Immediately flush with plenty of water for at least 15 minutes. After initial flushing, remove any contact lenses and continue flushing. If eye irritation persists, consult a doctor.
<b>Skin contact</b>	Wash off with soap and plenty of water. Remove and wash contaminated clothing before re-use. If on skin (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower. If skin irritation persists, call a physician.
<b>Inhalation</b>	Move to fresh air. If not breathing, give artificial respiration. If breathing has stopped, contact emergency medical services immediately.
<b>Ingestion</b>	Call a physician or Poison Control Center immediately. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Risk of product entering the lungs on vomiting after ingestion.

**Most important symptoms/effects, acute and delayed**

<b>Main Symptoms</b>	Causes skin irritation. Suspected of causing cancer. May be fatal if swallowed and enters airways.
----------------------	--

**Indication of immediate medical attention and special treatment needed, if necessary**

<b>Notes to physician</b>	Treat symptomatically.
---------------------------	------------------------

**5. FIRE-FIGHTING MEASURES****Suitable Extinguishing Media**

Water fog.Dry chemical. Foam.Carbon dioxide (CO2). Cool containers/tanks with water spray.

**Unsuitable Extinguishing Media** Do not use a solid water stream as it may scatter and spread fire. Keep away from sources of ignition - No smoking.

**Specific hazards arising from the chemical**

Flammable. Keep product and empty container away from heat and sources of ignition. In the event of fire and/or explosion do not breathe fumes. In the event of fire, cool tanks with water spray.

**Explosion Data**

**Sensitivity to Mechanical Impact** none.

**Sensitivity to Static Discharge** Yes.

**Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Use with adequate ventilation to keep the exposure levels below the OELS. Follow safe handling advice and personal protective equipment recommendations.

**Environmental precautions**

**Environmental precautions** Vapors can accumulate in low areas. Report spills as required by local and federal regulations. Do not allow material to contaminate ground water system. Do not flush into surface water or sanitary sewer system. Should not be released into the environment.

**Methods and materials for containment and cleaning up**

**Methods for Containment** Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from entering drains.

**Methods for cleaning up** Soak up with inert absorbent material. Contain liquid and collect with an inert, non-combustible material. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly. After cleaning, flush away traces with water. Prevent product from entering drains. Take precautionary measures against static discharges.

## 7. HANDLING AND STORAGE

**Precautions for safe handling**

**Advice on safe handling** Avoid breathing vapors or mists. Avoid contact with skin, eyes and clothing. Keep away from open flames, hot surfaces and sources of ignition. Handle in accordance with good industrial hygiene and safety practice. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded.

**Conditions for safe storage, including any incompatibilities**

**Technical measures/Storage conditions** Keep container tightly closed in a dry and well-ventilated place. Keep away from open flames, hot surfaces, and sources of ignition. Keep in properly labeled containers. Keep out of the reach of children. Store locked up. Keep cool.

**Incompatible products** Strong acids, alkalis, oxidizing agents.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Control parameters**

**Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
KEROSENE 8008-20-6	TWA: 200 mg/m <sup>3</sup> total hydrocarbon vapor application restricted to conditions in which there are negligible aerosol exposures Skin - potential significant contribution to overall exposure by the cutaneous route	-	TWA: 100 mg/m <sup>3</sup>
1,2,4-TRIMETHYL BENZENE 95-63-6	-	-	TWA: 25 ppm TWA: 125 mg/m <sup>3</sup>
XYLENE 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m <sup>3</sup> (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m <sup>3</sup>	Not Established
NAPHTHALENE 91-20-3	TWA: 10 ppm Skin - potential significant contribution to overall exposure by the cutaneous route	TWA: 10 ppm TWA: 50 mg/m <sup>3</sup> (vacated) TWA: 10 ppm (vacated) TWA: 50 mg/m <sup>3</sup> (vacated) STEL: 15 ppm (vacated) STEL: 75 mg/m <sup>3</sup>	IDLH: 250 ppm TWA: 10 ppm TWA: 50 mg/m <sup>3</sup> STEL: 15 ppm STEL: 75 mg/m <sup>3</sup>
ETHYL BENZENE 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m <sup>3</sup> (vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m <sup>3</sup>	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 125 ppm STEL: 545 mg/m <sup>3</sup>
VINYL ACETATE 108-05-4	STEL: 15 ppm TWA: 10 ppm	(vacated) TWA: 10 ppm (vacated) TWA: 30 mg/m <sup>3</sup> (vacated) STEL: 20 ppm (vacated) STEL: 60 mg/m <sup>3</sup>	Ceiling: 4 ppm 15 min Ceiling: 15 mg/m <sup>3</sup> 15 min
BENZENE 71-43-2	STEL: 2.5 ppm TWA: 0.5 ppm Skin - potential significant contribution to overall exposure by the cutaneous route	TWA: 10 ppm applies to industry segments exempt from the benzene standard at 29 CFR 1910.1028 TWA: 1 ppm (vacated) TWA: 10 ppm unless specified in 1910.1028 (vacated) STEL: 50 ppm 10 min unless specified in 1910.1028 (vacated) Ceiling: 25 ppm unless specified in 1910.1028 Ceiling: 25 ppm STEL: 5 ppm see 29 CFR 1910.1028	IDLH: 500 ppm TWA: 0.1 ppm STEL: 1 ppm

ACGIH: (American Conference of Governmental Industrial Hygienists)

OSHA: (Occupational Safety &amp; Health Administration)

NIOSH IDLH: Immediately Dangerous to Life or Health

**Other Exposure Guidelines**

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

**Exposure controls****Engineering Measures**Showers  
Eyewash stations  
Ventilation systems.**Individual protection measures, such as personal protective equipment****Eye/Face Protection**

Tightly fitting safety goggles.

**Skin and body protection**

Chemical resistant apron. Protective gloves.

**Respiratory protection**

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

**Hygiene measures**

Handle in accordance with good industrial hygiene and safety practice.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Physical and chemical properties**

Physical state	Liquid	Odor	Solvent
Appearance	Hazy	Odor Threshold	
Color	Yellow		
<u>Property</u>	<u>Values</u>	<u>Remarks • Methods</u>	
pH	No information available		
Melting/freezing point	No information available		
Boiling point/boiling range			
Flash Point	42 °C / 108 °F	(based on components) Based on lowest flashpoint of the products constituents.	
Evaporation rate	No information available		
Flammability (solid, gas)	No information available		
Flammability Limits in Air			
upper flammability limit			
lower flammability limit			
Vapor pressure			
Vapor density			
Specific Gravity	0.840		
Water solubility	Negligible		
Partition coefficient: n-octanol/water			
Autoignition temperature	No information available		
Decomposition temperature			
Viscosity	No information available		
Explosive properties			
<u>Other information</u>			
VOC Content(%)	95.37		

## 10. STABILITY AND REACTIVITY

**Reactivity**

No data available

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of hazardous reactions**

None under normal processing.

**Conditions to Avoid**

Heat, flames and sparks. Exposure to air or moisture over prolonged periods.

**Incompatible Materials**

Strong acids, alkalis, oxidizing agents.

**Hazardous Decomposition Products**

Carbon oxides , Hydrocarbons, Fumes. Thermal decomposition can lead to release of irritating gases and vapors.

## 11. TOXICOLOGICAL INFORMATION

**Information on likely routes of exposure****Product Information**

<b>Inhalation</b>	Respiratory irritation may occur if excessive exposure to product by inhalation.
<b>Eye contact</b>	Eye irritation may occur if excessive exposure to product occurs.
<b>Skin contact</b>	Causes skin irritation.
<b>Ingestion</b>	May be fatal if swallowed and enters airways.

**Component Information**

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
KEROSENE 8008-20-6	> 5000 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	> 5.28 mg/L ( Rat ) 4 h
SOLVENT NAPHTHA 64742-94-5	> 5000 mg/kg ( Rat )	> 2 mL/kg ( Rabbit )	> 590 mg/m <sup>3</sup> ( Rat ) 4 h
AROMATIC HYDROCARBON 64742-95-6	= 8400 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	= 3400 ppm ( Rat ) 4 h
1,2,4-TRIMETHYL BENZENE 95-63-6	= 3280 mg/kg ( Rat )	> 3160 mg/kg ( Rabbit )	= 18 g/m <sup>3</sup> ( Rat ) 4 h
XYLENE 1330-20-7	= 3500 mg/kg ( Rat )	> 4350 mg/kg ( Rabbit )	= 29.08 mg/L ( Rat ) 4 h
NAPHTHALENE 91-20-3	= 1110 mg/kg ( Rat )	= 1120 mg/kg ( Rabbit )	> 340 mg/m <sup>3</sup> ( Rat ) 1 h
ETHYL BENZENE 100-41-4	= 3500 mg/kg ( Rat )	= 15400 mg/kg ( Rabbit )	= 17.4 mg/L ( Rat ) 4 h
VINYL ACETATE 108-05-4	= 2900 mg/kg ( Rat )	= 2335 mg/kg ( Rabbit )	= 3680 ppm ( Rat ) 4 h

**Information on toxicological effects**

<b>Symptoms</b>	Causes skin irritation. Suspected of causing cancer. May be fatal if swallowed and enters airways.
-----------------	--

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

<b>Skin corrosion/irritation</b>	Irritating to skin.
<b>Sensitization</b>	Not a known sensitizer.
<b>Germ cell mutagenicity</b>	Not a germ cell mutagen.
<b>Carcinogenicity</b>	The table below indicates whether each agency has evaluated a listed ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
KEROSENE 8008-20-6	A3	Group 3	-	-
XYLENE 1330-20-7	-	Group 3	-	-
NAPHTHALENE 91-20-3	A3	Group 2B	Reasonably Anticipated	X
ETHYL BENZENE 100-41-4	A3	Group 2B	-	X
VINYL ACETATE 108-05-4	A3	Group 2B	-	X

ACGIH: (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC: (International Agency for Research on Cancer)

Group 2A - Probably Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

NTP: (National Toxicity Program)

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

OSHA: (Occupational Safety &amp; Health Administration)

X - Present

<b>Reproductive toxicity</b>	This product does not contain any known or suspected reproductive hazards.
------------------------------	--

<b>Specific target organ systemic toxicity (single exposure)</b>	No known effect based on information supplied.
<b>Specific target organ systemic toxicity (repeated exposure)</b>	No known effect based on information supplied.
<b>Chronic toxicity</b>	Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Chronic hydrocarbon abuse has been associated with irregular heart rhythms and potential cardiac arrest.
<b>Target Organ Effects</b>	No known effects under normal use conditions.
<b>Neurological effects</b>	Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.
<b>Aspiration hazard</b>	May be fatal if swallowed and enters airways.

#### Numerical measures of toxicity - Product Information

**Unknown Acute Toxicity** 0% of the mixture consists of ingredient(s) of unknown toxicity.

**The following values are calculated based on chapter 3.1 of the GHS document .**

<b>ATEmix (oral)</b>	5577 mg/kg
<b>ATEmix (dermal)</b>	49261 mg/kg
<b>ATEmix (inhalation-dust/mist)</b>	22.4 mg/l

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to microorganisms	Toxicity to daphnia and other aquatic invertebrates
SOLVENT NAPHTHA 64742-94-5	-	19 mg/L LC50 Pimephales promelas 96h static 2.34 mg/L LC50 Oncorhynchus mykiss 96h 1740 mg/L LC50 Lepomis macrochirus 96h static 45 mg/L LC50 Pimephales promelas 96h flow-through 41 mg/L LC50 Pimephales promelas 96h	-	0.95 mg/L EC50 Daphnia magna 48h
AROMATIC HYDROCARBON 64742-95-6	-	9.22 mg/L LC50 Oncorhynchus mykiss 96h	-	6.14 mg/L EC50 Daphnia magna 48h
1,2,4-TRIMETHYL BENZENE 95-63-6	-	7.19 - 8.28 mg/L LC50 Pimephales promelas 96h flow-through	-	6.14 mg/L EC50 Daphnia magna 48h
XYLENE 1330-20-7	-	13.4 mg/L LC50 Pimephales promelas 96h flow-through 2.661 - 4.093 mg/L LC50 Oncorhynchus mykiss 96h static 13.5 - 17.3 mg/L LC50 Oncorhynchus mykiss 96h 13.1 - 16.5 mg/L LC50 Lepomis macrochirus 96h flow-through 19 mg/L LC50 Lepomis macrochirus 96h 7.711 - 9.591 mg/L LC50 Lepomis macrochirus 96h static 23.53 - 29.97 mg/L LC50 Pimephales promelas 96h static 780 mg/L LC50 Cyprinus carpio 96h semi-static 780 mg/L LC50 Cyprinus carpio 96h 30.26 - 40.75 mg/L LC50 Poecilia reticulata 96h static	-	3.82 mg/L EC50 water flea 48h 0.6 mg/L LC50 Gammarus lacustris 48h
NAPHTHALENE 91-20-3	-	5.74 - 6.44 mg/L LC50 Pimephales promelas 96h flow-through 1.6 mg/L LC50 Oncorhynchus mykiss 96h flow-through 0.91 - 2.82	-	2.16 mg/L LC50 Daphnia magna 48h 1.96 mg/L EC50 Daphnia magna 48h Flow through 1.09 - 3.4 mg/L EC50 Daphnia magna 48h



		mg/L LC50 Oncorhynchus mykiss 96h static 1.99 mg/L LC50 Pimephales promelas 96h static 31.0265 mg/L LC50 Lepomis macrochirus 96h static		Static
ETHYL BENZENE 100-41-4	4.6 mg/L EC50 Pseudokirchneriella subcapitata 72h 438 mg/L EC50 Pseudokirchneriella subcapitata 96h 2.6 - 11.3 mg/L EC50 Pseudokirchneriella subcapitata 72h static 1.7 - 7.6 mg/L EC50 Pseudokirchneriella subcapitata 96h static	11.0 - 18.0 mg/L LC50 Oncorhynchus mykiss 96h static 4.2 mg/L LC50 Oncorhynchus mykiss 96h semi-static 7.55 - 11 mg/L LC50 Pimephales promelas 96h flow-through 32 mg/L LC50 Lepomis macrochirus 96h static 9.1 - 15.6 mg/L LC50 Pimephales promelas 96h static 9.6 mg/L LC50 Poecilia reticulata 96h static	-	1.8 - 2.4 mg/L EC50 Daphnia magna 48h
VINYL ACETATE 108-05-4	-	14 mg/L LC50 Pimephales promelas 96h static 15.04 - 21.54 mg/L LC50 Lepomis macrochirus 96h static 26.1 - 36.63 mg/L LC50 Poecilia reticulata 96h static	-	-

**Persistence and degradability**

.

**Bioaccumulation**

.

Chemical Name	log Pow
SOLVENT NAPHTHA 64742-94-5	6.1
1,2,4-TRIMETHYL BENZENE 95-63-6	3.63
XYLENE 1330-20-7	3.15
NAPHTHALENE 91-20-3	3.6
ETHYL BENZENE 100-41-4	3.2
VINYL ACETATE 108-05-4	0.73

**Other adverse effects**

No information available

**13. DISPOSAL CONSIDERATIONS****Waste treatment****Waste Disposal Methods**

This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261). Dispose of in accordance with federal, state, and local regulations. Dispose of in accordance with local regulations.

**Contaminated packaging**

Do not re-use empty containers.

**14. TRANSPORT INFORMATION****DOT Ground**

CONSUMER COMMODITY ORM-D  
or  
LIMITED QUANTITY

IATA UN1223, KEROSENE SOLUTION, 3, PGIII, LTD. QTY

IMDG UN1223, KEROSENE SOLUTION, 3, PGIII, LTD. QTY

**15. REGULATORY INFORMATION****SCHEDULE B CODE: 3811.90.1000.****International Inventories**

Chemical Name	TSCA	DSL/NDSL	EINECS/ELINCS	ENCS	IECSC	KECL	PICCS	AICS
KEROSENE	X	X	X	x	X	X	X	X
SOLVENT NAPHTHA	X	X	X	Not listed	X	X	X	X
AROMATIC HYDROCARBON	X	X	X	Not listed	X	X	X	X
1,2,4-TRIMETHYL BENZENE	X	X	X	X	X	X	X	X
XYLENE	X	X	X	X	X	X	X	X
NAPHTHALENE	X	X	X	X	X	X	X	X
ETHYL BENZENE	X	X	X	X	X	X	X	X
VINYL ACETATE	X	X	X	X	X	X	X	X

**Legend:****TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances**ENCS** - Japan Existing and New Chemical Substances**CHINA** - China Inventory of Existing Chemical Substances**KECL** - Korean Existing and Evaluated Chemical Substances**PICCS** - Philippines Inventory of Chemicals and Chemical Substances**AICS** - Australian Inventory of Chemical Substances**U.S. Federal Regulations****SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does contain a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %*	SARA 313 - Threshold Values %
1,2,4-TRIMETHYL BENZENE - 95-63-6	95-63-6	4.466	1.0
XYLENE - 1330-20-7	1330-20-7	2.233	1.0
NAPHTHALENE - 91-20-3	91-20-3	0.86407	0.1
ETHYL BENZENE - 100-41-4	100-41-4	0.2233	0.1

**SARA 311/312 Hazard Categories**

Acute Health Hazard	Yes
Chronic Health Star Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

**Clean Water Act**

This product does contain the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
XYLENE 1330-20-7	100 lb			X
NAPHTHALENE 91-20-3	100 lb	X	X	X
ETHYL BENZENE 100-41-4	1000 lb	X	X	X
VINYL ACETATE 108-05-4	5000 lb			X

**CERCLA**

This material, as supplied, does contain substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
XYLENE 1330-20-7	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
NAPHTHALENE 91-20-3	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
ETHYL BENZENE 100-41-4	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ
VINYL ACETATE 108-05-4	5000 lb	5000 lb	RQ 5000 lb final RQ RQ 2270 kg final RQ

**U.S. State Regulations****California Proposition 65**

This product contains the following Proposition 65 chemicals:



This product can expose you to chemicals including those listed below, which is [are] known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

Chemical Name	California Prop. 65
NAPHTHALENE - 91-20-3	Cancer/<1%
ETHYL BENZENE - 100-41-4	Cancer / <1%

**U.S. State Right-to-Know Regulations**

This product does not contain any substances regulated by state right-to-know regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
KEROSENE 8008-20-6	X	X	X
1,2,4-TRIMETHYL BENZENE 95-63-6	X	X	X
XYLENE 1330-20-7	X	X	X
NAPHTHALENE 91-20-3	X	X	X
ETHYL BENZENE 100-41-4	X	X	X
VINYL ACETATE 108-05-4	X	X	X
BENZENE 71-43-2	X	X	X

**EPA Pesticide Registration Number** Not applicable

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all the information required by the CPR.

**16. OTHER INFORMATION**

<u>NFPA</u>	Health Hazard 2	Flammability 3	Instability 0	Physical and chemical hazards -
<u>HMIS</u>	Health Hazard 2*	Flammability 3	Physical Hazard 0	Personal protection B

**Prepared By** American Jetway Corporation  
34136 Myrtle Street  
Wayne, MI 48184-0126  
**Issuing date** 15-May-2017  
**Revision Date** 21-Nov-2018  
**Revision Note**

(M)SDS sections updated: 2, 6

**Disclaimer**

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

**End of Safety Data Sheet**