

A00178 MST VANDALISM MRK RMVR 20net16

Version 1.1

Revision Date 07/14/2016

Print Date 02/06/2018

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : A00178 MST VANDALISM MRK RMVR 20net16

Material number : 00000000001001632

Manufacturer or supplier's details

Company : Zep Inc.

Address : 1310 Seaboard Industrial Blvd., NW
Atlanta, GA 30318

Telephone : 404-352-1680

Emergency telephone numbers
For SDS Information : Compliance Services 1-877-428-9937

For a Medical Emergency : 877-541-2016 Toll Free - All Calls Recorded

For a Transportation Emergency : CHEMTREC: 800-424-9300 - All Calls Recorded.
In the District of Columbia 202-483-7616

Recommended use of the chemical and restrictions on use

Recommended use : Specialty Cleaner and Remover

SECTION 2. HAZARDS IDENTIFICATION
Emergency Overview

| | |
|------------|------------------------------------|
| Appearance | Aerosol containing a liquefied gas |
| Colour | colourless |
| Odour | aromatic |

GHS Classification

Flammable aerosols : Category 1
 Gases under pressure : Liquefied gas
 Skin irritation : Category 2
 Eye irritation : Category 2A
 Reproductive toxicity : Category 2
 Specific target organ toxicity - single exposure : Category 3 (Central nervous system)
 Specific target organ toxicity - repeated exposure (Inhalation) : Category 2

GHS label elements

Hazard pictograms :



Signal word : Danger

 Hazard statements : H222 Extremely flammable aerosol.
 H280 Contains gas under pressure; may explode if heated.

A00178 MST VANDALISM MRK RMVR 20net16

Version 1.1

Revision Date 07/14/2016

Print Date 02/06/2018

H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.
 H361 Suspected of damaging fertility or the unborn child.
 H373 May cause damage to organs through prolonged or repeated exposure if inhaled.

Precautionary statements

: **Prevention:**

P201 Obtain special instructions before use.
 P202 Do not handle until all safety precautions have been read and understood.
 P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
 P211 Do not spray on an open flame or other ignition source.
 P251 Pressurized container: Do not pierce or burn, even after use.
 P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
 P264 Wash skin thoroughly after handling.
 P271 Use only outdoors or in a well-ventilated area.
 P280 Wear eye protection/ face protection.
 P280 Wear protective gloves.
 P281 Use personal protective equipment as required.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
 P304 + P340 + P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P308 + P313 IF exposed or concerned: Get medical advice/ attention.
 P332 + P313 If skin irritation occurs: Get medical advice/ attention.
 P337 + P313 If eye irritation persists: Get medical advice/ attention.
 P362 Take off contaminated clothing and wash before reuse.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
 P405 Store locked up.
 P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Disposal:

Dispose of contents/container in accordance with local regulation.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

| Chemical name | CAS-No. | Concentration [%] |
|---------------|----------|-------------------|
| acetone | 67-64-1 | >= 50 - < 70 |
| toluene | 108-88-3 | >= 10 - < 20 |

A00178 MST VANDALISM MRK RMVR 20net16

Version 1.1

Revision Date 07/14/2016

Print Date 02/06/2018

| | | |
|-----------------|----------|-------------|
| propane | 74-98-6 | >= 5 - < 10 |
| 2-butoxyethanol | 111-76-2 | >= 5 - < 10 |
| butanone | 78-93-3 | >= 5 - < 10 |
| butane | 106-97-8 | >= 5 - < 10 |

The exact percentages of disclosed substances are withheld as trade secrets.

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention.
- In case of skin contact : In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
Wash clothing before reuse.
Call a physician if irritation develops or persists.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : DO NOT induce vomiting unless directed to do so by a physician or poison control center.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Carbon dioxide (CO₂)
Foam
Dry chemical
Water
- Unsuitable extinguishing media : High volume water jet
- Hazardous combustion products : Carbon dioxide (CO₂)
Carbon monoxide
Smoke
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Further information : Use a water spray to cool fully closed containers.
Standard procedure for chemical fires.
- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

A00178 MST VANDALISM MRK RMVR 20net16

Version 1.1

Revision Date 07/14/2016

Print Date 02/06/2018

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Sweep up or vacuum up spillage and collect in suitable container for disposal.

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Dispose of rinse water in accordance with local and national regulations.
Do not breathe vapours or spray mist.
Always replace cap after use.
- Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.
No smoking.
Observe label precautions.
Keep in a cool, well-ventilated place.
Electrical installations / working materials must comply with the technological safety standards.
- Materials to avoid : Strong oxidizing agents
Do not store near acids.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
Components with workplace control parameters

| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible | Basis |
|------------|---------|----------------------------------|----------------------------------|-------|
| | | | | |

SAFETY DATA SHEET



A00178 MST VANDALISM MRK RMVR 20net16

Version 1.1

Revision Date 07/14/2016

Print Date 02/06/2018

| | | | concentration | |
|-----------------|----------|------|--------------------------|-----------|
| acetone | 67-64-1 | TWA | 500 ppm | ACGIH |
| | | STEL | 750 ppm | ACGIH |
| | | TWA | 250 ppm 590 mg/m3 | NIOSH REL |
| | | TWA | 1,000 ppm 2,400 mg/m3 | OSHA Z-1 |
| | | TWA | 750 ppm 1,800 mg/m3 | OSHA P0 |
| | | STEL | 1,000 ppm 2,400 mg/m3 | OSHA P0 |
| toluene | 108-88-3 | TWA | 20 ppm | ACGIH |
| | | TWA | 100 ppm 375 mg/m3 | NIOSH REL |
| | | ST | 150 ppm 560 mg/m3 | NIOSH REL |
| | | TWA | 200 ppm | OSHA Z-2 |
| | | CEIL | 300 ppm | OSHA Z-2 |
| | | Peak | 500 ppm | OSHA Z-2 |
| | | TWA | 100 ppm 375 mg/m3 | OSHA P0 |
| | | STEL | 150 ppm 560 mg/m3 | OSHA P0 |
| propane | 74-98-6 | TWA | 1,000 ppm | ACGIH |
| | | TWA | 1,000 ppm 1,800 mg/m3 | NIOSH REL |
| | | TWA | 1,000 ppm 1,800 mg/m3 | OSHA Z-1 |
| | | TWA | 1,000 ppm 1,800 mg/m3 | OSHA P0 |
| 2-butoxyethanol | 111-76-2 | TWA | 20 ppm | ACGIH |
| | | TWA | 5 ppm 24 mg/m3 | NIOSH REL |
| | | TWA | 50 ppm 240 mg/m3 | OSHA Z-1 |
| | | TWA | 25 ppm 120 mg/m3 | OSHA P0 |
| butanone | 78-93-3 | TWA | 200 ppm | ACGIH |
| | | STEL | 300 ppm | ACGIH |
| | | TWA | 200 ppm 590 mg/m3 | NIOSH REL |
| | | ST | 300 ppm 885 mg/m3 | NIOSH REL |
| | | TWA | 200 ppm 590 mg/m3 | OSHA Z-1 |
| | | TWA | 200 ppm 590 mg/m3 | OSHA P0 |
| | | STEL | 300 ppm 885 mg/m3 | OSHA P0 |
| butane | 106-97-8 | TWA | 800 ppm 1,900 mg/m3 | NIOSH REL |
| | | TWA | 800 ppm 1,900 mg/m3 | OSHA P0 |

Biological occupational exposure limits

SAFETY DATA SHEET



A00178 MST VANDALISM MRK RMVR 20net16

Version 1.1

Revision Date 07/14/2016

Print Date 02/06/2018

| Component | CAS-No. | Control parameters | Biological specimen | Sampling time | Permissible concentration | Basis |
|---------------------|----------|-------------------------|---------------------|----------------------------------------------------------|---------------------------|-----------|
| 2-PROPANONE | 67-64-1 | Acetone | Urine | End of shift (As soon as possible after exposure ceases) | 50 mg/l | ACGIH BEI |
| METHYLBENZENE | 108-88-3 | Toluene | In blood | Prior to last shift of workweek | 0.02 mg/l | ACGIH BEI |
| METHYLBENZENE | | Toluene | Urine | End of shift (As soon as possible after exposure ceases) | 0.03 mg/l | ACGIH BEI |
| METHYLBENZENE | | o-Cresol | Urine | End of shift (As soon as possible after exposure ceases) | 0.3 mg/g | ACGIH BEI |
| Remarks: Creatinine | | | | | | |
| 2-BUTOXYETHANOL | 111-76-2 | Butoxyacetic acid (BAA) | Urine | End of shift (As soon as possible after exposure ceases) | 200 mg/g | ACGIH BEI |
| Remarks: Creatinine | | | | | | |
| 2-BUTANONE | 78-93-3 | methyl ethyl ketone | Urine | End of shift (As soon as possible after exposure ceases) | 2 mg/l | ACGIH BEI |

Engineering measures : effective ventilation in all processing areas

Personal protective equipment

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment.
Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Remarks : The suitability for a specific workplace should be discussed

A00178 MST VANDALISM MRK RMVR 20net16

Version 1.1

Revision Date 07/14/2016

Print Date 02/06/2018

with the producers of the protective gloves.

- Eye protection : Safety glasses
Ensure that eyewash stations and safety showers are close to the workstation location.
- Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Hygiene measures : When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.
-

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : Aerosol containing a liquefied gas
- Colour : colourless
- Odour : aromatic
- Odour Threshold : No data available
- pH : No data available
- Melting point/freezing point : No data available
- Boiling point : No data available
- Flash point :
Not applicable
- Evaporation rate : No data available
- Flammability (solid, gas) : Extremely flammable aerosol.
- Upper explosion limit : No data available
- Lower explosion limit : No data available
- Vapour pressure : No data available
- Relative vapour density : No data available
- Density : 0.810 g/cm³
- Solubility(ies)
- Water solubility : partly soluble
- Partition coefficient: n-octanol/water : No data available
- Auto-ignition temperature : not determined
- Thermal decomposition : No data available
- Heat of combustion : 35.04 kJ/g

A00178 MST VANDALISM MRK RMVR 20net16

Version 1.1

Revision Date 07/14/2016

Print Date 02/06/2018

SECTION 10. STABILITY AND REACTIVITY

| | |
|------------------------------------|-------------------------------------------------------------------------------------------------------|
| Reactivity | : Stable |
| Chemical stability | : Stable under normal conditions. |
| Possibility of hazardous reactions | : Vapours may form explosive mixture with air. No decomposition if stored and applied as directed. |
| Conditions to avoid | : Heat, flames and sparks. Extremes of temperature and direct sunlight. |
| Incompatible materials | : Acids Oxidizing agents |
| Hazardous decomposition products | : Carbon monoxide Carbon dioxide (CO ₂) |

SECTION 11. TOXICOLOGICAL INFORMATION**Potential Health Effects****Carcinogenicity:**

| | |
|--------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|
| IARC | No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC. |
| ACGIH | Confirmed animal carcinogen with unknown relevance to humans 2-butoxyethanol 111-76-2 |
| OSHA | No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA. |
| NTP | No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP. |

Acute toxicity**Product:**

| | |
|---------------------------|-------------------------------------------------------------------------------------------------------------------------|
| Acute oral toxicity | : Acute toxicity estimate : 4,978 mg/kg Method: Calculation method |
| Acute inhalation toxicity | : Acute toxicity estimate : > 10 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Calculation method |
| Acute dermal toxicity | : Acute toxicity estimate : > 5,000 mg/kg Method: Calculation method |

Components:

A00178 MST VANDALISM MRK RMVR 20net16

Version 1.1

Revision Date 07/14/2016

Print Date 02/06/2018

acetone:

Acute oral toxicity : LD50 Rat: 5,800 mg/kg

Acute inhalation toxicity : LC50 Rat: 132 mg/l
Exposure time: 3 h

LC50 Rat: 50.1 mg/l

Acute dermal toxicity : LD50 Guinea pig: > 7,426 mg/kg

LD50 Rabbit: > 7,426 mg/kg

propane:Acute inhalation toxicity : LC50 Mouse: 1,237 mg/l
Exposure time: 2 hLC50 Rat: 658 mg/l
Exposure time: 4 h

LC50 Rat: 1,355 mg/l

butanone:

Acute oral toxicity : LD50 Oral Rat: 2,737 mg/kg

Acute inhalation toxicity : LC50 Mouse: 32,000 mg/l
Exposure time: 4 h

LC50 : 38,000 mg/l

Acute dermal toxicity : LD50 Dermal Rabbit: 6,480 mg/kg

butane:Acute inhalation toxicity : LC50 Mouse: 1,237 mg/l
Exposure time: 2 h

LC50 Rat: 1,355 mg/l

Skin corrosion/irritation**Product:**

Remarks: May cause skin irritation in susceptible persons.

Serious eye damage/eye irritation**Product:**

Remarks: Eye irritation

Respiratory or skin sensitisation

No data available

A00178 MST VANDALISM MRK RMVR 20net16

Version 1.1

Revision Date 07/14/2016

Print Date 02/06/2018

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

- acetone:**
- toluene:**
- propane:**
- 2-butoxyethanol:**
- butanone:**
- butane:**

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

Components:

toluene:
Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

Product:

Partition coefficient: n- : Remarks: No data available
octanol/water

Components:

toluene :

SAFETY DATA SHEET



A00178 MST VANDALISM MRK RMVR 20net16

Version 1.1

Revision Date 07/14/2016

Print Date 02/06/2018

Partition coefficient: n-octanol/water
butanone :
Partition coefficient: n-octanol/water
butane :
Partition coefficient: n-octanol/water

: Pow: 2.73
: log Pow: 0.29
: Pow: 2.89

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : No data available

Components:

toluene :

Additional ecological information : No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

| |
|-----------------------------------------------------------------------|
| Transportation Regulation: 49 CFR (USA): ORM-D, CONSUMER COMMODITY |
|-----------------------------------------------------------------------|

SAFETY DATA SHEET



A00178 MST VANDALISM MRK RMVR 20net16

Version 1.1

Revision Date 07/14/2016

Print Date 02/06/2018

Transportation Regulation: IMDG (Vessel):
UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation: IATA (Cargo Air):
UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: IATA (Passenger Air):
UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: TDG (Canada):
UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

| Components | CAS-No. | Component RQ (lbs) | Calculated product RQ (lbs) |
|------------|----------|--------------------|-----------------------------|
| toluene | 108-88-3 | 1000 | * |

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Sudden Release of Pressure Hazard
Acute Health Hazard
Chronic Health Hazard
Fire Hazard

SARA 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:
toluene 108-88-3 17 %

California Prop 65 WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

toluene 108-88-3

The components of this product are reported in the following inventories:

TSCA On TSCA Inventory

A00178 MST VANDALISM MRK RMVR 20net16

Version 1.1

Revision Date 07/14/2016


Print Date 02/06/2018

DSL All components of this product are on the Canadian DSL

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

SECTION 16. OTHER INFORMATION**Further information****NFPA:****HMIS III:**

| | |
|------------------------|-----------|
| HEALTH | 3* |
| FLAMMABILITY | 4 |
| PHYSICAL HAZARD | 2 |

0 = not significant, 1 = Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

OSHA - GHS Label Information:

Hazard pictograms



Signal word

: **Danger:**

Hazard statements

: Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure if inhaled.

Precautionary statements

: **Prevention:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapours/spray. Wash skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear eye protection/face protection. Wear protective gloves. Use personal protective equipment as required.
Response: IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/attention. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse.
Storage: Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.
Disposal: Dispose of contents/container in accordance with local regulation.

SAFETY DATA SHEET



A00178 MST VANDALISM MRK RMVR 20net16

Version 1.1

Revision Date 07/14/2016

Print Date 02/06/2018

| | |
|----------------|------------|
| Version: | 1.1 |
| Revision Date: | 07/14/2016 |
| Print Date: | 02/06/2018 |

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

Zep Inc. markets products under well recognized and established brand names such as Zep®, Zep Commercial®, Zep Professional®, Enforcer®, National Chemical™, Selig™, Misty®, Next Dimension™, Petro®, i-Chem®, TimeMist®, TimeWick™, MicrobeMax®, Country Vet®, Konk®, Original Bike Spirits®, Blue Coral®, Black Magic®, Rain-X®, Niagara National™, FC Forward Chemicals®, Rexodan®, Mykal™, and a number of private labeled brands.