



Penray Connector Sealer

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Date of issue: 10/23/2017

Revision date: 10/23/2017

Version: 1.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : Connector Sealer
Product code : 7015

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Connector Sealer

1.3. Supplier

The Penray Companies, Inc.
440 Denniston Ct.
Wheeling, IL 60090
T (800) 373-6729
rotto@penray.com

1.4. Emergency telephone number

Emergency number : (800) 373-6729
CHEMTREC (800) 424-9300
CHEMTREC International +1 (703) 527-3887 24 hr

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Flam. Aerosol 1
Press. Gas (Liq.)
Skin Irrit. 2
Repr. 2
STOT SE 3
STOT RE 2
Asp. Tox. 1

2.2. GHS Label elements, including precautionary statements

GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

Extremely flammable aerosol
Contains gas under pressure; may explode if heated
May be fatal if swallowed and enters airways
Causes skin irritation
May cause drowsiness or dizziness
Suspected of damaging fertility or the unborn child
May cause damage to organs through prolonged or repeated exposure

Precautionary statements (GHS-US) :

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat, hot surfaces, open flames, sparks. - No smoking.
Do not spray on an open flame or other ignition source.
Pressurized container: Do not pierce or burn, even after use.
Do not breathe dust, fume, gas, mist, spray, vapors.
Wash hands thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Wear eye protection, face protection, protective clothing, protective gloves.
If exposed or concerned: Get medical advice/attention.
If swallowed: Immediately call a poison center or doctor
Do NOT induce vomiting.
If on skin: Wash with plenty of water

7015

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Take off contaminated clothing and wash it before reuse.
If skin irritation occurs: Get medical advice/attention.
If inhaled: Remove person to fresh air and keep comfortable for breathing
Call a poison center or doctor if you feel unwell
Store locked up.
Protect from sunlight. Store in a well-ventilated place.
Do not expose to temperatures exceeding 50 °C/122 °F.
Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

| Name | Product identifier | % |
|---------------------|---------------------|---------|
| Toluene | (CAS-No.) 108-88-3 | 30 - 40 |
| Propane | (CAS-No.) 74-98-6 | 5 - 10 |
| Butane | (CAS-No.) 106-97-8 | 5 - 10 |
| Butene, homopolymer | (CAS-No.) 9003-29-6 | 1 - 5 |
| n-Heptane | (CAS-No.) 142-82-5 | < 5 |

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : If inhaled and if breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

First-aid measures after skin contact : IF ON SKIN: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.

First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. Never give anything by mouth to an unconscious person.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation : May cause irritation to the respiratory tract. May cause drowsiness or dizziness.

Symptoms/effects after skin contact : Causes skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.

Symptoms/effects after eye contact : May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.

Symptoms/effects after ingestion : May be fatal if swallowed and enters airways. May result in aspiration into the lungs, causing chemical pneumonia. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.

4.3. Immediate medical attention and special treatment, if necessary

Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.

Unsuitable extinguishing media : Do not use water jet.

5.2. Specific hazards arising from the chemical

Fire hazard : Extremely flammable aerosol. Products of combustion may include, and are not limited to: oxides of carbon.

Explosion hazard : Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.

7015

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Reactivity : No dangerous reactions known under normal conditions of use.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Use water spray or fog for cooling exposed containers.
Protection during firefighting : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate every possible source of ignition. Use only non-sparking tools. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

For containment : Stop leak if safe to do so. Remove ignition sources. Absorb and/or contain spill with inert material (sand, vermiculite or other appropriate material), then place in suitable container. Do not flush into surface water or sewer system. Wear recommended personal protective equipment.

Methods for cleaning up : Sweep or shovel spills into appropriate container for disposal. Provide ventilation.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Pressurized container: Do not pierce or burn, even after use. Hazardous waste due to potential risk of explosion.

Precautions for safe handling : Keep away from sources of ignition - No smoking. Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapors/spray. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke. Take precautionary measures against static discharge. Use only non-sparking tools. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Use only in well ventilated areas.

Hygiene measures : Wash contaminated clothing before reuse. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed.

Storage conditions : Keep out of the reach of children. Keep container tightly closed. Do not expose to temperatures exceeding 50 °C/ 122 °F. Keep in fireproof place. Store away from direct sunlight or other heat sources. Store in a dry, cool and well-ventilated place. Store locked up.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

| Toluene (108-88-3) | | |
|--------------------|--------------------------------------------------------------------------------------|---------------------------|
| ACGIH | ACGIH TWA (ppm) | 20 ppm |
| OSHA | OSHA PEL (TWA) (ppm) | 200 ppm |
| OSHA | OSHA PEL (Ceiling) (ppm) | 300 ppm |
| OSHA | Acceptable maximum peak above the acceptable ceiling concentration for an 8-hr shift | 500 ppm Peak (10 minutes) |
| IDLH | US IDLH (ppm) | 500 ppm |

7015

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

| Toluene (108-88-3) | | |
|----------------------------------------|------------------------------------------|-----------------------------|
| NIOSH | NIOSH REL (TWA) (mg/m ³) | 375 mg/m ³ |
| NIOSH | NIOSH REL (TWA) (ppm) | 100 ppm |
| NIOSH | NIOSH REL (STEL) (mg/m ³) | 560 mg/m ³ |
| NIOSH | NIOSH REL (STEL) (ppm) | 150 ppm |
| Propane (74-98-6) | | |
| ACGIH | Local name | Propane |
| ACGIH | Remark (ACGIH) | Simple Asphyxiant |
| ACGIH | Regulatory reference | ACGIH 2017 |
| OSHA | OSHA PEL (TWA) (mg/m ³) | 1800 mg/m ³ |
| OSHA | OSHA PEL (TWA) (ppm) | 1000 ppm |
| OSHA | Regulatory reference (US-OSHA) | OSHA |
| IDLH | US IDLH (ppm) | 2100 ppm (10% LEL) |
| NIOSH | NIOSH REL (TWA) (mg/m ³) | 1800 mg/m ³ |
| NIOSH | NIOSH REL (TWA) (ppm) | 1000 ppm |
| Butane (106-97-8) | | |
| ACGIH | ACGIH STEL (ppm) | 1000 ppm (explosion hazard) |
| IDLH | US IDLH (ppm) | 1600 ppm (>10% LEL) |
| NIOSH | NIOSH REL (TWA) (mg/m ³) | 1900 mg/m ³ |
| NIOSH | NIOSH REL (TWA) (ppm) | 800 ppm |
| Butene, homopolymer (9003-29-6) | | |
| Not applicable | | |
| n-Heptane (142-82-5) | | |
| ACGIH | ACGIH TWA (ppm) | 400 ppm |
| ACGIH | ACGIH STEL (ppm) | 500 ppm |
| OSHA | OSHA PEL (TWA) (mg/m ³) | 2000 mg/m ³ |
| OSHA | OSHA PEL (TWA) (ppm) | 500 ppm |
| IDLH | US IDLH (ppm) | 750 ppm |
| NIOSH | NIOSH REL (TWA) (mg/m ³) | 350 mg/m ³ |
| NIOSH | NIOSH REL (TWA) (ppm) | 85 ppm |
| NIOSH | NIOSH REL (ceiling) (mg/m ³) | 1800 mg/m ³ |
| NIOSH | NIOSH REL (ceiling) (ppm) | 440 ppm |

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Wear suitable gloves resistant to chemical penetration

Eye protection:

Safety glasses or goggles are recommended when using product.

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

7015

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Other information:

Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|---------------------------------------------|-------------------------------|
| Physical state | : Liquid |
| Appearance | : Aerosol |
| Color | : Colorless |
| Odor | : Solvent |
| Odor threshold | : No data available |
| pH | : No data available |
| Melting point | : No data available |
| Freezing point | : No data available |
| Boiling point | : No data available |
| Flash point | : - 76 °F (Butane) |
| Relative evaporation rate (butyl acetate=1) | : No data available |
| Flammability (solid, gas) | : Extremely flammable aerosol |
| Vapor pressure | : No data available |
| Relative vapor density at 20 °C | : No data available |
| Relative density | : 0.76 |
| Solubility | : No data available |
| Partition coefficient n-octanol/water | : No data available |
| Auto-ignition temperature | : No data available |
| Decomposition temperature | : No data available |
| Viscosity, kinematic | : No data available |
| Viscosity, dynamic | : No data available |
| Explosion limits | : No data available |
| Explosive properties | : No data available |
| Oxidizing properties | : No data available |

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

10.2. Chemical stability

No additional information available

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Heat. Sparks. Open flame. Direct sunlight. Incompatible materials.

10.5. Incompatible materials

Strong oxidizers.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

7015

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

| Toluene (108-88-3) | |
|-----------------------------|-------------------------------------------|
| LD50 oral rat | 2600 mg/kg |
| LD50 dermal rabbit | 12000 mg/kg |
| LC50 inhalation rat | 12.5 mg/l/4h |
| ATE US (oral) | 2600 mg/kg body weight |
| ATE US (dermal) | 12000 mg/kg body weight |
| ATE US (vapors) | 12.5 mg/l/4h |
| ATE US (dust, mist) | 12.5 mg/l/4h |
| Propane (74-98-6) | |
| LC50 inhalation rat | > 800000 ppm (Exposure time: 15 min) |
| Butane (106-97-8) | |
| LC50 inhalation rat | 658 g/m ³ (Exposure time: 4 h) |
| ATE US (vapors) | 658 mg/l/4h |
| ATE US (dust, mist) | 658 mg/l/4h |
| n-Heptane (142-82-5) | |
| LD50 dermal rabbit | 3000 mg/kg |
| LC50 inhalation rat | 103 g/m ³ (Exposure time: 4 h) |
| ATE US (dermal) | 3000 mg/kg body weight |
| ATE US (vapors) | 103 mg/l/4h |
| ATE US (dust, mist) | 103 mg/l/4h |

| | |
|-----------------------------------|---------------------------|
| Skin corrosion/irritation | : Causes skin irritation. |
| Serious eye damage/irritation | : Not classified |
| Respiratory or skin sensitization | : Not classified |
| Germ cell mutagenicity | : Not classified |
| Carcinogenicity | : Not classified |

| Toluene (108-88-3) | |
|---------------------------|----------------------|
| IARC group | 3 - Not classifiable |

| | |
|----------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Reproductive toxicity | : Suspected of damaging fertility or the unborn child. |
| Specific target organ toxicity – single exposure | : May cause drowsiness or dizziness. |
| Specific target organ toxicity – repeated exposure | : May cause damage to organs through prolonged or repeated exposure. |
| Aspiration hazard | : May be fatal if swallowed and enters airways. |
| Symptoms/effects after inhalation | : May cause irritation to the respiratory tract. May cause drowsiness or dizziness. |
| Symptoms/effects after skin contact | : Causes skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin. |
| Symptoms/effects after eye contact | : May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling. |
| Symptoms/effects after ingestion | : May be fatal if swallowed and enters airways. May result in aspiration into the lungs, causing chemical pneumonia. May cause gastrointestinal irritation, nausea, vomiting and diarrhea. |
| Other information | : Likely routes of exposure: ingestion, inhalation, skin and eye. |

SECTION 12: Ecological information

12.1. Toxicity

| | |
|-------------------|-------------------------------------------------------------------|
| Ecology - general | : May cause long-term adverse effects in the aquatic environment. |
|-------------------|-------------------------------------------------------------------|

| Toluene (108-88-3) | |
|-----------------------------|----------------------------------------------------------------------------------------|
| LC50 fish 1 | 15.22 - 19.05 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through]) |
| EC50 Daphnia 1 | 5.46 - 9.83 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static]) |
| LC50 fish 2 | 12.6 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static]) |
| EC50 Daphnia 2 | 11.5 mg/l (Exposure time: 48 h - Species: Daphnia magna) |
| n-Heptane (142-82-5) | |
| LC50 fish 1 | 375 mg/l (Exposure time: 96 h - Species: Cichlid fish) |

7015

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

12.2. Persistence and degradability

| 7015 | |
|-------------------------------|------------------|
| Persistence and degradability | Not established. |

12.3. Bioaccumulative potential

| 7015 | |
|---------------------------|------------------|
| Bioaccumulative potential | Not established. |

| Toluene (108-88-3) | |
|---------------------------------------|-----|
| Partition coefficient n-octanol/water | 2.7 |

| Propane (74-98-6) | |
|---------------------------------------|-----|
| Partition coefficient n-octanol/water | 2.3 |

| Butane (106-97-8) | |
|---------------------------------------|------|
| Partition coefficient n-octanol/water | 2.89 |

| n-Heptane (142-82-5) | |
|---------------------------------------|------|
| Partition coefficient n-octanol/water | 4.66 |

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on the global warming : No known effects from this product.

| Toluene (108-88-3) | |
|----------------------------------------------|-----|
| 1990 Hazardous Air Pollutant (Clean Air Act) | Yes |

Other information : No other effects known.

SECTION 13: Disposal considerations

13.1. Disposal methods

Product/Packaging disposal recommendations : Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation. The generation of waste should be avoided or minimized wherever possible.

Additional information : Flammable vapors may accumulate in the container.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

UN-No.(DOT) : UN1950
Proper Shipping Name (DOT) : Aerosols
Class (DOT) : 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115
Hazard labels (DOT) :



SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

15.2. International regulations

No additional information available

15.3. US State regulations

California Proposition 65 - This product contains substances known to the state of California to cause cancer, developmental and/or reproductive harm

7015

Safety Data Sheet


according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

SECTION 16: Other information

Date of issue : 10/23/2017
Revision date : 10/23/2017
Other information : None.
Prepared by : Nexreg Compliance Inc.
www.Nexreg.com



NFPA health hazard : 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.
NFPA fire hazard : 4 - Materials that rapidly or completely vaporize at atmospheric pressure and normal ambient temperature or that are readily dispersed in air and burn readily.
NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.