

SAFETY DATA SHEET

1. Identification

Product identifier: STONE AND CHIP GUARD COATING BLACK - 6799

Other means of identification

SDS number: RE1000044978

Recommended restrictions

Recommended use: Coating

Restrictions on use: Not known.

Manufacturer Information

Manufacturer

Company Name: IMPERIAL SUPPLIES LLC
Address: PO BOX 11008
GREEN BAY, WI 54307-1008
Telephone: 800-558-2808

Emergency telephone number: 1-866-836-8855

2. Hazard(s) identification

Hazard Classification

Physical Hazards

Flammable aerosol	Category 1
Gases under pressure	Liquefied gas

Health Hazards

Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 2A
Carcinogenicity	Category 1A
Toxic to reproduction	Category 2
Specific Target Organ Toxicity - Single Exposure	Category 3 ¹

Target Organs

1. Narcotic effect.

Environmental Hazards

Acute hazards to the aquatic environment	Category 3
---	------------

Label Elements

Hazard Symbol:



Signal Word:

Danger

Hazard Statement: Extremely flammable aerosol.
Causes skin irritation.
Causes serious eye irritation.
May cause cancer.
Suspected of damaging fertility or the unborn child.
May cause drowsiness or dizziness.
Harmful to aquatic life.
Contains gas under pressure; may explode if heated.

Precautionary Statements

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Avoid release to the environment.

Response: IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Call a POISON CENTER/doctor if you feel unwell. Specific treatment (see on this label). Take off contaminated clothing.

Storage: Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store locked up. Store in a well-ventilated place. Keep container tightly closed.

Disposal: Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Hazard(s) not otherwise classified (HNOC): None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
2-Propanone	67-64-1	20 - <50%
Toluene	108-88-3	10 - <20%
Propane	74-98-6	10 - <20%
Carbonic acid calcium salt (1:1)	471-34-1	5 - <10%
Benzene, dimethyl-	1330-20-7	1 - <5%
Carbon black	1333-86-4	1 - <5%
Benzene, ethyl-	100-41-4	0.1 - <1%
Crystalline Silica	14808-60-7	0.1 - <1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.

Inhalation: Move to fresh air.

Skin Contact:	Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash contaminated clothing before reuse. Get medical attention.
Eye contact:	Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention.

Most important symptoms/effects, acute and delayed

Symptoms:	No data available.
Hazards:	No data available.

Indication of immediate medical attention and special treatment needed

Treatment:	No data available.
-------------------	--------------------

5. Fire-fighting measures

General Fire Hazards:	Use water spray to keep fire-exposed containers cool. Fight fire from a protected location. Move containers from fire area if you can do so without risk.
------------------------------	---

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical:	Vapors may travel considerable distance to a source of ignition and flash back.
--	---

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No data available.

Special protective equipment for fire-fighters: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind. See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away.

Methods and material for containment and cleaning up: Absorb spill with vermiculite or other inert material, then place in a container for chemical waste.

Notification Procedures: Prevent entry into waterways, sewer, basements or confined areas. Stop the flow of material, if this is without risk. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop leak if you can do so without risk.

Environmental Precautions: Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water sources or sewer.

7. Handling and storage

Precautions for safe handling: Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Avoid contact with eyes. Wash hands thoroughly after handling. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid contact with skin.

Conditions for safe storage, including any incompatibilities: Store locked up. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Aerosol Level 2

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values	Source	
2-Propanone	STEL	1,000 ppm 2,400 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)	
	PEL	1,000 ppm 2,400 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)	
	TWA	250 ppm	US. ACGIH Threshold Limit Values, as amended (03 2015)	
	TWA	750 ppm 1,800 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)	
	STEL	500 ppm	US. ACGIH Threshold Limit Values, as amended (03 2015)	
	REL	250 ppm 590 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005)	
Toluene	STEL	150 ppm 560 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)	
	REL	100 ppm 375 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005)	
	TWA	100 ppm 375 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)	
	Ceiling	300 ppm	US. OSHA Table Z-2 (29 CFR 1910.1000), as amended (02 2006)	
	TWA	20 ppm	US. ACGIH Threshold Limit Values, as amended (2008)	
	TWA	200 ppm	US. OSHA Table Z-2 (29 CFR 1910.1000), as amended (02 2006)	
Propane	MAX. CONC	500 ppm	US. OSHA Table Z-2 (29 CFR 1910.1000), as amended (02 2006)	
	STEL	150 ppm 560 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005)	
	REL	1,000 ppm 1,800 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005)	
	PEL	1,000 ppm 1,800 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)	
Carbonic acid calcium salt (1:1) - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)	
	TWA	5 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)	
	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)	
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)	
	REL	10 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2010)	
	REL	5 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2010)	
	Carbonic acid calcium salt (1:1) - Respirable fraction.	TWA	15 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
	Carbonic acid calcium salt (1:1) - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
	Carbonic acid calcium salt (1:1) - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
	Carbonic acid calcium salt (1:1) - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)

Benzene, dimethyl-	TWA	100 ppm	435 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
	TWA	100 ppm		US. ACGIH Threshold Limit Values, as amended (2008)
	PEL	100 ppm	435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
	STEL	150 ppm	655 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
	STEL	150 ppm		US. ACGIH Threshold Limit Values, as amended (2008)
	STEL	150 ppm	655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2016)
	REL	100 ppm	435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2016)
Carbon black	REL		3.5 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005)
	PEL		3.5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Carbon black - Inhalable fraction.	TWA		3 mg/m3	US. ACGIH Threshold Limit Values, as amended (12 2010)
Carbon black	TWA		3.5 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
Carbon black - as PAHs	REL		0.1 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2016)
Benzene, ethyl-	STEL	125 ppm	545 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005)
	REL	100 ppm	435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005)
	PEL	100 ppm	435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
	STEL	125 ppm	545 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
	TWA	100 ppm	435 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
	TWA	20 ppm		US. ACGIH Threshold Limit Values, as amended (12 2010)
Ethanol	REL	1,000 ppm	1,900 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005)
	PEL	1,000 ppm	1,900 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
	TWA	1,000 ppm	1,900 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
	STEL	1,000 ppm		US. ACGIH Threshold Limit Values, as amended (2009)
Naphtha (petroleum), hydrotreated light	REL	100 ppm	400 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2010)
	TWA	100 ppm	400 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
	PEL	100 ppm	400 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (03 2016)
Crystalline Silica - Respirable dust.	REL		0.05 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005)
Crystalline Silica - Respirable.	TWA		2.4 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
	TWA		0.1 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
Crystalline Silica - Respirable fraction.	TWA		0.025 mg/m3	US. ACGIH Threshold Limit Values, as amended (2008)
Crystalline Silica - Respirable dust.	TWA		0.1 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
Crystalline Silica - Respirable dust.	TWA		0.05 mg/m3	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053), as amended (03 2016)
Crystalline Silica - Respirable dust.	PEL		0.05 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (03 2016)
Crystalline Silica - Respirable dust.	OSHA_ACT		0.025 mg/m3	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053), as amended (03 2016)
2-Propanol, 2-methyl-	PEL	100 ppm	300 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
	TWA	100 ppm		US. ACGIH Threshold Limit Values, as amended (2008)
	STEL	150 ppm	450 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
	REL	100 ppm	300 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005)

	STEL	150 ppm	450 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005)
	TWA	100 ppm	300 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
2-Propanone (acetone: Sampling time: End of shift.)	25 mg/l (Urine)	ACGIH BEL (03 2015)
Toluene (toluene: Sampling time: End of shift.)	0.03 mg/l (Urine)	ACGIH BEL (03 2013)
Toluene (o-Cresol, with hydrolysis: Sampling time: End of shift.)	0.3 mg/g (Creatinine in urine)	ACGIH BEL (03 2013)
Toluene (toluene: Sampling time: Prior to last shift of work week.)	0.02 mg/l (Blood)	ACGIH BEL (03 2013)
Benzene, dimethyl- (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEL (03 2013)
Benzene, ethyl- (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEL (02 2014)

Appropriate Engineering Controls No data available.

Individual protection measures, such as personal protective equipment

General information: Provide easy access to water supply and eye wash facilities. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Eye/face protection: Wear safety glasses with side shields (or goggles).

Skin Protection

Hand Protection: No data available.

Other:

Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.

Respiratory Protection: In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor.

Hygiene measures: Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Avoid contact with eyes. When using do not smoke. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Wash contaminated clothing before reuse. Avoid contact with skin.

9. Physical and chemical properties

Appearance

Physical state: liquid

Form: Spray Aerosol

Color: No data available.

Odor: No data available.

Odor threshold: No data available.

pH: No data available.

Melting point/freezing point: No data available.

Initial boiling point and boiling range: No data available.

Flash Point: -104.44 °C

Evaporation rate: No data available.

Flammability (solid, gas):	No data available.
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	3,447 - 4,826 hPa (20 °C)
Vapor density:	No data available.
Density:	No data available.
Relative density:	No data available.
Solubility(ies)	
Solubility in water:	No data available.
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	No data available.
Hazardous Decomposition Products:	No data available.

11. Toxicological information

Information on likely routes of exposure

Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.
Ingestion:	No data available.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.
Ingestion:	No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product: Not classified for acute toxicity based on available data.

Specified substance(s):

2-Propanone	LD 50 (Rat): 5,800 mg/kg
Toluene	LD 50 (Rat): 5,580 mg/kg
Carbonic acid calcium salt (1:1)	LD 50 (Rat): > 2,000 mg/kg
Benzene, dimethyl-	LD 50 (Rat): 3,523 mg/kg
Carbon black	LD 50 (Rat): > 8,000 mg/kg
Benzene, ethyl-	LD 50 (Rat): 3,500 mg/kg
Crystalline Silica	LD 50: > 5,000 mg/kg

Dermal

Product: Not classified for acute toxicity based on available data.

Specified substance(s):

2-Propanone	LD 50 (Rabbit): > 7,426 mg/kg
Toluene	LD 50 (Rabbit): > 5,000 mg/kg
Carbonic acid calcium salt (1:1)	LD 50 (Rat): > 2,000 mg/kg
Benzene, dimethyl-	LD 50: 2,000 mg/kg LD 50 (Rabbit): 12,126 mg/kg
Benzene, ethyl-	ATE: > 2,000 mg/kg
Crystalline Silica	LD 50: > 5,000 mg/kg

Inhalation

Product: ATEmix: 8.71 mg/l

Repeated dose toxicity

Product: No data available.

Specified substance(s):

2-Propanone	NOAEL (Rat(Male), Oral, 13 Weeks): 10,000 ppm(m) Oral Experimental result, Key study
Toluene	LOAEL (Rat(Female, Male), Oral, 13 Weeks): 1,250 mg/kg (Target Organ(s): Liver, Kidney) Oral Experimental result, Key study NOAEL (Rat(Female, Male), Inhalation): 625 ppm(m) Inhalation Experimental result, Key study NOAEL (Rat(Female, Male), Inhalation - vapor): 2,355 mg/l Inhalation Experimental result, Key study
Propane	NOAEL (Rat(Female, Male), Inhalation, >= 28 d): 4,000 ppm(m) Inhalation Experimental result, Key study LOAEL (Rat(Female, Male), Inhalation, >= 28 d): 12,000 ppm(m) Inhalation Experimental result, Key study
Carbonic acid calcium salt (1:1)	NOAEL (Mouse(Female, Male), Oral, 28 d): 1,300 mg/kg Oral Experimental result, Supporting study

Benzene, dimethyl-	NOAEL (Rat(Female), Oral, 90 d): 150 mg/kg Oral Experimental result, Key study
Carbon black	NOAEL (Rat(Female), Oral, 52 - 104 Weeks): 52 mg/kg Oral Experimental result, Key study NOAEL (Rat(Male), Inhalation): 1.1 mg/m ³ Inhalation Experimental result, Key study
Benzene, ethyl-	NOAEL (Mouse(Female, Male), Inhalation, 104 Weeks): 75 ppm(m) Inhalation Experimental result, Key study NOAEL (Rat(Female, Male), Oral, 28 d): 75 mg/kg Oral Experimental result, Key study

Skin Corrosion/Irritation

Product: No data available.

Specified substance(s):

2-Propanone	in vivo (Rabbit): Not irritant Experimental result, Supporting study
Toluene	in vivo (Rabbit): Irritating Experimental result, Key study
Carbonic acid calcium salt (1:1)	in vivo (Rabbit): Not irritant Experimental result, Key study
Benzene, dimethyl-	in vivo (Rabbit): Moderate irritant Experimental result, Weight of Evidence study estimated Irritating.
Carbon black	in vivo (Rabbit): Not irritant Experimental result, Key study

Serious Eye Damage/Eye Irritation

Product: No data available.

Specified substance(s):

2-Propanone	Irritating. Rabbit, 24 hrs: Minimum grade of severe eye irritant
Toluene	Rabbit, 24 - 72 hrs: Not irritating
Carbonic acid calcium salt (1:1)	Rabbit, 24 - 72 hrs: Not irritating
Benzene, dimethyl-	Rabbit, 1 hrs: Slightly irritating (Not Classified)
Carbon black	Rabbit, 24 - 72 hrs: Not irritating

Respiratory or Skin Sensitization

Product: No data available.

Specified substance(s):

2-Propanone	Skin sensitization:, in vivo (Guinea pig): Non sensitising
Toluene	Skin sensitization:, in vivo (Guinea pig): Non sensitising
Carbon black	Skin sensitization:, in vivo (Guinea pig): Non sensitising
Benzene, ethyl-	Skin sensitization:, in vivo (Human): Non sensitising

Carcinogenicity

Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Carbon black	Overall evaluation: 2B. Possibly carcinogenic to humans.
Benzene, ethyl-	Overall evaluation: 2B. Possibly carcinogenic to humans.
Crystalline Silica	Overall evaluation: 1. Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Crystalline Silica	Known To Be Human Carcinogen.
--------------------	-------------------------------

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended:

Crystalline Silica Cancer

Germ Cell Mutagenicity

In vitro

Product: No data available.

In vivo

Product: No data available.

Reproductive toxicity

Product: No data available.

Specified substance(s):

Toluene Suspected of damaging fertility or the unborn child.

Specific Target Organ Toxicity - Single Exposure

Product: No data available.

Specified substance(s):

2-Propanone Inhalation - vapor: Narcotic effect. - Category 3 with narcotic effects.

Toluene Inhalation - vapor: Narcotic effect. - Category 3 with narcotic effects.

Specific Target Organ Toxicity - Repeated Exposure

Product: No data available.

Specified substance(s):

Toluene Category 2

Benzene, ethyl- Category 2

Target Organs

Specific Target Organ Toxicity - Single Exposure: Narcotic effect.

Aspiration Hazard

Product: No data available.

Specified substance(s):

Toluene May be fatal if swallowed and enters airways.

Benzene, ethyl- May be fatal if swallowed and enters airways.

Other effects: No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

2-Propanone LC 50 (Oncorhynchus mykiss, 96 h): 5,540 mg/l Experimental result, Key study

Toluene LC 50 (Oncorhynchus kisutch, 96 h): 5.5 mg/l Experimental result, Key study

Propane LC 50 (Various, 96 h): 147.54 mg/l QSAR QSAR, Key study

Carbonic acid calcium salt (1:1) LC 50 (Western mosquitofish (Gambusia affinis), 96 h): > 56,000 mg/l Mortality

Carbon black	LC 0 (Danio rerio, 96 h): 1,000 mg/l Experimental result, Key study
Benzene, ethyl-	LC 50 (Fathead minnow (Pimephales promelas), 96 h): 38.9 - 62.83 mg/l Mortality
Aquatic Invertebrates	
Product:	No data available.
Specified substance(s):	
2-Propanone	LC 50 (Daphnia pulex, 48 h): 8,800 mg/l Experimental result, Key study
Toluene	LC 50 (Water flea (Daphnia magna), 48 h): 54.6 - 174.7 mg/l Mortality LC 50 (Ceriodaphnia dubia, 2 d): 3.78 mg/l Experimental result, Key study
Carbon black	EC 50 (Daphnia magna, 24 h): > 5,600 mg/l Experimental result, Key study
Benzene, ethyl-	LC 50 (Water flea (Daphnia magna), 24 h): 57 - 100 mg/l Mortality

Chronic hazards to the aquatic environment:

Fish

Product:	No data available.
Specified substance(s):	
Toluene	NOAEL (Oncorhynchus kisutch): 1.39 mg/l Experimental result, Key study LOAEL (Oncorhynchus kisutch): 2.77 mg/l Experimental result, Key study
Carbon black	NOAEL (Salmo sp.): 17 mg/l QSAR QSAR, Key study

Aquatic Invertebrates

Product:	No data available.
Specified substance(s):	
2-Propanone	LOAEL (Daphnia magna): 2,212 mg/l Experimental result, Key study NOAEL (Daphnia magna): 2,212 mg/l Experimental result, Key study
Toluene	LOAEL (Ceriodaphnia dubia): 2.76 mg/l Experimental result, Key study NOAEL (Ceriodaphnia dubia): 0.74 mg/l Experimental result, Key study
Carbon black	EC 50 (Daphnia sp.): 4.9 mg/l QSAR QSAR, Key study
Benzene, ethyl-	LC 50 (Ceriodaphnia dubia): 3.2 mg/l Other, Key study NOAEL (Ceriodaphnia dubia): 1 mg/l Other, Key study

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product:	No data available.
Specified substance(s):	
2-Propanone	90.9 % (28 d) Detected in water. Experimental result, Key study
Toluene	100 % (14 d) Detected in water. Experimental result, Weight of Evidence study 86 % Detected in water. Experimental result, Weight of Evidence study
Propane	100 % (385.5 h) Detected in water. Experimental result, Key study 50 % (3.19 d) Detected in water. QSAR, Weight of Evidence study

Benzene, dimethyl-	87.8 % Detected in water. Read-across from supporting substance (structural analogue or surrogate), Key study
Benzene, ethyl-	2.7 % Detected in water. Other, Supporting study 70 - 80 % (28 d) Detected in water. Experimental result, Key study

BOD/COD Ratio

Product: No data available.

Bioaccumulative potential

Bioconcentration Factor (BCF)

Product: No data available.

Specified substance(s):

2-Propanone	Haddock, adult, Bioconcentration Factor (BCF): 0.69 Aquatic sediment Experimental result, Not specified
Toluene	Leuciscus idus, Bioconcentration Factor (BCF): 90 Aquatic sediment Experimental result, Key study
Benzene, dimethyl-	Oncorhynchus mykiss, Bioconcentration Factor (BCF): > 7.6 - < 21.6 Aquatic sediment Experimental result, Key study
Benzene, ethyl-	Carassius auratus, Bioconcentration Factor (BCF): 15.5 Aquatic sediment Other, Supporting study

Partition Coefficient n-octanol / water (log Kow)

Product: No data available.

Specified substance(s):

Benzene, dimethyl-	Log Kow: 2.77 - 3.15 No Not specified, Not specified
Benzene, ethyl-	Log Kow: 3.13 - 3.14 No Other, Supporting study

Mobility in soil: No data available.

Known or predicted distribution to environmental compartments

2-Propanone	No data available.
Toluene	No data available.
Propane	No data available.
Carbonic acid calcium salt (1:1)	No data available.
Benzene, dimethyl-	No data available.
Carbon black	No data available.
Benzene, ethyl-	No data available.
Crystalline Silica	No data available.

Other adverse effects: Harmful to aquatic organisms.

13. Disposal considerations

Disposal instructions: Discharge, treatment, or disposal may be subject to national, state, or local laws.

Contaminated Packaging: No data available.

14. Transport information

DOT

UN Number:	UN 1950
UN Proper Shipping Name:	Aerosols, flammable
Transport Hazard Class(es)	
Class:	2.1
Label(s):	–
Packing Group:	–
Environmental Hazards:	No
Marine Pollutant	No
Special precautions for user:	Not regulated.

IMDG

UN Number:	UN 1950
UN Proper Shipping Name:	Aerosols, flammable
Transport Hazard Class(es)	
Class:	2.1
Label(s):	–
EmS No.:	
Packing Group:	–
Environmental Hazards:	No
Marine Pollutant	No
Special precautions for user:	Not regulated.

IATA

UN Number:	UN 1950
Proper Shipping Name:	Aerosols, flammable
Transport Hazard Class(es):	
Class:	2.1
Label(s):	–
Packing Group:	–
Environmental Hazards:	No
Marine Pollutant	No
Special precautions for user:	Not regulated.

15. Regulatory information

US Federal Regulations

Restrictions on use: Not known.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended

<u>Chemical Identity</u>	<u>OSHA hazard(s)</u>
Crystalline Silica	Lung effects Immune system effects Cancer Kidney effects

CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u>	<u>Reportable quantity</u>
2-Propanone	lbs. 5000
Toluene	lbs. 1000
Propane	lbs. 100
Benzene, dimethyl-	lbs. 100
Benzene, ethyl-	lbs. 1000
Ethanol	lbs. 100
2-Propanol, 2-methyl-	lbs. 100

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

- Fire Hazard
- Immediate (Acute) Health Hazards
- Delayed (Chronic) Health Hazard
- Flammable aerosol
- Skin Corrosion/Irritation
- Serious Eye Damage/Eye Irritation
- Carcinogenicity
- Toxic to reproduction
- Specific Target Organ Toxicity - Single Exposure

SARA 302 Extremely Hazardous Substance

<u>Chemical Identity</u>	<u>Reportable quantity</u>	<u>Threshold Planning Quantity</u>
2-Propanone		

SARA 304 Emergency Release Notification

<u>Chemical Identity</u>	<u>Reportable quantity</u>
2-Propanone	lbs. 5000
Toluene	lbs. 1000
Propane	lbs. 100
Benzene, dimethyl-	lbs. 100
Benzene, ethyl-	lbs. 1000
Ethanol	lbs. 100
2-Propanol, 2-methyl-	lbs. 100

SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
2-Propanone	10000 lbs
Toluene	10000 lbs
Propane	10000 lbs
Carbonic acid calcium salt (1:1)	10000 lbs
Benzene, dimethyl-	10000 lbs
Carbon black	10000 lbs
Benzene, ethyl-	10000 lbs
Ethanol	10000 lbs
Naphtha (petroleum), hydrotreated light	10000 lbs
Crystalline Silica	10000 lbs
2-Propanol, 2-methyl-	10000 lbs

SARA 313 (TRI Reporting)

<u>Chemical Identity</u>	<u>Reporting threshold for other users</u>	<u>Reporting threshold for manufacturing and processing</u>
Toluene	lbs	lbs.
Benzene, dimethyl-	lbs	lbs.
Benzene, ethyl-	lbs	lbs.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

US State Regulations

US. California Proposition 65

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

Toluene	Developmental toxin. 03 2008
Carbon black	Carcinogenic. 05 2011
Benzene, ethyl-	Carcinogenic. 05 2011
Crystalline Silica	Carcinogenic. 05 2011

US. New Jersey Worker and Community Right-to-Know Act

<u>Chemical Identity</u>
2-Propanone
Toluene
Propane

Carbonic acid calcium salt (1:1)
Benzene, dimethyl-
Carbon black
Benzene, ethyl-
Ethanol
Crystalline Silica

US. Massachusetts RTK - Substance List

Chemical Identity

Crystalline Silica

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity

2-Propanone
Toluene
Propane
Carbonic acid calcium salt (1:1)
Benzene, dimethyl-
Carbon black

US. Rhode Island RTK

No ingredient regulated by RI Right-to-Know Law present.

International regulations

Montreal protocol

2-Propanone

Stockholm convention

2-Propanone

Rotterdam convention

2-Propanone

Kyoto protocol

Inventory Status:

Australia AICS:	On or in compliance with the inventory
Canada DSL Inventory List:	On or in compliance with the inventory
EINECS, ELINCS or NLP:	Not in compliance with the inventory.
Japan (ENCS) List:	Not in compliance with the inventory.
China Inv. Existing Chemical Substances:	Not in compliance with the inventory.
Korea Existing Chemicals Inv. (KECI):	Not in compliance with the inventory.
Canada NDSL Inventory:	Not in compliance with the inventory.
Philippines PICCS:	On or in compliance with the inventory
US TSCA Inventory:	On or in compliance with the inventory
New Zealand Inventory of Chemicals:	On or in compliance with the inventory
Japan ISHL Listing:	Not in compliance with the inventory.
Japan Pharmacopoeia Listing:	Not in compliance with the inventory.
Mexico INSQ:	On or in compliance with the inventory
Ontario Inventory:	On or in compliance with the inventory
Taiwan Chemical Substance Inventory:	On or in compliance with the inventory

16. Other information, including date of preparation or last revision
--

Issue Date:	01/20/2021
Revision Information:	No data available.
Version #:	1.0
Further Information:	No data available.
Disclaimer:	This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.