

# SAFETY DATA SHEET

**DOW CORNING**

## MOLYKOTE(R) 33 EXTREME LOW TEMP. BEARING GREASE, MEDIUM

Version 4.0      Revision Date: 09/14/2017      SDS Number: 641153-00010      Date of last issue: 03/10/2017  
Date of first issue: 10/16/2014

---

### SECTION 1. IDENTIFICATION

Product name : MOLYKOTE(R) 33 EXTREME LOW TEMP. BEARING GREASE, MEDIUM

Product code : 000000000001889788

#### Manufacturer or supplier's details

Company name of supplier : Dow Corning Corporation

Address : South Saginaw Road  
Midland Michigan 48686

PO box : 65091

Telephone : (989) 496-6000

Emergency telephone : 24 Hour Emergency Telephone : (989) 496-5900  
CHEMTREC : (800) 424-9300

#### Recommended use of the chemical and restrictions on use

Recommended use : Lubricants and lubricant additives

---

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with 29 CFR 1910.1200

Not a hazardous substance or mixture.

#### GHS label elements

Not a hazardous substance or mixture.

#### Other hazards

None known.

---

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Silicone grease

#### Hazardous ingredients

Chemical name	CAS-No.	Concentration (% w/w)
Lithium stearate	4485-12-5	>= 14 - <= 21

---

### SECTION 4. FIRST AID MEASURES

If inhaled : If inhaled, remove to fresh air.  
Get medical attention if symptoms occur.

# SAFETY DATA SHEET

**DOW CORNING**

## MOLYKOTE(R) 33 EXTREME LOW TEMP. BEARING GREASE, MEDIUM

Version 4.0      Revision Date: 09/14/2017      SDS Number: 641153-00010      Date of last issue: 03/10/2017  
Date of first issue: 10/16/2014

---

- In case of skin contact : Wash with water and soap as a precaution.  
Get medical attention if symptoms occur.
- In case of eye contact : Flush eyes with water as a precaution.  
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.  
Get medical attention if symptoms occur.  
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : None known.
- Protection of first-aiders : No special precautions are necessary for first aid responders.
- Notes to physician : Treat symptomatically and supportively.
- 

### SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO2)  
Dry chemical
- Unsuitable extinguishing media : None known.
- Specific hazards during fire fighting : Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Carbon oxides  
Silicon oxides  
Formaldehyde  
Metal oxides
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.
- Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.  
Use personal protective equipment.
- 

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Follow safe handling advice and personal protective equipment recommendations.

# SAFETY DATA SHEET

**DOW CORNING**

## MOLYKOTE(R) 33 EXTREME LOW TEMP. BEARING GREASE, MEDIUM

Version 4.0      Revision Date: 09/14/2017      SDS Number: 641153-00010      Date of last issue: 03/10/2017  
Date of first issue: 10/16/2014

- Environmental precautions : Discharge into the environment must be avoided. Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material. For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

### SECTION 7. HANDLING AND STORAGE

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : Use only with adequate ventilation.
- Advice on safe handling : Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment. Take care to prevent spills, waste and minimize release to the environment.
- Conditions for safe storage : Keep in properly labeled containers. Store in accordance with the particular national regulations.
- Materials to avoid : Do not store with the following product types:  
Strong oxidizing agents

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Lithium stearate	4485-12-5	TWA	10 mg/m <sup>3</sup>	ACGIH

- Engineering measures : Processing may form hazardous compounds (see section 10). Ensure adequate ventilation, especially in confined areas.

# SAFETY DATA SHEET

**DOW CORNING**

## MOLYKOTE(R) 33 EXTREME LOW TEMP. BEARING GREASE, MEDIUM

Version 4.0      Revision Date: 09/14/2017      SDS Number: 641153-00010      Date of last issue: 03/10/2017  
Date of first issue: 10/16/2014

---

Minimize workplace exposure concentrations.

### Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection

Remarks : Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:  
Safety glasses

Skin and body protection : Skin should be washed after contact.

Hygiene measures : Ensure that eye flushing systems and safety showers are located close to the working place.  
When using do not eat, drink or smoke.  
Wash contaminated clothing before re-use.  
These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions.

---

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Grease

Color : white

Odor : slight

Odor Threshold : No data available

pH : Not applicable

Melting point/freezing point : No data available

Initial boiling point and boiling range : Not applicable

Flash point : > 101.1 °C

# SAFETY DATA SHEET

**DOW CORNING**

## MOLYKOTE(R) 33 EXTREME LOW TEMP. BEARING GREASE, MEDIUM

Version 4.0      Revision Date: 09/14/2017      SDS Number: 641153-00010      Date of last issue: 03/10/2017  
Date of first issue: 10/16/2014

---

Method: closed cup

Evaporation rate : Not applicable

Flammability (solid, gas) : Not classified as a flammability hazard

Self-ignition : The substance or mixture is not classified as pyrophoric. The substance or mixture is not classified as self heating.

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapor pressure : Not applicable

Relative vapor density : No data available

Relative density : 1.1

Solubility(ies)  
Water solubility : No data available

Partition coefficient: n-octanol/water : No data available

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity  
Viscosity, dynamic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Molecular weight : No data available

Particle size : No data available

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Use at elevated temperatures may form highly hazardous compounds.  
Can react with strong oxidizing agents.  
Hazardous decomposition products will be formed at elevated temperatures.

# SAFETY DATA SHEET

**DOW CORNING**

## MOLYKOTE(R) 33 EXTREME LOW TEMP. BEARING GREASE, MEDIUM

Version 4.0      Revision Date: 09/14/2017      SDS Number: 641153-00010      Date of last issue: 03/10/2017  
Date of first issue: 10/16/2014

---

Conditions to avoid : None known.

Incompatible materials : Oxidizing agents

### Hazardous decomposition products

Thermal decomposition : Benzene  
Formaldehyde

---

## SECTION 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

Skin contact  
Ingestion  
Eye contact

### Acute toxicity

Not classified based on available information.

### Ingredients:

#### Lithium stearate:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg  
Method: OECD Test Guideline 402  
Assessment: The substance or mixture has no acute dermal toxicity  
Remarks: Based on data from similar materials

### Skin corrosion/irritation

Not classified based on available information.

### Ingredients:

#### Lithium stearate:

Species: Rabbit  
Result: No skin irritation  
Remarks: Based on data from similar materials

### Serious eye damage/eye irritation

Not classified based on available information.

### Ingredients:

#### Lithium stearate:

Species: Rabbit  
Result: No eye irritation  
Method: OECD Test Guideline 405  
Remarks: Based on data from similar materials

# SAFETY DATA SHEET

**DOW CORNING**

## MOLYKOTE(R) 33 EXTREME LOW TEMP. BEARING GREASE, MEDIUM

Version 4.0      Revision Date: 09/14/2017      SDS Number: 641153-00010      Date of last issue: 03/10/2017  
Date of first issue: 10/16/2014

---

### Respiratory or skin sensitization

#### Skin sensitization

Not classified based on available information.

#### Respiratory sensitization

Not classified based on available information.

#### Product:

Assessment: Does not cause skin sensitization.

Test Type: Maximization Test  
Species: Guinea pig  
Result: negative  
Remarks: On basis of test data.

#### Ingredients:

##### Lithium stearate:

Test Type: Local lymph node assay (LLNA)  
Routes of exposure: Skin contact  
Species: Mouse  
Method: OECD Test Guideline 429  
Result: negative

### Germ cell mutagenicity

Not classified based on available information.

#### Product:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative  
Remarks: On basis of test data.

#### Ingredients:

##### Lithium stearate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative  
Remarks: Based on data from similar materials

### Carcinogenicity

Not classified based on available information.

#### Ingredients:

##### Lithium stearate:

Species: Mouse  
Application Route: Skin contact  
Exposure time: 104 weeks  
Result: negative  
Remarks: Based on data from similar materials

# SAFETY DATA SHEET

**DOW CORNING**

## MOLYKOTE(R) 33 EXTREME LOW TEMP. BEARING GREASE, MEDIUM

Version  
4.0

Revision Date:  
09/14/2017

SDS Number:  
641153-00010

Date of last issue: 03/10/2017  
Date of first issue: 10/16/2014

### II

#### IARC

No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

#### OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

#### NTP

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

#### Reproductive toxicity

Not classified based on available information.

#### Ingredients:

##### Lithium stearate:

Effects on fertility

: Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: Skin contact  
Result: negative  
Remarks: Based on data from similar materials

Effects on fetal development

: Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: Skin contact  
Result: negative  
Remarks: Based on data from similar materials

#### STOT-single exposure

Not classified based on available information.

#### STOT-repeated exposure

Not classified based on available information.

#### Repeated dose toxicity

#### Ingredients:

##### Lithium stearate:

Species: Rat

NOAEL: 88 mg/kg

Application Route: Ingestion

Exposure time: 90 Days

Remarks: Based on data from similar materials

Species: Rat

NOAEL: 1,089.75 mg/kg

Application Route: Skin contact

Exposure time: > 43 Days

Remarks: Based on data from similar materials



# SAFETY DATA SHEET

**DOW CORNING**

## MOLYKOTE(R) 33 EXTREME LOW TEMP. BEARING GREASE, MEDIUM

Version 4.0      Revision Date: 09/14/2017      SDS Number: 641153-00010      Date of last issue: 03/10/2017  
Date of first issue: 10/16/2014

II

### Aspiration toxicity

Not classified based on available information.

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

#### Ingredients:

##### Lithium stearate:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l  
Exposure time: 96 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 203  
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l  
Exposure time: 48 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 202  
Remarks: Based on data from similar materials

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

Toxicity to microorganisms : NOEC: 13 mg/l  
Exposure time: 28 d  
Remarks: Based on data from similar materials

### Persistence and degradability

#### Ingredients:

##### Lithium stearate:

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 78 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301C  
Remarks: Based on data from similar materials

### Bioaccumulative potential

#### Ingredients:

##### Lithium stearate:

Bioaccumulation : Species: Fish  
Bioconcentration factor (BCF): 0.12

# SAFETY DATA SHEET

**DOW CORNING**

## MOLYKOTE(R) 33 EXTREME LOW TEMP. BEARING GREASE, MEDIUM

Version 4.0      Revision Date: 09/14/2017      SDS Number: 641153-00010      Date of last issue: 03/10/2017  
Date of first issue: 10/16/2014

---



Remarks: Based on data from similar materials

### **Mobility in soil**

No data available

### **Other adverse effects**

No data available

---

## SECTION 13. DISPOSAL CONSIDERATIONS

### **Disposal methods**

Resource Conservation and Recovery Act (RCRA) : This product has been evaluated for RCRA characteristics and does not meet the criteria of hazardous waste if discarded in its purchased form.

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
If not otherwise specified: Dispose of as unused product.

---

## SECTION 14. TRANSPORT INFORMATION

### **International Regulations**

#### **UNRTDG**

Not regulated as a dangerous good

#### **IATA-DGR**

Not regulated as a dangerous good

#### **IMDG-Code**

Not regulated as a dangerous good

#### **Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

### **Domestic regulation**

#### **49 CFR**

Not regulated as a dangerous good

---

## SECTION 15. REGULATORY INFORMATION

### **EPCRA - Emergency Planning and Community Right-to-Know**

#### **CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

#### **SARA 304 Extremely Hazardous Substances Reportable Quantity**

This material does not contain any components with a section 304 EHS RQ.

# SAFETY DATA SHEET

**DOW CORNING**

## MOLYKOTE(R) 33 EXTREME LOW TEMP. BEARING GREASE, MEDIUM

Version 4.0      Revision Date: 09/14/2017      SDS Number: 641153-00010      Date of last issue: 03/10/2017  
Date of first issue: 10/16/2014

---

### **SARA 302 Extremely Hazardous Substances Threshold Planning Quantity**

This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards** : No SARA Hazards

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

### **US State Regulations**

#### **Pennsylvania Right To Know**

Dimethyl, phenylmethyl siloxane, trimethyl-terminated      63148-52-7  
Lithium stearate      4485-12-5

#### **California Prop. 65**

This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

#### **California Permissible Exposure Limits for Chemical Contaminants**

Lithium stearate      4485-12-5

#### **The ingredients of this product are reported in the following inventories:**

- KECI : All ingredients listed, exempt or notified.
- TCSI : All ingredients listed or exempt.
- REACH : For purchases from Dow Corning EU legal entities, all ingredients are currently pre/registered or exempt under REACH. Please refer to section 1 for recommended uses. For purchases from non-EU Dow Corning legal entities with the intention to export into EEA please contact your DC representative/local office.
- TSCA : All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.
- AICS : All ingredients listed or exempt.
- IECSC : All ingredients listed or exempt.
- ENCS/ISHL : All components are listed on ENCS/ISHL or exempted from inventory listing.
- PICCS : All ingredients listed or exempt.
- DSL : All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).
- NZIoC : All ingredients listed or exempt.

# SAFETY DATA SHEET

**DOW CORNING**

## MOLYKOTE(R) 33 EXTREME LOW TEMP. BEARING GREASE, MEDIUM

Version  
4.0

Revision Date:  
09/14/2017


SDS Number:  
641153-00010

Date of last issue: 03/10/2017  
Date of first issue: 10/16/2014

### SECTION 16. OTHER INFORMATION

#### Further information

##### NFPA:



Special hazard.

##### HMIS® IV:

HEALTH	/	0
FLAMMABILITY		1
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "/" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

#### Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)  
ACGIH / TWA : 8-hour, time-weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECS - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECL - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable

# SAFETY DATA SHEET

**DOW CORNING**

## **MOLYKOTE(R) 33 EXTREME LOW TEMP. BEARING GREASE, MEDIUM**

Version 4.0	Revision Date: 09/14/2017	SDS Number: 641153-00010	Date of last issue: 03/10/2017 Date of first issue: 10/16/2014
----------------	------------------------------	-----------------------------	---

---

Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 09/14/2017

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8