


Kit Name: Seam Sealer
Stock No.: 97120
Manufacturer Name: Saint-Gobain Abrasives, Inc.
Address: 1 New Bond Street
 Worcester, MA 01615



SECTION 1 : PRODUCT AND COMPANY IDENTIFICATION

Product Name: Seam Sealer (Part 1)
Product Code: 63642597120A
Synonyms: Epoxy Seam Sealer
Manufacturer Name: Saint-Gobain Abrasives, Inc.
Address: 1 New Bond Street
 Worcester, MA 01615
Website: www.Nortonabrasives.com
General Phone Number: 800-551-4413
Emergency Phone Number: 508-795-5000
CHEMTREC: For emergencies in the US, call CHEMTREC: 800-424-9300
Canutec: In Canada, call CANUTEC: (613) 996-6666 (call collect)

HMIS	
Health Hazard	2*
Fire Hazard	1
Reactivity	1
Personal Protection	X

* Chronic Health Effects

SECTION 2 : COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS#	Ingredient Percent	EC Num.
Bisphenol A Diglycidyl Ether R	25085-99-8	40 - 70 by weight	
Dimethyl Siloxane, Reaction Pr	67762-90-7	3 - 7 by weight	
Butyl Benzyl Phthalate	85-68-7	10 - 30 by weight	
Black Iron Oxide	1317-61-9	0.5 - 1.5 by weight	

SECTION 3 : HAZARDS IDENTIFICATION

SECTION 4 : FIRST AID MEASURES

Eye Contact: Immediately flush eyes with plenty of water for at least 15 to 20 minutes. Ensure adequate flushing of the eyes by separating the eyelids with fingers. Get immediate medical attention.

Skin Contact: Immediately wash skin with plenty of soap and water for 15 to 20 minutes, while removing contaminated clothing and shoes. Get medical attention if irritation develops or persists.

Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.

Ingestion: If swallowed, do NOT induce vomiting. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

SECTION 5 : FIRE FIGHTING MEASURES

Flash Point: >302 °F (>150°C)
Flash Point Method: TCC
Auto Ignition Temperature: Not determined.
Lower Flammable/Explosive Limit: Not determined.
Upper Flammable/Explosive Limit: Not determined.

Fire Fighting Instructions:	Evacuate area of unprotected personnel. Use cold water spray to cool fire exposed containers to minimize risk of rupture. Do not enter confined fire space without full protective gear. If possible, contain fire run-off water.
Extinguishing Media:	Use carbon dioxide (CO2) or dry chemical when fighting fires involving this material.
Unsuitable Media:	Water or foam may cause frothing.
Protective Equipment:	As in any fire, wear Self-Contained Breathing Apparatus (SCBA), MSHA/NIOSH (approved or equivalent) and full protective gear.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

Personal Precautions:	Evacuate area and keep unnecessary and unprotected personnel from entering the spill area.
Environmental Precautions:	Avoid runoff into storm sewers, ditches, and waterways.
Spill Cleanup Measures:	Absorb spill with inert material (e.g., dry sand or earth), then place in a chemical waste container. Provide ventilation. Clean up spills immediately observing precautions in the protective equipment section. After removal, flush spill area with soap and water to remove trace residue. Avoid personal contact and breathing vapors or mists. Ventilate area. Use proper personal protective equipment as listed in Section 8.
Other Precautions:	Pump or shovel to storage/salvage vessels.

SECTION 7 : HANDLING and STORAGE

Handling:	Use with adequate ventilation. Avoid breathing vapor, aerosol or mist.
Storage:	Store in a cool, dry, well ventilated area away from sources of heat and incompatible materials. Keep container tightly closed when not in use.
Special Handling Procedures:	Provide appropriate ventilation/respiratory protection against decomposition products (see Section 10) during welding/ flame cutting operations and to protect against dust during sanding/grinding of cured product.
Hygiene Practices:	Wash thoroughly after handling.

SECTION 8 : EXPOSURE CONTROLS, PERSONAL PROTECTION - EXPOSURE GUIDELINES

Engineering Controls:	Use appropriate engineering control such as process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Good general ventilation should be sufficient to control airborne levels. Where such systems are not effective wear suitable personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards. Consult with local procedures for selection, training, inspection and maintenance of the personal protective equipment.
Eye/Face Protection:	Wear appropriate protective glasses or splash goggles as described by 29 CFR 1910.133, OSHA eye and face protection regulation, or the European standard EN 166.
Skin Protection Description:	Wear appropriate protective gloves and other protective apparel to prevent skin contact. Consult manufacturer's data for permeability data.
Respiratory Protection:	A NIOSH approved air-purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.
Other Protective:	Facilities storing or utilizing this material should be equipped with an eyewash and a deluge shower safety station.

EXPOSURE GUIDELINES

SECTION 9 : PHYSICAL and CHEMICAL PROPERTIES

Physical State:	Paste.
Color:	black
Odor:	Epoxy like odor.
Boiling Point:	Not determined.
Melting Point:	Not determined.
Specific Gravity:	1.1
Solubility:	not soluble in water.
Vapor Density:	>1 (air = 1)
Vapor Pressure:	Not determined.
Evaporation Rate:	<1 (n-Butyl acetate = 1)
Flash Point:	>302 °F (>150°C)
Flash Point Method:	TCC
Auto Ignition Temperature:	Not determined.

SECTION 10 : STABILITY and REACTIVITY

Chemical Stability:	Stable under normal temperatures and pressures.
Hazardous Polymerization:	Not reported.
Conditions to Avoid:	Extreme heat, sparks, and open flame. Incompatible materials, oxidizers and oxidizing conditions.
Incompatible Materials:	Oxidizers, acids, and chlorinated organic compounds. Reactive metals (e.g. sodium, calcium, zinc). Sodium/calcium hypochlorite. Nitrous acid/ oxide, nitrites. Peroxides. Materials reactive with hydroxyl compounds.
Special Decomposition Products:	Carbon monoxide, silicone dioxide.

SECTION 11 : TOXICOLOGICAL INFORMATION

SECTION 12 : ECOLOGICAL INFORMATION

SECTION 13 : DISPOSAL CONSIDERATIONS

SECTION 14 : TRANSPORT INFORMATION

DOT Shipping Name:	Non regulated.
DOT UN Number:	Non regulated.
IATA Shipping Name:	Non regulated.
IATA UN Number:	Non regulated.
Canadian Shipping Name:	WHMIS Classification: D2B

SECTION 15 : REGULATORY INFORMATION

SECTION 16 : ADDITIONAL INFORMATION

Label Hazard Warning:	H360 - May damage fertility or the unborn child. H319 - Causes serious eye irritation. H315 - Causes skin irritation. H317 - May cause an allergic skin reaction. H400 - Very toxic to aquatic life. H411 - Toxic to aquatic life with long lasting effects. H351 - May cause cancer.
Label Precautions:	P201 - Obtain special instructions before use. P202 - Do not handle until all safety precautions have been read and understood. P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P264 - Wash hands thoroughly after handling. P272 - Contaminated work clothing should not be allowed out of the workplace. P273 - Avoid release to the environment. P280 - Wear protective gloves/protective clothing/eye protection/face protection. P302+P352 - IF ON SKIN: Wash with plenty of water. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308+P313 - IF exposed or concerned: Get medical advice/attention. P321 - P332+P313 - If skin irritation occurs: Get medical advice/attention. P333+P313 - If skin irritation or rash occurs: Get medical advice/attention. P337+P313 - If eye irritation persists: Get medical advice/attention. P362+P364 - Take off contaminated clothing and wash it before reuse. P391 - Collect spillage. P405 - Store locked up. P501 - Dispose of contents/container in accordance with Local, State, Federal and Provincial regulations.
HMIS Ratings:	
HMIS Health Hazard:	2*
HMIS Fire Hazard:	1
HMIS Reactivity:	1
HMIS Personal Protection:	X
SDS Creation Date:	August 09, 2010
SDS Revision Date:	December 14, 2015
SDS Revision Notes:	GHS Update

Copyright© 1996-2018 Enviance. All Rights Reserved.



SECTION 1 : PRODUCT AND COMPANY IDENTIFICATION

Product Name: Seam Sealer (Part 2)
Product Code: 97120B
Synonyms: Epoxy Seam Sealer
Manufacturer Name: Saint-Gobain Abrasives, Inc.
Address: 1 New Bond Street
 Worcester, MA 01615
Website: www.Nortonabrasives.com
General Phone Number: 800-551-4413
Emergency Phone Number: 508-795-5000
CHEMTREC: For emergencies in the US, call CHEMTREC: 800-424-9300
Canutec: In Canada, call CANUTEC: (613) 996-6666 (call collect)

HMIS	
Health Hazard	
Fire Hazard	1
Reactivity	1
Personal Protection	X

SECTION 2 : COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS#	Ingredient Percent	EC Num.
2,4,6-Tris (Dimethylaminomethyl)phenol	90-72-2	7 - 13 by weight	
Poly Alkoxyated Hydroxyalkyl	Proprietary	60 - 100 by weight	
Dimethyl Siloxane, Reaction Pr	67762-90-7	3 - 7 by weight	

SECTION 3 : HAZARDS IDENTIFICATION

Emergency Overview: WARNING! Potential Sensitizer. Irritant.
Route of Exposure: Eyes. Skin. Inhalation. Ingestion.
Potential Health Effects:
Eye: Can cause severe eye irritation and burns. Eye contact may cause permanent damage or blindness.
Skin: Causes severe skin irritation. May cause permanent skin damage. Allergic reactions are possible. May cause skin sensitization, an allergic reaction, which becomes evident on reexposure to this material.
Inhalation: Vapor or mist may cause severe respiratory system irritation. May cause respiratory sensitization with asthma-like symptoms in susceptible individuals.
Ingestion: Causes irritation, a burning sensation of the mouth, throat and gastrointestinal tract and abdominal pain.
Chronic Health Effects: Prolonged skin contact may lead to burning associated with severe reddening, swelling, and possible tissue destruction.
Signs/Symptoms: Overexposure may cause eye watering or discomfort, redness and swelling.
Target Organs: Eyes. Skin. Respiratory system. Digestive system.
Aggravation of Pre-Existing Conditions: Individuals with pre-existing skin disorders, asthma, allergies or known sensitization may be more susceptible to the effects of this product.

SECTION 4 : FIRST AID MEASURES

Eye Contact: Immediately flush eyes with plenty of water for at least 15 to 20 minutes. Ensure adequate flushing of the eyes by separating the eyelids with fingers. Get immediate medical attention.
Skin Contact: Immediately wash skin with plenty of soap and water for 15 to 20 minutes, while removing contaminated clothing and shoes. Get medical attention if irritation develops or persists.
Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.
Ingestion: If swallowed, do NOT induce vomiting. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

SECTION 5 : FIRE FIGHTING MEASURES

Flash Point:	300 °F (149C)
Flash Point Method:	TCC
Auto Ignition Temperature:	Not determined.
Lower Flammable/Explosive Limit:	Not determined.
Upper Flammable/Explosive Limit:	Not determined.
Fire Fighting Instructions:	Evacuate area of unprotected personnel. Use cold water spray to cool fire exposed containers to minimize risk of rupture. Do not enter confined fire space without full protective gear. If possible, contain fire run-off water.
Extinguishing Media:	Use carbon dioxide (CO2) or dry chemical when fighting fires involving this material.
Unsuitable Media:	Water or foam may cause frothing.
Protective Equipment:	As in any fire, wear Self-Contained Breathing Apparatus (SCBA), MSHA/NIOSH (approved or equivalent) and full protective gear.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

Personal Precautions:	Evacuate area and keep unnecessary and unprotected personnel from entering the spill area.
Environmental Precautions:	Avoid runoff into storm sewers, ditches, and waterways.
Spill Cleanup Measures:	Absorb spill with inert material (e.g., dry sand or earth), then place in a chemical waste container. Provide ventilation. Clean up spills immediately observing precautions in the protective equipment section. After removal, flush spill area with soap and water to remove trace residue. Avoid personal contact and breathing vapors or mists. Ventilate area. Use proper personal protective equipment as listed in Section 8.
Other Precautions:	Pump or shovel to storage/salvage vessels.

SECTION 7 : HANDLING and STORAGE

Handling:	Use with adequate ventilation. Avoid breathing vapor, aerosol or mist.
Storage:	Store in a cool, dry, well ventilated area away from sources of heat and incompatible materials. Keep container tightly closed when not in use.
Special Handling Procedures:	Provide appropriate ventilation/respiratory protection against decomposition products (see Section 10) during welding/flame cutting operations and to protect against dust during sanding/grinding of cured product.
Hygiene Practices:	Wash thoroughly after handling.

SECTION 8 : EXPOSURE CONTROLS, PERSONAL PROTECTION - EXPOSURE GUIDELINES

Engineering Controls:	Use appropriate engineering control such as process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Good general ventilation should be sufficient to control airborne levels. Where such systems are not effective wear suitable personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards. Consult with local procedures for selection, training, inspection and maintenance of the personal protective equipment.
Eye/Face Protection:	Wear appropriate protective glasses or splash goggles as described by 29 CFR 1910.133, OSHA eye and face protection regulation, or the European standard EN 166.
Skin Protection Description:	Wear appropriate protective gloves and other protective apparel to prevent skin contact. Consult manufacturer's data for permeability data.
Respiratory Protection:	A NIOSH approved air-purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.
Other Protective:	Facilities storing or utilizing this material should be equipped with an eyewash and a deluge shower safety station.

EXPOSURE GUIDELINES

SECTION 9 : PHYSICAL and CHEMICAL PROPERTIES

Physical State:	Paste
Color:	Grey
Odor:	Mercaptan
Boiling Point:	Not determined.
Melting Point:	Not determined.
Specific Gravity:	1.2
Solubility:	not soluble in water.
Vapor Density:	>1 (air = 1)
Vapor Pressure:	Not determined.

Evaporation Rate: <1 (n-Butyl acetate = 1)
pH: Slightly acidic.
Flash Point: 300 °F (149C)
Flash Point Method: TCC
Auto Ignition Temperature: Not determined.

SECTION 10 : STABILITY and REACTIVITY

Chemical Stability: Stable under normal temperatures and pressures.
Hazardous Polymerization: Not reported.
Conditions to Avoid: Extreme heat, sparks, and open flame. Incompatible materials, oxidizers and oxidizing conditions.
Incompatible Materials: Oxidizers, acids, and chlorinated organic compounds. Reactive metals (e.g. sodium, calcium, zinc). Sodium/calcium hypochlorite. Nitrous acid/ oxide, nitrites. Peroxides. Materials reactive with hydroxyl compounds.
Special Decomposition Products: Carbon monoxide, oxides of nitrogen, oxides of sulphur, hydrogen sulphide.

SECTION 11 : TOXICOLOGICAL INFORMATION

SECTION 12 : ECOLOGICAL INFORMATION

Ecotoxicity: No ecotoxicity data was found for the product.
Environmental Fate: No environmental information found for this product.

SECTION 13 : DISPOSAL CONSIDERATIONS

Waste Disposal: Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the classifications of hazardous waste prior to disposal. Furthermore, consult with your state and local waste requirements or guidelines, if applicable, to ensure compliance. Arrange disposal in accordance to the EPA and/or state and local guidelines.
RCRA Number: None.

SECTION 14 : TRANSPORT INFORMATION

DOT Shipping Name: Non regulated.
DOT UN Number: Non regulated.
IATA Shipping Name: Non regulated.
IATA UN Number: Non regulated.

SECTION 15 : REGULATORY INFORMATION

Dimethyl Siloxane, Reaction Pr :

TSCA Inventory Status: Listed
Canada WHMIS: Classification: D2B

SECTION 16 : ADDITIONAL INFORMATION

Label Hazard Warning: H318 - Causes serious eye damage.
H314 - Causes severe skin burns and eye damage.
Label Precautions: P260 - Do not breathe dust/fume/gas/mist/vapours/spray.
P264 - Wash hands thoroughly after handling.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P301+P330+P331 - IF SWALLOWED: Rinse mouth. Do not induce vomiting.
P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 - Immediately call a POISON CENTER or doctor/physician.
P321 - P363 - Wash contaminated clothing before reuse.
P405 - Store locked up.
P501 - Dispose of contents/container in accordance with Local, State, Federal and Provincial regulations.

HMIS Ratings:

HMIS Fire Hazard: 1
HMIS Reactivity: 1
HMIS Personal Protection: X

SDS Creation Date: August 09, 2010
SDS Revision Date: December 14, 2015
SDS Revision Notes: GHS Update

Copyright© 1996-2018 Enviance. All Rights Reserved.