

Safety Data Sheet

# Safety Data Sheet

## **Section 1. Identification**

Product name : ALPHA® RA-32 Flux Solder Wire Cored 40Sn/60Pb Alloy

Product code : M040RA32
Product type : Solid.

Date of issue/Date of : September 26 2016.

revision

Manufacturer - Supplier	Telephone no.:	Emergency phone:
Arpha Assembly Solutions Inc. Global Headquarters 300 Atrium Drive Somerset, New Jersey 08873	Main Phone: (908) 791-3000	DOMESTIC NORTH AMERICA 800-424-9300 INTERNATIONAL, CALL +1 703-527-3887 (collect calls accepted) Alpha Chemtrec# 5591
AVPHA METALS MEXICO SA DE CV Ave Nafta 800, Parque Industrial STIVA Apodaca NL 66600 Mexico	Tel: +52 81 1156-6602	Tel: 01 800 022 1400 Tel: +52 55 5559-1588
Arpha Assembly Solutions Brasil Soldas Ltda Rio Jaguarão, 1540 - Vila Buriti Manaus Amazonas 69072-055 Brasil	Tel: 55 92 3614-7400	Tel: 55 92 3614-7423

## Section 2. Hazards identification

**OSHA/HCS** status

Classification of the

substance or mixture

:

- : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
- : SKIN SENSITIZATION Category 1 CARCINOGENICITY Category 2

TOXIC TO REPRODUCTION (Fertility) - Category 1A TOXIC TO REPRODUCTION (Unborn child) - Category 1A

SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1

AQUATIC HAZARD (ACUTE) - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 1

**GHS label elements** 

Hazard pictograms







Signal word : Danger

Hazard statements : May cause an allergic skin reaction.

May damage fertility or the unborn chi

May damage fertility or the unborn child. Suspected of causing cancer.

Causes damage to organs through prolonged or repeated exposure.

Very toxic to aquatic life with long lasting effects.

**Precautionary statements** 

### Page: 2/12

## Section 2. Hazards identification

#### **General**

: Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.

#### **Prevention**

: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Wear protective gloves. Avoid release to the environment. Do not breathe dust. Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace.

#### Response

: Collect spillage. Get medical attention if you feel unwell. IF exposed or concerned: Get medical attention. IF ON SKIN: Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical attention.

**Storage** 

: Store locked up.

**Disposal** 

: Dispose of contents and container in accordance with all local, regional, national and international regulations.

**Hazards not otherwise** classified

: None known.

# Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Ingredient name	%	CAS number
lead	50-60	7439-92-1
tin	30-40	7440-31-5
Rosin/Resin	1-10	-
Proprietary Alcohol	0.1-1.0	-

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

### **Description of necessary first aid measures**

**Eye contact** 

: Check for and remove any contact lenses. Immediately flush eyes with running water for at least 30 minutes, keeping evelids open. Get medical attention.

Inhalation

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

**Skin contact** 

: Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 15 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

: Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position



## Section 4. First aid measures

and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

### Most important symptoms/effects, acute and delayed

## Potential acute health effects

Eye contactInhalationNo known significant effects or critical hazards.No known significant effects or critical hazards.

**Skin contact**: May cause an allergic skin reaction.

**Ingestion**: No known significant effects or critical hazards.

### **Over-exposure signs/symptoms**

**Eye contact** : No specific data.

**Inhalation** : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

**Skin contact**: Adverse symptoms may include the following:

irritation redness

reduced fetal weight increase in fetal deaths skeletal malformations

**Ingestion** : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

**Specific treatments**: No specific treatment.

**Protection of first-aiders**: No action shall be taken involving any personal risk or without suitable training. If it is

suspected that mists are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water

before removing it, or wear gloves.

See toxicological information (Section 11)

# Section 5. Fire-fighting measures

#### **Extinguishing media**

Suitable extinguishing

media

: Use an extinguishing agent suitable for the surrounding fire.

**Unsuitable extinguishing** 

media

: None known.

Specific hazards arising from the chemical

: This material is very toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous thermal decomposition products

: Decomposition products may include the following materials: metal oxide/oxides

## Section 5. Fire-fighting measures

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable

**Special protective** equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For nonemergency personnel".

**Environmental precautions** 

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

### Methods and materials for containment and cleaning up

**Small spill** 

: Move containers from spill area. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Place spilled material in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.

Large spill

: Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

### Precautions for safe handling

**Protective measures** 

: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

### Page: 5/12

## Section 7. Handling and storage

**Conditions for safe** storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

## Section 8. Exposure controls/personal protection

### **Control parameters**

Occupational exposure limits

Ingredient name	Exposure limits
lead	OSHA PEL (United States, 5/2005).
	TWA: 0.05 mg/m³ 8 hours.
	ACGIH TLV (United States, 4/2014). Notes: as Pb
	TWA: 0.05 mg/m³, (as Pb) 8 hours.
	OSHA PEL (United States, 2/2013). Notes: as Pb
	TWA: 50 μg/m³, (as Pb) 8 hours.
	NIOSH REL (United States, 10/2013). Notes: See Appendix C -
	Supplemental Exposure Limits Note: The REL and PEL also apply
	to other lead compounds (as Pb).
	TWA: 0.05 mg/m³ 10 hours.
tin	OSHA PEL (United States, 9/2005).
	TWA: 2 mg/m³ 8 hours.
	ACGIH TLV (United States, 4/2014).
	TWA: 2 mg/m³, (as Sn) 8 hours.
	NIOSH REL (United States, 10/2013).
	TWA: 2 mg/m³, (as Sn) 10 hours.
Proprietary Alcohol	AIHA WEEL (United States, 10/2011).
	TWA: 0.5 ppm 8 hours.

### Appropriate engineering controls

: If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

### **Environmental exposure** controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### **Individual protection measures**

**Hygiene measures** 

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

### **Eye/face protection**

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with sideshields.

#### **Skin protection**

## Page: 6/12

## Section 8. Exposure controls/personal protection

### **Hand protection**

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

#### **Body protection**

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** 

: Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

## Section 9. Physical and chemical properties

#### **Appearance**

Physical state: Solid.Color: Gray.Odor: None.

: Not available. Odor threshold рH : Not available. **Melting point** : Not available. **Boiling point** : Not available. Flash point : Not available. **Evaporation rate** : Not available. Flammability (solid, gas) : Not available. Lower and upper explosive : Not available.

(flammable) limits

Vapor pressure: Not available.Vapor density: Not available.Relative density: Not available.

**Solubility** : Insoluble in the following materials: cold water and hot water.

**VOC** : 1.8 g/l

Partition coefficient: n-

octanol/water

: Not available.

Auto-ignition temperature: Not available.Decomposition temperature: Not available.Viscosity: Not available.

## Section 10. Stability and reactivity

Reactivity

: No specific test data related to reactivity available for this product or its ingredients.

Chemical stability

: The product is stable.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

## Page: 7/12

## Section 10. Stability and reactivity

Incompatibility with various substances

Reactive or incompatible with the following materials: oxidizing materials, reducing materials, acids and alkalis.

**Hazardous decomposition** products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

**Other Hazardous** decomposition products : metal oxides, toxic. fumes

Chlorine, peroxides

**Hazardous polymerization** 

: Under normal conditions of storage and use, hazardous polymerization will not occur.

# **Section 11. Toxicological information**

# **Routes of entry**

: Dermal contact. Eye contact. Inhalation. Ingestion.

### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
lead	LD50 Oral	Rat	>5000 mg/kg	-
tin	LD50 Oral	Rat	>2000 mg/kg	-
Rosin/Resin	LD50 Oral	Mouse	2.2 g/kg	-
	LD50 Oral	Rat	3 g/kg	-
Proprietary Alcohol	LD50 Dermal	Rabbit	5000 mg/kg	-
	LD50 Oral	Rat	1600 mg/kg	-

### **Irritation/Corrosion**

Product/ingredient name	Result	Species	Score	Exposure	Observation
Proprietary Alcohol	Eyes - Moderate irritant	Rabbit	-	24 hours 20 milligrams	-

### **Sensitization**

Not available.

### **Mutagenicity**

Product/ingredient name	Test	Experiment	Result
lead	-	Subject: Mammalian-Animal	Equivocal

### **Carcinogenicity**

No applicable toxicity data

### **Additional information:**

### Classification

Product/ingredient name	OSHA	IARC	NTP
lead	-	2B	Reasonably anticipated to be a human carcinogen.

### Reproductive toxicity

Product/ingredient name	Maternal toxicity	Fertility	Development toxin	Species	Dose	Exposure
lead	-	-	Equivocal	Rat - Female	Oral: 520 mg/kg	-
	-	-	Equivocal	Rat - Female	Inhalation: 3 mg/m³	24 hours per day
	Equivocal	-	-	Mouse - Female	Oral: 300 mg/kg	-
	-	Equivocal	-	Mouse	Oral: 4099.2 mg/kg	-
Proprietary Alcohol	Positive	Positive	Positive	Rat	Oral: 150 mg/kg	18 days During Pregnancy



### ALPHA® RA-32 Flux Solder Wire Cored 40Sn/60Pb Alloy

## **Section 11. Toxicological information**

Posit	tive	Positive	Positive			9 days
					0 0	During
				D-4 M-1-		Pregnancy
-		Equivocal	-			6 hours per
						day
					TCLo	
-		Equivocal	-	Rat - Male	Dermal:	-
					65 g/kg	
					TDLo	

### **Teratogenicity**

Product/ingredient name	Result	Species	Dose	Exposure
lead	Equivocal - Oral	Mammal -	2118 mg/kg	-
		species unspecified		
	Equivocal - Inhalation	Rat	10 mg/m³	24 hours per day

## Specific target organ toxicity (single exposure)

Not available.

### Specific target organ toxicity (repeated exposure)

Name	• •	Route of exposure	Target organs
lead	Category 1		nervous system and reproductive organs

### **Aspiration hazard**

Not available.

Information on the likely routes of exposure

: Routes of entry anticipated: Oral, Dermal, Inhalation.

#### Potential acute health effects

**Eye contact** : No known significant effects or critical hazards. Inhalation : No known significant effects or critical hazards.

**Skin contact** : May cause an allergic skin reaction.

Ingestion : No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : No specific data.

Inhalation : Adverse symptoms may include the following:

> reduced fetal weight increase in fetal deaths skeletal malformations

**Skin contact** : Adverse symptoms may include the following:

> irritation redness

reduced fetal weight increase in fetal deaths skeletal malformations

Ingestion : Adverse symptoms may include the following:

> reduced fetal weight increase in fetal deaths skeletal malformations

### Delayed and immediate effects and also chronic effects from short and long term exposure

Page: 8/12

## Page: 9/12

## **Section 11. Toxicological information**

### **Short term exposure**

**Potential immediate** 

effects

: Not available.

Potential delayed effects

yed effects: Not available.

Long term exposure

**Potential immediate** 

: Not available.

effects

Potential delayed effects : Not available.

### Potential chronic health effects

General : Causes damage to organs through prolonged or repeated exposure. Once sensitized, a

severe allergic reaction may occur when subsequently exposed to very low levels.

Carcinogenicity : Suspected of causing cancer. Risk of cancer depends on duration and level of

exposure.

**Mutagenicity**: No known significant effects or critical hazards.

**Teratogenicity**: May damage the unborn child.

**Developmental effects**: No known significant effects or critical hazards.

Fertility effects : May damage fertility.

### **Numerical measures of toxicity**

### **Acute toxicity estimates**

Route	ATE value
Oral	108919.5 mg/kg

# Section 12. Ecological information

### **Toxicity**

Product/ingredient name	Result	Species	Exposure
lead	Acute EC50 105 ppb Marine water	Algae - Chaetoceros sp Exponential growth phase	72 hours
	Acute EC50 0.489 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Acute EC50 8000 µg/l Fresh water	Aquatic plants - Lemna minor	4 days
	Acute LC50 530 μg/l Fresh water	Crustaceans - Ceriodaphnia reticulata	48 hours
	Acute LC50 5100 μg/l Fresh water	Daphnia - Daphnia pulex	48 hours
	Acute LC50 0.44 ppm Fresh water	Fish - Cyprinus carpio - Juvenile (Fledgling, Hatchling, Weanling)	96 hours
	Chronic NOEC 0.25 mg/l Marine water Chronic NOEC 0.03 µg/l Fresh water	Algae - Ulva pertusa Fish - Cyprinus carpio	96 hours 4 weeks

### Persistence and degradability

Not available.

### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
Rosin/Resin	1.9 to 7.7	-	high

#### **Mobility in soil**

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects : No known significant effects or critical hazards.

A MacDermid Performance Solutions Business
A Platform Specialty Products Company

## Page: 10/12

## Section 13. Disposal considerations

### **Disposal methods**

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## **Section 14. Transport information**

	DOT Classification	TDG Classification	Mexico Classification	UN	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-	-	-
Transport hazard class(es)	-	-	-	-	-	-
Packing group	-	-	-	-	-	-
Environmental hazards	No.	No.	No.	No.	No.	No.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

## Section 15. Regulatory information

U.S. Federal regulations

: TSCA 5(a)2 proposed significant new use rule (SNUR): No products were found.

TSCA 5(a)2 final significant new use rule (SNUR): No products were found.

TSCA 12(b) one-time export notification: No products were found.

TSCA 12(b) annual export notification: lead

Refer to Proposed Rule (59 Federal Register 11122, March 9, 1994) for details on TSCA 12(b) applicability for lead.

**United States inventory** (TSCA 8b)

: All components are listed or exempted.

**SARA 302/304** 

**Composition/information on ingredients** 

No products were found.

**SARA 311/312** 

ALPHA® RA-32 Flux Solder Wire Cored 40Sn/60Pb Alloy

## Section 15. Regulatory information

Classification

: Immediate (acute) health hazard Delayed (chronic) health hazard

### **SARA 313**

	Product name	CAS number	%
Form R - Reporting requirements	lead	7439-92-1	50-60
Supplier notification	lead	7439-92-1	50-60

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

### California Prop. 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

### Canada

WHMIS (Canada) : Class D-2A: Material causing other toxic effects (Very toxic).

**Canada inventory** : All components are listed or exempted.

### **International lists**

**National inventory** 

**Australia** : All components are listed or exempted. China : All components are listed or exempted. **Europe** : All components are listed or exempted. **Japan** : All components are listed or exempted. **New Zealand** : All components are listed or exempted. **Philippines** : All components are listed or exempted. **Republic of Korea** : All components are listed or exempted. **Taiwan** : All components are listed or exempted.

## Section 16. Other information

## **Hazardous Material Information System (U.S.A.)**

Health	2
Flammability	1
Physical hazards	0

### Procedure used to derive the classification

Classification	Justification
Skin Sens. 1, H317	Calculation method
Carc. 2, H351	Calculation method
Repr. 1A, H360 (Fertility)	Calculation method
Repr. 1A, H360 (Unborn child)	Calculation method
STOT RE 1, H372	Calculation method
Aquatic Acute 1, H400	Calculation method
Aquatic Chronic 1, H410	Calculation method

#### **History**

Date of issue/Date of

revision

: September 26 2016.

Date of previous issue : May 15 2015.

A MacDermid Performance Solutions Business



Page: 11/12

#### Page: 12/12

## Section 16. Other information

Version

• 2

**Prepared by** 

: Regulatory Affairs Department

enthone.msds@macdermidenthone.com

**Key to abbreviations** 

: ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

UN = United Nations

▼ Indicates information that has changed from previously issued version.

### **Notice to reader**

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

4.5b3271

Alpha Assembly SDS GHS Americas

# alpha

Safety Data Sheet

# Safety Data Sheet

## **Section 1. Identification**

**Product name** : Solder Wire Cored 40Sn/60Pb Alloy, AC94 Flux

: M040AC94 **Product code** : Solid. **Product type** 

Date of issue/Date of

revision

: May 15 2015.

Manufacturer - Supplier	Telephone no.:	Fax no.	Emergency phone:
ALPHA Global Headquarters 300 Atrium Drive Somerset, New Jersey 08873	Toll Free: (800) 367-5460 Main Phone: (908) 791-3000	(908) 791-3090	UNITED STATES AND CANADA Tel: 800-424-9300 INTERNATIONAL, CALL Tel: +1 703-527-3887 (collect calls accepted) Alpha Chemtrec #5591
ALPHA METALS MEXICO SA DE CV Ave Nafta 800, Parque Industrial STIVA Apodaca NL 66600 Mexico	Tel: +52 81 1156-6602	Fax: +52 81 1156-6655	Tel: 01 800 022 1400 Tel: +52 55 5559-1588
Alent Brasil Soldas Ltda. Rio Jaguarão, 1540 - Vila Buriti Manaus Amazonas 69072-055 Brasil	Tel: 55 92 3614-7400	Fax: 55 92 3614-7400	Tel: 55 92 3614-7423

## Section 2. Hazards identification

**OSHA/HCS** status

: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture : CARCINOGENICITY - Category 2

TOXIC TO REPRODUCTION (Fertility) - Category 1A TOXIC TO REPRODUCTION (Unborn child) - Category 1A

SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1

AQUATIC HAZARD (ACUTE) - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 1

**GHS label elements** 

**Hazard pictograms** 





Signal word

**Hazard statements** : May damage fertility or the unborn child.

Suspected of causing cancer.

Causes damage to organs through prolonged or repeated exposure.

Very toxic to aquatic life with long lasting effects.

**Precautionary statements** 

General

: Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.

Page: 2/12

## Section 2. Hazards identification

Prevention

: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Avoid release to the environment. Do not breathe dust. Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling.

Response

: Collect spillage. Get medical attention if you feel unwell. IF exposed or concerned: Get medical attention.

**Storage** 

: Store locked up.

**Disposal** 

: Dispose of contents and container in accordance with all local, regional, national and international regulations.

Hazards not otherwise classified

: None known.

## Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Ingredient name	%	CAS number
lead	50-60	7439-92-1
tin	30-40	7440-31-5
Additive	1-10	-
Ammonium salt.	0.1-1.0	-

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

### **Description of necessary first aid measures**

Eye contact

: Check for and remove any contact lenses. Immediately flush eyes with running water for at least 30 minutes, keeping eyelids open. Get medical attention.

Inhalation

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

**Skin contact** 

: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 15 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

#### Most important symptoms/effects, acute and delayed

### Page: 3/12

## Section 4. First aid measures

### Potential acute health effects

Eye contact
 Inhalation
 No known significant effects or critical hazards.
 Skin contact
 No known significant effects or critical hazards.
 Ingestion
 No known significant effects or critical hazards.

### Over-exposure signs/symptoms

**Eye contact** : No specific data.

**Inhalation** : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

**Skin contact**: Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

**Ingestion** : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

#### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

**Specific treatments**: No specific treatment.

**Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is

suspected that mists are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water

before removing it, or wear gloves.

See toxicological information (Section 11)

# Section 5. Fire-fighting measures

## **Extinguishing media**

Suitable extinguishing

media

**Unsuitable extinguishing** 

media

: Use an extinguishing agent suitable for the surrounding fire.

: None known.

Specific hazards arising from the chemical

: This material is very toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged

to any waterway, sewer or drain.

Hazardous thermal decomposition products

: Decomposition products may include the following materials:

carbon dioxide carbon monoxide nitrogen oxides metal oxide/oxides

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

## Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For nonemergency personnel".

### **Environmental precautions**

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

## Methods and materials for containment and cleaning up

**Small spill** 

: Move containers from spill area. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor.

Large spill

: Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

### **Precautions for safe handling**

**Protective measures** 

: Put on appropriate personal protective equipment (see Section 8). Avoid exposure obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

**Advice on general** occupational hygiene : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

**Conditions for safe** storage, including any incompatibilities

: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

## Section 8. Exposure controls/personal protection

**Control parameters** 

**Occupational exposure limits** 

Page: 5/12

## Ocation O. Francoura contro

## Section 8. Exposure controls/personal protection

Ingredient name	Exposure limits
lead	OSHA PEL (United States, 5/2005).
	TWA: 0.05 mg/m³ 8 hours.
	ACGIH TLV (United States, 4/2014). Notes: as Pb
	TWA: 0.05 mg/m³, (as Pb) 8 hours.
	OSHA PEL (United States, 2/2013). Notes: as Pb
	TWA: 50 μg/m³, (as Pb) 8 hours.
	NIOSH REL (United States, 10/2013). Notes: See Appendix C -
	Supplemental Exposure Limits Note: The REL and PEL also apply
	to other lead compounds (as Pb).
	TWA: 0.05 mg/m³ 10 hours.
tin	OSHA PEL (United States, 9/2005).
	TWA: 2 mg/m³ 8 hours.
	ACGIH TLV (United States, 4/2014).
	TWA: 2 mg/m³, (as Sn) 8 hours.
	NIOSH REL (United States, 10/2013).
	TWA: 2 mg/m³, (as Sn) 10 hours.
Additive	AIHA WEEL (United States, 10/2011).
	TWA: 10 mg/m³ 8 hours.
Ammonium salt.	ACGIH TLV (United States, 4/2014).
	STEL: 20 mg/m³ 15 minutes. Form: Fume
	TWA: 10 mg/m <sup>3</sup> 8 hours. Form: Fume
	NIOSH REL (United States, 10/2013).
	STEL: 20 mg/m³ 15 minutes. Form: Fume
	TWA: 10 mg/m³ 10 hours. Form: Fume

# Appropriate engineering controls

: If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

# **Environmental exposure** controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### **Individual protection measures**

#### **Hygiene measures**

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

#### **Eye/face protection**

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with sideshields.

## Skin protection

**Hand protection** 

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

#### **Body protection**

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

## Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Page: 6/12

## Section 8. Exposure controls/personal protection

**Respiratory protection** 

: Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

## Section 9. Physical and chemical properties

**Appearance** 

Physical state : Solid.
Color : Gray.
Odor : None.

 Not available. Odor threshold pН : Not available. : Not available. **Melting point Boiling point** : Not available. : Not available. Flash point **Evaporation rate**  Not available. Flammability (solid, gas) : Not available. Lower and upper explosive : Not available.

(flammable) limits

Vapor pressure: Not available.Vapor density: Not available.Relative density: Not available.

**Solubility** : Insoluble in the following materials: cold water and hot water.

VOC
Partition coefficient: n-

octanol/water

Not available.

25.5 g/l

Auto-ignition temperature : Not available.

Decomposition temperature : Not available.

Viscosity : Not available.

## Section 10. Stability and reactivity

Reactivity

: No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability** 

: The product is stable.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Incompatibility with various substances

: Reactive or incompatible with the following materials: oxidizing materials, reducing materials, metals, acids, alkalis and moisture.

Chlorine, peroxides

Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Other Hazardous decomposition products

: metal oxides, toxic. fumes

Hazardous polymerization

: Under normal conditions of storage and use, hazardous polymerization will not occur.

## Page: 7/12

# Section 11. Toxicological information

## **Routes of entry**

: Dermal contact. Eye contact. Inhalation. Ingestion.

## **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
lead	LD50 Oral	Rat	>5000 mg/kg	-
tin	LD50 Oral	Rat	>2000 mg/kg	-
Additive	LD50 Oral	Mouse	11 g/kg	-
	LD50 Oral	Rat	8471 mg/kg	-
	LDLo Oral	Rabbit	10 g/kg	-
Ammonium salt.	LD50 Oral	Rat	1650 mg/kg	-

## **Irritation/Corrosion**

Product/ingredient name	Result	Species	Score	Exposure	Observation
Additive	Skin - Mild irritant	Human	-	72 hours 22 milligrams Intermittent	-
	Skin - Moderate irritant	Human	-	24 hours 20 Percent	-
Ammonium salt.	Eyes - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
	Eyes - Severe irritant	Rabbit	-	100 milligrams	-

## **Sensitization**

Not available.

## **Mutagenicity**

Product/ingredient name	Test	Experiment	Result
lead Additive	-	Subject: Mammalian-Animal Experiment: In vitro Subject: Mammalian-Human Cell: Germ	Equivocal Positive

## Carcinogenicity

No applicable toxicity data

## **Additional information:**

### **Classification**

Product/ingredient name	OSHA	IARC	NTP
lead	-	2B	Reasonably anticipated to be a human carcinogen.

## **Reproductive toxicity**

Product/ingredient name	Maternal toxicity	Fertility	Development toxin	Species	Dose	Exposure
lead	-	-	Equivocal	Rat - Female	Oral: 520 mg/kg	-
	-	-	Equivocal	Rat - Female	Inhalation: 3 mg/m³	24 hours per day
	Equivocal	-	-	Mouse - Female	Oral: 300 mg/kg	-
	-	Equivocal	-	Mouse	Oral: 4099.2 mg/kg	-

### **Teratogenicity**

Alpha is an Alent plc Company

Solder Wire Cored 40Sn/60Pb Alloy, AC94 Flux

Page: 8/12

## **Section 11. Toxicological information**

Product/ingredient name	Result	Species	Dose	Exposure
lead		Mammal - species unspecified	2118 mg/kg	-
	Equivocal - Inhalation	Rat	10 mg/m³	24 hours per day

### Specific target organ toxicity (single exposure)

Not available.

#### Specific target organ toxicity (repeated exposure)

Name	3 3 3	Route of exposure	Target organs
lead	Category 1		nervous system and reproductive organs

### **Aspiration hazard**

Not available.

Information on the likely routes of exposure

: Routes of entry anticipated: Oral, Dermal, Inhalation.

Potential acute health effects

Eye contact
 Inhalation
 No known significant effects or critical hazards.
 Skin contact
 No known significant effects or critical hazards.
 Ingestion
 No known significant effects or critical hazards.

## Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : No specific data.

**Inhalation** : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

**Skin contact**: Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

Ingestion : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

### Delayed and immediate effects and also chronic effects from short and long term exposure

**Short term exposure** 

**Potential immediate** 

: Not available.

effects

Potential delayed effects : Not available.

**Long term exposure** 

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

General : Causes damage to organs through prolonged or repeated exposure.

**Carcinogenicity** : Suspected of causing cancer. Risk of cancer depends on duration and level of

exposure.

Page: 9/12

# **Section 11. Toxicological information**

Mutagenicity

: No known significant effects or critical hazards.

**Teratogenicity** 

: May damage the unborn child.

**Developmental effects** 

: No known significant effects or critical hazards.

**Fertility effects** 

: May damage fertility.

## **Numerical measures of toxicity**

**Acute toxicity estimates** 

Not available.

## **Section 12. Ecological information**

## **Toxicity**

Product/ingredient name	Result	Species	Exposure
lead	Acute EC50 105 ppb Marine water	Algae - Chaetoceros sp Exponential growth phase	72 hours
	Acute EC50 0.489 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Acute EC50 8000 μg/l Fresh water	Aquatic plants - Lemna minor	4 days
	Acute LC50 530 μg/l Fresh water	Crustaceans - Ceriodaphnia reticulata	48 hours
	Acute LC50 5100 µg/l Fresh water	Daphnia - Daphnia pulex	48 hours
	Acute LC50 0.44 ppm Fresh water	Fish - Cyprinus carpio - Juvenile (Fledgling, Hatchling, Weanling)	96 hours
	Chronic NOEC 0.25 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Chronic NOEC 0.03 µg/l Fresh water	Fish - Cyprinus carpio	4 weeks
Additive	Acute EC50 6573.1 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute EC50 3910000 μg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 22.5 ppt Fresh water	Fish - Oreochromis mossambicus - Young	96 hours
	Chronic NOEC 2 g/L Fresh water	Fish - Heteropneustes fossilis	30 days
Ammonium salt.	Acute EC50 0.07 mg/l Marine water	Algae - Hormosira banksii - Gamete	72 hours
	Acute EC50 0.1 mg/l Fresh water	Crustaceans - Cypris subglobosa	48 hours
	Acute LC50 390 μg/l Fresh water	Daphnia - Daphnia magna - Young	48 hours
	Acute LC50 80 μg/l Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Chronic NOEC 0.6 mg/l Marine water	Algae - Entomoneis punctulata - Exponential growth phase	72 hours
	Chronic NOEC 330 µg/l Fresh water	Crustaceans - Crangonyx sp Juvenile (Fledgling, Hatchling, Weanling)	21 days
	Chronic NOEC 19.66 mg/l Fresh water	Daphnia - Daphnia magna	21 days
	Chronic NOEC 0.006 mg/l Fresh water	Fish - Ictalurus punctatus - Fry	30 days

### Persistence and degradability

Not available.

## **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
Additive	<-1.73	-	low
Ammonium salt.	-3.2	-	low

## **Mobility in soil**

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects : No known significant effects or critical hazards.

### Page: 10/12

## Section 13. Disposal considerations

**Disposal methods** 

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## Section 14. Transport information

	DOT Classification	TDG Classification	Mexico Classification	UN	IMDG	IATA
UN number	Not regulated.	Not available.	UN3077	UN3077	UN3077	UN3077
UN proper shipping name	-	(lead)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (lead)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (lead)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (lead)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (lead)
Transport hazard class(es)	-	Not available.	9	9	9	9
Packing group	-	-	III	III	III	III
Environmental hazards	No.	No.	Yes.	Yes.	Yes.	Yes.
Additional information - Mexico Classification	The environmen ≤5 kg.	tally hazardous su	ubstance mark is	not required wher	n transported in si	zes of ≤5 L or
Additional information - UN Classification	The environmen ≤5 kg.	tally hazardous su	ubstance mark is	not required wher	n transported in si	zes of ≤5 L or
Additional information - IMDG Classification	The marine pollu	ıtant mark is not r	equired when trar	nsported in sizes o	of ≤5 L or ≤5 kg.	_
Additional information - IATA Classification	The environmen ≤5 kg.	tally hazardous su	ubstance mark is	not required wher	n transported in si	zes of ≤5 L or

## **Section 14. Transport information**

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Page: 11/12

## **Section 15. Regulatory information**

**U.S. Federal regulations** 

: TSCA 5(a)2 proposed significant new use rule (SNUR): No products were found.

TSCA 5(a)2 final significant new use rules: Aliphatic alcohol. TSCA 12(b) one-time export notification: No products were found.

TSCA 12(b) annual export notification: lead

Refer to Proposed Rule (59 Federal Register 11122, March 9, 1994) for details on TSCA 12(b) applicability for lead.

**United States inventory** 

(TSCA 8b)

: All components are listed or exempted.

#### **SARA 302/304**

### **Composition/information on ingredients**

No products were found.

#### **SARA 311/312**

Classification : Delayed (chronic) health hazard

### **SARA 313**

	Product name	CAS number	%
Form R - Reporting requirements	lead	7439-92-1	50-60
Supplier notification	lead	7439-92-1	50-60

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

#### California Prop. 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

#### **Canada**

WHMIS (Canada) : Class D-2A: Material causing other toxic effects (Very toxic).

: All components are listed or exempted. Canada inventory


#### **International lists**

**National inventory** 

**Australia** : All components are listed or exempted. China : All components are listed or exempted. : All components are listed or exempted. **Europe** : All components are listed or exempted. **Japan New Zealand** : All components are listed or exempted. **Philippines** : All components are listed or exempted. Republic of Korea : All components are listed or exempted. : All components are listed or exempted. **Taiwan** 

## Section 16. Other information

## **Hazardous Material Information System (U.S.A.)**



### Procedure used to derive the classification

Classification	Justification
Carc. 2, H351	Calculation method
Repr. 1A, H360 (Fertility)	Calculation method
Repr. 1A, H360 (Unborn child)	Calculation method
STOT RE 1, H372	Calculation method
Aquatic Acute 1, H400	Calculation method
Aquatic Chronic 1, H410	Calculation method

#### **History**

Date of issue/Date of

revision

**Version** 

**Date of previous issue** 

. 1

Prepared by

: No previous validation.

: Regulatory Affairs Department

**Enthone Inc** 

: May 15 2015.

350 Frontage Road West Haven, CT 06516 Phone: (203) 934-8611 Fax: (203) 799-8179

enthonemsds@enthone.com

www.enthone.com

Key to abbreviations

: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

UN = United Nations

#### **Notice to reader**

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

4.5b3271

Alpha SDS GHS Americas





Safety Data Sheet

# Safety Data Sheet

## **Section 1. Identification**

Product name : Solder Paste Flux

Product code : 119653
Product type : Solid.

Date of issue/Date of

revision

: September 26 2016.

Manufacturer - Supplier	Telephone no.:	<b>Emergency phone:</b>
Arpha Assembly Solutions Inc. Global Headquarters 300 Atrium Drive Somerset, New Jersey 08873	Main Phone: (908) 791-3000	MESTIC NORTH AMERICA 800-424-9300 INTERNATIONAL, CALL +1 703-527-3887 (collect calls accepted) Alpha Chemtrec# 5591
APHA METALS MEXICO SA DE CV Ave Nafta 800, Parque Industrial STIVA Apodaca NL 66600 Mexico	Tel: +52 81 1156-6602	Tel: 01 800 022 1400 Tel: +52 55 5559-1588
Arpha Assembly Solutions Brasil Soldas Ltda Rio Jaguarão, 1540 - Vila Buriti Manaus Amazonas 69072-055 Brasil	Tel: 55 92 3614-7400	Tel: 55 92 3614-7423

## Section 2. Hazards identification

**OSHA/HCS** status

: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture

: ACUTE TOXICITY (oral) - Category 4 SKIN CORROSION/IRRITATION - Category 1B

SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1

**GERM CELL MUTAGENICITY - Category 2** 

SPECIFIC TARGET ORGAN TOXICITY (Respiratory tract irritation) - Category 3

AQUATIC HAZARD (ACUTE) - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 2

**GHS label elements** 

Hazard pictograms









Signal word

: Danger

**Hazard statements** 

: Harmful if swallowed.

Causes severe skin burns and eye damage. Suspected of causing genetic defects.

May cause respiratory irritation.

Very toxic to aquatic life.

Toxic to aquatic life with long lasting effects.

**Precautionary statements** 

Solder Paste Flux Page: 2/12

## Section 2. Hazards identification

General

: Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.

**Prevention** 

: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves. Wear eye or face protection. Wear protective clothing. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Avoid breathing dust. Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling.

Response

: Collect spillage. IF exposed or concerned: Get medical attention. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or physician. IF SWALLOWED: Immediately call a POISON CENTER or physician. Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. Wash contaminated clothing before reuse. Immediately call a POISON CENTER or physician. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or physician.

**Storage Disposal**  : Store locked up.

: Dispose of contents and container in accordance with all local, regional, national and international regulations.

Supplemental label elements

: Do not taste or swallow. Wash thoroughly after handling.

Hazards not otherwise classified

: Causes digestive tract burns.

## Section 3. Composition/information on ingredients

Substance/mixture

Ingredient name	%	CAS number
Proprietary	70-80	-
Zinc. Salt	20-30	-
Ammonium salt.	0.1-1.0	-

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

### **Description of necessary first aid measures**

**Eye contact** 

: Get medical attention immediately. Call a poison center or physician. Check for and remove any contact lenses. Immediately flush eyes with running water for at least 30 minutes, keeping eyelids open. Chemical burns must be treated promptly by a

Inhalation

: Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that mists are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.



Solder Paste Flux Page: 3/12

## Section 4. First aid measures

Skin contact

: Get medical attention immediately. Call a poison center or physician. Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 15 minutes. Chemical burns must be treated promptly by a physician. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

: Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

**Eye contact** : Causes serious eye damage. **Inhalation** : May cause respiratory irritation.

**Skin contact** : Causes severe burns.

Ingestion : Harmful if swallowed. Corrosive to the digestive tract. Causes burns.

#### Over-exposure signs/symptoms

**Eye contact**: Adverse symptoms may include the following:

pain watering redness

**Inhalation** : Adverse symptoms may include the following:

respiratory tract irritation

coughing

**Skin contact**: Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur

Ingestion : Adverse symptoms may include the following:

stomach pains

#### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician

: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

**Specific treatments** 

: No specific treatment.

Protection of first-aiders

: No action shall be taken involving any personal risk or without suitable training. If it is suspected that mists are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)



Solder Paste Flux Page: 4/12

## Section 5. Fire-fighting measures

#### **Extinguishing media**

Suitable extinguishing media

: Use an extinguishing agent suitable for the surrounding fire.

**Unsuitable extinguishing** media

: None known.

Specific hazards arising from the chemical

: This material is very toxic to aquatic life. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

**Hazardous thermal** decomposition products

: Decomposition products may include the following materials: halogenated compounds metal oxide/oxides

**Special protective actions** for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

**Special protective** equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For nonemergency personnel".

**Environmental precautions** 

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

### Methods and materials for containment and cleaning up

**Small spill** 

: Move containers from spill area. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Place spilled material in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.

Large spill

: Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.



Solder Paste Flux Page: 5/12

## Section 7. Handling and storage

#### **Precautions for safe handling**

#### **Protective measures**

Put on appropriate personal protective equipment (see Section 8). Avoid exposure obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

### Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

## **Conditions for safe** storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

## Section 8. Exposure controls/personal protection

#### **Control parameters**

Occupational exposure limits

Ingredient name	Exposure limits
Proprietary	ACGIH TLV (United States, 6/2007).
	TWA: 5 mg/m³
	STEL: 10 mg/m³
	OSHA PEL (United States, 6/2007).
	TWA: 5 mg/m³
Zinc. Salt	ACGIH TLV (United States, 4/2014).
	STEL: 2 mg/m³ 15 minutes. Form: Fume
	TWA: 1 mg/m³ 8 hours. Form: Fume
	NIOSH REL (United States, 10/2013).
	STEL: 2 mg/m³ 15 minutes. Form: Fume
	TWA: 1 mg/m³ 10 hours. Form: Fume
	OSHA PEL (United States, 2/2013).
	TWA: 1 mg/m³ 8 hours. Form: Fume
Ammonium salt.	ACGIH TLV (United States, 4/2014).
	STEL: 20 mg/m³ 15 minutes. Form: Fume
	TWA: 10 mg/m³ 8 hours. Form: Fume
	NIOSH REL (United States, 10/2013).
	STEL: 20 mg/m³ 15 minutes. Form: Fume
	TWA: 10 mg/m³ 10 hours. Form: Fume

### **Appropriate engineering** controls

: Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory

### **Environmental exposure** controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### **Individual protection measures**



Solder Paste Flux Page: 6/12

## Section 8. Exposure controls/personal protection

**Hygiene measures** 

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** 

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/ or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

**Skin protection** 

**Hand protection** 

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

**Body protection** 

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

: Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

## Section 9. Physical and chemical properties

**Appearance** 

Physical state : Solid.
Color : Gray.
Odor : None.

Odor threshold : Not available.

PH : Not available.

Melting point : Not available.

Boiling point : Not available.

Flash point : Not available.

Evaporation rate : Not available.

**Flammability (solid, gas)** : Non-flammable in the presence of the following materials or conditions: open flames,

sparks and static discharge and heat.

Lower and upper explosive

(flammable) limits

: Not available.

Vapor pressure: Not available.Vapor density: Not available.Relative density: Not available.

**Solubility** : Easily soluble in the following materials: cold water and hot water.

**VOC** : 0.9 g/l

Partition coefficient: n-

octanol/water

: Not available.

Auto-ignition temperature : Not available.

Decomposition temperature : Not available.

Solder Paste Flux Page: 7/12

## Section 9. Physical and chemical properties

**Viscosity** : Not available.

# Section 10. Stability and reactivity

Reactivity

: No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability** 

: The product is stable.

**Possibility of hazardous** 

: Under normal conditions of storage and use, hazardous reactions will not occur.

reactions

: Reactive or incompatible with the following materials: oxidizing materials, reducing

materials, metals, acids and alkalis.

**Incompatibility with various** substances

Chlorine., peroxides

**Hazardous decomposition** products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

**Other Hazardous** 

: Toxic fumes

decomposition products **Hazardous polymerization** 

: Under normal conditions of storage and use, hazardous polymerization will not occur.

## **Section 11. Toxicological information**

**Routes of entry** 

: Dermal contact. Eye contact. Inhalation. Ingestion.

### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
Zinc. Salt	LD50 Oral	Mouse	329 mg/kg	-
	LD50 Oral	Rat	350 mg/kg	-
Ammonium salt.	LD50 Oral	Rat	1650 mg/kg	-

#### **Irritation/Corrosion**

Product/ingredient name	Result	Species	Score	Exposure	Observation
Zinc. Salt	Skin - Severe irritant	Rabbit	-	120 hours 1 Percent	-
Ammonium salt.	Eyes - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
	Eyes - Severe irritant	Rabbit	-	100 milligrams	-

#### **Sensitization**

Not available.

### **Mutagenicity**

Not available.

#### **Carcinogenicity**

No applicable toxicity data

### **Additional information:**

#### Reproductive toxicity

Not available.

## **Teratogenicity**

Not available.

Specific target organ toxicity (single exposure)



Solder Paste Flux Page: 8/12

# **Section 11. Toxicological information**

Name	3 3 3	Route of exposure	Target organs
Zinc. Salt	Category 3		Respiratory tract irritation

### Specific target organ toxicity (repeated exposure)

Not available.

#### **Aspiration hazard**

Not available.

Information on the likely

routes of exposure

: Not available.

Potential acute health effects

**Eye contact** : Causes serious eye damage. **Inhalation** : May cause respiratory irritation.

**Skin contact** : Causes severe burns.

Ingestion : Harmful if swallowed. Corrosive to the digestive tract. Causes burns.

Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact**: Adverse symptoms may include the following:

pain watering redness

**Inhalation** : Adverse symptoms may include the following:

respiratory tract irritation

coughing

**Skin contact**: Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur

**Ingestion**: Adverse symptoms may include the following:

stomach pains

Delayed and immediate effects and also chronic effects from short and long term exposure

**Short term exposure** 

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

General : No known significant effects or critical hazards.Carcinogenicity : No known significant effects or critical hazards.

**Mutagenicity** : Suspected of causing genetic defects.

Teratogenicity : No known significant effects or critical hazards.

Developmental effects : No known significant effects or critical hazards.

Fertility effects : No known significant effects or critical hazards.

**Numerical measures of toxicity** 

Solder Paste Flux Page: 9/12

# Section 11. Toxicological information

### **Acute toxicity estimates**

Route	ATE value
Oral	441.3 mg/kg

# Section 12. Ecological information

### **Toxicity**

Product/ingredient name	Result	Species	Exposure
Zinc. Salt	Acute EC50 26 μg/l	Algae - Navicula incerta	96 hours
	Acute EC50 34 µg/l Fresh water	Algae - Chlorella vulgaris - Exponential growth phase	72 hours
	Acute EC50 1.8 mg/l Fresh water	Aquatic plants - Lemna aequinoctialis	96 hours
	Acute EC50 100 μg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 49.99 μg/l Fresh water	Crustaceans - Moina irrasa - Neonate	48 hours
	Acute LC50 0.027 mg/l Marine water	Fish - Limanda punctatissima - Pre-larvae	96 hours
	Chronic NOEC 20 µg/l Marine water	Algae - Chlorella sp Exponential growth phase	72 hours
	Chronic NOEC 1000 µg/l Fresh water	Crustaceans - Procambarus clarkii - Intermolt	21 days
	Chronic NOEC 80 μg/l Fresh water	Daphnia - Daphnia magna - Juvenile (Fledgling, Hatchling, Weanling)	21 days
	Chronic NOEC 31.5 µg/l Fresh water	Fish - Oncorhynchus mykiss	30 days
Ammonium salt.	Acute EC50 0.07 mg/l Marine water	Algae - Hormosira banksii - Gamete	72 hours
	Acute EC50 0.1 mg/l Fresh water	Crustaceans - Cypris subglobosa	48 hours
	Acute LC50 390 μg/l Fresh water	Daphnia - Daphnia magna - Young	48 hours
	Acute LC50 80 µg/l Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Chronic NOEC 0.6 mg/l Marine water	Algae - Entomoneis punctulata - Exponential growth phase	72 hours
	Chronic NOEC 330 µg/l Fresh water	Crustaceans - Crangonyx sp Juvenile (Fledgling, Hatchling, Weanling)	21 days
	Chronic NOEC 19.66 mg/l Fresh water Chronic NOEC 0.006 mg/l Fresh water	Daphnia - Daphnia magna Fish - Ictalurus punctatus - Fry	21 days 30 days

## Persistence and degradability

Not available.

### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
Proprietary	6	-	high
Zinc. Salt	-	60960	high
Ammonium salt.	-3.2	-	low

## **Mobility in soil**

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.



Solder Paste Flux Page: 10/12

## Section 13. Disposal considerations

### **Disposal methods**

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## **Section 14. Transport information**

	DOT Classification	TDG Classification	Mexico Classification	UN	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-	-	-
Transport hazard class(es)	-	-	-	-	-	-
Packing group	-	-	-	-	-	-
Environmental hazards	No.	No.	No.	No.	No.	No.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

## **Section 15. Regulatory information**

U.S. Federal regulations

: TSCA 5(a)2 proposed significant new use rule (SNUR): No products were found.

TSCA 5(a)2 final significant new use rule (SNUR): No products were found.

TSCA 12(b) one-time export notification: No products were found.

TSCA 12(b) annual export notification: No products were found.

**United States inventory** (TSCA 8b)

: All components are listed or exempted.

**SARA 302/304** 

**Composition/information on ingredients** 

No products were found.

**SARA 311/312** 

Classification : Immediate (acute) health hazard Delayed (chronic) health hazard

Solder Paste Flux Page: 11/12

## **Section 15. Regulatory information**

### **SARA 313**

	Product name	CAS number	%
Form R - Reporting requirements	Zinc. Salt	-	20-30
Supplier notification	Zinc. Salt	-	20-30

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

### California Prop. 65

WARNING: This product contains less than 0.1% of a chemical known to the State of California to cause cancer. WARNING: This product contains less than 1% of a chemical known to the State of California to cause birth defects or other reproductive harm.

#### Canada

WHMIS (Canada) : Class E: Corrosive material

**Canada inventory** : All components are listed or exempted.

### **International lists**

**National inventory** 

**Australia** : All components are listed or exempted. China : All components are listed or exempted. **Europe** : All components are listed or exempted. **New Zealand** : All components are listed or exempted. **Philippines** : All components are listed or exempted. Republic of Korea : All components are listed or exempted. **Taiwan** : All components are listed or exempted.

## Section 16. Other information

### **Hazardous Material Information System (U.S.A.)**

Health	3
Flammability	0
Physical hazards	0

### Procedure used to derive the classification

Classification	Justification
Acute Tox. 4, H302	Calculation method
Skin Corr. 1B, H314	Calculation method
Eye Dam. 1, H318	Calculation method
Muta. 2, H341	Calculation method
STOT SE 3, H335	Calculation method
Aquatic Acute 1, H400	Calculation method
Aquatic Chronic 2, H411	Calculation method

### **History**

Date of issue/Date of

revision

: September 26 2016.

Date of previous issue

: May 14 2015.

**Version** 

: 2



Solder Paste Flux Page: 12/12

## **Section 16. Other information**

Prepared by

: Regulatory Affairs Department

enthone.msds@macdermidenthone.com

**Key to abbreviations** 

: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

**UN = United Nations** 

**▼** Indicates information that has changed from previously issued version.

#### **Notice to reader**

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

4.5b3271

Alpha Assembly SDS GHS Americas