

1. Identification

| | | |
|---|---|----------------|
| Product identifier | SAFETY RED 085226-0 | |
| Other means of identification | | |
| Product Code | 09549 105161 713 | |
| Recommended use | Not available. | |
| Manufacturer/Importer/Supplier/Distributor information | | |
| Manufacturer | | |
| Company name | Quest Industrial Products, LLC. | |
| Address | N92 W14701 Anthony Avenue Menomonee Falls, WI 53051 United States | |
| Telephone | Phone | (262) 255-9500 |
| Website | quest-ip.com | |
| E-mail | info@quest-ip.com | |
| Emergency phone number | Chemtrec Phone | 800-424-9300 |

2. Hazard(s) identification

| | | |
|------------------------------|-----------------------------------|---------------|
| Physical hazards | Flammable aerosols | Category 1 |
| | Gases under pressure | Liquefied gas |
| Health hazards | Acute toxicity, oral | Category 4 |
| | Serious eye damage/eye irritation | Category 2B |
| | Carcinogenicity | Category 2 |
| | Reproductive toxicity | Category 2 |
| Environmental hazards | Not classified. | |
| OSHA defined hazards | Not classified. | |
| Label elements | | |



| | |
|--|---|
| Signal word | Danger |
| Hazard statement | Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Harmful if swallowed. Causes eye irritation. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. |
| Precautionary statement | |
| Prevention | Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection. |
| Response | If swallowed: Call a poison center/doctor if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Rinse mouth. If eye irritation persists: Get medical advice/attention. |
| Storage | Store locked up. Protect from sunlight. Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. |
| Disposal | Dispose of contents/container in accordance with local/regional/national/international regulations. |
| Hazard(s) not otherwise classified (HNOC) | None known. |
| Supplemental information | 47.75% of the mixture consists of component(s) of unknown acute oral toxicity. |

3. Composition/information on ingredients

Mixtures

| Chemical name | Common name and synonyms | CAS number | % |
|--|--------------------------|------------|-----------|
| CALCIUM CARBONATE | | 1317-65-3 | 10 to <20 |
| PROPANE | | 74-98-6 | 10 to <20 |
| ETHYL ACETATE | | 141-78-6 | 5 to <10 |
| MINERAL SPIRITS | | 64741-65-7 | 1 to <5 |
| N-BUTANE | | 106-97-8 | 1 to <5 |
| PETROLEUM NAPHTHA | | 8032-32-4 | 1 to <5 |
| PROPYLENE GLYCOL METHYL ETHER ACETATE | | 108-65-6 | 1 to <5 |
| ETHYLBENZENE | | 100-41-4 | 0.1 to <1 |
| SILICA, CRYSTALLINE QUARTZ | | 14808-60-7 | 0.1 to <1 |
| Other components below reportable levels | | | 50 to <60 |

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

| | |
|---|---|
| Inhalation | Move to fresh air. Call a physician if symptoms develop or persist. |
| Skin contact | No adverse effects due to skin contact are expected. Wash off with soap and water. Get medical attention if irritation develops and persists. |
| Eye contact | Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists. No specific first aid measures noted. |
| Ingestion | Not likely, due to the form of the product. Rinse mouth. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Get medical advice/attention if you feel unwell. |
| Most important symptoms/effects, acute and delayed | Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort. |
| Indication of immediate medical attention and special treatment needed | Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed. |
| General information | IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. |

5. Fire-fighting measures

| | |
|--|---|
| Suitable extinguishing media | Water fog. Foam. Dry chemical powder. Carbon dioxide (CO ₂). |
| Unsuitable extinguishing media | Do not use water jet as an extinguisher, as this will spread the fire. |
| Specific hazards arising from the chemical | Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed. |
| Special protective equipment and precautions for firefighters | Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. |
| Fire fighting equipment/instructions | In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out. |
| Specific methods | Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes. |
| General fire hazards | Extremely flammable aerosol. Contents under pressure. Pressurized container may explode when exposed to heat or flame. |

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid contact with eyes. Avoid prolonged exposure. Do not taste or swallow. When using, do not eat, drink or smoke. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Level 1 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Secure cylinders in an upright position at all times, close all valves when not in use. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

| Components | Type | Value | Form |
|-----------------------------------|------|-----------------------------------|----------------------|
| CALCIUM CARBONATE (CAS 1317-65-3) | PEL | 5 mg/m3 | Respirable fraction. |
| ETHYL ACETATE (CAS 141-78-6) | PEL | 15 mg/m3 1400 mg/m3 | Total dust. |
| ETHYLBENZENE (CAS 100-41-4) | PEL | 400 ppm 435 mg/m3 | |
| MINERAL SPIRITS (CAS 64741-65-7) | PEL | 100 ppm 400 mg/m3 | |
| PROPANE (CAS 74-98-6) | PEL | 100 ppm 1800 mg/m3 1000 ppm | |

US. OSHA Table Z-3 (29 CFR 1910.1000)

| Components | Type | Value | Form |
|---|------|-----------|-------------|
| SILICA, CRYSTALLINE QUARTZ (CAS 14808-60-7) | TWA | 0.3 mg/m3 | Total dust. |
| | | 0.1 mg/m3 | Respirable. |
| | | 2.4 mppcf | Respirable. |

US. ACGIH Threshold Limit Values

| Components | Type | Value | Form |
|---|------|-------------|----------------------|
| ETHYL ACETATE (CAS 141-78-6) | TWA | 400 ppm | |
| ETHYLBENZENE (CAS 100-41-4) | TWA | 20 ppm | |
| N-BUTANE (CAS 106-97-8) | STEL | 1000 ppm | |
| SILICA, CRYSTALLINE QUARTZ (CAS 14808-60-7) | TWA | 0.025 mg/m3 | Respirable fraction. |

US. NIOSH: Pocket Guide to Chemical Hazards

| Components | Type | Value | Form |
|---|---------|--|------------------|
| CALCIUM CARBONATE (CAS 1317-65-3) | TWA | 5 mg/m3 | Respirable. |
| ETHYL ACETATE (CAS 141-78-6) | TWA | 10 mg/m3 1400 mg/m3 | Total |
| ETHYLBENZENE (CAS 100-41-4) | STEL | 400 ppm 545 mg/m3 | |
| MINERAL SPIRITS (CAS 64741-65-7) | TWA | 125 ppm 435 mg/m3 100 ppm 400 mg/m3 | |
| N-BUTANE (CAS 106-97-8) | TWA | 100 ppm 1900 mg/m3 | |
| PETROLEUM NAPHTHA (CAS 8032-32-4) | Ceiling | 800 ppm 1800 mg/m3 | |
| PROPANE (CAS 74-98-6) | TWA | 350 mg/m3 1800 mg/m3 | |
| SILICA, CRYSTALLINE QUARTZ (CAS 14808-60-7) | TWA | 1000 ppm 0.05 mg/m3 | Respirable dust. |

US. Workplace Environmental Exposure Level (WEEL) Guides

| Components | Type | Value |
|--|------|--------|
| PROPYLENE GLYCOL METHYL ETHER ACETATE (CAS 108-65-6) | TWA | 50 ppm |

Biological limit values**ACGIH Biological Exposure Indices**

| Components | Value | Determinant | Specimen | Sampling Time |
|-----------------------------|----------|---|---------------------|---------------|
| ETHYLBENZENE (CAS 100-41-4) | 0.15 g/g | Sum of mandelic acid and phenylglyoxylic acid | Creatinine in urine | * |

* - For sampling details, please see the source document.

Exposure guidelines**US - California OELs: Skin designation**

PROPYLENE GLYCOL METHYL ETHER ACETATE (CAS 108-65-6) Can be absorbed through the skin.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

| | |
|---------------------------------------|---|
| Skin protection | |
| Hand protection | For prolonged or repeated skin contact use suitable protective gloves. |
| Other | Wear suitable protective clothing. |
| Respiratory protection | If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator. |
| Thermal hazards | Wear appropriate thermal protective clothing, when necessary. |
| General hygiene considerations | When using do not smoke. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. |

9. Physical and chemical properties

Appearance

| | |
|---|--|
| Physical state | Liquid. |
| Form | Aerosol. Liquefied gas. |
| Color | Not available. |
| Odor | Not available. |
| Odor threshold | Not available. |
| pH | Not available. |
| Melting point/freezing point | -305.68 °F (-187.6 °C) estimated |
| Initial boiling point and boiling range | -43.78 °F (-42.1 °C) estimated |
| Flash point | -156.0 °F (-104.4 °C) estimated |
| Evaporation rate | Not available. |
| Flammability (solid, gas) | Not applicable. |
| Upper/lower flammability or explosive limits | |
| Flammability limit - lower (%) | 2.4 % estimated |
| Flammability limit - upper (%) | 9.5 % estimated |
| Explosive limit - lower (%) | Not available. |
| Explosive limit - upper (%) | Not available. |
| Vapor pressure | 1667.05 hPa estimated |
| Vapor density | Not available. |
| Relative density | Not available. |
| Solubility(ies) | |
| Solubility (water) | Not available. |
| Partition coefficient (n-octanol/water) | Not available. |
| Auto-ignition temperature | 800 °F (426.67 °C) estimated |
| Decomposition temperature | Not available. |
| Viscosity | Not available. |
| Other information | |
| Density | 7.57 lbs/gal |
| Flammability class | Flammable IA estimated |
| Heat of combustion (NFPA 30B) | 11.68 kJ/g estimated |
| Percent volatile | 79.57 |
| Specific gravity | 0.91 |
| VOC | 4.5626116 lbs/gal Regulatory 333.937595 g/l Material 2.7868443 lbs/gal Material 546.721446 g/l Regulatory |

10. Stability and reactivity

| | |
|---|---|
| Reactivity | The product is stable and non-reactive under normal conditions of use, storage and transport. |
| Chemical stability | Material is stable under normal conditions. |
| Possibility of hazardous reactions | Hazardous polymerization does not occur. |
| Conditions to avoid | Heat. Avoid temperatures exceeding the flash point. Contact with incompatible materials. |
| Incompatible materials | Acids. Strong oxidizing agents. Nitrates. Fluorine. |
| Hazardous decomposition products | No hazardous decomposition products are known. |

11. Toxicological information

Information on likely routes of exposure

| | |
|---------------------|--|
| Inhalation | Prolonged inhalation may be harmful. |
| Skin contact | No adverse effects due to skin contact are expected. |
| Eye contact | Causes eye irritation. |
| Ingestion | Harmful if swallowed. |

Symptoms related to the physical, chemical and toxicological characteristics Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort.

Information on toxicological effects

Acute toxicity Harmful if swallowed.

| Components | Species | Test Results |
|----------------------------------|----------------|---------------------|
| ETHYL ACETATE (CAS 141-78-6) | | |
| <u>Acute</u> | | |
| Inhalation | | |
| LC50 | Rat | 16000 ppm, 6 Hours |
| LD50 | Mouse | 1500 ppm, 4 Hours |
| | Rabbit | 2500 ppm, 4 Hours |
| | Rat | 4000 ppm, 4 Hours |
| Oral | | |
| LD50 | Mouse | 0.44 g/kg |
| | Rabbit | 4.9 g/kg |
| | Rat | 11.3 ml/kg |
| | | 5.6 g/kg |
| ETHYLBENZENE (CAS 100-41-4) | | |
| <u>Acute</u> | | |
| Dermal | | |
| LD50 | Rabbit | 17800 mg/kg |
| Oral | | |
| LD50 | Rat | 3500 mg/kg |
| MINERAL SPIRITS (CAS 64741-65-7) | | |
| <u>Acute</u> | | |
| Inhalation | | |
| LC50 | Rat | 61 mg/l, 4 Hours |
| Oral | | |
| LD50 | Rat | > 25 ml/kg |
| N-BUTANE (CAS 106-97-8) | | |
| <u>Acute</u> | | |
| Inhalation | | |
| LC50 | Mouse | 680 mg/l, 2 Hours |
| | Rat | 658 mg/l, 4 Hours |

| Components | Species | Test Results |
|-----------------------------------|---------|-----------------------------|
| PETROLEUM NAPHTHA (CAS 8032-32-4) | | |
| Acute | | |
| Inhalation | | |
| LC50 | Rat | 3400 mg/l, 4 Hours |
| PROPANE (CAS 74-98-6) | | |
| Acute | | |
| Inhalation | | |
| LC50 | Rat | > 1442.847 mg/l, 15 Minutes |

* Estimates for product may be based on additional component data not shown.

| | |
|---|--|
| Skin corrosion/irritation | Prolonged skin contact may cause temporary irritation. |
| Serious eye damage/eye irritation | Causes eye irritation. |
| Respiratory or skin sensitization | |
| Respiratory sensitization | Not a respiratory sensitizer. |
| Skin sensitization | This product is not expected to cause skin sensitization. |
| Germ cell mutagenicity | No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic. |
| Carcinogenicity | Suspected of causing cancer. |
| IARC Monographs. Overall Evaluation of Carcinogenicity | |
| ETHYLBENZENE (CAS 100-41-4) | 2B Possibly carcinogenic to humans. |
| SILICA, CRYSTALLINE QUARTZ (CAS 14808-60-7) | 1 Carcinogenic to humans. |
| OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) | |
| Not listed. | |
| US. National Toxicology Program (NTP) Report on Carcinogens | |
| SILICA, CRYSTALLINE QUARTZ (CAS 14808-60-7) | Known To Be Human Carcinogen. |
| Reproductive toxicity | Suspected of damaging fertility or the unborn child. |
| Specific target organ toxicity - single exposure | Not classified. |
| Specific target organ toxicity - repeated exposure | Not classified. |
| Aspiration hazard | Not an aspiration hazard. |
| Chronic effects | Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects. |

12. Ecological information

| | |
|--------------------|--|
| Ecotoxicity | The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment. |
|--------------------|--|

| Components | Species | Test Results |
|----------------------------------|---------|---|
| ETHYL ACETATE (CAS 141-78-6) | | |
| Aquatic | | |
| Fish | LC50 | Indian catfish (Heteropneustes fossilis) 200.32 - 225.42 mg/l, 96 hours |
| ETHYLBENZENE (CAS 100-41-4) | | |
| Aquatic | | |
| Crustacea | EC50 | Water flea (Daphnia magna) 1.37 - 4.4 mg/l, 48 hours |
| Fish | LC50 | Fathead minnow (Pimephales promelas) 7.5 - 11 mg/l, 96 hours |
| MINERAL SPIRITS (CAS 64741-65-7) | | |
| Aquatic | | |
| Crustacea | EC50 | Water flea (Daphnia pulex) 2.7 - 5.1 mg/l, 48 hours |
| Fish | LC50 | Rainbow trout, donaldson trout (Oncorhynchus mykiss) 8.8 mg/l, 96 hours |
| | | 8.8 mg/l, 96 hours |

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

| | |
|---------------|------|
| ETHYL ACETATE | 0.73 |
| ETHYLBENZENE | 3.15 |
| N-BUTANE | 2.89 |
| PROPANE | 2.36 |

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

14. Transport information

DOT

| | |
|-------------------------------------|---|
| UN number | UN1950 |
| UN proper shipping name | Aerosols, flammable, 2.1 |
| Transport hazard class(es) | |
| Class | Not available. |
| Subsidiary risk | - |
| Packing group | Not applicable. |
| Special precautions for user | Read safety instructions, SDS and emergency procedures before handling. |

IATA

| | |
|-------------------------------------|---|
| UN number | UN1950 |
| UN proper shipping name | Aerosols, flammable, 2.1 |
| Transport hazard class(es) | |
| Class | Not available. |
| Subsidiary risk | - |
| Packing group | Not applicable. |
| Environmental hazards | No. |
| Special precautions for user | Read safety instructions, SDS and emergency procedures before handling. |

Other information

| | |
|-------------------------------------|------------|
| Passenger and cargo aircraft | Forbidden. |
| Cargo aircraft only | Forbidden. |

IMDG

| | |
|-------------------------------------|---|
| UN number | UN1950 |
| UN proper shipping name | Aerosols, flammable, 2.1 |
| Transport hazard class(es) | |
| Class | Not available. |
| Subsidiary risk | - |
| Packing group | Not applicable. |
| Environmental hazards | |
| Marine pollutant | No. |
| EmS | Not available. |
| Special precautions for user | Read safety instructions, SDS and emergency procedures before handling. |

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not established.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

| | |
|------------------------------|---------|
| ETHYL ACETATE (CAS 141-78-6) | Listed. |
| ETHYLBENZENE (CAS 100-41-4) | Listed. |
| N-BUTANE (CAS 106-97-8) | Listed. |
| PROPANE (CAS 74-98-6) | Listed. |

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes
Delayed Hazard - Yes
Fire Hazard - Yes
Pressure Hazard - No
Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting)

| Chemical name | CAS number | % by wt. |
|---------------|------------|-----------|
| ETHYLBENZENE | 100-41-4 | 0.1 to <1 |

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

ETHYLBENZENE (CAS 100-41-4)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

N-BUTANE (CAS 106-97-8)

PROPANE (CAS 74-98-6)

Safe Drinking Water Act (SDWA) Not regulated.

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

ETHYLBENZENE (CAS 100-41-4)
MINERAL SPIRITS (CAS 64741-65-7)
N-BUTANE (CAS 106-97-8)
PETROLEUM NAPHTHA (CAS 8032-32-4)
SILICA, CRYSTALLINE QUARTZ (CAS 14808-60-7)

US. Massachusetts RTK - Substance List

CALCIUM CARBONATE (CAS 1317-65-3)
ETHYL ACETATE (CAS 141-78-6)
ETHYLBENZENE (CAS 100-41-4)
MINERAL SPIRITS (CAS 64741-65-7)
N-BUTANE (CAS 106-97-8)
PROPANE (CAS 74-98-6)

SILICA, CRYSTALLINE QUARTZ (CAS 14808-60-7)

US. New Jersey Worker and Community Right-to-Know Act

CALCIUM CARBONATE (CAS 1317-65-3)

ETHYL ACETATE (CAS 141-78-6)

ETHYLBENZENE (CAS 100-41-4)

N-BUTANE (CAS 106-97-8)

PETROLEUM NAPHTHA (CAS 8032-32-4)

PROPANE (CAS 74-98-6)

SILICA, CRYSTALLINE QUARTZ (CAS 14808-60-7)

US. Pennsylvania Worker and Community Right-to-Know Law

CALCIUM CARBONATE (CAS 1317-65-3)

ETHYL ACETATE (CAS 141-78-6)

ETHYLBENZENE (CAS 100-41-4)

MINERAL SPIRITS (CAS 64741-65-7)

N-BUTANE (CAS 106-97-8)

PETROLEUM NAPHTHA (CAS 8032-32-4)

PROPANE (CAS 74-98-6)

SILICA, CRYSTALLINE QUARTZ (CAS 14808-60-7)

US. Rhode Island RTK

ETHYL ACETATE (CAS 141-78-6)

ETHYLBENZENE (CAS 100-41-4)

N-BUTANE (CAS 106-97-8)

PROPANE (CAS 74-98-6)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

ETHYLBENZENE (CAS 100-41-4) Listed: June 11, 2004

SILICA, CRYSTALLINE QUARTZ (CAS 14808-60-7) Listed: October 1, 1988

International Inventories

| Country(s) or region | Inventory name | On inventory (yes/no)* |
|-----------------------------|--|------------------------|
| Australia | Australian Inventory of Chemical Substances (AICS) | No |
| Canada | Domestic Substances List (DSL) | No |
| Canada | Non-Domestic Substances List (NDSL) | Yes |
| China | Inventory of Existing Chemical Substances in China (IECSC) | No |
| Europe | European Inventory of Existing Commercial Chemical Substances (EINECS) | No |
| Europe | European List of Notified Chemical Substances (ELINCS) | No |
| Japan | Inventory of Existing and New Chemical Substances (ENCS) | No |
| Korea | Existing Chemicals List (ECL) | No |
| New Zealand | New Zealand Inventory | No |
| Philippines | Philippine Inventory of Chemicals and Chemical Substances (PICCS) | No |
| United States & Puerto Rico | Toxic Substances Control Act (TSCA) Inventory | Yes |

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

| | |
|----------------------|---|
| Issue date | 03-06-2015 |
| Revision date | 05-07-2015 |
| Version # | 02 |
| HMIS® ratings | Health: 2* Flammability: 4 Physical hazard: 0 |
| NFPA ratings | Health: 2 Flammability: 4 Instability: 0 |

Disclaimer

The information in the sheet was written based on the best knowledge and experience currently available. THE INFORMATION CONTAINED HEREIN IS BASED ON DATA BELIEVED TO BE RELIABLE AND THE MANUFACTURER DISCLAIMS ANY LIABILITY INCURRED FROM THE USE OR RELIANCE UPON THE SAME. THE INFORMATION GIVEN IS DESIGNED ONLY AS A GUIDANCE FOR SAFE HANDLING, USE, PROCESSING, STORAGE, TRANSPORTATION, DISPOSAL AND RELEASE AND IS NOT TO BE CONSIDERED A WARRANTY OR QUALITY SPECIFICATION. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. This safety information is not a license to use this material as claimed by any patents of third parties. The user alone must finally determine whether a contemplated use of this material will infringe any such patents, and for obtaining any required licenses.