

NATIONAL CHEMICAL LABORATORIES, INC.

SAFETY DATA SHEET

Section 1 - Identification

Product Identifier	CITRA BLAST Foaming All Purpose
Other means of identification	2001
Recommended use	Foaming All Purpose Cleaner
Recommended restrictions	For commercial and industrial use only.
Manufacturer / Importer / Supplier	r / Distributor Information
Company Name	National Chemical Laboratories of PA, Inc.
Address	401 N. 10th Street - Philadelphia, PA 19123
Telephone	1 (215) 922-1200
Supplier Email	info@nclonline.com
Contact	CHEM-TEL
Emergency Phone	1 (800) 255-3924

Section 2 - Hazard(s) Identification

SDS Hazards an	d Warnings are based on the undiluted product	Refer to diluted SDS for Ready-To-Use Hazards ar	d Warnings.
	Classification	Category	
Physical Hazards	Not Classified		
	Gases Under Pressure, Compressed Gas		
Health Hazards	Acute toxicity, inhalation	4	
	Acute toxicity, oral	4	
	Sensitization, skin	1	
	Skin corrosion/irritation	2	
OSHA defined hazards	Not Classified.		
abel Elements			
Hazard Symbol			
Signal Word	Warning		
Hazard Statement	Flammable aerosol. Contains gas under pressure; may explode if heated. Causes eye irritation. Causes skin irritation. May cause an allergic skin reaction. Harmful if swallowed. Harmful if inhaled.		
Precautionary statement			
Prevention	Keep away from heat/sparks/open flames/hopen flames/hopen protection. Wash thoroughly after handling.	t surfaces. No smoking. Avoid breathing mist or vap Keep out of reach of children.	or. Wear eye/face
Response	•	Center or doctor/physician. If in eyes: Rinse cautiou: nd easy to do. Continue rinsing. If eye irritation persi	·
Storage	Protect from sunlight. Do not expose to temp	eratures exceeding 122°F/50°C. Store in a well-vent	ilated place.
Disposal	Dispose of waste and residues in accordance with local authority requirements.		
Hazard(s) not otherwise classified (HNOC)	None known.		
	Section 3 - Composition/I	nformation on ingredients	
Aixture			
Hazardous Components	Ingredient Name	CAS #	%
	Diethylene Glycol Monoethyl Ether	111-90-0	4 - 10
	Terpenes and Terpenoids, sweet orange-oil	68647-72-3	1 - 5
	Ethyl Alcohol	64-17-5	1 - 5
	Liquified Petroleum Gas	68476-86-8	1 - 5
	Section 4 - Firs	t-aid Measures	
nhalation	Move to fresh air and keen at rest. Call a nhy	cician if symptoms douglon and parsist	

Move to fresh air and keep at rest. Call a physician if symptoms develop and persist.

Specentact Rinse with water. Get medical attention if irritation develops and persits. Rinse mouth. Do not induce womting without advice from poison control center. Most important symptoms Riffects.acute and delayed Provide general supportive measures and treat symptomatically. Keep victim under observation. May cause an allergic skin reaction. Rinse mouth. Do not induce womting without advice from poison control center. Most important and special treatment Beneral information Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Soction 5 - Fire-fighting measures Mater fog. Dry chemical powder. Carbon dioxide (CO2). Ansuitable extinguishing media Mater fog. Dry chemical powder. Carbon dioxide (CO2). Ansuitable extinguishing media Mater fog. Dry chemical powder. Carbon dioxide (CO2). Ansuitable extinguishing media Self-contained breathing apparatus and full protective clothing must be worn in case of fire. In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. Form out, that was delayed freighting procedures and consider the hazards of other involved materials. Section 6 - A cocidental release measures Section 10 could consider the hazards of other involved materials. Presonal proceutions		
ngestion Binse mouth. Do not induce vomiting without advice from poison control center. Most Important symptoms (effects, acute and delayed indication of immediate medical periodic general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed midication of immediate medical periodic general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed medication of immediate medical periodic general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed medication of immediate medical periodical protective equipment indication of immediate medical periodic large from the chemical special protective equipment in case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzies, if possible. If not, withdraw and let fire burn out. Use standard firefighters increated inferighters Periodic pressure and consider the hazards of other involved materials. Section 6 - Accidental release measures Presonal precautions, protective reguipment and emergency regordine tand emergency regordine tand emergency esponal precautions, see section 8 of the SDS. Presonal precautions, protective requipment. Do not buch damaged contains or spliled materal underal. Stop leak if you can do so without risk. More the cylinder to a safe and open area: following product recovery, flush area with water. For waste disposal, see section 13 of the SDS. Presonal precautions. Refer to attazhed safety data sh	Skin contact	Wash off with soap and water. Get medical attention if irritation develops and persists.
Wast important symptoms Eye infristion. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause an allergic skin reaction. Infaction of immediate medial iteration and special treatment Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed scheral information Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Section 5 - Fire-fighting measures Jinuitable extinguishing media Water fog. Dry chemical powder. Carbon dioxide (CO2): None known. Sepecific hazards arising from he chemical perceition for fifefights; instructions Contents under pressure. Containers may explode when heated. Section of fife; Strop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers finatructions Incase of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers finatructions Presonal precautions, protective sequipment. Do not touch damaged containers or splited with water to prevent waper ressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozies, if possible. If not, withdraw and let fire burn out. Use standard firefighting procedures and consider the hazards of other involved materials. Section 6 - Accidental release measures equipment. Do not touch damaged containers or splited material levels. sproprinte protective equipment and clothing during clean-up. Emergency	Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
reaction, framediate medical medical medical medical medication of immediate medical personal properties measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed free treatment information in the medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Soction 5 - Fier-fightting measures witable extinguishing media personnel are aware of the material(s) involved, and take precautions to protect themselves. Soction 5 - Fier-fightting measures witable extinguishing media personnel are aware of the material(s) involved, and take precautions to protect themselves. Soction 5 - Fier-fightting measures witable extinguishing media personnel area aware of the material (s) involved, and take precautions to protect themselves. Solution of the chemical precautions for firefighters inre-fighting requipment in case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in fire fighting proceedures and consider the haards of other involved materials. Section 6 - Accidental release measures Personal precutors, protective equipment and clothing during dean-up. Emergency personal need self-contained breathing equipment. Do not touch damaged containers or spilled material unless waring appropriate protective equipment. So of the SDS. Novid discharge into daming, water courses or onto the ground. Section 7 - Handling and Sorage Prevent entry into waterways, sever, basements or confined areas. Following product recovery, flush area with water. For waste disposal, see	ngestion	Rinse mouth. Do not induce vomiting without advice from poison control center.
Iteration and special treatment Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Section 5 - Fire-fighting measures Socion 5 - Fire-fighting measures initiable extinguishing media Water fog. Dry chemical powder. Carbon dioxide (CO2). insultable extinguishing media Contents under pressure. Containers may explode when heated. ispecific hazards arising from the chemical breathing apparatus and full protective clothing must be worn in case of fire. In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Containers should be colled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozles, if possible. If not, withdraw and let fire burn out: use standard firefighting procedures and consider the hazards of other involved materials. Section 6 - Accidental release measures resonal preceutions, protective equipment and colting doming doming doming doming doming appratus and full ing doming domi	Nost Important symptoms /effects, acute and delayed	
Section 5 - Fire-fighting measures suitable extinguishing media Jnsuitable extinguishing media ispecific hazards arising from he chemical specific Methods Contents under pressure. Containers may explode when heated. Self-contained breathing apparatus and full protective clothing must be worn in case of fire. In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out. Use standard firelighting procedures and consider the hazards of other involved materials. Section 6 - Acccidental release measures Versonal precautions, protective squipment and emergency procedures. Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Emergency propriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS. Vetends and materials for containment and cleaning up appropriate protective o a safe and open area if t	ndication of immediate medical attention and special treatment	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
Suitable extinguishing media Water fog. Dry chemical powder. Carbon dioxid (CO2). Jnsuitable extinguishing media None known. sigecific hazards arising from he chemical specific hazards arising from pecial protective equipment indraceautions for firefighters: Contents under pressure. Containers may explode when heated. Self-contained breathing apparatus and full protective clothing must be worn in case of fire. In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzies, if possible. If not, withdraw and let fire burn out. Use standard firefighting procedures and consider the hazards of other involved materials. Section 6 - Acccidental release measures Section 10 - Acccidental release measures Presonal precautions, protective requipment and emergeny procedures. Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Emergeny personnel need self-contained breathing equipment. No on to touch damaged containers or spilled material unless waring appropriate protective cothing short transmental precautions. Wethods and materials for containment and cleaning up equipment. Now the cylinder to a safe and open area if the leak is irreparable. Isolate area unity containers. For waste disposal, see section 13 of the SDS. Refer to tatached safety data sheets and/or instructions for u	General Information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.
Insuitable extinguishing media None known. Specific hazards arising from the chemical Contents under pressure. Containers may explode when heated. Specific hazards arising from and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire. Self-contained breathing apparatus and full protective clothing must be worn in case of fire. Self-contained breathing apparatus and full protective clothing must be worn in case of fire. Self-contained breathing apparatus and full protective clothing must be worn in case of fire. Self-contained breathing apparatus and full protective clothing must be worn in case of fire. Specific Methods Use standard friefighting procedures and consider the hazards of other involved materials. Section 6 - Acccidental release measures Section 6 - Acccidental release measures Versonal precautions, protective equipment. Keep notective equipment and clothing during clean-up. Emergency personnel need self-contained breathing equipment and chaning up Verthods and materials for containment and cleaning up Keep conductive lathorities should be advised if significant. Stop leak if you can do so without risk. Move the cylinder to a safe and open are if the leak is irreparable. Isolate area until gas has dispersed. Prevent entry into waterways, sever, basements or confined areas. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS. Refer to attached safety data sheets and/or instructions for use. Elimina		Section 5 - Fire-fighting measures
india Contents under pressure. Containers may explode when heated. ispecific hazards arising from the chemical Self-contained breathing apparatus and full protective clothing must be worn in case of fire. inferefighting equipment ind precautions for firefighters In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out. Use standard firefighting procedures and consider the hazards of other involved materials. Section 6 - Acccidental release measures Self-contained breathing, yenground and guing clean-up. Emergency personnel need self-contained breathing, equipment. Do not touch damaged containers or spille material unless wearing appropriate protective clothing. Ventilate closed space before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal prectation, see section 8 of the SDS. Wethods and materials for sontainment and cleaning up Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or without risk. Move the cylinder to a safe and open area if the leak is ingrue built be leak is grouped. Section 7 - Handling and storage Needer to train, water courses or onto the ground. Verevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS.	Suitable extinguishing media	Water fog. Dry chemical powder. Carbon dioxide (CO2).
he chemical special protective equipment and precautions for firefighters sire-fighting equipment finstructions in case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent wapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out- specific Methods Use standard firefighting procedures and consider the hazards of other involved materials. Section 6 - Accidental release measures Resonal precautions, protective equipment and emergency procedures. Nethods and materials for concedures. Methods and materials for container and leak is left or burn or any propriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For presonal protection, see section 8 of the SDS. Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or fiames in immediate area). Keep combustibles (wood, paper, oil, ct.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground. MARMFUL IF INHALED DR SWALLOWED. VAPOR HARMFUL EYE, SKIN AND RESPIRATORY IRRITANT.Pressurized containers Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not sources of ignition. Ground and bod containers when transferring material. Do not reuse empty containers. Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipmen	Jnsuitable extinguishing nedia	None known.
and precautions for firefighters In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out. Use standard firefighting procedures and consider the hazards of other involved materials. Section 6 - Acccidental release measures Reep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 18 of the SDS. Nethods and materials for sontainment and cleaning during them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 13 of the SDS. Nethods are aution to exerce or burn, even after use. Do not use if spray black solate area until gas has dispersed. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground. Section 7 - Handling and storage Precautions for safe handling HARMFUL IF INHALED OR SWALLOWED. VAPOR HARMFUL LYE, SKIN AND RESPIRATORY IRRITANT. Press	Specific hazards arising from the chemical	Contents under pressure. Containers may explode when heated.
Instructions from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out. Use standard firefighting procedures and consider the hazards of other involved materials. Section 6 - Accidental release measures Personal precautions, protective equipment and conting during clean-up. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS. Wethods and materials for container bury into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS. Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS. Refer to attached safety OR SWALLOWED. VAPOR HARMFUL EVE, SKIN AND RESPIRATORY IRRITANT.Pressurized container: Do not pierce or bury, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any othe	Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Section 6 - Accidental release measures Personal precautions, protective supignent and emergency procedures. Keep uncessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS. Wethods and materials for containment and cleaning up Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS. Environmental precautions Avoid discharge into drains, water courses or onto the ground. Prevent entry into waterways, seewer, basements or confined areas. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS. Prevent entry into waterways, seewer, basements or out the ground. Section 7 - Handling and storage Prevent entry into ave after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke	Fire-fighting equipment /instructions	from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For
Personal precautions, protective Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS. Wethods and materials for containment and cleaning up Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS. Environmental precautions Avoid discharge into drains, water courses or onto the ground. Precautions for safe handling HARMFUL IF INHALED OR SWALLOWED. VAPOR HARMFUL. EYE, SKIN AND RESPIRATORY IRRITANT. Pressurized container: Do not pierce or burn, even after use. Do not sweks, or other sources of ignition. Grouph and ab dond containers when transferring material. Do not re-use empty containers. Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Keep out of reach of childrer Observe good industrial hygiene practices. Conditions for safe storage, neclusting in the subscif	Specific Methods	Use standard firefighting procedures and consider the hazards of other involved materials.
equipment and emergency procedures.appropriate protective equipment and clothing during clean-up. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.Wethods and materials for containment and cleaning upRefer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Nove the cylinder to a safe and open area if the leak is increparable. Isolate area until gas has dispersed. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS.Environmental precautionsAvoid discharge into drains, water courses or onto the ground.Preceutions for safe handling any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Ground and bond containers when transferring material. Do not re-use empty containers. Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Keep out of reach of childrer Observe good industrial hygiene practices. Level 1 Aerosol.Conditions for safe storage, ncluding any incompatibilitiesContents under pressure. Do not expose to heat or store ear an open flame, heat or other sources of ignit		Section 6 - Accidental release measures
containment and cleaning up flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. For Environmental precautions Avoid discharge into drains, water courses or onto the ground. Preceutions for safe handling HARMFUL IF INHALED OR SWALLOWED. VAPOR HARMFUL. EYE, SKIN AND RESPIRATORY IRRITANT.Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Ground and bond containers when transferring material. Do not re-use empty containers. Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Keep out of reach of childrer Observe good industrial hygiene practices. Conditions for safe storage, ncluding any incompatibilities Contents under pressure. Do not expose to heat or store at temperatures above 122°F/50°C as can may burst. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Keep containers tightly closed in a dry, cool and well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).	Personal precautions, protective equipment and emergency procedures.	appropriate protective equipment and clothing during clean-up. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For
Section 7 - Handling and storage Precautions for safe handling HARMFUL IF INHALED OR SWALLOWED. VAPOR HARMFUL. EYE, SKIN AND RESPIRATORY IRRITANT.Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Ground and bond containers when transferring material. Do not re-use empty containers. Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Keep out of reach of children Observe good industrial hygiene practices. Conditions for safe storage, ncluding any incompatibilities Level 1 Aerosol. Contents under pressure. Do not expose to heat or store at temperatures above 122°F/50°C as can may burst. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Keep containers tightly closed in a dry, cool and well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).	Methods and materials for containment and cleaning up	Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. For
 Precautions for safe handling HARMFUL IF INHALED OR SWALLOWED. VAPOR HARMFUL. EYE, SKIN AND RESPIRATORY IRRITANT.Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Ground and bond containers when transferring material. Do not re-use empty containers. Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Keep out of reach of childrer Observe good industrial hygiene practices. Level 1 Aerosol. Contents under pressure. Do not expose to heat or store at temperatures above 122°F/50°C as can may burst. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Keep containers tightly closed in a dry, cool and well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS). 	Environmental precautions	Avoid discharge into drains, water courses or onto the ground.
 Precautions for safe handling HARMFUL IF INHALED OR SWALLOWED. VAPOR HARMFUL. EYE, SKIN AND RESPIRATORY IRRITANT.Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Ground and bond containers when transferring material. Do not re-use empty containers. Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Keep out of reach of childrer Observe good industrial hygiene practices. Level 1 Aerosol. Contents under pressure. Do not expose to heat or store at temperatures above 122°F/50°C as can may burst. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Keep containers tightly closed in a dry, cool and well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS). 		Section 7 - Handling and storage
Conditions for safe storage, ncluding any incompatibilities Contents under pressure. Do not expose to heat or store at temperatures above 122°F/50°C as can may burst. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Keep containers tightly closed in a dry, cool and well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).	Precautions for safe handling	HARMFUL IF INHALED OR SWALLOWED. VAPOR HARMFUL. EYE, SKIN AND RESPIRATORY IRRITANT.Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Ground and bond containers when transferring material. Do not re-use empty containers. Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Keep out of reach of children.
	_	Level 1 Aerosol. Contents under pressure. Do not expose to heat or store at temperatures above 122°F/50°C as can may burst. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Keep containers
		Section 8 - Exposure control/personal protection

Occupational exposure limits

US. Workplace environmental Exposure Level (WEEL) Guides			
Component	Туре	Value	
Diethylene Glycol Monoethyl Ether (CAS 111-90-0)	TWA	140 mg/m³ , 25 ppm	
US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.2	1000)		
Components	Туре	Value	Form
Ethyl Alcohol (CAS 64-17-5)	TWA	1900 mg/m³, 1000 ppm	
Liquified Petroleum Gas (CAS 68476-86-8)	TWA	1000 ppm	Mist
US. ACGIH Threshold Limit Values			
Component	Туре	Value	Form
Liquified Petroleum Gas (CAS 68476-86-8)	TLV	1000 ppm	Mist
Ethyl Alcohol (CAS 64-17-5)	STEL	1000 ppm	
US. NIOSH: Pocket Guide to Chemical Hazards			
Components	Туре	Value	
Ethyl Alcohol (CAS 64-17-5)	IDLH	3300 ppm	

Ethyl Alcohol (CAS 64-17-5)	TWA 1900 mg/m ³ , 1000 ppm			
Biological limit values	No biological exposure limits noted for the ingredient(s).			
Exposure guidelines	Use personal protective equipment as required. Keep working clothes separately.			
Appropriate engineering controls	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide exposure limits have station.			
Individual protection measures, so	uch as personal protective equipment			
Eye/face protection	If use of product risks exposure to contact, wear safety glasses with side shields.			
Skin protection				
Hand protection	Impervious gloves are recommended for prolonged use.			
Other	If use of product risk exposure to contact, wear suitable protective clothing.			
Respiratory protection	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.			
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.			
General hygiene considerations	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.			

Section 9 - Physical and chemical properties

	Section 10 - Stability and reactivity		
Pressure	40 - 52 psig @ 70F		
VOC's	10.5 %		
Other Information			
Viscosity Temperature			
Viscosity			
Decomposition temperature	Not Available		
Auto-ignition temperature	Not Available		
n-octanol/water			
Partition Coefficient	Not available		
Solubilities (water)	Soluable (liquid)		
Relative density Relative density temperature	0.99 ± 0.01 (liquid) 75 °F (23.9 °C)		
Relative density			
Vapor pressure Vapor density	Not available. Not available.		
	9.5% estimated Not available.		
Explosive limit - lower (%) Explosive limit - upper (%)			
Flammability limit - upper (%)	Not available. 1.9% estimated		
Flammability limit - lower (%)			
Upper/lower flammability or expl	osive limits Not available.		
Flammability (solid, gas)	Not available.		
Evaporation rate	Not available.		
Flash point	-156.0 °F (-104.4 °C) Propellant estimated		
boiling range			
Initial boinging point and	Not available.		
Melting point/freezing point	Not available.		
рН	10.8		
Odor threshold	Not available.		
Odor	Citrus.		
Color	Straw.		
Form	Aerosol. Liquefied gas. Opaque foamy liquid.		
Physical state	Gas/Liquid mixture.		
Appearance			

	Section To - Stability and reactivity
Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possiblity of hazardous reactions	Hazardous polymerization does not occur.
Conditions to Avoid	Avoid heat, sparks, open flames and other ignition sources. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.

	VALETT	DATA OI			
Hazardous Decomposition Products	No hazardous decomposition products	s are known.			
	Section 11 - To	xicological	informati	on	
nformation on likely routes of e	exposure				
Ingestion	Expected to be a low ingestion hazard				
Inhalation	May cause respiratory tract irritation.	This product may be	aspirated onto	o the lungs and cau	se chemical pneumonitis.
Skin contact	Causes skin irritation. May cause sensitization by skin contact. Prolonged or repeated skin contact may cause drying, cracking, or irritation.				
Eye contact	Causes eye irritation.				
ymptoms related to the hysical, chemical and oxicological characteristics	Eye irritation. Symptoms may include a swelling of the conjunctiva.	discomfort or pain,e	xcess blinking a	and tear production	n, with marked redness and
nformation on toxicological effe	ects.				
cute toxicity	May be harmful if swallowed.				
Components	Level	Туре	Code	Species	Results
Ethyl Alcohol (CAS 64-17-5)	Acute	Inhalation Vapor	LC50	Rat	117 - 125 mg/l, 4 h
	Acute	Oral	LD50	Rat	10470 mg/kg
kin corrosion/irritation	Prolonged skin contact may cause tem	porary irritation.			
erious eye damage/ eye rritation	Causes eye irritation.				
Respiratory sensitization	This product is not expected to cause r	respiratory sensitizat	tion.		
kin sensitization	May cause sensitization by skin contac	:t.			
Germ cell mutagenicity	No data available to indicate product o	or any components p	present at great	ter than 0.1% are n	nutagenic or genotoxic.
arcinogenicity	Risk of cancer cannot be excluded with	n prolonged exposur	e.		
eproductive toxicity	This product is not expected to cause r	reproductive or deve	alonmental effe	acts	
pecific target organ toxicity -	Not classified.		lopinentai ene		
ngle exposure	Not classified.				
pecific target organ toxicity - epeated exposure	Not classified.				
spiration hazard	Not likely, due to the form of the prod	uct.			
hronic effects	Prolonged inhalation may be harmful.	May be harmful if a	bsorbed throug	gh skin.	
	Section 12 - E	cological In	formatio	n	
cotoxicity	The product is not classified as enviror				the possibility that large or
		frequent spills can have a harmful or damaging effect on the environment.			
ersistence and degradability	No data is available on the degradabili	No data is available on the degradability of this product.			
ioaccumulative potential	No data available.				
Partition coeficient n-octand	ol / water log (Kow)				
Components		Results			
Ethyl Alcohol (CAS 64-17-5	5)	-0.31			
Diethylene Glycol Monoet	thyl Ether (CAS 111-90-0)	-0.54			
Nobility in soil	No data available.				
Aobility in general	No data available.				
Other adverse effects	No other adverse environmental effec disruption, global warming potential)				n potential, endocrine
	Section 13 - D	isposal cons	deration	ıs	
Disposal instructions	Consult authorities before disposal. Co	ontents under pressu	ıre. Do not pun		r crush. Dispose of
	contents/container in accordance with	n local/regional/nation	onal/internatio	nal regulations.	
ocal disposal regulations	contents/container in accordance with Dispose in accordance with all applical		onal/internatio	nal regulations.	
		ble regulations.			aste disposal company.
lazardous waste code Vaste from residues / unused	Dispose in accordance with all applical	ble regulations. discussion between gulations. Empty cor	the user, the p	roducer and the wa	
Hazardous waste code Waste from residues / unused products	Dispose in accordance with all applical The waste code should be assigned in Dispose of in accordance with local reg	ble regulations. discussion between gulations. Empty cor in a safe manner. In approved waste h	the user, the p ntainers or liner andling site for	roducer and the wars may retain some	product residues. This material sal. Since emptied containers
lazardous waste code Vaste from residues / unused roducts	Dispose in accordance with all applical The waste code should be assigned in Dispose of in accordance with local reg and its container must be disposed of Empty containers should be taken to a	ble regulations. discussion between gulations. Empty cor in a safe manner. In approved waste h el warnings even aft	the user, the p ntainers or liner andling site for er container is	roducer and the wars rs may retain some recycling or dispose emptied. Do not re	product residues. This material sal. Since emptied containers
lazardous waste code Vaste from residues / unused roducts ontaminated packaging	Dispose in accordance with all applical The waste code should be assigned in Dispose of in accordance with local reg and its container must be disposed of Empty containers should be taken to a may retain product residue, follow lab Section 14 - 1	ble regulations. discussion between gulations. Empty cor in a safe manner. In approved waste h el warnings even aft	the user, the p ntainers or liner andling site for er container is	roducer and the wars rs may retain some recycling or dispose emptied. Do not re	product residues. This material sal. Since emptied containers
Local disposal regulations Hazardous waste code Waste from residues / unused products Contaminated packaging OT UN number	Dispose in accordance with all applical The waste code should be assigned in Dispose of in accordance with local reg and its container must be disposed of Empty containers should be taken to a may retain product residue, follow lab	ble regulations. discussion between gulations. Empty cor in a safe manner. In approved waste h el warnings even aft	the user, the p ntainers or liner andling site for er container is	roducer and the wars rs may retain some recycling or dispose emptied. Do not re	product residues. This material sal. Since emptied containers

Transport hazard class(es)	2.1
Packing group	Not Applicable.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Labels required	None/Ninguno
Packaging exemption	306
Packaging non bulk	None/Ninguno
Packaging bulk	None/Ninguno
Comment	This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.
ΙΑΤΑ	
UN number	UN1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	2.1
Packaging group	Not Applicable.
Environmental hazards	No.
Labels required	2.1
ERG Code	10L
Special precautions for user Other Information	Read safety instructions, SDS and emergency procedures before handling.
Passenger and Cargo aircraft	Allowed.
Cargo aircraft only	Allowed.
Packaging Exceptions	LTD QTY
IMDG	
UN number	UN1950
UN proper shipping name	AEROSOLS
Transport hazard class(es)	2.1
Packaging group	Not Applicable.
Environmental hazards Marine pollutant	No.
Labels required	2.1
EmS	F-D, S-U
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Packaging Exceptions	LTD QTY
Transportation in bulk according to Annex II of MARPOL 73/78 and IBC Code	Not applicable.

Section 15 - Regulatory Information

					7
federal regulations		a "Hazardous Chemical" as are on the U.S. EPA TSCA	•	ard Communication Standard, 29 CFR 19) 10.1200.
TSCA Section 12(b) Ex	port Notification (40 CF		Not regulated.		
Componen	its		Result	Comment	
Liquified Pe	etroleum Gas (CAS 68476	5-86-8)	8-12%		
US. OSHA Specifically	Regulated Substances (29 CFR 1910.1001-1050)	Not listed		
CERCLA Hazardous Su	ubstance List (40 CFR 302	2.4			
Componen	its		Result		
Diethylene	Glycol Monoethyl Ether	(CAS 111-90-0)	LISTED		
Ethyl Alcoh	nol (CAS 64-17-5)		LISTED		
Superfund Amendme	ents and Reauthorization	Act of 1986 (SARA)			
Hazard Categories	Immediate Hazard	No			
	Delayed Hazard	No			
	Fire Hazard	Yes			
	Pressure Hazard	Yes			
	Reactivity Hazard	No			
SARA 302 Extremely	hazardous substance	Not regulated.			
SARA 311/312 Hazard	dous chemical	No			
SARA 313 (TRI report	ing)				
Cher	nical name		CAS #	% by wt.	
			CITRA BLAST FOR	aming All Purpose 2001	Page

	_				
Diethylene Glycol Mo	onoethyl Ether		111-90-0	4 - 10	
Other federal regulations					
Clean Air Act (CAA) Section 112 Haza	rdous Air Pollutants (HS	Ps) List			
Com	ponents				
Dieth	ylene Glycol Monoethy	l Ether (CAS 111-90-0)			
Clean Air Act (CAA) Section 112(r) Act	cidental Release Preven	tion (40 CFR 68.130)	Diethylene gly	col monoethyl ether	(CAS 111-90-0)
Safe Drinking Water Act (SDWA)	Not regulated.				
Food and Drug Administration (FDA)	Not regulated.				
US state regulations					
US.Massachusetts RTK - Substance Li	st	Components			
		Ethyl Alcohol (CAS 64-1	17-5)		
		Diethylene Glycol Mon	oethyl Ether (CAS 11	1-90-0)	
US.New Jersey Worker and Commun	ity Right-to-Know Act	Components			
		Ethyl Alcohol (CAS 64-1	17-5)		
		Diethylene Glycol Mon	oethyl Ether (CAS 112	1-90-0)	
US.Pennsylvania RTK - Hazardous Sul	ostances	Components			
		Ethyl Alcohol (CAS 64-1	17-5)		
		Diethylene Glycol Mon	oethyl Ether (CAS 11	1-90-0)	
US.Rhode Island RTK		Components			
		Diethylene Glycol Mon	oethyl Ether (CAS 11	1-90-0)	
US - California Proposition 65	US - California Proposition 65		ct contains a chemica	I known to the State of	California to cause
		cancer.			
International Inventories					
Country(s) or region	Inventory Name				On Inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)			No	
Canada	Domestic Substances	List (DSL)			Yes
Canada	Non-Domestic Substa	inces List (NDSL)			No
China	Inventory of Existing Chemical Substances in China (IECSC)		Yes		
Europe	European Inventory of	of Existing Commercial Ch	emical Substances (I	EINECS)	No
Europe	European List of Notifed Chemical Substances (ELINCS)			No	
Japan		and New Chemical Substa	ances (ENCS)		No
Korea	Existing Chemicals Lis				No
New Zealand	New Zealand Invento	•			No
Philippines		of Chemicals and Chemica			No
Unites States Puerto Rico		trol Act (TSCA) Inventory			Yes
*A "Yes" indicates this product comp	lies with the inventory	requirements administer	ed by the governing	country(s).	

*A "No" indicates this product complex with the inventory requirements administered by the governing country(s). *A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

	Section 16 - Other information, including date of preparation or last version
Revision date	1/17/2018
Version #	02
Disclaimer	The information contained herein was obtained from current and reliable sources. However, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions for use, handling, storage and disposal of this product are beyond the manufacturer's control, it is the user's responsibility both to determine safe conditions for use of this product and to assume liability for loss, injury, damage or expense arising from the product's improper use. No warranty, expressed or implied, regarding the product described herein shall be created by or inferred from any statement or omission in this SDS. Various government agencies may have specific regulations concerning the transportation, handling, storage, use or disposal of this product which may not be reflected in this SDS. The user should review these regulations to ensure full compliance.